Name: Sapna **Roll No:** 1826080 **Subject:** IT

Computer Fundamentals Report

Modern Computer Characteristics and Technological Evolution Across Generations

Primary Characteristics of a Modern Digital Computer

1. High Speed

Modern computers execute billions of operations per second (GHz speeds), handling massive calculations and data tasks in microseconds.

2. Accuracy & Reliability

Computers produce precise results consistently, eliminating human fatigue and error. Faulty outputs stem from incorrect input data or code.

3. Storage Capacity

Primary memory (RAM) and secondary storage (SSDs/HDDs) allow massive amounts of data and instructions to be retained for processing.

4. Automation & Versatility

Computers execute instructions automatically without human intervention, handling diverse tasks from business processing to AI research.

Hardware Technology Across the Five Generations

Generation	Approx. Period	Key Hardware Technology
First Generation	1940–1956	Vacuum Tubes (Thermionic valves) and magnetic drums.
Second Generation	1956–1963	Transistors (replacing fragile and bulky vacuum tubes).
Third Generation	1964–1971	Integrated Circuits (ICs) / Semiconductor silicon chips.
Fourth Generation	1971–Present	Microprocessors utilizing VLSI (Very Large Scale Integration).
Fifth Generation	Present & Beyond	ULSI (Ultra Large Scale Integration), AI processors, and parallel processing.

Name: Sapna **Roll No:** 1826080 **Subject:** IT

Campus Automation Systems

Deploying Optical Data Scanners and Electronic Card Readers for Attendance and Library Management

Automating campus workflows using data capture technologies significantly reduces administrative bottlenecks, human errors, and processing time.

1. Optical Data Scanning Devices (Barcode & OMR Scanners)

Attendance Automation

Student ID cards with barcodes are scanned upon entry, instantly logging timestamps into the central campus database.

Library Checkouts

Librarians use barcode readers to scan patron IDs followed by book barcodes, updating circulation status automatically.

2. Electronic Card Readers (RFID & Smart Card Readers)

Contactless Attendance (RFID)

RFID proximity readers at lecture halls or gates detect smart cards within range, registering presence simultaneously without queues.

Self-Service Library Kiosks

Smart card readers integrated into kiosks verify user identity via chips, allowing independent book checkouts.

Campus Data Capture Summary

Technology	Attendance Deployment	Library Checkout Deployment
Optical Barcode	Line-of-sight scanning of individual ID cards.	Standard barcode scanning for inventory and book issuance.
OMR	Bulk processing of physical paper attendance sheets/exams.	Paper-based feedback forms and library survey evaluations.
RFID / Smart Cards	Automated gate check-ins with high throughput.	Bulk book scanning and friction-free self-checkout kiosks.

Name: Sapna **Roll No:** 1826080 **Subject:** IT

Input Device Architectural Comparison

Point-and-Draw Devices (Mouse/Trackball) vs. Graphics Digitizers / Drawing Tablets

1. Coordinate Tracking & Pressure Sensitivity

Relative vs. Absolute Tracking

Mice use relative motion deltas (Δx, Δy) requiring desk movement. Drawing tablets use an active electromagnetic grid mapping physical (X, Y) coordinates directly to screen pixels.

Discrete vs. Continuous Pressure

Mice provide binary click states. Digitizers support thousands of pressure levels and tilt detection for organic brush stroke modulation.

2. Application Suitability: CAD vs. Digital Art

Application Domain	Point-and-Draw (Mouse / Trackball)	Graphics Digitizers / Tablets
CAD (Computer-Aided Design)	**Optimal:** Multi-button precision, scroll wheel zooming, and grid snap align with rigorous drafting.	**Secondary:** Used for freehand markup or sculpting 3D meshes; less efficient for rigid vector drafting.
Digital Art & Illustration	**Limited:** Results in uniform lines and hand fatigue due to lack of pressure sensitivity.	**Optimal:** Essential tool providing natural hand-eye coordination and dynamic pressure response.

Name: Sapna **Roll No:** 1826080 **Subject:** IT

Biometric Security Critique

Vision vs. Voice Authentication in High-Ambient-Noise, Public Environments

Deploying biometrics in publicly exposed environments presents severe challenges. Below is a critique of vision-input and voice recognition devices.

1. Operational Reliability & Vulnerabilities

Vision-Input (Facial Recognition)

Reliability: Degraded by harsh outdoor lighting, shadows, glare, and masks.
Security: Vulnerable to 2D prints, 3D silicone masks, and video deepfakes.

Voice Recognition Devices

Reliability: Extremely vulnerable to high ambient background noise (traffic, crowds) and user illness.
Security: Susceptible to audio replay attacks and AI voice cloning.

Comparative Vulnerability Summary

Modality	Primary Operational Failure Modes	Key Security Vulnerabilities
Vision-Input (Facial)	Variable lighting, glare, shadows, physical occlusions (masks/glasses).	Presentation attacks (2D prints, 3D masks) and deepfakes.
Voice Recognition	High ambient background noise, acoustic interference, vocal fatigue.	Audio replay attacks and AI voice cloning / speech spoofing.

Name: Sapna **Roll No:** 1826080 **Subject:** IT

Computer Architecture & Signal Flow

Functional Block Diagram and System Bus Interactions

Digital computers function through data, instructions, and control signals coordinating across hardware components via the System Bus.

Core Functional Blocks & Instruction Cycle

Principal Hardware Blocks

CPU: Contains ALU, Control Unit, and Registers.
Memory: RAM/ROM for active programs.
I/O: Bridges internal architecture with peripherals.

Instruction Cycle & Data Flow

Execution follows Fetch, Decode, and Execute phases. Program Counter provides memory addresses via the Address Bus, fetching instructions over the Data Bus.

System Bus Signal Classification

Bus Type	Nature / Direction	Primary Function
Address Bus	Unidirectional (CPU to Memory/I/O)	Specifies physical memory location or I/O device port address.
Data Bus	Bidirectional (CPU ↔ Memory/I/O)	Carries actual binary data words or machine instructions.
Control Bus	Bidirectional / Mixed	Transmits timing pulses, read/write commands, and interrupts.

Name: Sapna **Roll No:** 1826080 **Subject:** IT

Comparative Analysis of Programming Languages

Low-Level vs. High-Level Languages Across Architectural Parameters

Programming languages span from hardware-centric binary notation to human-readable semantic abstractions, balancing performance against developer productivity.

Language Hierarchy Overview

Low-Level Languages

Machine Language: Raw binary (1s and 0s) executable directly by the CPU.
Assembly Language: Symbolic mnemonics (MOV, ADD) translated via Assembler.

High-Level Languages

Languages like Python, Java, and C++ use English-like syntax, abstracting hardware registers and memory addresses via Compilers or Interpreters.

Comprehensive Feature Comparison Matrix

Parameter	Machine Language	Assembly Language	High-Level Language
Execution Speed	Maximum (Direct CPU execution)	Very High (Near-optimal)	Moderate to Fast
Hardware Dependence	Absolute (CPU specific)	High (Processor family)	Platform Independent
Translation Needed	None (Native binary)	Assembler required	Compiler / Interpreter
Primary Use Cases	Firmware bootstrap	Device drivers, embedded	Enterprise apps, AI/ML