

In the optimal case, you deploy an application to Kubernetes and it will run without issues. There may be many reasons why an application doesn't behave the way it should. For example, the application is misconfigured, the application exposes a runtime problem like a deadlock, or it can't connect to another microservice running inside of the cluster. `kubectl` offers a number of commands to troubleshoot an issue with an application running in a container. In this lab, you will try them one by one against an already running Pod.

Retrieving Container Logs

You can use the following command to see the logs for a running container:

`kubectl logs nginx`

```
$
$ kubectl logs nginx
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/04/09 13:52:00 [notice] 1#1: using the "epoll" event method
2023/04/09 13:52:00 [notice] 1#1: nginx/1.23.0
2023/04/09 13:52:00 [notice] 1#1: built by gcc 10.2.1 20210110 (Debian 10.2.1-6)
2023/04/09 13:52:00 [notice] 1#1: OS: Linux 5.15.0-56-generic
2023/04/09 13:52:00 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2023/04/09 13:52:00 [notice] 1#1: start worker processes
2023/04/09 13:52:00 [notice] 1#1: start worker process 30
2023/04/09 13:52:00 [notice] 1#1: start worker process 31
$
```

If you have multiple containers in your Pod, you can choose the container to view using the `-c` flag. The `nginx` Pod only runs a single container. Therefore, you do not have to explicitly spell out the container name. If you want, you can state the container. The following command has the same effect as the first one. We are targeting the container named `server`:

`kubectl logs nginx -c server`

```
2023/04/09 13:52:00 [notice] 1#1: start worker process 31
$ kubectl logs nginx -c server
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/04/09 13:52:00 [notice] 1#1: using the "epoll" event method
2023/04/09 13:52:00 [notice] 1#1: nginx/1.23.0
2023/04/09 13:52:00 [notice] 1#1: built by gcc 10.2.1 20210110 (Debian 10.2.1-6)
2023/04/09 13:52:00 [notice] 1#1: OS: Linux 5.15.0-56-generic
2023/04/09 13:52:00 [notice] 1#1: getrlimit(RLIMIT_NOFILE): 1048576:1048576
2023/04/09 13:52:00 [notice] 1#1: start worker processes
```

By default, `kubectl logs` lists the current logs and exits. If you instead want to continuously stream the logs back to the terminal without exiting, you can add the `-f` (follow) command-line flag.

`kubectl logs nginx -f`

```

2023/04/09 13:52:00 [notice] 1#1: start worker process 31
$ kubectl logs nginx -f
/docker-entrypoint.sh: /docker-entrypoint.d/ is not empty, will attempt to perform configuration
/docker-entrypoint.sh: Looking for shell scripts in /docker-entrypoint.d/
/docker-entrypoint.sh: Launching /docker-entrypoint.d/10-listen-on-ipv6-by-default.sh
10-listen-on-ipv6-by-default.sh: info: Getting the checksum of /etc/nginx/conf.d/default.conf
10-listen-on-ipv6-by-default.sh: info: Enabled listen on IPv6 in /etc/nginx/conf.d/default.conf
/docker-entrypoint.sh: Launching /docker-entrypoint.d/20-envsubst-on-templates.sh
/docker-entrypoint.sh: Launching /docker-entrypoint.d/30-tune-worker-processes.sh
/docker-entrypoint.sh: Configuration complete; ready for start up
2023/04/09 13:52:00 [notice] 1#1: using the "epoll" event method
2023/04/09 13:52:00 [notice] 1#1: nginx/1.23.0
2023/04/09 13:52:00 [notice] 1#1: built by gcc 10.2.1 20210110 (Debian 10.2.1-6)

```

Executing a Command in the Container

You can also use the exec command to execute a command in a running container:

```
kubectl exec -it nginx -- bash
```

This will provide you with an interactive shell inside the running container so that you can perform more debugging. To target a specific container, use the -c command-line option.

To leave the container's shell, run the exit command.

```

$ kubectl exec -it nginx -- bash
root@nginx:/# ls
bin    dev          docker-entrypoint.sh  home  lib64  mnt  proc  run  srv  tmp  var
boot  docker-entrypoint.d  etc          lib   media  opt  root  sbin sys  usr
root@nginx:/# df -h
Filesystem      Size  Used Avail Use% Mounted on
overlay          24G   15G   8.4G   63% /
tmpfs            64M    0    64M    0% /dev
/dev/vda2        24G   15G   8.4G   63% /etc/hosts
shm              64M    0    64M    0% /dev/shm
tmpfs            3.8G  12K   3.8G    1% /run/secrets/kubernetes.io/serviceaccount
tmpfs            2.0G    0    2.0G    0% /proc/acpi
tmpfs            2.0G    0    2.0G    0% /proc/scsi
tmpfs            2.0G    0    2.0G    0% /sys/firmware
root@nginx:/# exit
exit
$ 

```

Attaching a Terminal to the Container

If you don't have bash or some other terminal available within your container, you can always attach to the running process:

```
kubectl attach -it nginx
```

This will attach to the running process. It is similar to kubectl logs but will allow you to send input to the running process, assuming that process is set up to read from standard input.

Copying a File to the Container

You can also copy files to and from a container using the cp command. The first command copies the local file named debugger.sh to the container while renaming it at the same time:

```
kubectl cp /root/debugger.sh nginx:/tmp/ps.sh
```

You should now find the file in the correct directory inside of the container:

```
kubectl exec nginx -- ls /tmp/ps.sh
```

```
$
$ kubectl attach -it nginx
error: Unable to use a TTY - container server did not allocate one
If you don't see a command prompt, try pressing enter.

ddsd
ls
^C$
$ kubectl cp /root/debugger.sh nginx:/tmp/ps.sh
$ kubectl exec nginx -- ls /tmp/ps.sh
/tmp/ps.sh
$
```

The same command works if you need to download a file from the container to your local file system. Simply reverse the source and target file location:

```
kubectl cp nginx:/etc/nginx/nginx.conf /root/nginx.conf
```

The downloaded file is now available on your local machine:

```
$ kubectl cp nginx:/etc/nginx/nginx.conf /root/nginx.conf
tar: Removing leading '/' from member names
tar: Removing leading '/' from hard link targets
$ ls /root/nginx.conf
/root/nginx.conf
$
```

Retrieving Container Events

If you want to view Kubernetes events, you can use the `kubectl get events` command to see a list of the latest 10 events on all objects in a given namespace:

```
kubectl get events
```

Additionally, you can stream events as they happen by adding `--watch` to the `kubectl get events` command. You may also wish to include `-A` to see events in all namespaces.

```
see kubectl get -help for usage.
$ kubectl get events --watch -A
NAMESPACE   LAST SEEN   TYPE      REASON                OBJECT                MESSAGE
default      9m45s       Normal    NodeHasSufficientMemory node/controlplane     Node controlplane status is now: NodeHasSufficientMemory
default      9m45s       Normal    NodeHasNoDiskPressure node/controlplane     Node controlplane status is now: NodeHasNoDiskPressure
default      9m45s       Normal    NodeHasSufficientPID   node/controlplane     Node controlplane status is now: NodeHasSufficientPID
default      9m35s       Normal    Starting               node/controlplane     Starting kubelet.
default      9m35s       Normal    NodeHasSufficientMemory node/controlplane     Node controlplane status is now: NodeHasSufficientMemory
default      9m35s       Normal    NodeHasNoDiskPressure node/controlplane     Node controlplane status is now: NodeHasNoDiskPressure
default      9m35s       Normal    NodeHasSufficientPID   node/controlplane     Node controlplane status is now: NodeHasSufficientPID
default      9m35s       Normal    NodeAllocatableEnforced node/controlplane     Updated Node Allocatable limit across pods
default      9m23s       Normal    RegisteredNode         node/controlplane     Node controlplane event: Registered Node controlplane in Control
default      9m20s       Normal    Starting               node/controlplane
default      9m15s       Normal    NodeReady              node/controlplane     Node controlplane status is now: NodeReady
default      9m18s       Warning   FailedScheduling       pod/nginx             0/1 nodes are available: 1 node(s) had taint {node-role.kubernetes
), that the pod didn't tolerate.
default      9m5s       Normal    Scheduled              pod/nginx             Successfully assigned default/nginx to node01
default      9m4s       Normal    Pulling                pod/nginx             Pulling image "nginx:1.23.0"
```