



# Analyzing Hardware Parameters in GPU based HPC Platform



Saptarshi Bhowmik<sup>1</sup>, Nikhil Jain<sup>2</sup>, Abhinav Bhatele<sup>3</sup> and Xin Yuan<sup>1</sup>

1. Florida State University, 2. NVIDIA, Inc, 3. University of Maryland

## Goals

- Use discrete-event simulations to study various hardware design parameters and their impact on the performance of HPC workloads
- Study several parameters including network bandwidth, number of GPUs per node in the context of two most popular network topologies Fat-Tree and 1d-Dragonfly

## Introduction

Today's high-end HPC clusters employ many GPUs per node. The performance of applications on such a platform depends heavily on the interconnection network performance [1]. As such, it is important to understand the impact of hardware parameters on the overall application and system performance. In this research, we perform extensive simulation study to understand hardware parameters and their impact on the performance of HPC workload.

## Method

### System Configuration

- **Interconnection Network** Two network topology that is implemented in TraceR-CODES simulator, 1d - Dragonfly and Fat-Tree with Adaptive Routing.
- **Number of GPU's per node** from 1-GPU/Node, 2-GPU/Node, 4-GPU/Node and 8-GPU/Node configuration.
- **Link bandwidths** Base bandwidth  $x$  is 10 Gbps, from  $x/8$ ,  $x/4$ ,  $x/2$ ,  $x$ ,  $2x$ ,  $4x$ ,  $8x$  bandwidths are used.

Traces	Computation Intensive	Communication Intensive
Stencil4d	✗	✓
Kripke	✓	✗
Laghos	✓	✗
Subcomm-a2a	✗	✓
Sw4lite	✓	✓
Amg	✓	✓


Table: Application Traces

## Method

We are running 20 Workloads of randomly selected jobs from the above application from ranks 32, 64, 128, 256 and 512. We make sure that each rank of an application appears atleast 4 times across all 20 workloads.

## Results


**First**, Impact of Number of GPU's per node on Application performance.




- **GPUs per node** The communication intensive applications slowdown when the number of GPUs per node is increased, among the proxy applications only AMG shows slowdown.

## Results


**Second**, Impact of Bandwidth and different GPU's per node on Application Performance.



Ratio of Bandwidth,GPUs per node mapping for Stencil in Fat-Tree



Ratio of Bandwidth,GPUs per node for Subcom3d-a2a in 1d-Dragonfly



Ratio of Bandwidth,GPUs per node mapping for Sw4lite in Fat-Tree

## Result

- **Link Bandwidth** As we increase the number of GPU's per node. More bandwidth is needed to make the performance at par with lower GPU's per node configuration.
- In Subcom3d-a2a applications, applications with fewer ranks are performing better as more GPU's are mapped to one node, as there is more intra-node communication.

## Future Work

- Every application has a sweet spot where the performance is the best, figure out the sweet spot for other HPC applications.
- Try to study how other simulation environment and hardware design, such as NIC scheduling policies effect the performance of applications

## References

This work was performed under the auspices of the U.S. Department of Energy by Lawrence Livermore National Laboratory under Contract DE-AC52-07NA27344 (LLNL-POST-783752).