AWG strands
FEP- 6Y
Insulated

FEP insulated cables for operating voltages above 1 kV

Technical data

Silver-coated, heat-resistant,
flexible, insulated with Teflon®-FEP
Colour: natural/transparent

Operating temperature

-90°C to +200°C

Special features

Small outer diameter
High heat resistance
Low capacitance

Operating voltage at 50 Hz	AC test voltage	Outer diameter approx.
2.0 kV	10 kVeff	3.1 mm
2.0 kV	10 kVeff	3.5 mm
3.0 kV	15 kVeff	6.8 mm

FEP insulated cables for operating voltages above 1 kV

AWG strands
FEP- 6Y
Insulated

Net price including copper and silver

Cross-section and conductor structure	in EUR per 100 m on collection of at least 50 m	100 m	500 m	Ordering information
AWG 18 = 0.93 mm² with 7 x 0.40 silver-coated	442.00	340.00	272.00	HE 18 - 726 - 31
AWG 16 = 1.3 mm² with 19 x 0.29 silver-coated	520.00	400.00	320.00	HE 16 - 1929 - 35
AWG 10 = 4.7 mm² with 37 x 0.40 silver-coated	1,989.00	1,530.00	1,224.00	HE 10 - 3726 - 68

AWG strands
FEP- 6Y
Insulated

Hook-up wires with Teflon®-FEP insulation

Technical data

		Outer diameter approx.
Insulation wall thickness	approx. 0.25 mm	
Strand diameter	1.10 mm	
Conductor resistance at 20°C	approx. 40 Ω/km	
Insulation resistance at 20°C	1,500 MΩ x km	1.3 - 1.5 mm
Operating voltage/peak voltage	600 V / 900 V	
AC test voltage	2,500 V	
Operating temperature	-100°C to +200°C	

Hook-up wires with Teflon®-FEP insulation

AWG strands
FEP- 6Y
Insulated

Only available while stocks last!

Net price including copper

Cross-section and conductor structure	in EUR per 100 m on collection of at least 100 m	1,000 m	Ordering information
0.5 mm² with 27 x 0.15 tinned	*12.00*	*9.00*	Li 6Y 0.5 mm²

Colours usually available ex-stock: yellow-green