



My Basic Network Scan

Report generated by Tenable Nessus™

Sat, 09 May 2026 14:38:50 EDT

TABLE OF CONTENTS

Vulnerabilities by Plugin

• 53514 (1) - MS11-030: Vulnerability in DNS Resolution Could Allow Remote Code Execution (2509553) (r.....	5
• 108797 (1) - Unsupported Windows OS (remote).....	7
• 97833 (1) - MS17-010: Security Update for Microsoft Windows SMB Server (4013389) (ETERNALBLUE) (ETER.....	8
• 57608 (1) - SMB Signing not required.....	11
• 10114 (1) - ICMP Timestamp Request Remote Date Disclosure.....	13
• 10736 (8) - DCE Services Enumeration.....	15
• 11219 (3) - Nessus SYN scanner.....	20
• 11011 (2) - Microsoft Windows SMB Service Detection.....	21
• 10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure.....	22
• 10287 (1) - Traceroute Information.....	23
• 10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure.....	24
• 11936 (1) - OS Identification.....	25
• 19506 (1) - Nessus Scan Information.....	26
• 20094 (1) - VMware Virtual Machine Detection.....	28
• 25220 (1) - TCP/IP Timestamps Supported.....	29
• 35716 (1) - Ethernet Card Manufacturer Detection.....	30
• 45590 (1) - Common Platform Enumeration (CPE).....	31
• 53513 (1) - Link-Local Multicast Name Resolution (LLMNR) Detection.....	32
• 54615 (1) - Device Type.....	33
• 86420 (1) - Ethernet MAC Addresses.....	34
• 96982 (1) - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check).....	35
• 100871 (1) - Microsoft Windows SMB Versions Supported (remote check).....	36
• 106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check).....	37
• 110723 (1) - Target Credential Status by Authentication Protocol - No Credentials Provided.....	38
• 117886 (1) - OS Security Patch Assessment Not Available.....	40

• 209654 (1) - OS Fingerprints Detected.....	41
--	----

Vulnerabilities by Plugin

53514 (1) - MS11-030: Vulnerability in DNS Resolution Could Allow Remote Code Execution (2509553) (remote check)

Synopsis

Arbitrary code can be executed on the remote host through the installed Windows DNS client.

Description

A flaw in the way the installed Windows DNS client processes Link- local Multicast Name Resolution (LLMNR) queries can be exploited to execute arbitrary code in the context of the NetworkService account.

Note that Windows XP and 2003 do not support LLMNR and successful exploitation on those platforms requires local access and the ability to run a special application. On Windows Vista, 2008, 7, and 2008 R2, however, the issue can be exploited remotely.

See Also

<https://www.nessus.org/u?361871b1>

Solution

Microsoft has released a set of patches for Windows XP, 2003, Vista, 2008, 7, and 2008 R2.

Risk Factor

Critical

VPR Score

7.3

EPSS Score

0.4693

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.3 (CVSS2#E:F/RL:OF/RC:C)

STIG Severity

I

References

BID	47242
CVE	CVE-2011-0657
MSKB	2509553
XREF	IAVA:2011-A-0039-S
XREF	MSFT:MS11-030

Exploitable With

Core Impact (true) Metasploit (true)

Plugin Information

Published: 2011/04/21, Modified: 2023/10/17

Plugin Output

192.168.75.129 (udp/5355/llmnr)

108797 (1) - Unsupported Windows OS (remote)

Synopsis

The remote OS or service pack is no longer supported.

Description

The remote version of Microsoft Windows is either missing a service pack or is no longer supported. As a result, it is likely to contain security vulnerabilities.

See Also

<https://support.microsoft.com/en-us/lifecycle>

Solution

Upgrade to a supported service pack or operating system

Risk Factor

Critical

CVSS v3.0 Base Score

10.0 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H)

CVSS v2.0 Base Score

10.0 (CVSS2#AV:N/AC:L/Au:N/C:C/I:C/A:C)

References

XREF IAVA:0001-A-0501

Plugin Information

Published: 2018/04/03, Modified: 2025/10/21

Plugin Output

192.168.75.129 (tcp/0)

The following Windows version is installed and not supported:

Microsoft Windows 7 Ultimate

97833 (1) - MS17-010: Security Update for Microsoft Windows SMB Server (4013389) (ETERNALBLUE) (ETERNALCHAMPION) (ETERNALROMANCE) (ETERNALSYNERGY) (WannaCry) (EternalRocks) (Petya) (uncredentialed check)

Synopsis

The remote Windows host is affected by multiple vulnerabilities.

Description

The remote Windows host is affected by the following vulnerabilities :

- Multiple remote code execution vulnerabilities exist in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit these vulnerabilities, via a specially crafted packet, to execute arbitrary code. (CVE-2017-0143, CVE-2017-0144, CVE-2017-0145, CVE-2017-0146, CVE-2017-0148)
- An information disclosure vulnerability exists in Microsoft Server Message Block 1.0 (SMBv1) due to improper handling of certain requests. An unauthenticated, remote attacker can exploit this, via a specially crafted packet, to disclose sensitive information. (CVE-2017-0147)

ETERNALBLUE, ETERNALCHAMPION, ETERNALROMANCE, and ETERNALSYNERGY are four of multiple Equation Group vulnerabilities and exploits disclosed on 2017/04/14 by a group known as the Shadow Brokers. WannaCry / WannaCrypt is a ransomware program utilizing the ETERNALBLUE exploit, and EternalRocks is a worm that utilizes seven Equation Group vulnerabilities. Petya is a ransomware program that first utilizes CVE-2017-0199, a vulnerability in Microsoft Office, and then spreads via ETERNALBLUE.

See Also

<http://www.nessus.org/u?68fc8eff>

<http://www.nessus.org/u?321523eb>

<http://www.nessus.org/u?065561d0>

<http://www.nessus.org/u?d9f569cf>

<https://blogs.technet.microsoft.com/filecab/2016/09/16/stop-using-smb1/>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

<https://github.com/stamparm/EternalRocks/>

<http://www.nessus.org/u?59db5b5b>

Solution

Microsoft has released a set of patches for Windows Vista, 2008, 7, 2008 R2, 2012, 8.1, RT 8.1, 2012 R2, 10, and 2016. Microsoft has also released emergency patches for Windows operating systems that are no longer supported, including Windows XP, 2003, and 8.

For unsupported Windows operating systems, e.g. Windows XP, Microsoft recommends that users discontinue the use of SMBv1. SMBv1 lacks security features that were included in later SMB versions. SMBv1 can be disabled by following the vendor instructions provided in Microsoft KB2696547. Additionally, US-CERT recommends that users block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

High

CVSS v3.0 Base Score

8.8 (CVSS:3.0/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H)

CVSS v3.0 Temporal Score

8.4 (CVSS:3.0/E:H/RL:O/RC:C)

VPR Score

9.8

EPSS Score

0.9432

CVSS v2.0 Base Score

9.3 (CVSS2#AV:N/AC:M/Au:N/C:C/I:C/A:C)

CVSS v2.0 Temporal Score

8.1 (CVSS2#E:H/RL:OF/RC:C)

STIG Severity

I

References

BID	96703
BID	96704
BID	96705
BID	96706
BID	96707
BID	96709
CVE	CVE-2017-0143
CVE	CVE-2017-0144

CVE	CVE-2017-0145
CVE	CVE-2017-0146
CVE	CVE-2017-0147
CVE	CVE-2017-0148
MSKB	4012212
MSKB	4012213
MSKB	4012214
MSKB	4012215
MSKB	4012216
MSKB	4012217
MSKB	4012606
MSKB	4013198
MSKB	4013429
MSKB	4012598
XREF	EDB-ID:41891
XREF	EDB-ID:41987
XREF	MSFT:MS17-010
XREF	IAVA:2017-A-0065
XREF	CISA-KNOWN-EXPLOITED:2022/05/03
XREF	CISA-KNOWN-EXPLOITED:2022/08/10
XREF	CISA-KNOWN-EXPLOITED:2022/04/15
XREF	CISA-KNOWN-EXPLOITED:2022/04/27
XREF	CISA-KNOWN-EXPLOITED:2022/06/14

Exploitable With

CANVAS (true) Core Impact (true) Metasploit (true)

Plugin Information

Published: 2017/03/20, Modified: 2025/12/29

Plugin Output

192.168.75.129 (tcp/445/cifs)

Sent:
00000054ff534d4225000000001803c8000000000000000000000000e8ee0008000110000000
00ffffff0000000000000000000000005400000054000200230000001100005c00500049005000
45005c0000000000

Received:
ff534d4225050200c09803c800000000000000000000000000000000000000e8ee00080001000000

57608 (1) - SMB Signing not required

Synopsis

Signing is not required on the remote SMB server.

Description

Signing is not required on the remote SMB server. An unauthenticated, remote attacker can exploit this to conduct man-in-the-middle attacks against the SMB server.

See Also

<http://www.nessus.org/u?df39b8b3>

<http://technet.microsoft.com/en-us/library/cc731957.aspx>

<http://www.nessus.org/u?74b80723>

<https://www.samba.org/samba/docs/current/man-html/smb.conf.5.html>

<http://www.nessus.org/u?a3cac4ea>

Solution

Enforce message signing in the host's configuration. On Windows, this is found in the policy setting 'Microsoft network server: Digitally sign communications (always)'. On Samba, the setting is called 'server signing'. See the 'see also' links for further details.

Risk Factor

Medium

CVSS v3.0 Base Score

5.3 (CVSS:3.0/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:L/A:N)

CVSS v3.0 Temporal Score

4.6 (CVSS:3.0/E:U/RL:O/RC:C)

CVSS v2.0 Base Score

5.0 (CVSS2#AV:N/AC:L/Au:N/C:N/I:P/A:N)

CVSS v2.0 Temporal Score

3.7 (CVSS2#E:U/RL:OF/RC:C)

Plugin Information

Published: 2012/01/19, Modified: 2022/10/05

Plugin Output

192.168.75.129 (tcp/445/cifs)

10114 (1) - ICMP Timestamp Request Remote Date Disclosure

Synopsis

It is possible to determine the exact time set on the remote host.

Description

The remote host answers to an ICMP timestamp request. This allows an attacker to know the date that is set on the targeted machine, which may assist an unauthenticated, remote attacker in defeating time-based authentication protocols.

Timestamps returned from machines running Windows Vista / 7 / 2008 / 2008 R2 are deliberately incorrect, but usually within 1000 seconds of the actual system time.

Solution

Filter out the ICMP timestamp requests (13), and the outgoing ICMP timestamp replies (14).

Risk Factor

Low

VPR Score

2.2

EPSS Score

0.0037

CVSS v2.0 Base Score

2.1 (CVSS2#AV:L/AC:L/Au:N/C:P/I:N/A:N)

References

CVE	CVE-1999-0524
XREF	CWE:200

Plugin Information

Published: 1999/08/01, Modified: 2024/10/07

Plugin Output

192.168.75.129 (icmp/0)

The ICMP timestamps seem to be in little endian format (not in network format)
The difference between the local and remote clocks is -784 seconds.

10736 (8) - DCE Services Enumeration

Synopsis

A DCE/RPC service is running on the remote host.

Description

By sending a Lookup request to the portmapper (TCP 135 or epmapper PIPE) it was possible to enumerate the Distributed Computing Environment (DCE) services running on the remote port. Using this information it is possible to connect and bind to each service by sending an RPC request to the remote port/pipe.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/08/26, Modified: 2021/10/04

Plugin Output

192.168.75.129 (tcp/135/epmap)

The following DCERPC services are available locally :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WindowsShutdown

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc08D490

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WindowsShutdown

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc08D490

Object UUID : 6d726574-7273-0076-0000-000000000000

```

UUID : c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1.0
Description : Unknown RPC service
Annotation : Impl friendly name
Type : Local RPC service
Named pipe : LRPC-efc3c9e0b7a92d5dae

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000001
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Local RPC service
Named pipe : WMsgKRpc08FA01

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 06bba54a-be05-49f9-b0a0-30f790261023, version 1.0
Description : Unknown RPC service
Annotation : Security Center
Type : Local RPC service
Named pipe : OLE3FE40210F4C9481DAF70B86085C9

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 4b112204-0e19-11d3-b42b-0000f81feb9f, version 1.0
Description : SSDP service
Windows process : unknow
Type : Local RPC service
Named pipe : LRPC-63bd15f164940bf5fe

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Local RPC service
Named pipe : LRPC-f1d4ed776040b6e7d0

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234 [...]

```

192.168.75.129 (tcp/445/cifs)

```

The following DCERPC services are available remotely :

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\InitShutdown
Netbios name : \\WIN-845Q99004PP

Object UUID : b08669ee-8cb5-43a5-a017-84fe00000000
UUID : 76f226c3-ec14-4325-8a99-6a46348418af, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\InitShutdown
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
Named pipe : \pipe\lsass
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service

```



```

Named pipe : \PIPE\protected_storage
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 1ff70682-0a51-30e8-076d-740be8cee98b, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 378e52b0-c0a9-11cf-822d-00aa0051e40f, version 1.0
Description : Scheduler Service
Windows process : svchost.exe
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name : \\WIN-845Q99004PP

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 552d076a-cb29-4e44-8b6a-d15e59e2c0af, version 1.0
Description : Unknown RPC service
Annotation : IP Transition Configuration endpoint
Type : Remote RPC service
Named pipe : \PIPE\atsvc
Netbios name [...]

```

192.168.75.129 (tcp/49152/dce-rpc)

The following DCERPC services are available on TCP port 49152 :

```

Object UUID : 765294ba-60bc-48b8-92e9-89fd77769d91
UUID : d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49152
IP : 192.168.75.129

```

192.168.75.129 (tcp/49153/dce-rpc)

The following DCERPC services are available on TCP port 49153 :

```

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1.0
Description : Unknown RPC service
Annotation : Event log TCPIP
Type : Remote RPC service
TCP Port : 49153
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 30adc50c-5cbc-46ce-9a0e-91914789e23c, version 1.0
Description : Unknown RPC service
Annotation : NRP server endpoint
Type : Remote RPC service

```

```

TCP Port : 49153
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d5, version 1.0
Description : DHCP Client Service
Windows process : svchost.exe
Annotation : DHCP Client LRPC Endpoint
Type : Remote RPC service
TCP Port : 49153
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 3c4728c5-f0ab-448b-bda1-6ce01eb0a6d6, version 1.0
Description : Unknown RPC service
Annotation : DHCPv6 Client LRPC Endpoint
Type : Remote RPC service
TCP Port : 49153
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 06bba54a-be05-49f9-b0a0-30f790261023, version 1.0
Description : Unknown RPC service
Annotation : Security Center
Type : Remote RPC service
TCP Port : 49153
IP : 192.168.75.129

```

192.168.75.129 (tcp/49154/dce-rpc)

The following DCERPC services are available on TCP port 49154 :

```

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 86d35949-83c9-4044-b424-db363231fd0c, version 1.0
Description : Unknown RPC service
Type : Remote RPC service
TCP Port : 49154
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 552d076a-cb29-4e44-8b6a-d15e59e2c0af, version 1.0
Description : Unknown RPC service
Annotation : IP Transition Configuration endpoint
Type : Remote RPC service
TCP Port : 49154
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : a398e520-d59a-4bdd-aa7a-3c1e0303a511, version 1.0
Description : Unknown RPC service
Annotation : IKE/Authip API
Type : Remote RPC service
TCP Port : 49154
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 98716d03-89ac-44c7-bb8c-285824e51c4a, version 1.0
Description : Unknown RPC service
Annotation : XactSrv service
Type : Remote RPC service
TCP Port : 49154
IP : 192.168.75.129

```

192.168.75.129 (tcp/49155/dce-rpc)

The following DCERPC services are available on TCP port 49155 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 367abb81-9844-35f1-ad32-98f038001003, version 2.0
Description : Service Control Manager
Windows process : svchost.exe
Type : Remote RPC service
TCP Port : 49155
IP : 192.168.75.129

192.168.75.129 (tcp/49156/dce-rpc)

The following DCERPC services are available on TCP port 49156 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 6b5bdd1e-528c-422c-af8c-a4079be4fe48, version 1.0
Description : Unknown RPC service
Annotation : Remote Fw APIs
Type : Remote RPC service
TCP Port : 49156
IP : 192.168.75.129

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345678-1234-abcd-ef00-0123456789ab, version 1.0
Description : IPsec Services (Windows XP & 2003)
Windows process : lsass.exe
Annotation : IPSec Policy agent endpoint
Type : Remote RPC service
TCP Port : 49156
IP : 192.168.75.129

192.168.75.129 (tcp/49157/dce-rpc)

The following DCERPC services are available on TCP port 49157 :

Object UUID : 00000000-0000-0000-0000-000000000000
UUID : 12345778-1234-abcd-ef00-0123456789ac, version 1.0
Description : Security Account Manager
Windows process : lsass.exe
Type : Remote RPC service
TCP Port : 49157
IP : 192.168.75.129

11219 (3) - Nessus SYN scanner

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Plugin Information

Published: 2009/02/04, Modified: 2025/07/14

Plugin Output

192.168.75.129 (tcp/135/epmap)

```
Port 135/tcp was found to be open
```

192.168.75.129 (tcp/139/smb)

```
Port 139/tcp was found to be open
```

192.168.75.129 (tcp/445/cifs)

```
Port 445/tcp was found to be open
```

11011 (2) - Microsoft Windows SMB Service Detection

Synopsis

A file / print sharing service is listening on the remote host.

Description

The remote service understands the CIFS (Common Internet File System) or Server Message Block (SMB) protocol, used to provide shared access to files, printers, etc between nodes on a network.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2002/06/05, Modified: 2021/02/11

Plugin Output

192.168.75.129 (tcp/139/smb)

```
An SMB server is running on this port.
```

192.168.75.129 (tcp/445/cifs)

```
A CIFS server is running on this port.
```

10150 (1) - Windows NetBIOS / SMB Remote Host Information Disclosure

Synopsis

It was possible to obtain the network name of the remote host.

Description

The remote host is listening on UDP port 137 or TCP port 445, and replies to NetBIOS nbtscan or SMB requests.

Note that this plugin gathers information to be used in other plugins, but does not itself generate a report.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/10/12, Modified: 2021/02/10

Plugin Output

192.168.75.129 (udp/137/netbios-ns)

The following 6 NetBIOS names have been gathered :

WIN-845Q99004PP	= Computer name
WORKGROUP	= Workgroup / Domain name
WIN-845Q99004PP	= File Server Service
WORKGROUP	= Browser Service Elections
WORKGROUP	= Master Browser
__MSBROWSE__	= Master Browser

The remote host has the following MAC address on its adapter :

00:0c:29:20:0c:09

10287 (1) - Traceroute Information

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 1999/11/27, Modified: 2026/04/27

Plugin Output

192.168.75.129 (udp/0)

```
For your information, here is the traceroute from 192.168.75.128 to 192.168.75.129 :
192.168.75.128
192.168.75.129

Hop Count: 1
```

10785 (1) - Microsoft Windows SMB NativeLanManager Remote System Information Disclosure

Synopsis

It was possible to obtain information about the remote operating system.

Description

Nessus was able to obtain the remote operating system name and version (Windows and/or Samba) by sending an authentication request to port 139 or 445. Note that this plugin requires SMB to be enabled on the host.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2001/10/17, Modified: 2021/09/20

Plugin Output

192.168.75.129 (tcp/445/cifs)

```
The remote Operating System is : Windows 7 Ultimate 7601 Service Pack 1
The remote native LAN manager is : Windows 7 Ultimate 6.1
The remote SMB Domain Name is : WIN-845Q990O4PP
```


11936 (1) - OS Identification

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2003/12/09, Modified: 2025/06/03

Plugin Output

192.168.75.129 (tcp/0)

```
Remote operating system : Microsoft Windows 7 Ultimate
Confidence level : 99
Method : MSRPC
```

```
The remote host is running Microsoft Windows 7 Ultimate
```

19506 (1) - Nessus Scan Information

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2005/08/26, Modified: 2026/03/04

Plugin Output

192.168.75.129 (tcp/0)

Information about this scan :

```
Nessus version : 10.12.0
Nessus build : 20184
Plugin feed version : 202605090804
Scanner edition used : Nessus
Scanner OS : LINUX
Scanner distribution : debian10-x86-64
Scan type : Normal
```

```
Scan name : My Basic Network Scan
Scan policy used : Basic Network Scan
Scanner IP : 192.168.75.128
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : 89.658 ms
Thorough tests : no
Experimental tests : no
Scan for Unpatched Vulnerabilities : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin did not launch)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None
Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2026/5/9 14:36 EDT (UTC -04:00)
Scan duration : 153 sec
Scan for malware : no
Fully Scan Operational Technology devices : yes
Safely Scan Operational Technology devices with OT Discovery : no
```

20094 (1) - VMware Virtual Machine Detection

Synopsis

The remote host is a VMware virtual machine.

Description

According to the MAC address of its network adapter, the remote host is a VMware virtual machine.

Solution

Since it is physically accessible through the network, ensure that its configuration matches your organization's security policy.

Risk Factor

None

Plugin Information

Published: 2005/10/27, Modified: 2019/12/11

Plugin Output

192.168.75.129 (tcp/0)

```
The remote host is a VMware virtual machine.
```

25220 (1) - TCP/IP Timestamps Supported

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2007/05/16, Modified: 2023/10/17

Plugin Output

192.168.75.129 (tcp/0)

35716 (1) - Ethernet Card Manufacturer Detection

Synopsis

The manufacturer can be identified from the Ethernet OUI.

Description

Each ethernet MAC address starts with a 24-bit Organizationally Unique Identifier (OUI). These OUIs are registered by IEEE.

See Also

<https://standards.ieee.org/faqs/regauth.html>

<http://www.nessus.org/u?794673b4>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2009/02/19, Modified: 2020/05/13

Plugin Output

192.168.75.129 (tcp/0)

The following card manufacturers were identified :

00:0C:29:20:0C:09 : VMware, Inc.

45590 (1) - Common Platform Enumeration (CPE)

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2010/04/21, Modified: 2026/01/05

Plugin Output

192.168.75.129 (tcp/0)

```
The remote operating system matched the following CPE :
```

```
cpe:/o:microsoft:windows_7::ultimate -> Microsoft Windows 7
```

53513 (1) - Link-Local Multicast Name Resolution (LLMNR) Detection

Synopsis

The remote device supports LLMNR.

Description

The remote device answered to a Link-local Multicast Name Resolution (LLMNR) request. This protocol provides a name lookup service similar to NetBIOS or DNS. It is enabled by default on modern Windows versions.

See Also

<http://www.nessus.org/u?51eae65d>

<http://technet.microsoft.com/en-us/library/bb878128.aspx>

Solution

Make sure that use of this software conforms to your organization's acceptable use and security policies.

Risk Factor

None

Plugin Information

Published: 2011/04/21, Modified: 2023/10/17

Plugin Output

192.168.75.129 (udp/5355/llmnr)

```
According to LLMNR, the name of the remote host is 'WIN-845Q99004PP'.
```


54615 (1) - Device Type

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2011/05/23, Modified: 2025/03/12

Plugin Output

192.168.75.129 (tcp/0)

```
Remote device type : general-purpose  
Confidence level : 99
```

86420 (1) - Ethernet MAC Addresses

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2015/10/16, Modified: 2025/06/10

Plugin Output

192.168.75.129 (tcp/0)

```
The following is a consolidated list of detected MAC addresses:  
- 00:0C:29:20:0C:09
```

96982 (1) - Server Message Block (SMB) Protocol Version 1 Enabled (uncredentialed check)

Synopsis

The remote host supports the SMBv1 protocol.

Description

The remote host (Windows and/or Samba server) supports Server Message Block Protocol version 1 (SMBv1). Microsoft recommends that users discontinue the use of SMBv1 due to the lack of security features that were included in later SMB versions. Additionally, most security and compliance agencies recommend that users disable SMBv1 per SMB best practices.

See Also

<http://www.nessus.org/u?59bfc3ef>

<http://www.nessus.org/u?b9d9ebf9>

<http://www.nessus.org/u?8dcab5e4>

<http://www.nessus.org/u?234f8ef8>

<http://www.nessus.org/u?4c7e0cf3>

Solution

Disable SMBv1 according to the vendor instructions in Microsoft KB2696547. Additionally, block SMB directly by blocking TCP port 445 on all network boundary devices. For SMB over the NetBIOS API, block TCP ports 137 / 139 and UDP ports 137 / 138 on all network boundary devices.

Risk Factor

None

References

XREF IAVT:0001-T-0710

Plugin Information

Published: 2017/02/03, Modified: 2025/08/13

Plugin Output

192.168.75.129 (tcp/445/cifs)

```
The remote host supports SMBv1.
```

100871 (1) - Microsoft Windows SMB Versions Supported (remote check)

Synopsis

It was possible to obtain information about the version of SMB running on the remote host.

Description

Nessus was able to obtain the version of SMB running on the remote host by sending an authentication request to port 139 or 445.

Note that this plugin is a remote check and does not work on agents.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2017/06/19, Modified: 2019/11/22

Plugin Output

192.168.75.129 (tcp/445/cifs)

```
The remote host supports the following versions of SMB :  
SMBv1  
SMBv2
```

106716 (1) - Microsoft Windows SMB2 and SMB3 Dialects Supported (remote check)

Synopsis

It was possible to obtain information about the dialects of SMB2 and SMB3 available on the remote host.

Description

Nessus was able to obtain the set of SMB2 and SMB3 dialects running on the remote host by sending an authentication request to port 139 or 445.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2018/02/09, Modified: 2020/03/11

Plugin Output

192.168.75.129 (tcp/445/cifs)

The remote host supports the following SMB dialects :

version	_introduced in windows version_
2.0.2	Windows 2008
2.1	Windows 7

The remote host does NOT support the following SMB dialects :

version	_introduced in windows version_
2.2.2	Windows 8 Beta
2.2.4	Windows 8 Beta
3.0	Windows 8
3.0.2	Windows 8.1
3.1	Windows 10
3.1.1	Windows 10

110723 (1) - Target Credential Status by Authentication Protocol - No Credentials Provided

Synopsis

Nessus was able to find common ports used for local checks, however, no credentials were provided in the scan policy.

Description

Nessus was not able to successfully authenticate directly to the remote target on an available authentication protocol. Nessus was able to connect to the remote port and identify that the service running on the port supports an authentication protocol, but Nessus failed to authenticate to the remote service using the provided credentials. There may have been a protocol failure that prevented authentication from being attempted or all of the provided credentials for the authentication protocol may be invalid. See plugin output for error details.

Please note the following :

- This plugin reports per protocol, so it is possible for valid credentials to be provided for one protocol and not another. For example, authentication may succeed via SSH but fail via SMB, while no credentials were provided for an available SNMP service.
- Providing valid credentials for all available authentication protocols may improve scan coverage, but the value of successful authentication for a given protocol may vary from target to target depending upon what data (if any) is gathered from the target via that protocol. For example, successful authentication via SSH is more valuable for Linux targets than for Windows targets, and likewise successful authentication via SMB is more valuable for Windows targets than for Linux targets.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0504

Plugin Information

Published: 2018/06/27, Modified: 2024/04/19

Plugin Output

192.168.75.129 (tcp/0)

SMB was detected on port 445 but no credentials were provided.

SMB local checks were not enabled.

117886 (1) - OS Security Patch Assessment Not Available

Synopsis

OS Security Patch Assessment is not available.

Description

OS Security Patch Assessment is not available on the remote host.

This does not necessarily indicate a problem with the scan.

Credentials may not have been provided, OS security patch assessment may not be supported for the target, the target may not have been identified, or another issue may have occurred that prevented OS security patch assessment from being available. See plugin output for details.

This plugin reports non-failure information impacting the availability of OS Security Patch Assessment. Failure information is reported by plugin 21745 : 'OS Security Patch Assessment failed'. If a target host is not supported for OS Security Patch Assessment, plugin 110695 : 'OS Security Patch Assessment Checks Not Supported' will report concurrently with this plugin.

Solution

n/a

Risk Factor

None

References

XREF IAVB:0001-B-0515

Plugin Information

Published: 2018/10/02, Modified: 2021/07/12

Plugin Output

192.168.75.129 (tcp/0)

The following issues were reported :

```
- Plugin      : no_local_checks_credentials.nasl
  Plugin ID   : 110723
  Plugin Name : Target Credential Status by Authentication Protocol - No Credentials Provided
  Message     :
  Credentials were not provided for detected SMB service.
```


209654 (1) - OS Fingerprints Detected

Synopsis

Multiple OS fingerprints were detected.

Description

Using a combination of remote probes (TCP/IP, SMB, HTTP, NTP, SNMP, etc), it was possible to gather one or more fingerprints from the remote system. While the highest-confidence result was reported in plugin 11936, "OS Identification", the complete set of fingerprints detected are reported here.

Solution

n/a

Risk Factor

None

Plugin Information

Published: 2025/02/26, Modified: 2025/03/03

Plugin Output

192.168.75.129 (tcp/0)

Following OS Fingerprints were found

Remote operating system : Microsoft Windows Server 2012 R2
Confidence level : 56
Method : MLSinFP
Type : unknown
Fingerprint : unknown

Remote operating system : Microsoft Windows 7
Microsoft Windows Server 2008 R2
Confidence level : 70
Method : Misc
Type : general-purpose
Fingerprint : unknown

Remote operating system : Microsoft Windows
Confidence level : 70
Method : SinFP
Type : general-purpose
Fingerprint : SinFP:
P1:B11113:F0x12:W8192:00204ffff:M1460:
P2:B11113:F0x12:W8192:00204ffff010303080402080affffffff44454144:M1460:
P3:B00000:F0x00:W0:00:M0
P4:191800_7_p=139

Remote operating system : Windows 6.1
Confidence level : 70

Method : smb
Type : general-purpose
Fingerprint : unknown

Remote operating system : Microsoft Windows 7 Ultimate
Confidence level : 99
Method : MSRPC
Type : general-purpose
Fingerprint : unknown