

Programming Using C++ Level 1

Break Statement



Programming Using C++

Level 1

Break Statement

Definition

◆ The break statement is used to immediately stop a loop and continue execution with the statement after the loop.

Explanation

- ◆ In this program, a for loop searches through the array for the value 20.
- ◆ When `arr[i] == searchFor` becomes true, the program prints the index of the element and uses `break` to stop the loop immediately.
- ◆ Without `break`, the loop would continue checking the remaining elements even after finding 20.

Steps in main()

1. Create an integer array containing 10 elements.
2. Set searchFor to 20.
3. Start a for loop from index 0.
4. Compare arr[i] with searchFor.
5. If they are equal, print the index.
6. Use break to exit the loop.
7. Continue with the code after the loop.

💡 Example

Array:

10, 20, 44, 55, 33, 22, 99, 88, 99, 100

The loop checks:

0 → 10 ≠ 20

1 → 20 = 20 → found

The program prints:

Element 20 found at index: 1

➡ Result

The value 20 is found at index 1, and the break statement immediately stops the for loop.

Note

Array indexes start from 0, so the first element is at index 0 and the second element is at index 1.

⊘ Warning

◆ break only stops the nearest loop or switch statement containing it. It does not stop the entire program.

✦✦ Summary

- ✓ break immediately exits the current loop.
- ✓ It is useful when the required element or condition has already been found.
- ✓ In this example, break prevents unnecessary searching after finding 20.

Thank you 😊