CSS Cheat Sheet

Properties:

Background

Property	Values	Notes
background-color:	you can use a color name (red) or a hexadecimal code (#ff000) examples: background-color: red; background-color: #ff0000;	For a full list of color names: http://www.w3schools.co m/cssref/css_colorname s.asp
background-image:	url(image.jpg);	
background-attachment:	scroll; scrolls the background with the page fixed; background stays fixed when scrolling	
background-repeat:	repeat; tiles the image in both directions repeat-x; tiles the image horizontally, along the x axis repeat-y; tiles the image vertically, along the y axis no-repeat; doesn't tile the image	

Text

Property	Values	Notes
font-family:	Helvetica, Arial, Sans-Serif; Times New Roman, Serif;	Can have one font with fallback fonts. Any font names with spaces need to be wrapped in quotes.
font-size:	font-size: 20px;	Pixels (px), Ems (em), Rems (rem) are the most common values.
font-weight:	normal; bold; bolder; lighter; 100, 200, 300, 400, 500, 600, 700, 800 or 900;	When using a value for font-weight 400 is the same as normal and 700 is the same as bold.

font-style:	normal; text is shown normally italic; text is shown in italic	
text-align:	left; aligns text to the left center; centers text right; aligns text to the right justify; stretches the lines so that each line has equal width	
text-decoration:	none; displays normal text underline; displays a line below the text overline; displays a line above the text line-through; displays a line through the text	
color:	you can use a color name (red) or a hexadecimal code (#ff000) examples: color: red; color: #ff0000;	For a full list of color names: http://www.w3schools.co m/cssref/css_colorname s.asp
line-height:	line-height: 20px;	Pixels (px), Ems (em), Rems (rem) are the most common values.

Border

Property	Values	Notes
border-width:	border-width: 3px;	Adjusts border thickness, default is 1px
border-color:	you can use a color name (red) or a hexadecimal code (#ff000) examples: border-color: red; border-color: #ff0000;	Applies a color to the border, default is black
border-style:	none, dotted, dashed, solid, double, groove, ridge	Changes the appearance of the border, default is none
border-radius:	border-radius: 10px; border-radius: 50%	Defines the shape of a borders corners. Percentages (%), Pixels (px), Ems (em), Rems (rem) are the most common values.

Box-Model

Property	Values	Notes
display:	inline; block; inline-block; none; hides the element	This one is tricky, checkout http://learnlayout.com/display.html for really good explanation.
float:	none; element is not floated and will be displayed just where it occurs in the text left; floats an element to the left right; floats an element to the right	
width:	width: 50% width: 200px;	Defines a set width for an item. Percentages (%), Pixels (px), Ems (em), Rems (rem) are the most common values.
min-width: max-width:	min-width: 50% min-width: 200px; max-width: 50% max-width: 200px;	min-width prevents the element from becoming smaller than the specified value. max-width prevents the element from becoming larger than the specified
height:	height: 50% height: 200px;	value. Defines a set height for an item. Percentages (%), Pixels (px), Ems (em), Rems (rem) are the most common values.
min-height: max-height:	min-height: 50% min-height: 200px; max-height: 50% max-height: 200px;	min-height prevents the element from becoming smaller than the specified value.
		max-height prevents the element from becoming larger than the specified value.

margin:	margin: auto; let's browser calculate the margin margin: 20px; margin: 2%;	Adds space around the outside of an element. Keeps items outside of the element from touching the border.
padding:	margin: 20px; margin: 2%;	Adds space around the inside of an element. Keeps items contained within the element from touching the border.

Selectors:

Selector	Definition	Example
:hover	Applies styles to an element when the mouse cursor is currently over it.	p:hover { color: orange; }
:active	Applies styles when a link is activated (clicked on)	a:active { color: green; }
:visited	Applies styles to a link when it has been visited in the past in the browser.	a:visited { color: purple; }

For a full list of CSS properties and selectors visit http://css-tricks.com/almanac/