

MFES

January 1, 2018

Contents

1	Agenda	2
2	Appointment	3
3	HealthProfessional	3
4	Hospital	5
5	Patient	8
6	Person	9
7	SafetyNetHospital	10
8	Schedule	11
9	Specialty	13
10	Surgery	13
11	Task	15
12	Training	16
13	Treatment	17
14	Types	18
15	PersonTest	18
16	RunTests	21
17	SafetyNetHospitalTest	21
18	TaskTest	27
19	TrainingTest	32

1 Agenda

```
class Agenda
instance variables

private healthProfessional : HealthProfessional;
private agenda : set of (Schedule);

inv card agenda >= 0;

operations
-- Agenda constructor

public Agenda : HealthProfessional ==> Agenda
  Agenda(h) == (healthProfessional := h; agenda := {}); return self
post healthProfessional = h and agenda = {};

-- Returns the agenda's health professional

pure public getHealthProfessional : () ==> HealthProfessional
  getHealthProfessional() == (return healthProfessional);

-- Returns the agenda's schedules

pure public getAgenda : () ==> set of (Schedule)
  getAgenda() == (return agenda);

-- Adds a schedule to the agenda

public addSchedule : Schedule ==> ()
  addSchedule(s) == (agenda := agenda union {s})
pre s not in set agenda and forall sch in set agenda & not overlap(s, sch)
post s in set agenda;

-- Removes a schedule from the agenda

public removeSchedule : Schedule ==> ()
  removeSchedule(s) == (agenda := agenda \ {s})
pre s in set agenda
post s not in set agenda;

-- Checks if a schedule overlaps with other schedule

pure public overlap: Schedule * Schedule ==> bool
  overlap(t1, t2) == (return t1.overlap(t1, t2));
end Agenda
```

Function or operation	Line	Coverage	Calls
Agenda	11	100.0%	44
addSchedule	24	100.0%	84
getAgenda	20	100.0%	208
getHealthProfessional	16	100.0%	1175
overlap	36	100.0%	40
removeSchedule	30	100.0%	64
Agenda.vdmpp		100.0%	1615

2 Appointment

```
class Appointment is subclass of Task

instance variables
  private priority : Types'Priority;

  inv priority <> nil;
  inv medicalAssoc.getType() = <Doctor>;
operations
  -- Appointment constructor
  public Appointment: HealthProfessional * Schedule * Patient * Hospital==> Appointment
    Appointment(d, s, p, h) == (medicalAssoc := d; priority := <Medium>; Task(d, s, p, h, <
      Appointment>))

  post medicalAssoc = d and priority = <Medium>;

  -- Urgency Appointment constructor
  public Appointment: HealthProfessional * Types'Priority * Schedule * Patient * Hospital ==>
    Appointment
    Appointment(d, p, s, pat, h) == (medicalAssoc := d; priority := p; Task(d, s, pat, h, <
      Urgencies>))
  pre p <> nil
  post medicalAssoc = d and priority = p;

  -- Returns the appointment's priority
  pure public getPriority : () ==> Types'Priority
    getPriority() == (return priority);

  -- Sets the appointment's priority
  public setPriority : Types'Priority ==> ()
    setPriority(p) == (priority := p)

  pre taskType = <Urgencies>;

end Appointment
```

Function or operation	Line	Coverage	Calls
Appointment	12	100.0%	16
addPrescription	36	0.0%	0
getPrescriptions	27	100.0%	4
getPriority	23	100.0%	12
removePrescription	42	0.0%	0
setPriority	31	100.0%	4
Appointment.vdmpp		100.0%	36

3 HealthProfessional

```
class HealthProfessional is subclass of Person

instance variables
  private medicalNumber: Types'String;
```

```

private specialties:set of (Specialty);
private patients : set of(Patient);
private type : Types`Type;

inv card patients >= 0;
  inv card specialties < 5;
inv type <> nil;
inv len medicalNumber > 5;
operations
  -- Health Professional constructor

public HealthProfessional: Types`String * Types`String * Types`String * Types`String * Types`
  String * Types`String * Types`Type ==> HealthProfessional
  HealthProfessional(a, fn, ln, c, pn, s, t) == (medicalNumber := s; type := t; specialties :=
  {}); patients := {}; Person(a, fn, ln, c, pn))
pre t <> nil and len s > 5
post medicalNumber = s and type = t and specialties = {} and patients = {};

  -- Returns the health professional's number

pure public getMedicalNumber: () ==> Types`String
  getMedicalNumber() == (return medicalNumber);

  -- Returns the health professional's specialties

pure public getSpecialties: () ==> set of (Specialty)
  getSpecialties() == (return specialties);

  -- Returns all the health professional's patients

pure public getPatients: () ==> set of (Patient)
  getPatients() == (return patients);

  -- Returns the health professional's type

pure public getType : () ==> Types`Type
  getType() == (return type);

  -- Removes a specialty from the health professional's specialties

public removeSpecialty: Specialty ==> ()
  removeSpecialty(s) == (specialties := specialties \ {s})
pre s in set specialties
post s not in set specialties;

  -- Adds a specialty to the health professional's specialties

public addSpecialty: Specialty ==> ()
  addSpecialty(s) == (specialties := specialties union {s})
pre s not in set specialties
post s in set specialties;

  -- Adds a patient to the health professional's patients

public addPatient : Patient ==> ()
  addPatient(p) == (patients := patients union {p})
pre p not in set patients
post p in set patients;

  -- Removes a patient from the health professional's patients

public removePatient : Patient ==> ()
  removePatient(p) == (patients := patients \ {p})
pre p in set patients
post p not in set patients;

```

```
end HealthProfessional
```

Function or operation	Line	Coverage	Calls
HealthProfessional	15	100.0%	136
addPatient	49	100.0%	48
addSpecialty	43	100.0%	8
getMedicalNumber	21	100.0%	16
getPatients	29	100.0%	144
getSpecialties	25	100.0%	44
getType	33	100.0%	692
removePatient	55	100.0%	4
removeSpecialty	37	100.0%	8
HealthProfessional.vdmpp		100.0%	1100

4 Hospital

```
class Hospital
instance variables
  private medicalAssociated: set of (HealthProfessional);
  private agenda : set of (Agenda);
  private name: Types`String;
  private address: Types`String;
  private tasks: set of (Task);
  private trainings: set of (Training);
  private safetyNet: SafetyNetHospital;

  inv card medicalAssociated >= 0;
  inv card agenda <= card medicalAssociated;
  inv card tasks >= 0;
  inv card trainings >= 0;
operations
  -- Hospital constructor

  public Hospital: Types`String * Types`String * SafetyNetHospital ==> Hospital
    Hospital(n, a, s) == (name := n; address := a; safetyNet := s; medicalAssociated := {}; tasks
      := {}; trainings := {}; agenda := {});
    safetyNet.addHospital(self); return self
  post name = n and address = a and safetyNet = s and medicalAssociated = {} and tasks = {} and
    trainings = {} and agenda = {};

  -- Returns the hospital's name

  pure public getName: () ==> Types`String
    getName() == (return name);

  -- Returns the hospital's address

  pure public getAddress: () ==> Types`String
    getAddress() == (return address);

  -- Returns the tasks created on this hospital

  pure public getTasks: () ==> set of (Task)
```

```

getTasks() == (return tasks);

-- Returns the trainings created on this hospital

pure public getTrainings : () ==> set of (Training)
getTrainings() == (return trainings);

-- Returns all the agendas of the health professionals of this hospital

pure public getAgendas : () ==> set of (Agenda)
getAgendas() == (return agenda);

-- Returns the schedules of a health professional's agenda

pure public getAgenda : HealthProfessional ==> Agenda
getAgenda(h) == (
  dcl a1 : Agenda;
  for all a2 in set agenda do
    if(a2.getHealthProfessional() = h)
      then a1 := a2;
  return a1);

-- Removes an agenda

public removeAgenda : Agenda ==> ()
removeAgenda(a) == (agenda := agenda \ {a})
pre a in set agenda
post a not in set agenda;

-- Adds a health professional to the hospital's health professionals

public addMedAssociated: HealthProfessional ==> ()
addMedAssociated(d) == (
  dcl agendaNew : Agenda;
  agendaNew := new Agenda(d);
  medicalAssociated := {d} union medicalAssociated;
  agenda := agenda union {agendaNew})
pre d not in set medicalAssociated
post d in set medicalAssociated;

-- Removes a health professional from the hospital's health professionals

public removeMedAssociated: HealthProfessional ==> ()
removeMedAssociated(d) == (
  for all t in set tasks do
    if(d = t.getMedAssoc())
      then removeTask(t);
  for all t in set trainings do
    if(d = t.getMedAssoc())
      then removeTraining(t);
  for all a in set agenda do
    if(a.getHealthProfessional().getCC() = d.getCC())
      then removeAgenda(a);
  medicalAssociated := medicalAssociated \ {d})
pre d in set medicalAssociated
post d not in set medicalAssociated;

-- Adds a task to the hospital

public addTask: Task ==> ()
addTask(d) == (
  if(d.getPatient() not in set d.getMedAssoc().getPatients())
    then d.getMedAssoc().addPatient(d.getPatient());
  tasks := {d} union tasks;
  for all a in set agenda do

```

```

    if(a.getHealthProfessional().getCC() = d.getMedAssoc().getCC())
    then a.removeSchedule(d.getSchedule());
pre d not in set tasks and d.getSchedule() in set getAgenda(d.getMedAssoc()).getAgenda()
post d in set tasks and d.getPatient() in set d.getMedAssoc().getPatients() and d.getSchedule()
    not in set getAgenda(d.getMedAssoc()).getAgenda();

-- Removes a task from the hospital

public removeTask: Task ==> ()
removeTask(d) == (
    for all a in set agenda do
        if(a.getHealthProfessional() = d.getMedAssoc())
        then a.addSchedule(d.getSchedule());
    tasks := tasks \ {d}
pre d in set tasks and d.getSchedule() not in set getAgenda(d.getMedAssoc()).getAgenda()
post d not in set tasks and d.getSchedule() in set getAgenda(d.getMedAssoc()).getAgenda();

-- Adds a training to the hospital

public addTraining: Training ==> ()
addTraining(d) == (
    for all a in set agenda do
        if(a.getHealthProfessional() = d.getMedAssoc())
        then a.removeSchedule(d.getSchedule());
    trainings := {d} union trainings
pre d not in set trainings and d.getSchedule() in set getAgenda(d.getMedAssoc()).getAgenda()
post d in set trainings and d.getSchedule() not in set getAgenda(d.getMedAssoc()).getAgenda();

-- Removes a training from the hospital

public removeTraining: Training ==> ()
removeTraining(d) == (
    for all a in set agenda do
        if(a.getHealthProfessional() = d.getMedAssoc())
        then a.addSchedule(d.getSchedule());
    trainings := trainings \ {d}
pre d in set trainings and d.getSchedule() not in set getAgenda(d.getMedAssoc()).getAgenda()
post d not in set trainings and d.getSchedule() in set getAgenda(d.getMedAssoc()).getAgenda();

-- Returns the tasks of a hospital by its type

pure public getTasksByType: Types`TaskType ==> set of (Task)
getTasksByType(s) == (
    decl tasksTotal: set of (Task);
    tasksTotal := {};
    for all t in set tasks do
        if(t.getType() = s)
        then tasksTotal := tasksTotal union {t};
    return tasksTotal);

-- Returns the trainings of a hospital by its type

pure public getTrainingsByType: Types`Purpose ==> set of (Training)
getTrainingsByType(s) == (
    decl train: set of (Training);
    train := {};
    for all t in set trainings do
        if(t.getPurpose() = s)
        then train := train union {t};
    return train);

-- Returns the health professionals of a hospital

pure public getMedicalAssociated: () ==> set of (HealthProfessional)
getMedicalAssociated() == (

```

```

    return medicalAssociated);

-- Returns the health professionals of a hospital by its type

pure public getMedicalAssociatedByType: Types`Type ==> set of (HealthProfessional)
getMedicalAssociatedByType(type) == (
    dcl med: set of(HealthProfessional);
    med := {};
    for all d in set medicalAssociated do
        if(d.getType() = type)
            then med := med union {d};
    return med);
end Hospital

```

Function or operation	Line	Coverage	Calls
Hospital	17	100.0%	28
addMedAssociated	58	100.0%	44
addTask	84	100.0%	48
addTraining	106	100.0%	8
getAddress	27	100.0%	12
getAgenda	43	100.0%	123
getAgendas	39	100.0%	16
getMedicalAssociated	146	100.0%	3
getMedicalAssociatedByType	151	100.0%	176
getName	23	100.0%	40
getTasks	31	100.0%	8
getTasksByType	126	100.0%	96
getTrainings	35	100.0%	4
getTrainingsByType	136	100.0%	48
removeAgenda	52	100.0%	4
removeMedAssociated	68	100.0%	4
removeTask	96	100.0%	8
removeTraining	116	100.0%	8
Hospital.vdmpp		100.0%	678

5 Patient

```

class Patient is subclass of Person
instance variables
    private healthNumber: Types`String;

    inv len healthNumber > 5;
operations
    -- Patient constructor

    public Patient: Types`String * Types`String * Types`String * Types`String * Types`String * Types
        `String ==> Patient
        Patient(a, fn, ln, c, pn, n) == ( healthNumber := n; Person(a, fn, ln, c, pn))
    pre len n > 5
    post healthNumber = n;

```



```

-- Returns the patient's health number

pure public getHealthNumber : () ==> Types`String
  getHealthNumber() == (return healthNumber);

end Patient

```

Function or operation	Line	Coverage	Calls
Patient	8	100.0%	72
getHealthNumber	14	100.0%	4
Patient.vdmpp		100.0%	76

6 Person

```

class Person

instance variables
  protected address: Types`String;
  protected firstName: Types`String;
  protected lastName: Types`String;
  protected cc : Types`String;
  protected phoneNumber: Types`String;

operations
  -- Person constructor

  public Person: Types`String * Types`String * Types`String * Types`String * Types`String ==>
    Person
    Person(a, fn, ln, c, pn) == ( address := a; firstName := fn; lastName := ln; cc := c;
      phoneNumber := pn; return self)
  post address = a and firstName = fn and lastName = ln and cc = c and phoneNumber = pn;

  -- Returns the person's cc number

  pure public getCC : () ==> Types`String
    getCC() == (return cc);

  -- Returns all the person's information

  pure public getInfo: () ==> Types`String
    getInfo() == (return "Name: " ^ firstName ^ " " ^ lastName ^ "\nAddress: " ^ address ^ "\nPhone
      Number: " ^ phoneNumber ^ "\nCC: " ^ cc);

end Person

```

Function or operation	Line	Coverage	Calls
Person	12	100.0%	208
getCC	17	100.0%	780
getInfo	21	100.0%	20
Person.vdmpp		100.0%	1008

7 SafetyNetHospital

```
class SafetyNetHospital
instance variables
  private hospitals: set of (Hospital);

  inv card hospitals >= 0;
operations
  -- Safety Net constructor

  public SafetyNetHospital : () ==> SafetyNetHospital
    SafetyNetHospital() == (hospitals := {}); return self
  post hospitals = {};

  -- Adds an hospital to the safety net's hospitals

  public addHospital : Hospital ==> ()
    addHospital(h) == (hospitals := hospitals union {h})
  pre h not in set hospitals
  post h in set hospitals;

  -- Removes an hospital from the safety net's hospitals

  public removeHospital : Hospital ==> ()
    removeHospital(h) == (hospitals := hospitals \ {h})
  pre h in set hospitals
  post h not in set hospitals;

  -- Returns all the hospitals registered

  pure public getHospitals : () ==> set of (Hospital)
    getHospitals() == (return hospitals);

  -- Returns the hospital with more tasks (by type) created

  pure public getHospitalsMoreAppointments : Types`TaskType ==> Hospital
    getHospitalsMoreAppointments(t) == (
      dcl max: int, hosp: Hospital;
      max := -1;
      for all h in set hospitals do
        if((card h.getTasksByType(t)) > max)
          then (max := (card h.getTasksByType(t)); hosp := h);
      return hosp);

  -- Returns the health professionals (by type) that works on more than one hospital

  pure public getMedMoreHospitals : Types`Type ==> set of (HealthProfessional)
    getMedMoreHospitals(t) == (
      dcl doctors: set of (HealthProfessional);
      doctors := {};
      for all h in set hospitals do (
        dcl med: set of (HealthProfessional), list: set of (Hospital);
        med := h.getMedicalAssociatedByType(t);

        list := hospitals \ {h};
        for all m in set med do(
          for all l in set list do
            if(m.getType() = t and m in set l.getMedicalAssociatedByType(t) and m not in
              set doctors)
              then doctors := doctors union {m};
          );
        );
      return doctors;
```

```

    );
    -- Returns the health professionals by patient and type

pure public getMedAssociatedByPatient: Patient * Types`Type ==> map Hospital to set of(
    HealthProfessional)
getMedAssociatedByPatient(p, t) == (
    dcl maps: map Hospital to set of(HealthProfessional), med : set of (
        HealthProfessional);
    maps := { |-> };
    med := {};
    for all h in set hospitals do (
        for all m in set h.getMedicalAssociatedByType(t) do
            if(p in set m.getPatients())
            then med := med union {m};

    maps := maps munion {h |-> med};
    med := {};);
    return maps);
    -- Returns the health professionals by type and hospital

pure public getMedByHospital: Types`Type ==> map Hospital to set of(HealthProfessional)
getMedByHospital(t) == (
    dcl maps: map Hospital to set of(HealthProfessional);
    maps := { |-> };
    for all h in set hospitals do
        maps := maps munion {h |-> h.getMedicalAssociatedByType(t)};
    return maps);
end SafetyNetHospital

```

Function or operation	Line	Coverage	Calls
SafetyNetHospital	8	100.0%	16
addHospital	13	100.0%	28
getHospitals	25	100.0%	24
getHospitalsMoreAppointments	29	100.0%	16
getMedAssociatedByPatient	57	100.0%	8
getMedByHospital	71	100.0%	8
getMedMoreHospitals	38	100.0%	24
removeHospital	19	100.0%	8
SafetyNetHospital.vdmpp		100.0%	132

8 Schedule

```

class Schedule

instance variables
    private startHour: Types`Date;
    private endHour: Types`Date;

    inv lessThan(startHour, endHour);
operations
    -- Schedule constructor

    public Schedule: Types`Date * Types`Date ==> Schedule
        Schedule(d, d2) == (startHour := d; endHour := d2; return self)
    pre lessThan(d, d2)

```

```

post startHour = d and endHour = d2;

-- Sets the schedule start hour and endHour's values

public setSchedule : Types'Date * Types'Date ==> ()
  setSchedule(d1, d2) == (startHour := d1; endHour := d2;)
pre lessThan(d1, d2)
post startHour = d1 and endHour = d2;

-- Returns the startHour's value

pure public getScheduleStart : () ==> Types'Date
  getScheduleStart() == (return startHour);

-- Returns the endHour's value

pure public getScheduleEnd : () ==> Types'Date
  getScheduleEnd() == (return endHour);

-- Checks if two schedules overlap

pure public overlap : Schedule * Schedule ==> bool
  overlap(d1, d2) == (
    if((lessThan(d1.startHour, d2.startHour) and greaterThan(d1.endHour, d2.startHour)) or
      (not lessThan(d1.startHour, d2.startHour) and lessThan(d1.startHour, d2.endHour)))
      then return true;
      return false;;
  )
  -- Checks if a date is lower than other

pure static public lessThan : Types'Date * Types'Date ==> bool
  lessThan(d1, d2) == (
    if(d1.year < d2.year)
      then return true
    else if(d1.year > d2.year)
      then return false;
    if(d1.month < d2.month)
      then return true
    else if(d1.month > d2.month)
      then return false;
    if(d1.day < d2.day)
      then return true
    else if(d1.day > d2.day)
      then return false;
    if(d1.time.hour < d2.time.hour)
      then return true
    else if(d1.time.hour > d2.time.hour)
      then return false;
    return (d1.time.min < d2.time.min););
  -- Checks if a date is greater than other

pure static public greaterThan : Types'Date * Types'Date ==> bool
  greaterThan(d1, d2) == (
    if(d1.year < d2.year)
      then return false
    else if(d1.year > d2.year)
      then return true;
    if(d1.month < d2.month)
      then return false
    else if(d1.month > d2.month)
      then return true;
    if(d1.day < d2.day)
      then return false
    else if(d1.day > d2.day)
      then return true;
    if(d1.time.hour < d2.time.hour)

```

```

        then return false
      else if(d1.time.hour > d2.time.hour)
        then return true;
      return (d1.time.min > d2.time.min)););
end Schedule

```

Function or operation	Line	Coverage	Calls
Schedule	10	100.0%	108
getScheduleEnd	26	100.0%	92
getScheduleStart	22	100.0%	188
greaterThan	57	100.0%	88
lessThan	37	100.0%	936
overlap	30	100.0%	40
setSchedule	16	100.0%	4
Schedule.vdmpp		100.0%	1456

9 Specialty

```

class Specialty
instance variables
  private name: Types`String;
operations
  -- Specialty constructor

  public Specialty : Types`String ==> Specialty
    Specialty(n) == (name := n; return self)
  post name = n;

  -- Returns the specialty's name

  pure public getName : () ==> Types`String
    getName() == (return name);
end Specialty

```

Function or operation	Line	Coverage	Calls
Specialty	7	100.0%	8
getName	12	100.0%	8
Specialty.vdmpp		100.0%	16

10 Surgery

```

class Surgery is subclass of Task
instance variables
  private secondaryDoctors:set of (HealthProfessional);

```

```

private other:set of (HealthProfessional);

inv card secondaryDoctors >= 0;
inv card other >= 0;
inv medicalAssoc.getType() = <Surgeon>;
operations
  -- Surgery constructor

public Surgery: HealthProfessional * Schedule * Patient * Hospital ==> Surgery
  Surgery(s, sch, p, h) == (medicalAssoc := s ; other := {}; secondaryDoctors := {}; Task(s, sch,
    p, h, <Surgery>))
post medicalAssoc = s and other = {} and secondaryDoctors = {};

  -- Adds an auxiliary surgeon to the surgery

public addSecondaryDoctor : HealthProfessional ==> ()
  addSecondaryDoctor(s) == (secondaryDoctors := secondaryDoctors union {s})
pre s <> medicalAssoc and s.getType() = <Surgeon> and s not in set secondaryDoctors
post s in set secondaryDoctors;

  -- Removes an auxiliary surgeon from the surgery

public removeSecondaryDoctor : HealthProfessional ==> ()
  removeSecondaryDoctor(s) == (secondaryDoctors := secondaryDoctors \ {s})
pre s.getType() = <Surgeon> and s in set secondaryDoctors
post s not in set secondaryDoctors;

  -- Adds a nurse to the surgery

public addOther : HealthProfessional ==> ()
  addOther(s) == (other := other union {s})
pre s.getType() = <Nurse> and s not in set other
post s in set other;

  -- Removes a nurse from the surgery

public removeOther : HealthProfessional ==> ()
  removeOther(s) == (other := other \ {s})
pre s.getType() = <Nurse> and s in set other
post s not in set other;

  -- Sets the surgery's main surgeon

public setMainDoctor : HealthProfessional ==> ()
  setMainDoctor(s) == (medicalAssoc := s)
pre s.getType() = <Surgeon> and s not in set secondaryDoctors;

  -- Returns the auxiliary staff of a surgery by type

pure public getSurgeryPersons : Types`Type ==> set of (HealthProfessional)
  getSurgeryPersons(t) == (
    dcl med : set of (HealthProfessional);
    if (t = <Surgeon>)
      then med := secondaryDoctors
    else
      med := other;
    return med);
end Surgery

```

Function or operation	Line	Coverage	Calls
-----------------------	------	----------	-------

Surgery	11	100.0%	16
addOther	28	100.0%	4
addSecondaryDoctor	16	100.0%	4
getSurgeryPersons	45	100.0%	24
removeOther	34	100.0%	4
removeSecondaryDoctor	22	100.0%	4
setMainDoctor	40	100.0%	4
Surgery.vdmpp		100.0%	60

11 Task

```

class Task
instance variables
  protected schedule: Schedule;
  protected patient: Patient;
  protected hospital: Hospital;
  protected medicalAssoc: HealthProfessional;
  protected taskType : Types'TaskType;

  inv taskType <> nil;
operations
  -- Task constructor

  public Task: HealthProfessional * Schedule * Patient * Hospital * Types'TaskType ==> Task
    Task(med, s, p, h, t) == (schedule := s; patient := p; hospital := h; taskType := t;
      medicalAssoc := med; return self)
  pre med.getCC() <> p.getCC()
  post schedule = s and patient = p and hospital = h and medicalAssoc = med;

  -- Returns the task's schedule

  pure public getSchedule: () ==> Schedule
    getSchedule() == (return schedule);

  -- Returns the task's patient

  pure public getPatient: () ==> Patient
    getPatient() == (return patient);

  -- Returns the task's hospital

  pure public getHospital: () ==> Hospital
    getHospital() == (return hospital);

  -- Returns the task's type

  pure public getType: () ==> Types'TaskType
    getType() == (return taskType);

  -- Returns the task's health professional associated

  pure public getMedAssoc : () ==> HealthProfessional
    getMedAssoc() == (return medicalAssoc);

  -- Sets the task's schedule

  public setSchedule : Schedule ==> ()
    setSchedule(s) == (

```

```

    for all a in set hospital.getAgendas() do
        if(a.getHealthProfessional().getCC() = medicalAssoc.getCC())
            then (a.addSchedule(schedule); a.removeSchedule(s));
        schedule := s)
    pre s in set hospital.getAgenda(medicalAssoc).getAgenda()
    post s not in set hospital.getAgenda(medicalAssoc).getAgenda();

    -- Returns the surgery's associated

    pure public getSurgeryPersons : Types`Type ==> set of (HealthProfessional)
        getSurgeryPersons(t) == ( return {}; );

end Task

```

Function or operation	Line	Coverage	Calls
Task	12	100.0%	80
getHospital	26	100.0%	4
getMedAssoc	34	100.0%	536
getPatient	22	100.0%	140
getSchedule	18	100.0%	348
getSurgeryPersons	48	100.0%	4
getType	30	100.0%	488
setSchedule	38	100.0%	4
Task.vdmpp		100.0%	1604

12 Training

```

class Training

instance variables
    private medicalAssociated: HealthProfessional;
    private purpose: Types`Purpose;
    private schedule: Schedule;

    inv purpose <> nil;
operations
    -- Training constructor

    public Training: Types`Purpose * Schedule * HealthProfessional ==> Training
        Training(p, s, h) == (purpose := p; schedule := s; medicalAssociated := h; return self)
    post purpose = p and schedule = s and medicalAssociated = h;

    -- Returns the training's schedule

    pure public getSchedule : () ==> Schedule
        getSchedule() == (return schedule);

    -- Returns the training's purpose

    pure public getPurpose : () ==> Types`Purpose
        getPurpose() == (return purpose);

    -- Returns the health professional associated to the training

    pure public getMedAssoc : () ==> HealthProfessional

```



```

    getMedAssoc() == (return medicalAssociated);

-- Sets the training's purpose

public setPurpose : Types`Purpose ==> ()
    setPurpose(p) == (purpose := p);

end Training

```

Function or operation	Line	Coverage	Calls
Training	11	100.0%	24
getMedAssoc	24	100.0%	120
getPurpose	20	100.0%	28
getSchedule	16	100.0%	88
setPurpose	28	100.0%	4
Training.vdmpp		100.0%	264

13 Treatment

```

class Treatment is subclass of Task
instance variables
    public med: HealthProfessional;
    public name: Types`String;

    inv med.getType() = <Nurse> or med.getType() = <Technician>;
operations
    -- Treatment constructor

    public Treatment: HealthProfessional * Types`String * Schedule * Patient * Hospital ==>
        Treatment
        Treatment(m, n, s, p, h) == (name := n; med := m; Task(m, s, p, h, <Other>))
    post name = n and med = m;

    -- Returns the treatment's name

    pure public getName: () ==> Types`String
        getName() == (return name);

    -- Returns the health professional associated to the treatment

    pure public getMed : () ==> HealthProfessional
        getMed() == (return med);

end Treatment

```

Function or operation	Line	Coverage	Calls
Treatment	9	100.0%	16
getMed	18	100.0%	4
getName	14	100.0%	4
Treatment.vdmpp		100.0%	24

14 Types

```

class Types
types
  public String = seq1 of (char);
  public Priority = <High> | <Medium> | <Low>;
  public Type = <Doctor> | <Surgeon> | <Nurse> | <Technician>;
  public TaskType = <Appointment> | <Urgencies> | <Surgery> | <Other>;
  public Purpose = <Training> | <AddSkills>;
  public Time :: hour : nat
    min: nat
  inv t == t.hour >= 0 and t.hour < 24 and t.min >= 0 and t.min < 60;
  public Date :: year: nat1
    month: nat1
    day: nat1
    time: Time
  inv d == d.month <= 12 and d.day <= daysOfMonth(d.month, d.year);

operations
  -- Gets the days of a month

  public static pure daysOfMonth : nat1 * nat1 ==> nat1
  daysOfMonth(month, year) == (
    if(month = 1 or month = 3 or month = 5 or month = 7 or month = 8 or month = 10 or
      month = 12)
    then return 31
    else if(month = 4 or month = 6 or month = 9 or month = 11)
    then return 30
    else if(month = 2)
    then if ((year mod 4) = 0 and (year mod 100) <> 0 or (year mod 400) = 0)
    then return 29;
    return 28;);

end Types

```

Function or operation	Line	Coverage	Calls
daysOfMonth	19	100.0%	92
Types.vdmpp		100.0%	92

15 PersonTest

```

class PersonTest
instance variables
  private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111"
    , "0987654321");
  private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
    123432156", "921349076", "111111222", <Doctor>);
  private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "
    234512389", "921349134", "111111232", <Surgeon>);
  private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes",
    "123444654", "921378643", "111222333", <Nurse>);
  private technician: HealthProfessional := new HealthProfessional("Rua Antero Marques", "Inês",
    "Pinto", "123432151", "921348765", "123432578", <Technician>);
operations

```

```

private assertTrue: bool ==> ()
    assertTrue(cond) == return
pre cond;

public testGetInformation: () ==> ()
testGetInformation() == (
    IO`print("\n Getting patient informations \n");
    assertTrue(patient.getHealthNumber() = "0987654321");
    assertTrue(patient.getCC() = "123456789");
    assertTrue(patient.getInfo() = "Name: " ^ "Rui" ^ " " ^ "Andrade" ^ "\nAddress: " ^ "Rua 1
        Maio" ^ "\nPhone Number: " ^ "223456111" ^ "\nCC: " ^ "123456789");

    IO`print("\n Getting doctor informations \n");
    assertTrue(doctor.getMedicalNumber() = "111111222");
    assertTrue(doctor.getCC() = "123432156");
    assertTrue(doctor.getInfo() = "Name: " ^ "Ana" ^ " " ^ "Marques" ^ "\nAddress: " ^ "Rua de
        Cima" ^ "\nPhone Number: " ^ "921349076" ^ "\nCC: " ^ "123432156");
    assertTrue(doctor.getType() = <Doctor>);

    IO`print("\n Getting surgeon informations \n");
    assertTrue(surgeon.getMedicalNumber() = "111111232");
    assertTrue(surgeon.getCC() = "234512389");
    assertTrue(surgeon.getInfo() = "Name: " ^ "Diogo" ^ " " ^ "Viana" ^ "\nAddress: " ^ "Rua 2" ^
        "\nPhone Number: " ^ "921349134" ^ "\nCC: " ^ "234512389");
    assertTrue(surgeon.getType() = <Surgeon>);

    IO`print("\n Getting nurse informations \n");
    assertTrue(nurse.getMedicalNumber() = "111222333");
    assertTrue(nurse.getCC() = "123444654");
    assertTrue(nurse.getInfo() = "Name: " ^ "Lisete" ^ " " ^ "Antunes" ^ "\nAddress: " ^ "Rua de
        Baixo" ^ "\nPhone Number: " ^ "921378643" ^ "\nCC: " ^ "123444654");
    assertTrue(nurse.getType() = <Nurse>);

    IO`print("\n Getting technician informations \n");
    assertTrue(technician.getMedicalNumber() = "123432578");
    assertTrue(technician.getCC() = "123432151");
    assertTrue(technician.getInfo() = "Name: " ^ "Inês" ^ " " ^ "Pinto" ^ "\nAddress: " ^ "Rua
        Antero Marques" ^ "\nPhone Number: " ^ "921348765" ^ "\nCC: " ^ "123432151");
    assertTrue(technician.getType() = <Technician>);
);

public testAddRemovePatient : () ==> ()
testAddRemovePatient() == (
    IO`print("\n Number of patients: ");
    IO`print(card doctor.getPatients());
    assertTrue(card doctor.getPatients() = 0);

    IO`print("\n Adding a patient \n");
    doctor.addPatient(patient);

    IO`print("\n Number of patients: ");
    IO`print(card doctor.getPatients());
    assertTrue(card doctor.getPatients() = 1);

    IO`print("\n Removing a patient \n");
    doctor.removePatient(patient);

    IO`print("\n Number of patients: ");
    IO`print(card doctor.getPatients());
    assertTrue(card doctor.getPatients() = 0);

    IO`print("\n Adding a patient \n");
    assertTrue(card surgeon.getPatients() = 0);

```

```

surgeon.addPatient(patient);
IO`print("\n Number of patients: ");
IO`print(card surgeon.getPatients());
assertTrue(card surgeon.getPatients() = 1);
);

public testAddRemoveSpecialty : () ==> ()
testAddRemoveSpecialty() == (
  dcl specialty1: Specialty := new Specialty("General"), specialty2: Specialty := new Specialty(
    "Cardio");

  IO`print("\n Number of specialties: ");
  IO`print(card doctor.getSpecialties());
  assertTrue(card doctor.getSpecialties() = 0);

  IO`print("\n Adding a specialty \n");
  doctor.addSpecialty(specialty1);

  IO`print("\n Number of specialties: ");
  IO`print(card doctor.getSpecialties());

  assertTrue(specialty1.getName() = "General");
  assertTrue(card doctor.getSpecialties() = 1);
  assertTrue(doctor.getSpecialties() = {specialty1});

  IO`print("\n Adding a specialty \n");
  doctor.addSpecialty(specialty2);

  IO`print("\n Number of specialties: ");
  IO`print(card doctor.getSpecialties());

  assertTrue(specialty2.getName() = "Cardio");
  assertTrue(card doctor.getSpecialties() = 2);
  assertTrue(doctor.getSpecialties() = {specialty1, specialty2});

  IO`print("\n Removing a specialty \n");
  doctor.removeSpecialty(specialty1);

  IO`print("\n Number of specialties: ");
  IO`print(card doctor.getSpecialties());

  assertTrue(card doctor.getSpecialties() = 1);
  assertTrue(doctor.getSpecialties() = {specialty2});
);

public static main: () ==> ()
main() == (
  dcl personTest: PersonTest := new PersonTest();
  IO`print("\n *****Running PersonTest***** \n");
  personTest.testGetInformation();
  personTest.testAddRemovePatient();
  personTest.testAddRemoveSpecialty();
);

end PersonTest

```

Function or operation	Line	Coverage	Calls
-----------------------	------	----------	-------

assertTrue	9	100.0%	264
main	112	100.0%	4
testAddRemovePatient	45	100.0%	4
testAddRemoveSpecialty	74	100.0%	4
testGetInformation	13	100.0%	4
PersonTest.vdmpp		100.0%	280

16 RunTests

```

class RunTests

operations

public static main: () ==> ()
  main() == (
    dcl taskTest: TaskTest := new TaskTest(), personTest: PersonTest := new PersonTest(),
      trainingTest: TrainingTest := new TrainingTest(), safetyNetTest: SafetyNetHospitalTest :=
        new SafetyNetHospitalTest();

    personTest.main();
    taskTest.main();
    trainingTest.main();
    safetyNetTest.main();
    IO`print("\n\n ===== All TaskTest run successfully ===== \n\n");
    IO`print("\n\n ===== All TrainingTesr run successfully ===== \n\n");
    IO`print("\n\n ===== All PersonTest run successfully ===== \n\n");
    IO`print("\n\n ===== All SafetyNetHospitalTest run successfully ===== \n\n");
  );
end RunTests

```

Function or operation	Line	Coverage	Calls
main	4	100.0%	4
RunTests.vdmpp		100.0%	4

17 SafetyNetHospitalTest

```

class SafetyNetHospitalTest
instance variables
  private safetyNet: SafetyNetHospital := new SafetyNetHospital();

  private time1: Types`Time := mk_Types`Time(12, 10);
  private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
  private time2: Types`Time := mk_Types`Time(12, 30);
  private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
  private schedule: Schedule := new Schedule(date1, date2);

  private time3: Types`Time := mk_Types`Time(12, 15);
  private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
  private time4: Types`Time := mk_Types`Time(12, 35);
  private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
  private schedule2: Schedule := new Schedule(date3, date4);

```

```

private time5: Types`Time := mk_Types`Time(12, 40);
private date5: Types`Date := mk_Types`Date(2017, 12, 25, time5);
private time6: Types`Time := mk_Types`Time(12, 50);
private date6: Types`Date := mk_Types`Date(2017, 12, 25, time6);
private schedule3: Schedule := new Schedule(date5, date6);

private time7: Types`Time := mk_Types`Time(12, 10);
private date7: Types`Date := mk_Types`Date(2017, 11, 22, time7);
private time8: Types`Time := mk_Types`Time(12, 30);
private date8: Types`Date := mk_Types`Date(2017, 11, 22, time8);
private schedule4: Schedule := new Schedule(date7, date8);

private time9: Types`Time := mk_Types`Time(12, 35);
private date9: Types`Date := mk_Types`Date(2017, 11, 23, time9);
private time10: Types`Time := mk_Types`Time(12, 45);
private date10: Types`Date := mk_Types`Date(2017, 11, 23, time10);
private schedule5: Schedule := new Schedule(date9, date10);

private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111",
  "0987654321");
private patient2: Patient := new Patient("Rua 1 Maio", "Diogo", "Andrade", "123321123", "
  911112345", "908765123");
private patient3: Patient := new Patient("Rua 1 Maio", "Vitor", "Andrade", "135790864", "
  912345334", "123432130");
private patient4: Patient := new Patient("Rua 1 Maio", "Simone", "Andrade", "234123765", "
  931238654", "0987654143");

private hospital: Hospital := new Hospital("Hospital das Camlias", "Rua de Cima", safetyNet);

private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
  123432156", "921349076", "111111222", <Doctor>);
private doctor2: HealthProfessional := new HealthProfessional("Rua de Cima", "Anabela", "
  Marques", "123432157", "921349077", "111111223", <Doctor>);
private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "
  234512389", "921349134", "111111232", <Surgeon>);
private secSurgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diana", "Viana", "
  234512390", "921349135", "111111235", <Surgeon>);
private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes",
  "123444654", "921378643", "111222333", <Nurse>);
private technician: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lus", "
  Antunes", "123444655", "921377654", "111222345", <Technician>);

private appointment: Appointment := new Appointment(doctor, schedule, patient, hospital);
private appointment2: Appointment := new Appointment(doctor, schedule3, patient4, hospital);
private appointment3: Appointment := new Appointment(doctor2, schedule3, patient, hospital);
private urgencies: Appointment := new Appointment(doctor2, <High>, schedule, patient2, hospital)
  ;
private surgery: Surgery := new Surgery(surgeon, schedule, patient3, hospital);
private treatment: Treatment := new Treatment(technician, "Fisioterapia", schedule, patient4,
  hospital);

private purpose: Types`Purpose := <Training>;
private training : Training := new Training(purpose, schedule3, nurse);
private train : Training := new Training(purpose, schedule4, doctor);
operations

private assertTrue: bool ==> ()
  assertTrue(cond) == return
pre cond;

public testAddRemoveHospitals: () ==> ()
  testAddRemoveHospitals() == (
    dcl h1: Hospital, h2: Hospital, h3: Hospital;

```

```

h1 := new Hospital("Hospital dos Lusadas", "Rua de Cima", safetyNet);
h2 := new Hospital("Hospital Novo", "Rua 1 de Maio", safetyNet);
h3 := new Hospital("Hospital da Trofa", "Rua da Trofa", safetyNet);
IO`print("\n Number of hospitals: ");
IO`print(card safetyNet.getHospitals());

IO`print("\n\n Getting hospitals information \n");
assertTrue(h1.getName() = "Hospital dos Lusadas");
assertTrue(h2.getName() = "Hospital Novo");
assertTrue(h3.getName() = "Hospital da Trofa");

assertTrue(h1.getAddress() = "Rua de Cima");
assertTrue(h2.getAddress() = "Rua 1 de Maio");
assertTrue(h3.getAddress() = "Rua da Trofa");

IO`print("\n Removing hospitals \n");
assertTrue(card safetyNet.getHospitals() = 4);
safetyNet.removeHospital(h1);

IO`print("\n Removing hospitals \n");
assertTrue(card safetyNet.getHospitals() = 3);
safetyNet.removeHospital(h2);
assertTrue(card safetyNet.getHospitals() = 2);

IO`print("\n Number of hospitals: ");
IO`print(card safetyNet.getHospitals());
);

public testAddRemoveMedHospital : () ==> ()
testAddRemoveMedHospital() == (
  decl agendal : Agenda, agenda2 : Agenda, agenda3 : Agenda, agenda4: Agenda, agenda5: Agenda;

  IO`print("\n Adding health professionals \n");
  hospital.addMedAssociated(doctor);
  hospital.addMedAssociated(doctor2);
  hospital.addMedAssociated(surgeon);
  hospital.addMedAssociated(nurse);
  hospital.addMedAssociated(technician);

  IO`print("\n Adding agendas to health professionals \n");
  for all a in set hospital.getAgendas() do
    if(a.getHealthProfessional() = doctor)
      then agendal := a
    else if(a.getHealthProfessional() = doctor2)
      then agenda2 := a
    else if(a.getHealthProfessional() = surgeon)
      then agenda3 := a
    else if(a.getHealthProfessional() = nurse)
      then agenda4 := a
    else
      agenda5 := a;);

  IO`print("\n Checking agenda \n");
  assertTrue(hospital.getAgenda(doctor) = agendal);

  IO`print("\n Adding schedules to agendas \n");
  agendal.addSchedule(schedule);
  agendal.addSchedule(schedule3);
  agendal.addSchedule(schedule4);

  agenda2.addSchedule(schedule);
  agenda2.addSchedule(schedule3);

  agenda3.addSchedule(schedule);

```

```

agenda4.addSchedule(schedule3);

agenda5.addSchedule(schedule);

IO`print("\n Checking agendas \n");
assertTrue(card agenda1.getAgenda() = 3);
assertTrue(card agenda2.getAgenda() = 2);
assertTrue(card agenda3.getAgenda() = 1);
assertTrue(card agenda4.getAgenda() = 1);
assertTrue(card agenda5.getAgenda() = 1);

IO`print("\n Total number of doctors: ");
IO`print(card hospital.getMedicalAssociatedByType(<Doctor>));
IO`print("\n Total number of surgeons: ");
IO`print(card hospital.getMedicalAssociatedByType(<Surgeon>));
IO`print("\n Total number of nurses: ");
IO`print(card hospital.getMedicalAssociatedByType(<Nurse>));
IO`print("\n Total number of technicians: ");
IO`print(card hospital.getMedicalAssociatedByType(<Technician>));

assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 2);
assertTrue(card hospital.getMedicalAssociatedByType(<Surgeon>) = 1);
assertTrue(card hospital.getMedicalAssociatedByType(<Nurse>) = 1);
assertTrue(card hospital.getMedicalAssociatedByType(<Technician>) = 1);

IO`print("\n Total number of doctors: ");
IO`print(card hospital.getMedicalAssociatedByType(<Doctor>));

assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 2);

assertTrue(card hospital.getMedicalAssociated() = 5);

IO`print("\n Removing a doctor \n");
hospital.addTask(appointment);
hospital.addTraining(train);
hospital.removeMedAssociated(doctor);
assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 1);

IO`print("\n Total number of doctors: ");
IO`print(card hospital.getMedicalAssociatedByType(<Doctor>));

hospital.addMedAssociated(doctor);

for all a in set hospital.getAgendas() do
  if(a.getHealthProfessional().getCC() = doctor.getCC())

    then agendal := a;

    agendal.addSchedule(schedule);
    agendal.addSchedule(schedule3);
    assertTrue(card agendal.getAgenda() = 2);

);

public testAddRemoveTaskHospital : () ==> ()
testAddRemoveTaskHospital() == (
  IO`print("\n Adding tasks \n");
  hospital.addTask(appointment);
  hospital.addTask(appointment2);
  hospital.addTask(appointment3);
  hospital.addTask(urgencies);
  hospital.addTask(surgery);
  hospital.addTask(treatment);

```



```

        IO`print("\n\n Total number of appointments: ");
        IO`print(card hospital.getTasksByType(<Appointment>));
        IO`print("\n Total number of urgencies: ");
        IO`print(card hospital.getTasksByType(<Urgencies>));
        IO`print("\n Total number of surgeries: ");
        IO`print(card hospital.getTasksByType(<Surgery>));
        IO`print("\n Total number of other treatments: ");
        IO`print(card hospital.getTasksByType(<Other>));

        IO`print("\n\n Total number of tasks: ");
        IO`print(card hospital.getTasks());

        assertTrue(card hospital.getTasks() = 6);

        assertTrue(card hospital.getTasksByType(<Appointment>) = 3);
        assertTrue(card hospital.getTasksByType(<Urgencies>) = 1);
        assertTrue(card hospital.getTasksByType(<Surgery>) = 1);
        assertTrue(card hospital.getTasksByType(<Other>) = 1);

        IO`print("\n\n Removing an appointment \n");
        hospital.removeTask(appointment);
        assertTrue(card hospital.getTasksByType(<Appointment>) = 2);

        IO`print("\n Total number of appointments: ");
        IO`print(card hospital.getTasksByType(<Appointment>));

        IO`print("\n Adding an appointment \n");
        hospital.addTask(appointment);
        assertTrue(card hospital.getTasksByType(<Appointment>) = 3);

        IO`print("\n Total number of appointments: ");
        IO`print(card hospital.getTasksByType(<Appointment>));
    );

    public testAddRemoveTrainingHospital : () ==> ()
    testAddRemoveTrainingHospital() == (
        IO`print("\n\n Total number of trainings: ");
        IO`print(card hospital.getTrainingsByType(<Training>) + card hospital.getTrainingsByType(<AddSkills>));

        assertTrue(card hospital.getTrainingsByType(<Training>) = 0);
        assertTrue(card hospital.getTrainingsByType(<AddSkills>) = 0);

        IO`print("\n Adding a training \n");
        hospital.addTraining(training);
        assertTrue(card hospital.getTrainingsByType(<Training>) = 1);

        IO`print("\n Total number of trainings: ");
        IO`print(card hospital.getTrainingsByType(<Training>) + card hospital.getTrainingsByType(<AddSkills>));

        assertTrue(card hospital.getTrainings() = (card hospital.getTrainingsByType(<Training>) +
            card hospital.getTrainingsByType(<AddSkills>)));

        IO`print("\n Removing a training \n");
        hospital.removeTraining(training);
        assertTrue(card hospital.getTrainingsByType(<Training>) = 0);

        IO`print("\n\n Total number of trainings: ");
        IO`print(card hospital.getTrainingsByType(<Training>) + card hospital.getTrainingsByType(<AddSkills>));
    );

```

```

public testGetHospitalsMoreAppointments : () ==> ()
testGetHospitalsMoreAppointments() == (
  IO`print("\n Checking Safety Net Hospitals with more appointments, etc \n");
  assertTrue(safetyNet.getHospitalsMoreAppointments(<Appointment>).getName() = "Hospital das
    Camlias");
  assertTrue(safetyNet.getHospitalsMoreAppointments(<Urgencies>).getName() = "Hospital das
    Camlias");
  assertTrue(safetyNet.getHospitalsMoreAppointments(<Surgery>).getName() = "Hospital das
    Camlias");
  assertTrue(safetyNet.getHospitalsMoreAppointments(<Other>).getName() = "Hospital das Camlias
    ");
);

public testGetMedMoreHospitals : () ==> ()
testGetMedMoreHospitals() == (
  for all t in set safetyNet.getHospitals() do
    if(t.getName() <> "Hospital das Camlias")

      then t.addMedAssociated(doctor);

  IO`print("\n Checking Safety Net Doctors that works in more than 1 hospital \n");
  IO`print("\n Number of Doctors: ");
  IO`print(card safetyNet.getMedMoreHospitals(<Doctor>));
  assertTrue(card safetyNet.getMedMoreHospitals(<Doctor>) = 1);
  assertTrue(safetyNet.getMedMoreHospitals(<Doctor>) = {doctor});
);

public testGetMedAssociatedByPatient : () ==> ()

testGetMedAssociatedByPatient() == (
  dcl mapTest : map Hospital to set of (HealthProfessional);
  IO`print("\n\n Getting Doctors associated by patient by hospital \n");
  mapTest := safetyNet.getMedAssociatedByPatient(patient, <Doctor>);

  assertTrue(card mapTest(hospital) = 2);
  assertTrue(mapTest(hospital) = {doctor, doctor2});
);

public testGetMedByHospital : () ==> ()
testGetMedByHospital() == (
  dcl mapTest : map Hospital to set of (HealthProfessional);
  IO`print("\n\n Getting Doctors associated by hospital \n");
  mapTest := safetyNet.getMedByHospital(<Doctor>);

  assertTrue(card mapTest(hospital) = 2);
  assertTrue(mapTest(hospital) = {doctor, doctor2});

  mapTest := safetyNet.getMedByHospital(<Surgeon>);

  assertTrue(card mapTest(hospital) = 1);
  assertTrue(mapTest(hospital) = {surgeon});
);

public static main: () ==> ()
main() == (
  dcl safetyNetTest: SafetyNetHospitalTest := new SafetyNetHospitalTest();
  IO`print("\n *****Running SafetyNetHospitalTest***** \n");
  safetyNetTest.testAddRemoveHospitals();
  safetyNetTest.testAddRemoveMedHospital();
  safetyNetTest.testAddRemoveTaskHospital();
  safetyNetTest.testAddRemoveTrainingHospital();
  safetyNetTest.testGetHospitalsMoreAppointments();
  safetyNetTest.testGetMedMoreHospitals();

```

```

    safetyNetTest.testGetMedAssociatedByPatient();
    safetyNetTest.testGetMedByHospital();
);
end SafetyNetHospitalTest

```

Function or operation	Line	Coverage	Calls
assertTrue	60	100.0%	186
main	292	100.0%	3
testAddRemoveHospitals	64	100.0%	4
testAddRemoveMedHospital	95	100.0%	3
testAddRemoveTaskHospital	177	100.0%	3
testAddRemoveTrainingHospital	220	100.0%	4
testGetHospitalsMoreAppointments	245	100.0%	3
testGetMedAssociatedByPatient	267	100.0%	3
testGetMedByHospital	277	100.0%	3
testGetMedMoreHospitals	254	100.0%	3
SafetyNetHospitalTest.vdmpp		100.0%	215

18 TaskTest

```

class TaskTest

instance variables
  private safetyNet: SafetyNetHospital := new SafetyNetHospital();

  private time1: Types`Time := mk_Types`Time(12, 10);
  private date: Types`Date := mk_Types`Date(2017, 11, 25, time1);
  private d: Types`Date := mk_Types`Date(2017, 2, 25, time1);
  private d2: Types`Date := mk_Types`Date(2016, 2, 25, time1);
  private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
  private time2: Types`Time := mk_Types`Time(12, 30);
  private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
  private schedule: Schedule := new Schedule(date1, date2);

  private time3: Types`Time := mk_Types`Time(12, 15);
  private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
  private time4: Types`Time := mk_Types`Time(12, 35);
  private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
  private schedule2: Schedule := new Schedule(date3, date4);

  private time5: Types`Time := mk_Types`Time(12, 40);
  private date5: Types`Date := mk_Types`Date(2017, 12, 25, time5);
  private time6: Types`Time := mk_Types`Time(12, 50);
  private date6: Types`Date := mk_Types`Date(2017, 12, 25, time6);
  private schedule3: Schedule := new Schedule(date5, date6);

  private time7: Types`Time := mk_Types`Time(12, 10);
  private date7: Types`Date := mk_Types`Date(2018, 11, 22, time7);
  private time8: Types`Time := mk_Types`Time(12, 30);
  private date8: Types`Date := mk_Types`Date(2018, 11, 22, time8);
  private schedule4: Schedule := new Schedule(date7, date8);

  private time9: Types`Time := mk_Types`Time(12, 35);

```

```

private date9: Types`Date := mk_Types`Date(2017, 11, 22, time9);
private time10: Types`Time := mk_Types`Time(12, 45);
private date10: Types`Date := mk_Types`Date(2017, 11, 22, time10);
private schedule5: Schedule := new Schedule(date9, date10);

private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111"
, "0987654321");
private patient2: Patient := new Patient("Rua 1 Maio", "Diogo", "Andrade", "123321123", "
911112345", "908765123");
private patient3: Patient := new Patient("Rua 1 Maio", "Vitor", "Andrade", "135790864", "
912345334", "123432130");
private patient4: Patient := new Patient("Rua 1 Maio", "Simone", "Andrade", "234123765", "
931238654", "0987654143");

private hospital: Hospital := new Hospital("Hospital dos Lus adas", "Rua de Cima", safetyNet);
private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
123432156", "921349076", "111111222", <Doctor>);
private doctor2: HealthProfessional := new HealthProfessional("Rua de Cima", "Anabela", "
Marques", "123432157", "921349077", "111111223", <Doctor>);
private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "
234512389", "921349134", "111111232", <Surgeon>);
private secSurgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diana", "Viana", "
234512390", "921349135", "111111235", <Surgeon>);
private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes",
"123444654", "921378643", "111222333", <Nurse>);
private technician: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lu s", "
Antunes", "123444655", "921377654", "111222345", <Technician>);

private appointment: Appointment := new Appointment(doctor, schedule, patient, hospital);
private urgencies: Appointment := new Appointment(doctor2, <High>, schedule, patient2, hospital)
;
private surgery: Surgery := new Surgery(surgeon, schedule3, patient3, hospital);
private treatment: Treatment := new Treatment(technician, "Fisioterapia", schedule, patient4,
hospital);
operations
private assertTrue: bool ==> ()
  assertTrue(cond) == return

pre cond;

public testGetsSetsTask : () ==> ()
  testGetsSetsTask() == (

    dcl agenda1 : Agenda, agenda2 : Agenda, agenda3 : Agenda, agenda4: Agenda;
    hospital.addMedAssociated(doctor);
    hospital.addMedAssociated(doctor2);
    hospital.addMedAssociated(surgeon);
    hospital.addMedAssociated(technician);

    for all a in set hospital.getAgendas() do(
      if(a.getHealthProfessional() = doctor)
      then agenda1 := a
      else if (a.getHealthProfessional() = doctor2)
      then agenda2 := a
      else if (a.getHealthProfessional() = surgeon)
      then agenda3 := a
      else
        agenda4 := a;);

    assertTrue(hospital.getAgenda(doctor).getAgenda() = {});
    assertTrue(card hospital.getAgenda(doctor).getAgenda() = 0);

    agenda1.addSchedule(schedule);
    agenda1.addSchedule(schedule3);

```

```

assertTrue(agenda1.getHealthProfessional().getCC() = doctor.getCC());

assertTrue(card agenda1.getAgenda() = 2);

agenda2.addSchedule(schedule);

assertTrue(card agenda2.getAgenda() = 1);

agenda3.addSchedule(schedule3);

assertTrue(card agenda3.getAgenda() = 1);

agenda4.addSchedule(schedule);

assertTrue(card agenda4.getAgenda() = 1);

agenda4.removeSchedule(schedule);

assertTrue(card agenda4.getAgenda() = 0);

agenda4.addSchedule(schedule);

assertTrue(card agenda4.getAgenda() = 1);

hospital.addTask(appointment);
hospital.addTask(urgencies);
hospital.addTask(surgery);
hospital.addTask(treatment);

IO`print("\n Getting appointment informations \n");
assertTrue(appointment.getPatient().getCC() = "123456789");
assertTrue(appointment.getHospital().getName() = "Hospital dos Lus adas");

assertTrue(appointment.getType() = <Appointment>);
assertTrue(urgencies.getType() = <Urgencies>);
assertTrue(surgery.getType() = <Surgery>);
assertTrue(treatment.getType() = <Other>);

IO`print("\n Getting tasks informations \n");
assertTrue(appointment.getMedAssoc().getCC() = "123432156");
assertTrue(card appointment.getSurgeryPersons(<Nurse>) = 0);
assertTrue(urgencies.getMedAssoc().getCC() = "123432157");
assertTrue(surgery.getMedAssoc().getCC() = "234512389");

IO`print("\n Checking schedules \n");
assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleStart().time.min = 10);

assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 30);

assertTrue(appointment.getSchedule().lessThan(appointment.getSchedule().getScheduleStart(),
    appointment.getSchedule().getScheduleEnd()) = true);

appointment.getSchedule().setSchedule(date3, date4);
assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);

```

```

    assertTrue(appointment.getSchedule().getScheduleStart().time.min = 15);

    assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
    assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
    assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
    assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
    assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 35);

    appointment.setSchedule(schedule3);

    assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
    assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
    assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
    assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);
    assertTrue(appointment.getSchedule().getScheduleStart().time.min = 40);

    assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
    assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
    assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
    assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
    assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 50);
);

public testAppointment : () ==> ()
testAppointment() == (
    IO`print("\n Checking appointment priority \n");
    assertTrue(appointment.getPriority() = <Medium>);
    assertTrue(urgencies.getPriority() = <High>);

    urgencies.setPriority(<Low>);
    assertTrue(urgencies.getPriority() = <Low>);
);

public testSurgery: () ==> ()
testSurgery() == (
    IO`print("\n Checking surgery informations \n");
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 0);

    surgery.addSecondaryDoctor(secSurgeon);
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 1);

    surgery.removeSecondaryDoctor(secSurgeon);
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 0);

    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 0);
    surgery.addOther(nurse);
    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 1);

    surgery.removeOther(nurse);
    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 0);

    assertTrue(surgery.getMedAssoc().getCC() = "234512389");
    surgery.setMainDoctor(secSurgeon);
    assertTrue(surgery.getMedAssoc().getCC() = "234512390");
);

public testTreatment : () ==> ()
testTreatment() == (
    IO`print("\n Checking treatment informations \n");
    IO`print("\n Checking schedule functions \n");
    assertTrue(treatment.getName() = "Fisioterapia");
    assertTrue(treatment.getMed().getCC() = "123444655");
);

```

```

public testScheduleFunctions: () ==> ()
testScheduleFunctions() == (
  dcl sch : Schedule, sch1 : Schedule, sch2 : Schedule, dateNew: Types`Date, dateNew2 : Types`
    Date;
  dateNew := mk_Types`Date(2017, 10, 25, time1);
  dateNew2 := mk_Types`Date(2017, 10, 25, time2);
  sch := new Schedule(dateNew, dateNew2);

  dateNew := mk_Types`Date(2017, 10, 26, time1);
  dateNew2 := mk_Types`Date(2017, 10, 26, time2);
  sch1 := new Schedule(dateNew, dateNew2);

  dateNew := mk_Types`Date(2017, 11, 26, time1);

  dateNew2 := mk_Types`Date(2017, 11, 26, time2);
  sch2 := new Schedule(dateNew, dateNew2);

  IO`print("\n Checking schedule functions \n");
  assertTrue(appointment.getSchedule().lessThan(appointment.getSchedule().getScheduleStart(),
    appointment.getSchedule().getScheduleEnd()));
  assertTrue(appointment.getSchedule().greaterThan(appointment.getSchedule().getScheduleEnd(),
    appointment.getSchedule().getScheduleStart()));

  assertTrue(appointment.getSchedule().lessThan(appointment.getSchedule().getScheduleStart(),
    schedule4.getScheduleStart()));
  assertTrue(not(schedule4.lessThan(schedule4.getScheduleStart(), schedule5.getScheduleStart())
    ));
  assertTrue(sch.lessThan(sch.getScheduleStart(), schedule.getScheduleStart()));
  assertTrue(not(sch1.lessThan(sch1.getScheduleStart(), sch.getScheduleStart())));
  assertTrue(not(schedule3.lessThan(schedule3.getScheduleStart(), sch2.getScheduleStart())));
  assertTrue(sch.lessThan(sch.getScheduleStart(), sch1.getScheduleStart()));

  assertTrue(appointment.getSchedule().greaterThan(schedule4.getScheduleStart(), schedule5.
    getScheduleStart()));
  assertTrue(not(appointment.getSchedule().greaterThan(appointment.getSchedule().
    getScheduleStart(), schedule4.getScheduleStart())));
  assertTrue(not(sch.greaterThan(sch.getScheduleStart(), schedule.getScheduleStart())));
  assertTrue(sch1.greaterThan(sch1.getScheduleStart(), sch.getScheduleStart()));
  assertTrue(schedule.greaterThan(schedule.getScheduleStart(), sch.getScheduleStart()));
  assertTrue(not(sch.greaterThan(sch.getScheduleStart(), sch1.getScheduleStart())));

  IO`print("\n Checking overlap \n");
  assertTrue(schedule.overlap(schedule, schedule2));

);

public static main: () ==> ()
main() == (
  dcl taskTest: TaskTest := new TaskTest();
  IO`print("\n\n *****Running TaskTest***** \n");
  taskTest.testGetsSetsTask();
  taskTest.testAppointment();

  taskTest.testSurgery();
  taskTest.testTreatment();
  taskTest.testScheduleFunctions();
);

end TaskTest

```

Function or operation	Line	Coverage	Calls
-----------------------	------	----------	-------

assertTrue	59	100.0%	156
main	293	100.0%	2
testAppointment	174	100.0%	2
testGetsSetsTask	63	100.0%	2
testScheduleFunctions	256	100.0%	2
testSurgery	225	100.0%	2
testTreatment	248	100.0%	2
TaskTest.vdmpp		100.0%	168

19 TrainingTest

```

class TrainingTest
instance variables
  private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
    123432156", "921349076", "111111222", <Doctor>);
  private purpose: Types`Purpose := <Training>;

  private time1: Types`Time := mk_Types`Time(12, 10);
  private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
  private time2: Types`Time := mk_Types`Time(12, 30);
  private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
  private schedule: Schedule := new Schedule(date1, date2);

  private time3: Types`Time := mk_Types`Time(12, 15);
  private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
  private time4: Types`Time := mk_Types`Time(12, 35);
  private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
  private schedule2: Schedule := new Schedule(date3, date4);

  private training : Training := new Training(purpose, schedule, doctor);
operations

  private assertTrue: bool ==> ()
    assertTrue(cond) == return
  pre cond;

  public testGetsSets : () ==> ()
    testGetsSets() == (
      IO`print("\n Testing Training gets and sets \n");
      assertTrue(training.getPurpose() = <Training>);
      assertTrue(training.getMedAssoc().getCC() = "123432156");

      training.setPurpose(<AddSkills>);
      assertTrue(training.getPurpose() = <AddSkills>);

      assertTrue(training.getSchedule().getScheduleStart().year = 2017);
      assertTrue(training.getSchedule().getScheduleStart().month = 12);
      assertTrue(training.getSchedule().getScheduleStart().day = 25);
      assertTrue(training.getSchedule().getScheduleStart().time.hour = 12);
      assertTrue(training.getSchedule().getScheduleStart().time.min = 10);

      assertTrue(training.getSchedule().getScheduleEnd().year = 2017);
      assertTrue(training.getSchedule().getScheduleEnd().month = 12);
      assertTrue(training.getSchedule().getScheduleEnd().day = 25);
      assertTrue(training.getSchedule().getScheduleEnd().time.hour = 12);
      assertTrue(training.getSchedule().getScheduleEnd().time.min = 30);

```



```

);

public static main: () ==> ()
  main() == (
    dcl trainingTest: TrainingTest := new TrainingTest();
    IO`print("\n *****Running TrainingTest***** \n");
    trainingTest.testGetsSets();
  );
end TrainingTest

```

Function or operation	Line	Coverage	Calls
assertTrue	21	100.0%	52
main	47	100.0%	2
testGetsSets	25	100.0%	2
TrainingTest.vdmpp		100.0%	56