

MFES

December 23, 2017

Contents

1	PersonTest	1
2	RunTests	3
3	SafetyNetHospitalTest	3
4	TaskTest	7
5	TrainingTest	10
6	Appointment	11
7	HealthProfessional	12
8	Hospital	14
9	Medicament	16
10	Patient	17
11	Person	17
12	Prescription	18
13	SafetyNetHospital	19
14	Schedule	20
15	Specialty	21
16	Surgery	22
17	Task	23
18	Training	24
19	Treatment	25
20	Types	26

1 PersonTest

```
class PersonTest
instance variables
  private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111"
    , "0987654321");
  private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
    123432156", "921349076", "111111222", <Doctor>);
  private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "
    234512389", "921349134", "111111232", <Surgeon>);
  private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes",
    "123444654", "921378643", "111222333", <Nurse>);
  private technician: HealthProfessional := new HealthProfessional("Rua Antero Marques", "Ins", "
    Pinto", "123432151", "921348765", "123432578", <Technician>);
operations

  private assertTrue: bool ==> ()
    assertTrue(cond) == return
  pre cond;

  public testGetInformation: () ==> ()
    testGetInformation() == (
      assertTrue(patient.getHealthNumber() = "0987654321");
      assertTrue(patient.getCC() = "123456789");
      assertTrue(patient.getInfo() = "Name: " ^ "Rui" ^ " " ^ "Andrade" ^ "\nAddress: " ^ "Rua 1
        Maio" ^ "\nPhone Number: " ^ "223456111" ^ "\nCC: " ^ "123456789");

      assertTrue(doctor.getMedicalNumber() = "111111222");
      assertTrue(doctor.getCC() = "123432156");
      assertTrue(doctor.getInfo() = "Name: " ^ "Ana" ^ " " ^ "Marques" ^ "\nAddress: " ^ "Rua de
        Cima" ^ "\nPhone Number: " ^ "921349076" ^ "\nCC: " ^ "123432156");
      assertTrue(doctor.getType() = <Doctor>);

      assertTrue(surgeon.getMedicalNumber() = "111111232");
      assertTrue(surgeon.getCC() = "234512389");
      assertTrue(surgeon.getInfo() = "Name: " ^ "Diogo" ^ " " ^ "Viana" ^ "\nAddress: " ^ "Rua 2" ^
        "\nPhone Number: " ^ "921349134" ^ "\nCC: " ^ "234512389");
      assertTrue(surgeon.getType() = <Surgeon>);

      assertTrue(nurse.getMedicalNumber() = "111222333");
      assertTrue(nurse.getCC() = "123444654");
      assertTrue(nurse.getInfo() = "Name: " ^ "Lisete" ^ " " ^ "Antunes" ^ "\nAddress: " ^ "Rua de
        Baixo" ^ "\nPhone Number: " ^ "921378643" ^ "\nCC: " ^ "123444654");
      assertTrue(nurse.getType() = <Nurse>);

      assertTrue(technician.getMedicalNumber() = "123432578");
      assertTrue(technician.getCC() = "123432151");
      assertTrue(technician.getInfo() = "Name: " ^ "Ins" ^ " " ^ "Pinto" ^ "\nAddress: " ^ "Rua
        Antero Marques" ^ "\nPhone Number: " ^ "921348765" ^ "\nCC: " ^ "123432151");
      assertTrue(technician.getType() = <Technician>);
    );

  public testAddRemovePatient : () ==> ()
    testAddRemovePatient() == (
      assertTrue(card doctor.getPatients() = 0);

      doctor.addPatient(patient);
      assertTrue(card doctor.getPatients() = 1);

      doctor.removePatient(patient);
      assertTrue(card doctor.getPatients() = 0);
```

```

    assertTrue(card surgeon.getPatients() = 0);

    surgeon.addPatient(patient);
    assertTrue(card surgeon.getPatients() = 1);
};

public testAddRemoveSpecialty : () ==> ()
testAddRemoveSpecialty() == (
    dcl specialty1: Specialty := new Specialty("General"), specialty2: Specialty := new Specialty(
        "Cardio");

    assertTrue(card doctor.getSpecialties() = 0);

    doctor.addSpecialty(specialty1);
    assertTrue(specialty1.getName() = "General");

    assertTrue(card doctor.getSpecialties() = 1);
    assertTrue(doctor.getSpecialties() = {specialty1});

    doctor.addSpecialty(specialty2);
    assertTrue(specialty2.getName() = "Cardio");

    assertTrue(card doctor.getSpecialties() = 2);
    assertTrue(doctor.getSpecialties() = {specialty1, specialty2});

    doctor.removeSpecialty(specialty1);
    assertTrue(card doctor.getSpecialties() = 1);
    assertTrue(doctor.getSpecialties() = {specialty2});
);

public static main: () ==> ()
main() == (
    dcl personTest: PersonTest := new PersonTest();
    personTest.testGetInformation();
    personTest.testAddRemovePatient();
    personTest.testAddRemoveSpecialty();
);

end PersonTest

```

Function or operation	Line	Coverage	Calls
assertTrue	9	100.0%	297
main	79	100.0%	9
testAddRemovePatient	40	100.0%	9
testAddRemoveSpecialty	56	100.0%	9
testGetInformation	13	100.0%	9
PersonTest.vdmpp		100.0%	333

2 RunTests

```
class RunTests
```

operations

```
public static main: () ==> ()
main() == (
  dcl taskTest: TaskTest := new TaskTest(), personTest: PersonTest := new PersonTest(),
  trainingTest: TrainingTest := new TrainingTest(), safetyNetTest: SafetyNetHospitalTest :=
    new SafetyNetHospitalTest();

  personTest.main();
  taskTest.main();
  trainingTest.main();
  safetyNetTest.main();
);
end RunTests
```

Function or operation	Line	Coverage	Calls
main	4	100.0%	9
RunTests.vdmpp		100.0%	9

3 SafetyNetHospitalTest

```
class SafetyNetHospitalTest
types
instance variables
  private safetyNet: SafetyNetHospital := new SafetyNetHospital();

  private time1: Types`Time := mk_Types`Time(12, 10);
  private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
  private time2: Types`Time := mk_Types`Time(12, 30);
  private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
  private schedule: Schedule := new Schedule(date1, date2);

  private time3: Types`Time := mk_Types`Time(12, 15);
  private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
  private time4: Types`Time := mk_Types`Time(12, 35);
  private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
  private schedule2: Schedule := new Schedule(date3, date4);

  private time5: Types`Time := mk_Types`Time(12, 40);
  private date5: Types`Date := mk_Types`Date(2017, 12, 25, time5);
  private time6: Types`Time := mk_Types`Time(12, 50);
  private date6: Types`Date := mk_Types`Date(2017, 12, 25, time6);
  private schedule3: Schedule := new Schedule(date5, date6);

  private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111",
    "0987654321");
  private patient2: Patient := new Patient("Rua 1 Maio", "Diogo", "Andrade", "123321123", "
    911112345", "908765123");
  private patient3: Patient := new Patient("Rua 1 Maio", "Vitor", "Andrade", "135790864", "
    912345334", "123432130");
  private patient4: Patient := new Patient("Rua 1 Maio", "Simone", "Andrade", "234123765", "
    931238654", "0987654143");

  private hospital: Hospital := new Hospital("Hospital das Camlias", "Rua de Cima", safetyNet);

  private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
    123432156", "921349076", "111111222", <Doctor>);
```

```

private doctor2: HealthProfessional := new HealthProfessional("Rua de Cima", "Anabela", "
    Marques", "123432157", "921349077", "111111223", <Doctor>);
private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "
    234512389", "921349134", "111111232", <Surgeon>);
private secSurgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diana", "Viana", "
    234512390", "921349135", "111111235", <Surgeon>);
private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes",
    "1234444654", "921378643", "111222333", <Nurse>);
private technician: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lus", "
    Antunes", "1234444655", "921377654", "111222345", <Technician>);

private appointment: Appointment := new Appointment(doctor, schedule, patient, hospital);
private appointment2: Appointment := new Appointment(doctor, schedule3, patient4, hospital);
private appointment3: Appointment := new Appointment(doctor2, schedule3, patient, hospital);

private urgencies: Appointment := new Appointment(doctor2, <High>, schedule, patient2, hospital)
;
private surgery: Surgery := new Surgery(surgeon, schedule, patient3, hospital);
private treatment: Treatment := new Treatment(technician, "Fisioterapia", schedule, patient4,
    hospital);

private purpose: Types`Purpose := <Training>;
private training : Training := new Training(purpose, schedule, doctor);
operations
private assertTrue: bool ==> ()
    assertTrue(cond) == return
pre cond;

public testAddRemoveHospitals: () ==> ()
    testAddRemoveHospitals() == (
        dcl h1: Hospital, h2: Hospital, h3: Hospital;
        h1 := new Hospital("Hospital dos Lusadas", "Rua de Cima", safetyNet);
        h2 := new Hospital("Hospital Novo", "Rua 1 de Maio", safetyNet);
        h3 := new Hospital("Hospital da Trofa", "Rua da Trofa", safetyNet);

        assertTrue(h1.getName() = "Hospital dos Lusadas");
        assertTrue(h2.getName() = "Hospital Novo");
        assertTrue(h3.getName() = "Hospital da Trofa");

        assertTrue(h1.getAddress() = "Rua de Cima");
        assertTrue(h2.getAddress() = "Rua 1 de Maio");
        assertTrue(h3.getAddress() = "Rua da Trofa");

        assertTrue(card safetyNet.getHospitals() = 4);
        safetyNet.removeHospital(h1);
        assertTrue(card safetyNet.getHospitals() = 3);
        safetyNet.removeHospital(h2);
        assertTrue(card safetyNet.getHospitals() = 2);
    );

public testAddRemoveTaskHospital : () ==> ()
    testAddRemoveTaskHospital() == (
        assertTrue(card hospital.getTasksByType(<Appointment>) = 3);
        assertTrue(card hospital.getTasksByType(<Urgencies>) = 1);
        assertTrue(card hospital.getTasksByType(<Surgery>) = 1);
        assertTrue(card hospital.getTasksByType(<Other>) = 1);

        hospital.removeTask(appointment);
        assertTrue(card hospital.getTasksByType(<Appointment>) = 2);

        hospital.addTask(appointment);
        assertTrue(card hospital.getTasksByType(<Appointment>) = 3);

```

```

);

public testAddRemoveMedHospital : () ==> ()
testAddRemoveMedHospital() == (
    assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 0);
    assertTrue(card hospital.getMedicalAssociatedByType(<Surgeon>) = 0);
    assertTrue(card hospital.getMedicalAssociatedByType(<Nurse>) = 0);
    assertTrue(card hospital.getMedicalAssociatedByType(<Technician>) = 0);

    hospital.addMedAssociated(doctor);
    assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 1);
    hospital.addTraining(training);

    hospital.removeMedAssociated(doctor);
    assertTrue(card hospital.getMedicalAssociatedByType(<Doctor>) = 0);

    hospital.addMedAssociated(doctor);
    hospital.addMedAssociated(surgeon);
    hospital.addMedAssociated(nurse);
    hospital.addMedAssociated(technician);
);

public testAddRemoveTrainingHospital : () ==> ()
testAddRemoveTrainingHospital() == (
    assertTrue(card hospital.getTrainingsByType(<Training>) = 0);
    assertTrue(card hospital.getTrainingsByType(<AddSkills>) = 0);

    hospital.addTraining(training);
    assertTrue(card hospital.getTrainingsByType(<Training>) = 1);

    hospital.removeTraining(training);
    assertTrue(card hospital.getTrainingsByType(<Training>) = 0);
);

public testOverlap : () ==> ()
testOverlap() == (
    assertTrue(hospital.overlap(schedule, schedule2));
    assertTrue(hospital.overlap(schedule, schedule3) = false);
);

public testGetHospitalsMoreAppointments : () ==> ()

testGetHospitalsMoreAppointments() == (
    assertTrue(safetyNet.getHospitalsMoreAppointments(<Appointment>).getName() = "Hospital das
        Camlias");
    assertTrue(safetyNet.getHospitalsMoreAppointments(<Urgencies>).getName() = "Hospital das
        Camlias");
    assertTrue(safetyNet.getHospitalsMoreAppointments(<Surgery>).getName() = "Hospital das
        Camlias");
    assertTrue(safetyNet.getHospitalsMoreAppointments(<Other>).getName() = "Hospital das Camlias
        ");
);

public testGetMedMoreHospitals : () ==> ()
testGetMedMoreHospitals() == (
    for all t in set safetyNet.getHospitals() do

        if(t.getName() <> "Hospital das Camlias")
            then t.addMedAssociated(doctor);

    assertTrue(card safetyNet.getMedMoreHospitals(<Doctor>) = 1);
    assertTrue(safetyNet.getMedMoreHospitals(<Doctor>) = {doctor});

```

```

);

public testGetMedAssociatedByPatient : () ==> ()
testGetMedAssociatedByPatient() == (
    dcl mapTest : map Hospital to set of (HealthProfessional);

    mapTest := safetyNet.getMedAssociatedByPatient(patient, <Doctor>);

    assertTrue(card mapTest(hospital) = 1);
    assertTrue(mapTest(hospital) = {doctor});
);

public testGetMedByHospital : () ==> ()
testGetMedByHospital() == (
    dcl mapTest : map Hospital to set of (HealthProfessional);
    mapTest := safetyNet.getMedByHospital(<Doctor>);

    assertTrue(card mapTest(hospital) = 1);
    assertTrue(mapTest(hospital) = {doctor});

    mapTest := safetyNet.getMedByHospital(<Surgeon>);

    assertTrue(card mapTest(hospital) = 1);
    assertTrue(mapTest(hospital) = {surgeon});
);

public static main: () ==> ()
main() == (
    dcl safetyNetTest: SafetyNetHospitalTest := new SafetyNetHospitalTest();
    safetyNetTest.testAddRemoveHospitals();
    safetyNetTest.testAddRemoveTaskHospital();
    safetyNetTest.testAddRemoveTrainingHospital();
    safetyNetTest.testAddRemoveMedHospital();
    safetyNetTest.testOverlap();
    safetyNetTest.testGetHospitalsMoreAppointments();
    safetyNetTest.testGetMedMoreHospitals();
    safetyNetTest.testGetMedAssociatedByPatient();
    safetyNetTest.testGetMedByHospital();
);

end SafetyNetHospitalTest

```

Function or operation	Line	Coverage	Calls
assertTrue	41	100.0%	117
main	161	100.0%	8
testAddRemoveHospitals	45	100.0%	7
testAddRemoveMedHospital	81	100.0%	3
testAddRemoveTaskHospital	67	100.0%	3
testAddRemoveTrainingHospital	101	100.0%	3
testGetHospitalsMoreAppointments	119	100.0%	3
testGetMedAssociatedByPatient	137	100.0%	3
testGetMedByHospital	147	100.0%	3
testGetMedMoreHospitals	127	100.0%	3
testOverlap	113	100.0%	4
SafetyNetHospitalTest.vdmpp		100.0%	157

4 TaskTest

```
class TaskTest

instance variables
private safetyNet: SafetyNetHospital := new SafetyNetHospital();
private time1: Types`Time := mk_Types`Time(12, 10);
private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
private time2: Types`Time := mk_Types`Time(12, 30);
private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
private schedule: Schedule := new Schedule(date1, date2);

private time3: Types`Time := mk_Types`Time(12, 15);
private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
private time4: Types`Time := mk_Types`Time(12, 35);
private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
private schedule2: Schedule := new Schedule(date3, date4);

private patient: Patient := new Patient("Rua 1 Maio", "Rui", "Andrade", "123456789", "223456111", "0987654321");
private hospital: Hospital := new Hospital("Hospital dos Lusadas", "Rua de Cima", safetyNet);
private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "123432156", "921349076", "111111222", <Doctor>);
private doctor2: HealthProfessional := new HealthProfessional("Rua de Cima", "Anabela", "Marques", "123432157", "921349077", "111111223", <Doctor>);
private surgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diogo", "Viana", "234512389", "921349134", "111111232", <Surgeon>);
private secSurgeon: HealthProfessional := new HealthProfessional("Rua 2", "Diana", "Viana", "234512390", "921349135", "111111235", <Surgeon>);
private nurse: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lisete", "Antunes", "123444654", "921378643", "111222333", <Nurse>);
private technician: HealthProfessional := new HealthProfessional("Rua de Baixo", "Lus", "Antunes", "123444655", "921377654", "111222345", <Technician>);

private appointment: Appointment := new Appointment(doctor, schedule, patient, hospital);
private urgencies: Appointment := new Appointment(doctor2, <High>, schedule, patient, hospital);
private surgery: Surgery := new Surgery(surgeon, schedule, patient, hospital);
private treatment: Treatment := new Treatment(technician, "Fisioterapia", schedule, patient, hospital);

private medicament: Medicament := new Medicament("Brufen");
private prescription: Prescription := new Prescription("123");
operations

private assertTrue: bool ==> ()
  assertTrue(cond) == return
pre cond;

public testGetsSetsTask : () ==> ()
  testGetsSetsTask() == (
    assertTrue(appointment.getPatient().getCC() = "123456789");
    assertTrue(appointment.getHospital().getName() = "Hospital dos Lusadas");

    assertTrue(appointment.getType() = <Appointment>);
    assertTrue(urgencies.getType() = <Urgencies>);
    assertTrue(surgery.getType() = <Surgery>);
    assertTrue(treatment.getType() = <Other>);

    assertTrue(appointment.getMedAssoc().getCC() = "123432156");
    assertTrue(urgencies.getMedAssoc().getCC() = "123432157");
    assertTrue(surgery.getMedAssoc().getCC() = "234512389");
```



```

assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleStart().time.min = 10);

assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 30);

assertTrue(appointment.getSchedule().compareTo(appointment.getSchedule().getScheduleStart(),
    appointment.getSchedule().getScheduleEnd()) = false);
assertTrue(appointment.getSchedule().compareToLess(appointment.getSchedule().
    getScheduleStart(), appointment.getSchedule().getScheduleEnd()) = true);

appointment.getSchedule().setSchedule(date3, date4);
assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleStart().time.min = 15);

assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 35);

appointment.setSchedule(schedule2);

assertTrue(appointment.getSchedule().getScheduleStart().year = 2017);
assertTrue(appointment.getSchedule().getScheduleStart().month = 12);
assertTrue(appointment.getSchedule().getScheduleStart().day = 25);
assertTrue(appointment.getSchedule().getScheduleStart().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleStart().time.min = 15);

assertTrue(appointment.getSchedule().getScheduleEnd().year = 2017);
assertTrue(appointment.getSchedule().getScheduleEnd().month = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().day = 25);
assertTrue(appointment.getSchedule().getScheduleEnd().time.hour = 12);
assertTrue(appointment.getSchedule().getScheduleEnd().time.min = 35);
);

public testAppointment : () ==> ()
testAppointment() == (
    assertTrue(appointment.getPriority() = <Medium>);
    assertTrue(urgencies.getPriority() = <High>);

    urgencies.setPriority(<Low>);
    assertTrue(urgencies.getPriority() = <Low>);

    assertTrue(card appointment.getPrescriptions() = 0);
    assertTrue(card urgencies.getPrescriptions() = 0);

    assertTrue(medicament.getName() = "Brufen");
    assertTrue(prescription.getCode() = "123");
    assertTrue(card prescription.getMedicaments() = 0);

    prescription.addMedicament(medicament);
    assertTrue(card prescription.getMedicaments() = 1);
    assertTrue(prescription.getMedicaments() = {medicament});

```

```

prescription.removeMedicament(medicament);
assertTrue(card prescription.getMedicaments() = 0);
assertTrue(prescription.getMedicaments() = {});

appointment.addPrescription(prescription);
urgencies.addPrescription(prescription);
assertTrue(card appointment.getPrescriptions() = 1);
assertTrue(card urgencies.getPrescriptions() = 1);

appointment.removePrescription(prescription);
urgencies.removePrescription(prescription);
assertTrue(card appointment.getPrescriptions() = 0);
assertTrue(card urgencies.getPrescriptions() = 0);
);

public testSurgery: () ==> ()
testSurgery() == (
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 0);

    surgery.addSecondaryDoctor(secSurgeon);
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 1);

    surgery.removeSecondaryDoctor(secSurgeon);
    assertTrue(card surgery.getSurgeryPersons(<Surgeon>) = 0);

    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 0);
    surgery.addOther(nurse);
    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 1);

    surgery.removeOther(nurse);
    assertTrue(card surgery.getSurgeryPersons(<Nurse>) = 0);

    assertTrue(surgery.getMainDoctor().getCC() = "234512389");
    surgery.setMainDoctor(secSurgeon);
    assertTrue(surgery.getMainDoctor().getCC() = "234512390");
);

public testTreatment: () ==> ()
testTreatment() == (
    assertTrue(treatment.getName() = "Fisioterapia");
    assertTrue(treatment.getMed().getCC() = "123444655");
);

public static main: () ==> ()
main() == (
    dcl taskTest: TaskTest := new TaskTest();
    taskTest.testGetsSetsTask();
    taskTest.testAppointment();
    taskTest.testSurgery();
    taskTest.testTreatment();
);

end TaskTest

```

Function or operation	Line	Coverage	Calls
assertTrue	34	100.0%	603
main	157	100.0%	9

testAppointment	95	100.0%	9
testGetsSetsTask	38	100.0%	27
testSurgery	129	100.0%	9
testTreatment	151	100.0%	45
TaskTest.vdmpp		100.0%	702

5 TrainingTest

```

class TrainingTest
instance variables
  private doctor: HealthProfessional := new HealthProfessional("Rua de Cima", "Ana", "Marques", "
    123432156", "921349076", "111111222", <Doctor>);
  private purpose: Types`Purpose := <Training>;

  private time1: Types`Time := mk_Types`Time(12, 10);
  private date1: Types`Date := mk_Types`Date(2017, 12, 25, time1);
  private time2: Types`Time := mk_Types`Time(12, 30);
  private date2: Types`Date := mk_Types`Date(2017, 12, 25, time2);
  private schedule: Schedule := new Schedule(date1, date2);

  private time3: Types`Time := mk_Types`Time(12, 15);
  private date3: Types`Date := mk_Types`Date(2017, 12, 25, time3);
  private time4: Types`Time := mk_Types`Time(12, 35);
  private date4: Types`Date := mk_Types`Date(2017, 12, 25, time4);
  private schedule2: Schedule := new Schedule(date3, date4);

  private training : Training := new Training(purpose, schedule, doctor);
operations

  private assertTrue: bool ==> ()
    assertTrue(cond) == return
  pre cond;

  public testGetsSets : () ==> ()
    testGetsSets() == (
      assertTrue(training.getPurpose() = <Training>);
      assertTrue(training.getMedAssoc().getCC() = "123432156");

      training.setPurpose(<AddSkills>);
      assertTrue(training.getPurpose() = <AddSkills>);

      assertTrue(training.getSchedule().getScheduleStart().year = 2017);
      assertTrue(training.getSchedule().getScheduleStart().month = 12);
      assertTrue(training.getSchedule().getScheduleStart().day = 25);
      assertTrue(training.getSchedule().getScheduleStart().time.hour = 12);
      assertTrue(training.getSchedule().getScheduleStart().time.min = 10);

      assertTrue(training.getSchedule().getScheduleEnd().year = 2017);
      assertTrue(training.getSchedule().getScheduleEnd().month = 12);
      assertTrue(training.getSchedule().getScheduleEnd().day = 25);
      assertTrue(training.getSchedule().getScheduleEnd().time.hour = 12);
      assertTrue(training.getSchedule().getScheduleEnd().time.min = 30);

      training.setSchedule(schedule2);

      assertTrue(training.getSchedule().getScheduleStart().year = 2017);
      assertTrue(training.getSchedule().getScheduleStart().month = 12);

```

```

    assertTrue(training.getSchedule().getScheduleStart().day = 25);
    assertTrue(training.getSchedule().getScheduleStart().time.hour = 12);
    assertTrue(training.getSchedule().getScheduleStart().time.min = 15);

    assertTrue(training.getSchedule().getScheduleEnd().year = 2017);
    assertTrue(training.getSchedule().getScheduleEnd().month = 12);
    assertTrue(training.getSchedule().getScheduleEnd().day = 25);
    assertTrue(training.getSchedule().getScheduleEnd().time.hour = 12);
    assertTrue(training.getSchedule().getScheduleEnd().time.min = 35);
  };

  public static main: () ==> ()
  main() == (
    decl trainingTest: TrainingTest := new TrainingTest();
    trainingTest.testGetsSets();
  );
end TrainingTest

```

Function or operation	Line	Coverage	Calls
assertTrue	21	100.0%	414
main	60	100.0%	9
testGetsSets	25	100.0%	9
TrainingTest.vdmpp		100.0%	432

6 Appointment

```

class Appointment is subclass of Task

instance variables
  private prescriptions: set of (Prescription);
  private priority : Types`Priority;

  inv priority <> nil;
  inv card prescriptions >= 0;
  inv medicalAssoc.getType() = <Doctor>;
operations

  public Appointment: HealthProfessional * Schedule * Patient * Hospital ==> Appointment
    Appointment(d, s, p, h) == (medicalAssoc := d; priority := <Medium>; prescriptions := {}); Task(
      d, s, p, h, <Appointment>))
  post medicalAssoc = d and prescriptions = {} and priority = <Medium>;

  public Appointment: HealthProfessional * Types`Priority * Schedule * Patient * Hospital ==>
    Appointment
    Appointment(d, p, s, pat, h) == (medicalAssoc := d; priority := p; prescriptions := {}); Task(d,
      s, pat, h, <Urgencies>))
  pre p <> nil
  post medicalAssoc = d and prescriptions = {} and priority = p;

  pure public getPriority : () ==> Types`Priority
    getPriority() == (return priority);

  pure public getPrescriptions : () ==> set of (Prescription)

```

```

    getPrescriptions() == (return prescriptions);

public setPriority : Types`Priority ==> ()
    setPriority(p) == (priority := p)
pre type = <Urgencies>;

public addPrescription : Prescription ==> ()
    addPrescription(p) == (prescriptions := prescriptions union {p})
pre p not in set prescriptions
post p in set prescriptions;

public removePrescription : Prescription ==> ()
    removePrescription(p) == (prescriptions := prescriptions \ {p})
pre p in set prescriptions
post p not in set prescriptions;

end Appointment

```

Function or operation	Line	Coverage	Calls
Appointment	11	100.0%	36
addPrescription	30	100.0%	18
getPrescriptions	23	100.0%	54
getPriority	20	100.0%	27
removePrescription	35	100.0%	18
setPriority	26	100.0%	18
Appointment.vdmpp		100.0%	171

7 HealthProfessional

```

class HealthProfessional is subclass of Person

instance variables
    private medicalNumber: Types`String;
    private specialties:set of (Specialty);
    private patients : set of(Patient);
    private type : Types`Type;

    inv card patients >= 0;
    inv card specialties < 5;
    inv type <> nil;
operations

    public HealthProfessional: Types`String * Types`String * Types`String * Types`String * Types`
        String * Types`String * Types`Type ==> HealthProfessional
        HealthProfessional(a, fn, ln, c, pn, s, t) == (medicalNumber := s; type := t; specialties :=
            {} ; patients := {} ; Person(a, fn, ln, c, pn))
    pre t <> nil
    post medicalNumber = s and type = t and specialties = {} and patients = {};

    pure public getMedicalNumber: () ==> Types`String
        getMedicalNumber() == (return medicalNumber);

```

```

pure public getSpecialties: () ==> set of (Specialty)
  getSpecialties() == (return specialties);

pure public getPatients: () ==> set of (Patient)
  getPatients() == (return patients);

pure public getType : () ==> Types`Type
  getType() == (return type);

public removeSpecialty: Specialty ==> ()
  removeSpecialty(s) == (specialties := specialties \ {s})
pre s in set specialties
post s not in set specialties;

public addSpecialty: Specialty ==> ()
  addSpecialty(s) == (specialties := specialties union {s})
pre s not in set specialties
post s in set specialties;

public addPatient : Patient ==> ()
  addPatient(p) == (patients := patients union {p})
pre p not in set patients
post p in set patients;

public removePatient : Patient ==> ()
  removePatient(p) == (patients := patients \ {p})
pre p in set patients
post p not in set patients;

end HealthProfessional

```

Function or operation	Line	Coverage	Calls
HealthProfessional	13	100.0%	312
addPatient	40	100.0%	179
addSpecialty	35	100.0%	18
getMedicalNumber	18	100.0%	36
getPatients	24	100.0%	399
getSpecialties	21	100.0%	63
getType	27	100.0%	617
removePatient	45	100.0%	9
removeSpecialty	30	100.0%	9
HealthProfessional.vdmpp		100.0%	1642

8 Hospital

```

class Hospital

```

```

instance variables
  private medicalAssociated: set of (HealthProfessional);
  private name: Types'String;
  private address: Types'String;
  private tasks: set of(Task);
  private trainings: set of(Training);
  private safetyNet: [SafetyNetHospital];

  inv safetyNet <> nil;
  inv card medicalAssociated >= 0;
  inv card tasks >= 0;
operations

  public Hospital: Types'String * Types'String * SafetyNetHospital ==> Hospital
    Hospital(n, a, s) == (name := n; address := a; safetyNet := s; medicalAssociated := {}; tasks
      := {}; trainings := {});
    safetyNet.addHospital(self); return self)
  pre safetyNet <> nil
  post name = n and address = a and safetyNet = s and medicalAssociated = {} and tasks = {} and
    trainings = {};

  pure public getName: () ==> Types'String
    getName() == (return name);

  pure public getAddress: () ==> Types'String
    getAddress() == (return address);

  public addMedAssociated: HealthProfessional ==> ()
    addMedAssociated(d) == (medicalAssociated := {d} union medicalAssociated)
  pre d not in set medicalAssociated
  post d in set medicalAssociated;

  public removeMedAssociated: HealthProfessional ==> ()
    removeMedAssociated(d) == (
      for all t in set tasks do
        if (d = t.getMedAssoc())
          then removeTask(t);
      for all t in set trainings do
        if (d = t.getMedAssoc())
          then removeTraining(t);
      medicalAssociated := medicalAssociated \ {d})
  pre d in set medicalAssociated
  post d not in set medicalAssociated;

  public addTask: Task ==> ()
    addTask(d) == (
      if (d.getPatient() not in set d.getMedAssoc().getPatients())
        then d.getMedAssoc().addPatient(d.getPatient());
      tasks := {d} union tasks)
  pre d not in set tasks and forall t in set tasks &
    not (overlap(d.getSchedule(), t.getSchedule()) and (d.getMedAssoc().getCC() = t.getMedAssoc().
      getCC())
    and d.getPatient().getCC() = t.getPatient().getCC() and d.getMedAssoc().getCC() = t.getPatient
      ().getCC() and d.getPatient().getCC() = t.getMedAssoc().getCC())
    and forall tr in set trainings & not (overlap(d.getSchedule(), tr.getSchedule()) and (d.
      getMedAssoc().getCC() = tr.getMedAssoc().getCC())
  post d in set tasks and d.getPatient() in set d.getMedAssoc().getPatients();

```

```

public removeTask: Task ==> ()
  removeTask(d) == (tasks := tasks \ {d})
pre d in set tasks
post d not in set tasks;

public addTraining: Training ==> ()
  addTraining(d) == (trainings := {d} union trainings)
pre d not in set trainings and forall t in set trainings & not (overlap(d.getSchedule(), t.
    getSchedule()))
and forall tr in set tasks & not (overlap(d.getSchedule(), tr.getSchedule()) and (d.getMedAssoc
    ().getCC() = tr.getMedAssoc().getCC()))

or d.getMedAssoc().getCC() = tr.getPatient().getCC())
post d in set trainings;

public removeTraining: Training ==> ()
  removeTraining(d) == (trainings := trainings \ {d})

pre d in set trainings
post d not in set trainings;

pure public getTasksByType: Types`TaskType ==> set of (Task)
  getTasksByType(s) == (
    dcl tasksTotal: set of (Task);
    tasksTotal := {};
    for all t in set tasks do
      if (t.getType() = s)
        then tasksTotal := tasksTotal union {t};

    return tasksTotal);

pure public getTrainingsByType: Types`Purpose ==> set of (Training)
  getTrainingsByType(s) == (
    dcl train: set of (Training);
    train := {};
    for all t in set trainings do
      if (t.getPurpose() = s)
        then train := train union {t};

    return train);

pure public getMedicalAssociatedByType: Types`Type ==> set of (HealthProfessional)
  getMedicalAssociatedByType(type) == (
    dcl med: set of (HealthProfessional);
    med := {};
    for all d in set medicalAssociated do
      if (d.getType() = type)
        then med := med union {d};

    return med);

pure public overlap: Schedule * Schedule ==> bool
  overlap(t1, t2) == (
    if (t1.compareDate(t1.getScheduleStart(), t2.getScheduleStart())
      or (not t1.compareDateLess(t1.getScheduleStart(), t2.getScheduleStart())
      or not t1.compareDateLess(t1.getScheduleEnd(), t2.getScheduleStart()))
      then return true
    else
      return false);

end Hospital

```


Function or operation	Line	Coverage	Calls
Hospital	15	100.0%	64
addMedAssociated	27	100.0%	48
addTask	44	66.6%	0
addTraining	59	32.6%	0
getAddress	24	100.0%	27
getMedicalAssociatedByType	89	100.0%	40
getName	21	100.0%	84
getTasksByType	69	100.0%	36
getTrainingsByType	79	100.0%	2
overlap	99	100.0%	32
removeMedAssociated	32	100.0%	8
removeTask	54	100.0%	6
removeTraining	64	100.0%	4
Hospital.vdmpp		82.2%	351

9 Medicament

```

class Medicament

instance variables
  private name:Types`String;
operations

  public Medicament: Types`String ==> Medicament
    Medicament(n) == (name := n; return self)
  post name = n;

  pure public getName: () ==> Types`String
    getName() == (return name);

end Medicament

```

Function or operation	Line	Coverage	Calls
Medicament	6	100.0%	18
getName	10	100.0%	9
Medicament.vdmpp		100.0%	27

10 Patient

```

class Patient is subclass of Person
instance variables

```

```

    private healthNumber: Types`String;
operations

    public Patient: Types`String * Types`String * Types`String * Types`String * Types`String * Types`String ==> Patient
        `String ==> Patient
        Patient(a, fn, ln, c, pn, n) == ( healthNumber := n; Person(a, fn, ln, c, pn))
    post healthNumber = n;

    pure public getHealthNumber : () ==> Types`String
        getHealthNumber() == (return healthNumber);

end Patient

```

Function or operation	Line	Coverage	Calls
Patient	5	100.0%	109
getHealthNumber	9	100.0%	9
Patient.vdmpp		100.0%	118

11 Person

```

class Person

instance variables
    protected address: Types`String;
    protected firstName: Types`String;
    protected lastName: Types`String;
    protected cc : Types`String;
    protected phoneNumber: Types`String;
operations

    public Person: Types`String * Types`String * Types`String * Types`String * Types`String ==>
        Person
        Person(a, fn, ln, c, pn) == ( address := a; firstName := fn; lastName := ln; cc := c;
            phoneNumber := pn; return self)
    post address = a and firstName = fn and lastName = ln and cc = c and phoneNumber = pn;

    pure public getCC : () ==> Types`String
        getCC() == (return cc);

    pure public getInfo: () ==> Types`String
        getInfo() == (return "Name: " ^ firstName ^ " " ^ lastName ^ "\nAddress: " ^ address ^ "\nPhone
            Number: " ^ phoneNumber ^ "\nCC: " ^ cc);

end Person

```

Function or operation	Line	Coverage	Calls
Person	10	100.0%	421
getCC	14	100.0%	989
getInfo	17	100.0%	45

Person.vdmpp		100.0%	1455
--------------	--	--------	------

12 Prescription

```

class Prescription

instance variables
  private medicaments: set of (Medicament);
  private code: Types`String;

operations

public Prescription: Types`String ==> Prescription
  Prescription(c) == (code := c; medicaments := {}); return self
post code = c and medicaments = {};

pure public getCode : () ==> Types`String
  getCode() == (return code);

public addMedicament: Medicament ==> ()
  addMedicament(m) == (medicaments := {m} union medicaments)
pre m not in set medicaments
post m in set medicaments;

public removeMedicament: Medicament ==> ()
  removeMedicament(m) == (medicaments := medicaments \ {m})
pre m in set medicaments
post m not in set medicaments;

pure public getMedicaments: () ==> set of (Medicament)
  getMedicaments() == (return medicaments);

end Prescription

```

Function or operation	Line	Coverage	Calls
Prescription	8	100.0%	18
addMedicament	15	100.0%	9
getCode	12	100.0%	9
getMedicaments	25	100.0%	45
removeMedicament	20	100.0%	9
Prescription.vdmpp		100.0%	90

13 SafetyNetHospital

```

class SafetyNetHospital
instance variables
  private hospitals: set of (Hospital);

```

```

inv card hospitals >= 0;
operations

public SafetyNetHospital : () ==> SafetyNetHospital
  SafetyNetHospital() == (hospitals := {}); return self
post hospitals = {};

public addHospital : Hospital ==> ()
  addHospital(h) == (hospitals := hospitals union {h})
pre h not in set hospitals
post h in set hospitals;

public removeHospital : Hospital ==> ()
  removeHospital(h) == (hospitals := hospitals \ {h})
pre h in set hospitals
post h not in set hospitals;

pure public getHospitals : () ==> set of (Hospital)
  getHospitals() == (return hospitals);

-- Mudar --

pure public getHospitalsMoreAppointments : Types`TaskType ==> Hospital
  getHospitalsMoreAppointments(t) == (
    dcl max: int, hosp: Hospital;
    max := -1;
    for all h in set hospitals do
      if((card h.getTasksByType(t)) > max)
        then (max := (card h.getTasksByType(t)); hosp := h);
    return hosp);

pure public getMedMoreHospitals : Types`Type ==> set of(HealthProfessional)
  getMedMoreHospitals(t) == (
    dcl doctors: set of(HealthProfessional);
    doctors := {};
    for all h in set hospitals do (
      dcl med: set of (HealthProfessional), list: set of(Hospital);
      med := h.getMedicalAssociatedByType(t);

      list := hospitals \ {h};
      for all m in set med do(
        for all l in set list do
          if(m.getType() = t and m in set l.getMedicalAssociatedByType(t) and m not in set doctors)
            then doctors := doctors union {m};
        );
      );
    return doctors;
  );

pure public getMedAssociatedByPatient: Patient * Types`Type ==> map Hospital to set of(
  HealthProfessional)
  getMedAssociatedByPatient(p, t) == (
    dcl maps: map Hospital to set of(HealthProfessional), med : set of (
      HealthProfessional);
    maps := { |-> };
    med := {};

```

```

    for all h in set hospitals do (
      for all m in set h.getMedicalAssociatedByType(t) do
        if(p in set m.getPatients())
          then med := med union {m};

      maps := maps munion {h |-> med};
      med := {};);
    return maps);

pure public getMedByHospital: Types`Type ==> map Hospital to set of(HealthProfessional)
getMedByHospital(t) == (
  decl maps: map Hospital to set of(HealthProfessional);
  maps := { |-> };
  for all h in set hospitals do
    maps := maps munion {h |-> h.getMedicalAssociatedByType(t)};
  return maps);
end SafetyNetHospital

```

Function or operation	Line	Coverage	Calls
SafetyNetHospital	8	100.0%	37
addHospital	12	100.0%	64
getHospitals	22	100.0%	35
getHospitalsMoreAppointments	26	100.0%	32
getMedAssociatedByPatient	54	100.0%	16
getMedByHospital	68	100.0%	16
getMedMoreHospitals	35	100.0%	32
removeHospital	17	100.0%	36
SafetyNetHospital.vdmpp		100.0%	268

14 Schedule

```

class Schedule

types
instance variables
  private startHour: Types`Date;
  private endHour: Types`Date;

  inv compareDateLess(startHour, endHour) = true and startHour.year = endHour.year and startHour.
    month = endHour.month and startHour.day = endHour.day;
operations

public Schedule: Types`Date * Types`Date ==> Schedule
  Schedule(d, d2) == (startHour := d; endHour := d2; return self)
pre compareDateLess(d, d2)
post startHour = d and endHour = d2;

public setSchedule : Types`Date * Types`Date ==> ()
  setSchedule(d1, d2) == (startHour := d1; endHour := d2;)
pre compareDateLess(d1, d2);

pure public getScheduleStart : () ==> Types`Date

```

```

getScheduleStart() == (return startHour);

pure public getScheduleEnd : () ==> Types`Date
getScheduleEnd() == (return endHour);

pure public compareDateLess : Types`Date * Types`Date ==> bool
compareDateLess(d1, d2) == (return (d1.year <= d2.year and d1.month <= d2.month and d1.day <=
d2.day and d1.time.hour <= d2.time.hour and d1.time.min < d2.time.min));

pure public compareDate : Types`Date * Types`Date ==> bool
compareDate(d1, d2) == (return (d1.year = d2.year and d1.month = d2.month and d1.day = d2.day
and d1.time.hour = d2.time.hour and d1.time.min = d2.time.min));

end Schedule

```

Function or operation	Line	Coverage	Calls
Schedule	10	100.0%	128
compareDate	28	100.0%	343
compareDateLess	25	100.0%	450
getScheduleEnd	22	100.0%	314
getScheduleStart	19	100.0%	1156
setSchedule	15	100.0%	9
Schedule.vdmpp		100.0%	2400

15 Specialty

```

class Specialty

instance variables
  private name: Types`String;
operations

  public Specialty : Types`String ==> Specialty
    Specialty(n) == (name := n; return self)
  post name = n;

  pure public getName : () ==> Types`String
    getName() == (return name);

end Specialty

```

Function or operation	Line	Coverage	Calls
Specialty	6	100.0%	18
getName	10	100.0%	18
Specialty.vdmpp		100.0%	36

16 Surgery

```
class Surgery is subclass of Task
instance variables
  private secondaryDoctors:set of (HealthProfessional);
  private other:set of (HealthProfessional);

  inv card secondaryDoctors >= 0;
  inv card other >= 0;
operations

public Surgery: HealthProfessional * Schedule * Patient * Hospital ==> Surgery
  Surgery(s, sch, p, h) == (medicalAssoc := s ; other := {}; secondaryDoctors := {} ; Task(s, sch,
    p, h, <Surgery>))
post medicalAssoc = s and other = {} and secondaryDoctors = {};

public addSecondaryDoctor : HealthProfessional ==> ()
  addSecondaryDoctor(s) == (secondaryDoctors := secondaryDoctors union {s})
pre s <> medicalAssoc and s.getType() = <Surgeon> and s not in set secondaryDoctors
post s in set secondaryDoctors;

public removeSecondaryDoctor : HealthProfessional ==> ()
  removeSecondaryDoctor(s) == (secondaryDoctors := secondaryDoctors \ {s})
pre s.getType() = <Surgeon> and s in set secondaryDoctors
post s not in set secondaryDoctors;

public addOther : HealthProfessional ==> ()
  addOther(s) == (other := other union {s})
pre s.getType() = <Nurse> and s not in set other
post s in set other;

public removeOther : HealthProfessional ==> ()
  removeOther(s) == (other := other \ {s})
pre s.getType() = <Nurse> and s in set other
post s not in set other;

public setMainDoctor : HealthProfessional ==> ()
  setMainDoctor(s) == (medicalAssoc := s)
pre s.getType() = <Surgeon> and s not in set secondaryDoctors;

public getMainDoctor : () ==> HealthProfessional
  getMainDoctor() == (return medicalAssoc);

public getSurgeryPersons : Types`Type ==> set of (HealthProfessional)
  getSurgeryPersons(t) == (
    dcl med : set of (HealthProfessional);
    if(t = <Surgeon>)
      then med := secondaryDoctors
    else
      med := other;
    return med);
end Surgery
```

Function or operation	Line	Coverage	Calls
Surgery	9	100.0%	36
addOther	23	100.0%	9
addSecondaryDoctor	13	100.0%	9
getMainDoctor	37	100.0%	18
getSurgeryPersons	40	100.0%	54
removeOther	28	100.0%	9
removeSecondaryDoctor	18	100.0%	9
setMainDoctor	33	100.0%	9
Surgery.vdmpp		100.0%	153

17 Task

```

class Task
instance variables
  protected schedule:[Schedule];
  protected patient:[Patient];
  protected hospital:[Hospital];
  protected medicalAssoc:[HealthProfessional];
  protected type : Types`TaskType;

  inv patient <> nil;
  inv hospital <> nil;
  inv type <> nil;
operations

  public Task: HealthProfessional * Schedule * Patient * Hospital * Types`TaskType ==> Task
    Task(med, s, p, h, t) == (schedule := s; patient := p; hospital := h; type := t; medicalAssoc
      := med;
      h.addTask(self); return self)
  pre med.getCC() <> p.getCC()
  post schedule = s and patient = p and hospital = h and medicalAssoc = med;

  pure public getSchedule: () ==> Schedule
    getSchedule() == (return schedule);

  pure public getPatient: () ==> Patient
    getPatient() == (return patient);

  pure public getHospital: () ==> Hospital
    getHospital() == (return hospital);

  pure public getType: () ==> Types`TaskType
    getType() == (return type);

  pure public getMedAssoc : () ==> HealthProfessional
    getMedAssoc() == (return medicalAssoc);

  public setSchedule : Schedule ==> ()
    setSchedule(s) == (schedule := s);

end Task

```


Function or operation	Line	Coverage	Calls
Task	13	100.0%	161
getHospital	25	100.0%	9
getMedAssoc	31	100.0%	1091
getPatient	22	100.0%	530
getSchedule	19	100.0%	969
getType	28	100.0%	483
setSchedule	34	100.0%	9
Task.vdmpp		100.0%	3252

18 Training

```

class Training

instance variables
  private medicalAssociated:[HealthProfessional];
  private purpose:[Types`Purpose];
  private schedule:[Schedule];

  inv medicalAssociated <> nil;
  inv purpose <> nil;
  inv schedule <> nil;

operations

  public Training: Types`Purpose * Schedule * HealthProfessional ==> Training
    Training(p, s, h) == (purpose := p; schedule := s; medicalAssociated := h; return self)
  post purpose = p and schedule = s and medicalAssociated = h;

  pure public getSchedule : () ==> Schedule
    getSchedule() == (return schedule);

  pure public getPurpose : () ==> Types`Purpose
    getPurpose() == (return purpose);

  pure public getMedAssoc : () ==> HealthProfessional
    getMedAssoc() == (return medicalAssociated);

  public setSchedule : Schedule ==> ()
    setSchedule(s) == (schedule := s);

  public setPurpose : Types`Purpose ==> ()
    setPurpose(p) == (purpose := p);

end Training

```

Function or operation	Line	Coverage	Calls
Training	13	100.0%	36
getMedAssoc	23	100.0%	17
getPurpose	20	100.0%	26
getSchedule	17	100.0%	180
setPurpose	29	100.0%	9
setSchedule	26	100.0%	9
Training.vdmpp		100.0%	277

19 Treatment

```

class Treatment is subclass of Task
instance variables
  public med: [HealthProfessional];
  public name: Types`String;

  inv med.getType() = <Nurse> or med.getType() = <Technician>;
operations

  public Treatment: HealthProfessional * Types`String * Schedule * Patient * Hospital ==>
    Treatment
    Treatment(m, n, s, p, h) == (name := n; med := m; Task(m, s, p, h, <Other>))
  post name = n and med = m;

  pure public getName: () ==> Types`String
  getName() == (return name);

  pure public getMed : () ==> HealthProfessional
  getMed() == (return med);

end Treatment

```

Function or operation	Line	Coverage	Calls
Treatment	9	100.0%	36
getMed	16	100.0%	9
getName	13	100.0%	9
Treatment.vdmpp		100.0%	54

20 Types

```

class Types
types
  public String = seq1 of (char);
  public Priority = <High> | <Medium> | <Low>;
  public Type = <Doctor> | <Surgeon> | <Nurse> | <Technician>;
  public TaskType = <Appointment> | <Urgencies> | <Surgery> | <Other>;

```

```

public Purpose = <Training> | <AddSkills>;
public Time :: hour : nat
    min: nat
inv t == t.hour >= 0 and t.hour < 24 and t.min >= 0 and t.min < 60;
public Date :: year: nat1
    month: nat1
    day: nat1
    time: Time
inv d == d.month <= 12 and d.day <= 31;
end Types

```

Function or operation	Line	Coverage	Calls
Types.vdmpp		100.0%	0