

"null value appear in datagridview in after new column added my datagridview have one name column. i am trying to add one image column with that datagridview. once i add the image column it made that name column as null. please refer the below code:..

```

public void call(string
usr){.    user = usr;.    querystring = ""select name 'name' from adk_my_prodsyssecgroup"";.
try.    {.    specdataadapter = new sqldataadapter(querystring, con);.    specds = new
dataset();.    con.open();.    specdataadapter.fill(specds, ""report_table"");.
dgvdisp.datasource = specds;.    dgvdisp.datamember = ""report_table"";.
dgvdisp.columns[dgvdisp.columncount - 1].autosizemode =
datagridviewautosizecolumnmode.fill;.    con.close();..    if (user == ""secgrp"").    {.
datagridviewimagecolumn set = new datagridviewimagecolumn();.    set.name = ""set"";.
set.headertext = ""settings"";.    dgvdisp.columns.insert(1, set);.    for (int rows = 0;
rows < dgvdisp.rows.count; rows++).    {.
messagebox.show(dgvdisp.rows[rows].cells[0].value.toString());.    }.    }.    catch
(exception ex).    {.    dispmessagebox disp = new dispmessagebox(""fail to retrieve data.
please try again"");.    disp.showdialog();.    }.}..public void calling(){.    sqlconnection con =
new sqlconnection(connetionstring);..    for (int rows = 0; rows < dgvdisp.rows.count; rows++).
{.    sqlcommand command = new sqlcommand(""select settings from
adk_my_prodsyssecgroup where name="" + convert.toString(dgvdisp.rows[rows].cells[0].value)
+ """"", con);.    con.open();.    sqldatareader reader = command.executereader();.    if
(reader.hasrows).    {.    while (reader.read()).    {.    if (reader.getint32(0) ==
1).    {.    image image = properties.resources.start;.    //set.image =
image;.    dgvdisp.rows[rows].cells[""set""].value = image;.    }.    if
(reader.getint32(0) == 0).    {.    image image = properties.resources.finish;.
//set.image = image;.    dgvdisp.rows[rows].cells[""set""].value = image;.    }.
}.    }.    reader.close();.    con.close();.    }.}...here in the call method, dgvdisp
datagridview shows the value, but when i tried to get the value from calling method, the
datagridview shows null value when i retrieve name field...please suggest..."

```

"how to sum all the fractions in a loop? i'd like to calculate the sum of the following numbers using a loop.. $\frac{1}{3} + \frac{3}{5} + \frac{5}{7} + \dots + \frac{95}{97} + \frac{97}{99}$...print the sum..so far this is what i wrote but i could only get it to print the fractions..s = ".for j in range(30, 0, -1):. s += ""{}/{} + ""..format(31-j, j). sum = +=j.print sum"

"Python: rearrange an interger number to a largest palindrome number i have written the following code to solve the topic ""rearrange an interger number to a largest palindrome number""..example:..input data is 485, the output should be 'not palindrome number'..input data is 445, the output should be 454..input data is 24266, the output should be 62426 (largest palindrome, not 26462)..please take a look and help me correct this..the problem i met:..input 112 -> it just returns 2..thank you!..

```

def largest_palindrome(self, number):.    a =
list(str(number)).    duplicate = [item for item, count in collections.counter(a).items() if count
> 1].    if (round(len(a)/2,0) != len(duplicate)):.    print 'not palindrome number'.
else:.    uniq = [].    max_item = a[0].    for i in range (1, len (a)):.    if a[i]
> max_item:.    max_item = a[i].    uniq=uniq.append(max_item).
return uniq"

```

"why is sorted documented as taking an iterable instead of a collection? is there some deeper meaning why python's sorted is documented as taking an iterable (which may be infinite) instead of a collection (which is sized)?..for example, this will run forever..

```
# do not run.import
itertools..for item in sorted(itertools.count()):.. print(item)...
```


i get that they'd want to allow sorted to work on a collection's iterable object instead of the collection itself, but isn't there a fundamental difference (perhaps to be reflected in collections.abc) between iterables that are guaranteed to raise a stopiteration and iterables that may be infinite?"

"how to update config file from code behind page in c# i am working on a web application which extracts data from databases. databases are residing on server. i want the user to provide server name, username and password from the web application, which will help me to modify my connection string in web.config file from the code behind page. so, how can i update the config file from the code behind page in c#?..guide me on what do i need to do here."

"is there a way for me to get detailed formatted information on a python class? so, i know i can use dir() to get information about class members etc. what i'm looking for is a way to get a nicely formatted report on everything related to a class (the members, docstrings, inheritance hierarchy, etc.)...i want to be able to run this on the command-line so i can explore code and debug better."

"implementing exception handling in javascript i would like to know the best and easiest way to implement exception handling in javascript. i'm looking for a ""one point"" solution. i've got lot of functions and wouldn't want to go around and implement try-catch. ..i feel window.onerror would be a better approach, since i just have to implement this in one place and any exceptions that occurs in any of the functions, i would be able to handle it using window.onerror. however, this seems to be supported only in ie. is there any similar way that i can use so that it supports all major standard browsers...thanks in advance."

"how to pass variable to anonymous function i want to pass variable setTimeoutfunction and do something with that. when i alert value of i it shows me numbers that i did not expected. what i m doing wrong? i want log values from 1 till 8...

```
var end=8;.for (var i = 1; i &lt;= end; i ++ ) {
setTimeout(function (i) {.. console.log(i); .. }, 800);. }
```

"Javascript - sum/total is reading nan i am making a pricing sheet that allows you to input the quantity of an item and will automatically calculate the cost. i have created the equations and now just need to add the results to give a total, which isn't working and displays a nan error. is it because the data is not formatted as numbers? or is it something to do with the order that my functions are loading? i am new to javascript, any help would be great,.cheers!..
!doctype
html>..
html>..
<body>..
<p>item 1</p>..
<input type=""number"" onkeyup=""equation1() sum()"" onkeydown=""equation1(); sum()"" value=""3"" id=""box1"">..
<p id=""result1""></p>..
<div class=""clear""></div>..
<p>item 2</p>..
<input type=""number"" onkeyup=""equation2() sum()"" onkeydown=""equation2(); sum()"" value=""1"" id=""box2"">..
<p

```

id="result2"></p></div>..
<p>total</p>..
class="clear"></div>..
<script>..
document.getElementById("box1").value;..
var y = x * 6.23;..
var z = "$" +
y.toFixed(2);..
document.getElementById("result1").innerHTML = z;..
function
equation1() {..
var x = document.getElementById("box1").value;..
var y = x *
6.23;..
var z = "$" + y.toFixed(2);..
document.getElementById("result1").innerHTML = z;..
}..
var x =
document.getElementById("box2").value;..
var y = x * 8.15;..
var z = "$" +
y.toFixed(2);..
document.getElementById("result2").innerHTML = z;..
function
equation2() {..
var x = document.getElementById("box2").value;..
var y = x *
8.15;..
var z = "$" + y.toFixed(2);..
document.getElementById("result2").innerHTML = z;..
}..
var price1 =
document.getElementById("result1");..
var price2 =
document.getElementById("result1");..
var x = +price1 + +price2;..
var z = "$" +
x.toFixed(2);..
document.getElementById("total").innerHTML = z;..
function sum() {..
var price1 = document.getElementById("result1");..
var price2 =
document.getElementById("result1");..
var x = +price1 + +price2;..
var z =
"$" + x.toFixed(2);..
document.getElementById("total").innerHTML = z;..
}..
</script>..
</body>..
</html>

```

"significance of javascript:void(0) returning ""undefined"" i have more than a few doubts regarding javascript:void(0)..the following are my doubts....i know it returns ""undefined"" but what is the significance of it. or in other words, at what situation or circumstance do we use javascript:void(0); what exactly does the programmer want when he uses javascript:void(0).i'm asking this question because i dont have a clear understanding of javascript:void(0) and it might be stupid. but what would happen if i use javascript:myfunction("some argument") instead..like for example ...please focus more on the second part."

"classes inside interface i was trying to develop an interface and that interface will contain static class..class c1 {.. static interface i // a static interface or class can contain static members.static members can be. //accessed without instantiating the particular class. {.. static class c2 {.. }. }.. public static void main(string a[]) {.. c1.i.c2 ob1 = new c1.i.c2();.. system.out.println("object created");.. }..but my query is that can interface contain classes which are not static and if yes , then how their object would be created , please advise. thanks"

"Java how to count the sum of all digits in double variable i've this code and i managed to count 77! number. however i'm a bit confused how to count the sum of all digits in double variable ?..77!= 1.4518309202828584e113. and i can't use integer data types here. what should i do?..package org.kodejava.example.io;..import java.io.fileoutputstream;import java.io.ioexception;import java.io.outputstream;import java.util.arrays;..public class many {

```
public static void main(string[] args) {    system.out.println(factorial(77)).    }.. public static
double factorial(double n) {.    if (n == 0) return 1;.    return n * factorial(n-1);.    }.}
```

"why doesn't the menu bar appear i'm trying to learn java swing and started looking at this example:

<https://docs.oracle.com/javase/tutorial/uiswing/examples/components/topleveldemoproject/src/components/topleveldemo.java>..i put the code into intellij but the menu bar isn't appearing, i don't know why..the code is here: package components;..import java.awt.*;..import java.awt.event.*;..import javax.swing.*;../* topleveldemo.java requires no other files. */..public class topleveldemo { /**. * create the gui and show it. for thread safety,. * this method should be invoked from the. * event-dispatching thread.. */. private static void createandshowgui() { //create and set up the window.. JFrame frame = new JFrame("topleveldemo"); frame.setDefaultCloseOperation(JFrame.EXIT_ON_CLOSE); //create the menu bar. make it have a green background.. JMenuBar greenmenubar = new JMenuBar(); greenmenubar.setOpaque(true); greenmenubar.setBackground(new Color(154, 165, 127)); greenmenubar.setPreferredSize(new Dimension(200, 20)); //create a yellow label to put in the content pane.. JLabel yellowlabel = new JLabel(); yellowlabel.setOpaque(true); yellowlabel.setBackground(new Color(248, 213, 131)); yellowlabel.setPreferredSize(new Dimension(200, 180)); //set the menu bar and add the label to the content pane.. frame.setJMenuBar(greenmenubar); frame.getContentPane().add(yellowlabel, BorderLayout.CENTER); //display the window.. frame.pack(); frame.setVisible(true); }.. public static void main(String[] args) { //schedule a job for the event-dispatching thread.. //creating and showing this application's gui.. javax.swing.SwingUtilities.invokeLater(new Runnable() { public void run() { createandshowgui(); } }); }..}

"watch setting value of properties is there a possibility to watch value changes of properties without calling propertychanged (system.componentmodel) for every property in setter?..i tried watching my properties with timer, but this has an unnecessary negative effect on performance and is too slow (15ms for every run)."

"how do we access static properties in a class since the latter is not an object? i am new to c# and i came across the following query. since a class is not an object but just a blueprint(template), how is it possible to define static members on the class and access them by using the class name? this does not make sense to me. my understanding is class does not exist as an entity, so where static properties live? where am i wrong?"

"target variable based on string in java i need to allow the user to target a variable using a string name. example,..int number = 5;..string variabletarget = "number";...i need to target the int, number, and then change its value in later code. any way?..i cannot think of any way to do it. there seems to be a lot of class targeting, but i already have that."