

Assignment 4: Data Wrangling (Fall 2024)

Sarah Sussman

OVERVIEW

This exercise accompanies the lessons in Environmental Data Analytics on Data Wrangling

Directions

1. Rename this file `<FirstLast>_A04_DataWrangling.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. Ensure that code in code chunks does not extend off the page in the PDF.

Set up your session

- 1a. Load the `tidyverse`, `lubridate`, and `here` packages into your session.

```
# Load necessary packages
library(tidyverse)
```

```
## -- Attaching core tidyverse packages ----- tidyverse 2.0.0 --
## v dplyr      1.1.4      v readr      2.1.5
## v forcats    1.0.0      v stringr   1.5.1
## v ggplot2    3.5.1      v tibble    3.2.1
## v lubridate  1.9.3      v tidyr     1.3.1
## v purrr      1.0.2
## -- Conflicts ----- tidyverse_conflicts() --
## x dplyr::filter() masks stats::filter()
## x dplyr::lag()     masks stats::lag()
## i Use the conflicted package (<http://conflicted.r-lib.org/>) to force all conflicts to become errors
```

```
library(lubridate)
library(here)
```

```
## here() starts at /home/guest/EDA_Spring2025
```

```
library(dplyr)
```

- 1b. Check your working directory.

```
# Check working directory
getwd()
```

```
## [1] "/home/guest/EDA_Spring2025"
```

1c. Read in all four raw data files associated with the EPA Air dataset, being sure to set string columns to be read in a factors. See the README file for the EPA air datasets for more information (especially if you have not worked with air quality data previously).

```
#1a
EPAair_03_NC2018 <- read.csv("Data/Raw/EPAair_03_NC2018_raw.csv"),
                        stringsAsFactors = TRUE)
#1b
EPAair_03_NC2019 <- read.csv("Data/Raw/EPAair_03_NC2019_raw.csv"),
                        stringsAsFactors = TRUE)
#1c
EPAair_PM25_NC2018 <- read.csv("Data/Raw/EPAair_PM25_NC2018_raw.csv"),
                        stringsAsFactors = TRUE)
#2
EPAair_PM25_NC2019 <- read.csv("Data/Raw/EPAair_PM25_NC2019_raw.csv"),
                        stringsAsFactors = TRUE)
```

2. Add the appropriate code to reveal the dimensions of the four datasets.

```
dim(EPAair_03_NC2018)
```

```
## [1] 9737  20
```

```
dim(EPAair_03_NC2019)
```

```
## [1] 10592  20
```

```
dim(EPAair_PM25_NC2018)
```

```
## [1] 8983  20
```

```
dim(EPAair_PM25_NC2019)
```

```
## [1] 8581  20
```

All four datasets should have the same number of columns but unique record counts (rows). Do your datasets follow this pattern? Yes! They 20 columns and unique record counts (rows)

Wrangle individual datasets to create processed files.

3. Change the Date columns to be date objects.

```

EPAair_03_NC2018$Date <- mdy(EPAair_03_NC2018$Date)
EPAair_03_NC2019$Date <- mdy(EPAair_03_NC2019$Date)
EPAair_PM25_NC2018$Date <- mdy(EPAair_PM25_NC2018$Date)
EPAair_PM25_NC2019$Date <- mdy(EPAair_PM25_NC2019$Date)

```

4. Select the following columns: Date, DAILY_AQI_VALUE, Site.Name, AQS_PARAMETER_DESC, COUNTY, SITE_LATITUDE, SITE_LONGITUDE

```

EPAair_03_NC2018_Select <- select(EPAair_03_NC2018, Date, DAILY_AQI_VALUE:Site.Name, AQS_PARAMETER_DESC)
EPAair_03_NC2019_Select <- select(EPAair_03_NC2019, Date, DAILY_AQI_VALUE:Site.Name, AQS_PARAMETER_DESC)
EPAair_PM25_NC2018_Select <- select(EPAair_PM25_NC2018, Date, DAILY_AQI_VALUE:Site.Name, AQS_PARAMETER_DESC)
EPAair_PM25_NC2019_Select <- select(EPAair_PM25_NC2019, Date, DAILY_AQI_VALUE:Site.Name, AQS_PARAMETER_DESC)

```

5. For the PM2.5 datasets, fill all cells in AQS_PARAMETER_DESC with “PM2.5” (all cells in this column should be identical).

```

EPAair_PM25_NC2018_Select$AQS_PARAMETER_DESC <- "PM2.5"
EPAair_PM25_NC2019_Select$AQS_PARAMETER_DESC <- "PM2.5"

```

6. Save all four processed datasets in the Processed folder. Use the same file names as the raw files but replace “raw” with “processed”.

```

#3
write.csv(EPAair_03_NC2018_Select, row.names = FALSE,
          file = "./Data/Processed/EPAair_03_NC2018_processed.csv")

#4
write.csv(EPAair_03_NC2019_Select, row.names = FALSE,
          file = "./Data/Processed/EPAair_03_NC2019_processed.csv")

#5
write.csv(EPAair_PM25_NC2018_Select, row.names = FALSE,
          file = "./Data/Processed/EPAair_PM25_NC2018_processed.csv")

#6
write.csv(EPAair_PM25_NC2019_Select, row.names = FALSE,
          file = "./Data/Processed/EPAair_PM25_NC2019_processed.csv")

```

Combine datasets

7. Combine the four datasets with rbind. Make sure your column names are identical prior to running this code.

```

# Read in files
EPAair_03_NC2018_processed <- read.csv(("Data/Processed/EPAair_03_NC2018_processed.csv"),
                                       stringsAsFactors = TRUE)

EPAair_03_NC2019_processed <- read.csv(("Data/Processed/EPAair_03_NC2019_processed.csv"),

```

```

stringsAsFactors = TRUE)

EPAair_PM25_NC2018_processed <- read.csv("Data/Processed/EPAair_PM25_NC2018_processed.csv"),
stringsAsFactors = TRUE)

EPAair_PM25_NC2019_processed <- read.csv("Data/Processed/EPAair_PM25_NC2019_processed.csv"),
stringsAsFactors = TRUE)

# Combine datasets
EPAair_AirQuality_2018_2019 <- rbind(EPAair_03_NC2018_processed,
                                     EPAair_03_NC2019_processed,
                                     EPAair_PM25_NC2018_processed,
                                     EPAair_PM25_NC2019_processed)

```

8. Wrangle your new dataset with a pipe function (%>%) so that it fills the following conditions:

- Include only sites that the four data frames have in common:

“Linville Falls”, “Durham Armory”, “Leggett”, “Hattie Avenue”,
 “Clemmons Middle”, “Mendenhall School”, “Frying Pan Mountain”, “West Johnston Co.”, “Garinger High School”, “Castle Hayne”, “Pitt Agri. Center”, “Bryson City”, “Millbrook School”

(the function `intersect` can figure out common factor levels - but it will include sites with missing site information, which you don’t want...)

- Some sites have multiple measurements per day. Use the split-apply-combine strategy to generate daily means: group by date, site name, AQS parameter, and county. Take the mean of the AQI value, latitude, and longitude.
- Add columns for “Month” and “Year” by parsing your “Date” column (hint: `lubridate` package)
- Hint: the dimensions of this dataset should be 14,752 x 9.

```

# I cannot get this to work so I am just commenting out what I have tried.
# I'm sorry :(

# EPAair_AirQuality_2018_2019_wrangled <- EPAair_AirQuality_2018_2019 %>%
#   filter(Site.Name %in% c("Linville Falls", "Durham Armory", "Leggett", "Hattie Avenue", "Clemmons Mid

# group_by(Date, Site.Name, AQS_PARAMETER_DESC, COUNTY) %>%
#   summarise(meanAQI = mean(DAILY_AQI_VALUE),
#             #meanlatitude = mean(SITE_LATITUDE),
#             #meanlongitude = mean(SITE_LONGITUDE)) %>%
# EPAair_AirQuality_2018_2019_wrangled <- mutate(EPAair_AirQuality_2018_2019_wrangled, month = I can't

```

9. Spread your datasets such that AQI values for ozone and PM2.5 are in separate columns. Each location on a specific date should now occupy only one row.

```

# I am commenting out what I think I am supposed to do for the next questions.
# I didn't finish question 8 so I can't actually run the code I am typing.

# EPAair_AirQuality_2018_2019_wrangled_gathered <- subset(EPAair_AirQuality_2018_2019_wrangled, !is.na(
# count(EPAair_AirQuality_2018_2019_wrangled, AQS_PARAMETER_DESC)

```

10. Call up the dimensions of your new tidy dataset.

```
# dim()
```

11. Save your processed dataset with the following file name: “EPAair_O3_PM25_NC1819_Processed.csv”

```
#7
```

```
#8
```

```
#9
```

```
#10
```

```
#11
```

Generate summary tables

12. Use the split-apply-combine strategy to generate a summary data frame. Data should be grouped by site, month, and year. Generate the mean AQI values for ozone and PM2.5 for each group. Then, add a pipe to remove instances where mean **ozone** values are not available (use the function **drop_na** in your pipe). It’s ok to have missing mean PM2.5 values in this result.

13. Call up the dimensions of the summary dataset.

```
#12
```

```
#13
```

14. Why did we use the function **drop_na** rather than **na.omit**? Hint: replace **drop_na** with **na.omit** in part 12 and observe what happens with the dimensions of the summary data frame.

Answer: **drop_na** removes the NA observation from a column, while **na.omit** removes the entire observation that has a NA value.