

Tests of the radiation hardness of scintillators in a high energy proton-proton collider environment

Joshua Kunkle^{a,*}, Alberto Belloni^a, Jeff Calderon^a, Pawel De Barbaro^f, Sarah C. Eno^a, Kenichi Hatakeyama^d, Geng-Yuan Jeng^a, Julie Schnurr^a, Yao Yao^a, Sung Woo Youn^b

^a*Dept. Physics, U. Maryland, College Park MD 30742 USA*

^b*Institute for Basic Science, Center for Axion and Precision Physics Research, IBS Center for Axion and Precision Physics Research Room 4315, Department of Physics, Natural Science Building (E6-2), KAIST, 291 Daehak-ro, Yuseong-gu, Daejeon 305-701, South Korea*

^c*Fermi National Accelerator Laboratory, Batavia, IL, USA*

^d*Baylor University, Waco, Texas, USA*

^e*The University of Iowa, Iowa City, IA, USA*

^f*The University of Rochester, Rochester, NY, USA*

Abstract

Radiation damage to the attenuation length and light output of scintillating materials may depend not just on the deposited energy, but also on the dose rate and the type and energy of the interacting particle. We present the results of measurements of the damage to several different types of scintillating material irradiated in the CMS collision hall at the Large Hadron Collider. The materials received a dose of **xxx** over a period of **xxx** months. Their light output was measured at several intermediate doses.

Keywords: organic scintillator, liquid scintillator, radiation hardness, calorimetry

1. Introduction

Radiation damage to the attenuation length and light output of scintillating materials may depend not just on the deposited energy (dose), but also on the dose rate and the type and energy of the interacting particle. We present the

*Corresponding author

Email address: jkunkle@cern.ch (Joshua Kunkle)

5 results of measurements of the damage to several different types of scintillating
material irradiated in the CMS collision hall at the Large Hadron Collider (LHC)
during its operation at a center-of-mass energy of 13 TeV during 2015. The
materials received a dose of xxx over a period of xxx months. Their light
output was measured at several intermediate doses. Irradiation in the collision
10 hall of a running high energy proton-proton collider allows access to very low
dose rates that would not be affordable at reactors, electron linacs, and ^{60}Co
sources and with a particle type and energy spectrum most appropriate for those
designing detectors for hadron colliders.

During the running of the LHC from its commissioning in 2009 through
15 2012, the CMS detector was exposed to an integrated luminosity of 25 fb^{-1} .
Parts of the CMS endcap calorimeter are estimated to have received doses of
0.1 to 0.2 Mrad [1]. Studies of the radiation hardness of scintillator tiles prior to
installation in the detector, using an electron linac and ^{60}Co sources, indicated
an exponential reduction in light output with accumulated dose, with an expo-
20 nential constant of around 7 Mrad [2, 3]. However, although the dose received
by the CMS tiles was small compared to this number, significant light loss was
observed [4].

2. Tile designs

3. Radiation parameters

25 4. Measurement techniques

5. Results

6. Conclusions

We presented results on radiation damage to scintillating materials in

7. Acknowledgments

30 The authors would like to thank Randy Ruchti of Notre Dame for providing the capillaries. We would like to thank the University of Maryland FabLab, especially **who helped**, for help with fiber sputtering. This work was supported in part by U.S. Department of Energy Grant DESC0010072.

References

- 35 [1] ECFA High Luminosity LHC Experiments Workshop: Physics and Technology Developments Summary submitted to ECFA. 96th Plenary ECFA meeting.
URL <https://cds.cern.ch/record/1983664>
- [2] V. Hagopian, I. Daly, Radiation damage of fibers, AIP Conference Proceedings 450 (1) (1998) 53–61. doi:<http://dx.doi.org/10.1063/1.56958>.
- 40 [3] A. Byon-Wagner, Radiation hardness test programs for the {SDC} calorimeter, Radiation Physics and Chemistry 41 (12) (1993) 263 – 271. doi:[http://dx.doi.org/10.1016/0969-806X\(93\)90064-2](http://dx.doi.org/10.1016/0969-806X(93)90064-2).
- [4] J. F. Butler, D. U. C. B.-L. I. Contardo, M. M. Klute, J. U. o. M. Mans, L. I.-
45 B. Silvestris, Technical Proposal for the Phase-II Upgrade of the CMS Detector, Tech. Rep. CERN-LHCC-2015-010. LHCC-P-008, CERN, Geneva, upgrade Project Leader Deputies: Lucia Silvestris (INFN-Bari), Jeremy Mans (University of Minnesota) Additional contacts: Lucia.Silvestris@cern.ch, Jeremy.Mans@cern.ch (Jun 2015).
50 URL <https://cds.cern.ch/record/2020886>