

# Writing modular code: Functions & command line args

Programming Bootcamp 2015

Day 6 – 6/19/15

Sign in!

# Today's schedule

1. Defining your own functions
2. Using command line arguments
3. Good programming practices

# 1. Defining your own functions

# Defining your own functions

## Why do it?

- Allows you to re-use a certain piece of code without re-writing it
- Organizes your code into functional pieces
- Makes your code easier to read and understand

# Defining a function

Syntax:

```
def function_name(parameters) :  
    statements  
    var = something  
return var
```

Example:

```
def strAdd(num1, num2) :  
    result = int(num1) + int(num2)  
return result
```

# Defining a function

## Syntax:

```
def function_name(parameters) :  
    statements  
    var = something  
return var
```

This is the value that the function returns when we use it. To give a familiar example, the `int()` function's return value is the string converted to an integer.

Which value we return must be considered carefully, since no other information inside the function will be accessible when we call it. All we can do is capture the return value.

## Example:

```
def strAdd(num1, num2) :  
    result = int(num1) + int(num2)  
return result
```

# Using a custom function

```
def strAdd(num1, num2):  
    result = int(num1) + int(num2)  
    return result
```

# Using a custom function

```
def strAdd(num1, num2):  
    result = int(num1) + int(num2)  
    return result  
  
first = raw_input("First number? ")  
second = raw_input("Second number? ")  
added = strAdd(first, second)  
print added
```



# Using a custom function

```
def strAdd(num1, num2):  
    result = int(num1) + int(num2)  
    return result
```



Function must be defined before it can be used (usually we define all our definitions at the very top of the script or in a separate script)

```
first = raw_input("First number? ")  
second = raw_input("Second number? ")  
added = strAdd(first, second)  
print added
```



Here is where execution actually starts (the first un-indented line)




Here is where we "call" our function

# Using a custom function

```
4  def strAdd(num1, num2):  
5      result = int(num1) + int(num2)  
6      return result  
  
1  first = raw_input("First number? ")  
2  second = raw_input("Second number? ")  
3/7 added = strAdd(first, second)  
8  print added
```

# Using a custom function


**START**



```
4  def strAdd(num1, num2):  
5      result = int(num1) + int(num2)  
6      return result  
  
1  first = raw_input("First number? ")  
2  second = raw_input("Second number? ")  
3/7 added = strAdd(first, second)  
8  print added
```

# Using a custom function

**START**




The diagram illustrates the execution flow of the code. A blue curved arrow originates from the word 'START' and points to line 1 of the main code block. Another blue curved arrow originates from the function call 'strAdd' on line 3/7 and points back to the function definition on lines 4-6, indicating a call to the custom function.

```
4  def strAdd(num1, num2):  
5      result = int(num1) + int(num2)  
6      return result  
  
1  first = raw_input("First number? ")  
2  second = raw_input("Second number? ")  
3/7 added = strAdd(first, second)  
8  print added
```

# Using a custom function

**START**




```
4  def strAdd(num1, num2):  
5      result = int(num1) + int(num2)  
6      return result  
  
1  first = raw_input("First number? ")  
2  second = raw_input("Second number? ")  
3/7 → added = strAdd(first, second)  
8  print added
```

The diagram illustrates the execution flow of the code. A blue arrow originates from the 'START' label and points to line 1. Another blue arrow points from line 6 to line 3, indicating the return of the function. A third blue arrow points from line 3 back to line 6, showing the return value being assigned to the 'added' variable.

# Using a custom function

**START**

```
4  def strAdd(num1, num2):  
5      result = int(num1) + int(num2)  
6  return result  
  
1  first = raw_input("First number? ")  
2  second = raw_input("Second number? ")  
3/7 added = strAdd(first, second)  
8  print added
```



**End**

# What will this code print?

```
def strAdd(num1, num2):  
    result = int(num1) + int(num2)  
    return result  
  
first = raw_input("First number? ")  
second = raw_input("Second number? ")  
added = strAdd(first, second)  
print added
```

## Result:

First number? *<input>* 5  
Second number? *<input>* 4



Assuming we input these  
values for first and second

# What will this code print?

```
def strAdd(num1, num2):  
    result = int(num1) + int(num2)  
    return result  
  
first = raw_input("First number? ")  
second = raw_input("Second number? ")  
added = strAdd(first, second)  
print added
```

## Result:

```
First number? <input> 5  
Second number? <input> 4  
9
```



# A more useful example: counting

Result of using `.count()`:

```
>>> seq = "CGCACGCACGCGC"  
>>> seq.count("CGC")  
3
```

Notice that there are actually 4 possible instances of “CGC” in this sequence – the “CGCGC” at the end can be counted as having two instances.

The `.count()` only counts non overlapping instances. What if that’s not what we want?

# A more useful example: counting

*# Count (potentially overlapping) instances of a subsequence in a string*

```
def count_occurrences(seq, subseq):
    seq = seq.upper()
    subseq = subseq.upper()
    count = 0
    index = 0
    done = False
    while not done:
        index = seq.find(subseq, index)
        if (index == -1):
            done = True
        else:
            count += 1
            index += 1 # add one so this pos won't be found again
    return count
```

*# main script*

```
seq = raw_input("Full sequence: ")
subseq = raw_input("Subseq to search for: ")
result = count_occurrences(seq, subseq)
print "The subseq occurs", result, "times in the full seq"
```

# A more useful example: counting

Result of using `.count()`:

```
>>> seq = "CGCACGCACGCGC"  
>>> seq.count("CGC")  
3
```

Result:

Full sequence: CGCACGCACGCGC

Subseq to search for: CGC

The subseq occurs **4** times in the full seq

# Keep your functions in a separate file

If you have a set of functions you want to use in various different scripts (e.g. a function to read in a fasta file), you can save these functions in a separate file and then *import* them into other scripts. Example:

## **useful\_fns.py:**

```
# Count (potentially overlapping) instances of a  
subsequence in a string
```

```
def count_occurrences(seq, subseq):  
    seq = seq.upper()  
    subseq = subseq.upper()  
    count = 0  
    index = 0  
    done = False  
    while not done:  
        index = seq.find(subseq, index)  
        if (index == -1):  
            done = True  
        else:  
            count += 1  
            index += 1  
    return count
```

## **test.py:**

```
import useful_fns  
  
seq = raw_input("Full sequence: ")  
subseq = raw_input("Subseq to search for: ")  
result = useful_fns.count_occurrences(seq, subseq)  
print "The subseq occurs", result, "times"
```

## **Result:**

```
> python test.py  
Full sequence: CGCACGCACGCGC  
Subseq to search for: CGC  
The subseq occurs 4 times
```

# Keep your functions in a separate file

If you have a set of functions you want to use in various different scripts (e.g. a function to read in a fasta file), you can save these functions in a separate file and then *import* them into other scripts. Example:


## **useful\_fns.py:**

*# Count (potentially overlapping) instances of a subsequence in a string*

```
def count_occurrences(seq, subseq):  
    seq = seq.upper()  
    subseq = subseq.upper()  
    count = 0  
    index = 0  
    done = False  
    while not done:  
        index = seq.find(subseq, index)  
        if (index == -1):  
            done = True  
        else:  
            count += 1  
            index += 1  
    return count
```

## **test.py:**

```
import useful_fns  
  
seq = raw_input("Full sequence: ")  
subseq = raw_input("Subseq to search for: ")  
result = useful_fns.count_occurrences(seq, subseq)  
print "The subseq occurs", result, "times"
```



## **Result:**

```
> python test.py
```

```
Full sequence: CGCAGCAGCGCG
```

```
Subseq to search for: CGC
```

```
The subseq occurs 4 times
```

we save the file of functions as `useful_fns.py`, but then import it using just the file name (no `.py`). Then we can access the functions in this file by saying `useful_fns.functionName()`

# A note on “scope”

- Variables you *create* within a function are considered to be in a different “scope” than the rest of your code
- This means that those variables are inaccessible outside of the function definition block
- Reusing a variable name within a function definition block will not overwrite any variable defined outside the block.
- Somewhat confusingly, functions *can* sometimes use variables defined within the main body (as long as it has been created before the function is called). However, doing this generally considered bad practice, since it makes the effects of a function harder to predict (especially if you plan to use it in many different scripts).
- The best practice is to only allow functions to use the external variables that are supplied directly as parameters.

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} function scope

} main scope



# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...
```

} function scope

```
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} main scope

```
>>> print result
```

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} function scope

} main scope

```
>>> print result  
2500
```

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...
```

} function scope

```
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} main scope

```
>>> print result  
2500  
>>> print z
```

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} function scope

} main scope

```
>>> print result  
2500  
>>> print z  
1
```

← The z defined in the main scope was not overwritten  
by the z defined in the function scope

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} function scope  
  
} main scope

```
>>> print result  
2500  
>>> print z  
1  
>>> print c
```

# Example of scope

```
>>> def someFn(val):  
...     c = val * 10  
...     z = c * c  
...     return z  
...  
>>> x = 5  
>>> z = 1  
>>> result = someFn(x)
```

} function scope

} main scope

```
>>> print result
```

```
2500
```

```
>>> print z
```

```
1
```

```
>>> print c
```

```
Traceback (most recent call last):
```

```
  File "<stdin>", line 1, in <module>
```

```
NameError: name 'c' is not defined
```

There is no `c` defined in the main scope, and we cannot access the `c` defined in the function scope, so this creates a `NameError`

## 2. Command line args

# Command line arguments

Usually when we run a python script, we type this into the terminal:

```
python filename.py
```


We can also provide additional information when we run our script ("arguments"):

```
python filename.py arg1 arg2 agr3
```



# Command line arguments

You can add as many command line args as you want. All args will be automatically stored (in order) in a list called `argv`. The first item in this list will be the name of your script, followed by any arguments you included.



# Using `argv`

Before we can use the `argv` list, we must import the `sys` package. This package is already included with your installation of python, we just have to tell python to import it when we start our script.

To do this, simply put this line at the top of your script:

```
import sys
```

We then access `argv` by typing:

```
sys.argv[...]
```

# Example: argTest.py

```
import sys

scriptName = sys.argv[0]
arg1 = sys.argv[1]
arg2 = sys.argv[2]
print "Script", scriptName, "had args:", arg1, arg2
```

## Result

```
> python argTest.py apple banana
Script argTest.py had args: apple banana
```

# Example: argTest.py

```
import sys

scriptName = sys.argv[0]
arg1 = sys.argv[1]
arg2 = sys.argv[2]
print "Script", scriptName, "had args:", arg1, arg2
```

What if we did this? (only one arg provided)

```
> python argTest.py apple
```

# Example: argTest.py

```
import sys

scriptName = sys.argv[0]
arg1 = sys.argv[1]
arg2 = sys.argv[2]
print "Script", scriptName, "had args:", arg1, arg2
```

## What if we did this? (only one arg provided)

```
> python argTest.py apple
Traceback (most recent call last):
  File "argTest.py", line 5, in <module>
    arg2 = sys.argv[2]
IndexError: list index out of range
```

# Example 2: addMe.py

To gracefully exit when the wrong arguments are provided, you could do something like this:

```
import sys

if len(sys.argv) == 3:
    num1 = int(sys.argv[1])
    num2 = int(sys.argv[2])
else:
    print "You must provide two numbers. Exiting."
    sys.exit()

print num1 + num2
```

## Result

```
> python addMe.py 100 50
150
```

## Or:

```
> python addMe.py 302
You must provide two numbers. Exiting.
```

# Example 2: addMe.py

To gracefully exit when the wrong arguments are provided, you could do something like this:

```
import sys
```

```
if len(sys.argv) == 3:  
    num1 = int(sys.argv[1])  
    num2 = int(sys.argv[2])
```

```
else:
```

```
    print "You must provide two numbers. Exiting."
```

```
    sys.exit()
```

```
print num1 + num2
```

Check if the length of the `argv` list is what we expect.  
\*Remember the script name is the first arg, so a script with 2 args has an `argv` of length 3.

If not, use this piece of code to immediately terminate the whole script.

## Result

```
> python addMe.py 100 50  
150
```

## Or:

```
> python addMe.py 302  
You must provide two numbers. Exiting.
```

# Why use command line args?

- If you plan to run your script on multiple datasets, you can simply supply different filenames to the command instead of editing a hard-coded file name
- Facilitates the creation of “pipelines”, for the above reason
- If you are keeping track of what commands you run on your data (which you should!), having all the relevant info as part of the command itself (the file name, certain parameters, etc.) makes what you did more transparent and reproducible.
- The rule of thumb is: if you NEVER plan to change a variable, no matter what dataset you run your code on, it's ok to hard code it. Otherwise, consider making it a command line arg.
- Later we'll go over how to make more user-friendly command line args (e.g. `-h --infile=file.txt --verbose`)



### 3. Coding best practices

# Some guidelines

- Writing code that is **clear** is more important than writing code that is **concise**
  - so doing something in two steps instead of one is totally fine if it makes your code clearer!
- Comment your code
  - avoid "obvious" comments
  - make sure to keep comments accurate if the code changes
- Use descriptive variable names
  - this goes hand in hand with clarity
- Test your code using small test sets
  - especially important for research! small errors can lead to big mistakes...
- Avoid copy-pasting code -- if you use the same code multiple times, consider making it a function!

# The Zen of Python

```
>>> import this  
The Zen of Python, by Tim Peters
```

Beautiful is better than ugly.

**Explicit is better than implicit.**

Simple is better than complex.

Complex is better than complicated.

Flat is better than nested.

Sparse is better than dense.

**Readability counts.**

Special cases aren't special enough to break the rules.

**Although practicality beats purity.**

**Errors should never pass silently.**

Unless explicitly silenced.

**In the face of ambiguity, refuse the temptation to guess.**

There should be one-- and preferably only one --obvious way to do it.

Although that way may not be obvious at first unless you're Dutch.

Now is better than never.

Although never is often better than *\*right\** now.

If the implementation is hard to explain, it's a bad idea.

If the implementation is easy to explain, it may be a good idea.

Namespaces are one honking great idea -- let's do more of those!

# Some additional opinions

- <https://www.python.org/dev/peps/pep-0008/>
- <http://docs.python-guide.org/en/latest/writing/style/>
- <http://code.tutsplus.com/tutorials/top-15-best-practices-for-writing-super-readable-code--net-8118>
- many more...

**Note:** don't worry if you don't do everything in these guidelines (you'll notice I don't do many of them!). Some points are just more important than others, and you should try to understand why something is a guideline before you blindly follow it 100% of the time.

For more discussion of this:

<http://programmers.stackexchange.com/questions/14856/what-popular-best-practices-are-not-always-best-and-why>