

CHANFER Technical Specifications

Detailed Engineering Reference for Procurement & Engineering Teams

This document provides comprehensive technical specifications for all CHANFER machinery. It is intended for procurement managers, project engineers, and factory planners evaluating our equipment. All specifications are subject to final engineering review and project-specific configuration.

1. General Standards & Certifications

- ISO 9001:2015 Quality Management System
- CE Marking (EU Machinery Directive 2006/42/EC)
- EAC Certification (TR CU 010/2011 — EAEU markets)
- GOST-R certification (Russia)
- SONCAP (Nigeria), PVoC (Kenya), COC (Egypt) available on request
- FDA-compliant materials for food-contact applications (where applicable)

2. Materials of Construction

Component	Standard	Optional
Frame	SS304 stainless steel, 3mm wall	SS316L
Product contact parts	SS316L, Ra ≤ 0.8μm	SS316L electropolished Ra ≤ 0.4μm
Piping (product)	SS316L sanitary tri-clamp	PTFE-lined for high-pH products
Piping (CIP)	SS304 sanitary	—
Seals & gaskets	EPDM (FDA)	Viton (chemical resistant), PTFE
Filler nozzles	SS316L with ceramic tips	Plastic for low-budget lines
Cap feeders	SS304 + engineering plastic	—
Conveyor belts	Modular plastic (Intralox-style)	Stainless steel flat wire
Control panel housing	SS304 with IP65 rating	—

3. Electrical & Control Specifications

- PLC: Siemens S7-1200 (standard) / S7-1500 (premium) / Mitsubishi FX5U (alternative)
- HMI: 10" color touchscreen, IP65, multi-language (EN/FR/RU/AR/ES/ZH)
- Servo drives: Siemens SINAMICS V90 / Mitsubishi MR-JE
- Variable frequency drives: Schneider ATV320 / ABB ACS150
- Sensors: SICK / IFM / Banner (German/US brands, easy global sourcing)
- Pneumatics: Festo (Germany) / SMC (Japan)
- Low-voltage components: Schneider, Eaton, Siemens

- Main power: 380V/50Hz/3-phase (standard) | 220V/60Hz available | 480V/60Hz available
- Control voltage: 24VDC for safety circuits
- Network: Profinet, Modbus TCP, Ethernet/IP supported

4. Performance Specifications by Line Type

4.1 Bottle Filling Lines (PET/HDPE)

Parameter	CF-3000	CF-6000	CF-10000	CF-15000	CF-25000
Output (BPH)	3,000	6,000	10,000	15,000	25,000
Filling heads	12	24	32	40	60
Capping heads	4	8	10	12	16
Filling accuracy	±0.5%	±0.5%	±0.3%	±0.3%	±0.2%
Bottle size (ml)	100-2000	200-3000	250-5000	500-5000	500-5000
Power (kW)	12	18	28	42	65
Air (m³/min)	0.4	0.6	1.0	1.4	2.2
Footprint (m)	8×3	12×4	15×5	18×6	22×7
Weight (tons)	3.5	6.2	9.5	14.0	22.0

4.2 Pouch Packaging Lines (FFS / Premade)

Parameter	ZP-1200	ZP-2400	ZP-4000
Output (bags/min)	20-30	40-60	60-90
Pouch size (mm)	80×120 – 350×450	100×150 – 400×500	120×180 – 450×600
Pouch type	Premade (zipper, spout)	FFS roll film	FFS rotary
Filling accuracy	±1.0%	±0.8%	±0.5%
Power (kW)	8	14	22
Air (m³/min)	0.3	0.5	0.8
Footprint (m)	5×2.5	8×3.5	11×4.5
Weight (tons)	2.2	4.5	7.8

4.3 Drum Filling Lines (5L – 200L)

Parameter	DF-100	DF-200	DF-400
Output (drums/hr)	60-100	120-200	200-400
Drum size (L)	5-30	20-60	60-200
Filling type	Net weight	Servo + weight	Servo + weight + auto cap
Filling accuracy	±0.2%	±0.1%	±0.1%
Power (kW)	4.0	7.5	12.0
Air (m³/min)	0.2	0.4	0.7
Footprint (m)	4×3	7×4	12×5
Weight (tons)	1.2	2.8	5.5

5. Utility Requirements

5.1 Compressed Air

- Pressure: 0.6 – 0.8 MPa (87 – 116 PSI)
- Quality: ISO 8573-1 Class 3.4.1 (oil-free, dry, filtered to 5µm)
- Consumption: 0.2 – 2.2 m³/min (line size dependent)
- Receiver tank: 1,000L minimum recommended

5.2 Water (for RO/CIP)

- Inlet pressure: 0.2 – 0.4 MPa
- Temperature: 15 – 25°C
- TDS: < 500 ppm (for RO system inlet)
- Connection: 1" BSP or NPT

5.3 Steam (for CIP heating, if applicable)

- Pressure: 0.3 – 0.5 MPa saturated

- Consumption: 50 – 300 kg/hr (line size dependent)

6. Noise, Safety, Environmental

- Noise level: ≤ 78 dB(A) at 1m distance (compliant with EU 2003/10/EC)
- Safety: Emergency stop buttons at every station, safety interlocks on moving parts, light curtains at operator access points
- Footprint planning: Allow 1.5m clearance on all sides for maintenance
- Environmental: No emissions to atmosphere. Waste water from CIP should be treated per local regulations (typically 30-50% of CIP volume becomes wastewater)

7. Documentation Package

Every CHANFER line ships with: 1) Operation Manual (multi-language), 2) Maintenance Schedule & Spare Parts List, 3) Electrical Schematics (EPLAN/PDF), 4) P&ID; Drawings, 5) Foundation & Installation Drawings (AutoCAD), 6) Test Reports (FAT, materials, CE/EAC certificates), 7) Warranty Certificate, 8) Software Backup (PLC + HMI programs).

Engineering Contact

For technical questions, custom configurations, or to request a detailed specification for a specific project, contact our engineering team:

engineering@chanferpack.com | WhatsApp: +86 191 2880 3719

Response time: 24 hours for standard queries, 48 hours for custom engineering.

© 2026 Guangzhou Chanfer Intelligent Equipment Co., Ltd.