

Problem 5: Now the wide open design problem. The haunting elegance of the stack architecture has stayed in the back of your mind ever since the debate. Now that you have seen superscalar execution, register renaming, forwarding, Tomasulo and all that, you wonder “why can’t I apply these techniques to stack machines to find instruction level parallelism there too?” You grab your favorite loop as a test case

```
for (i = 0; i < n; i++) A[i] = A[i] + alpha;
```

which, of course, compiles as

```
for (ptr = A; ptr < &A[n]; ptr++) *ptr += alpha;
```

On entry to this loop there are three values at the Top of Stack:

TOS-8:	Alpha
TOS-4:	ArrayEnd
TOS:	Ptr

The stack code for the loop is as follows.

```
vscal:
    push @0    ; push a copy of Ptr
    load       ; Load the array value (replacing Ptr)
    push @12   ; push a copy of the scale value, alpha
    fadd        ; alpha + *ptr
    push @4    ; push a copy of Ptr
    store       ; *ptr := alpha + *ptr
    pushIm 4   ; pointer increment value
    add         ; ptr++ (update on the stack)
    push @4    ; push ArrayEnd
    push @4    ; push ptr
    sub
    blt vscal
```

The `push @X` instruction pushes the value at offset X from the top of stack. `pushIM X` pushes immediate value X. All other operations pop their operands from the top of stack, remove them, and push a result, if one is generated.

Your starting point for your design is based roughly on the MIPS R10000. It has several function units with a reservation station per function unit and forwarding of results to the function units, as indicated in the diagram below. A large collection of physical registers are provided. They are not in the instruction set architecture. The architected state is the stack and PC. You are to describe how to do the renaming such that you could overlap the execution of multiple iterations of this loop. You will need to invent the mechanism to perform the necessary renaming. You may assume there are enough physical registers to perform one or more iterations of the loop, but not an

arbitrary number of overlapping iterations. You may assume there is a mechanism `ALLOC` that will allocate a free register and provide that register number, if one is available. If none are free, it will indicate a failure. You may, similarly, assume there is an operation `FREE(Reg)` which frees the specified register.


How much stack space is required to execute this loop? Because of this, you don't need to worry about stack overflow/underflow. You do need to deal with limits on the available physical registers and function units.

Describe the instruction issue and operand fetch process for different kinds of instructions that appear in the example.

Under what conditions will the machine wait – holding the issue of an instruction?

Explain when a physical register can be freed.

Explain what limits the number of iterations of the loop that can potentially execute concurrently.



The key idea is to introducing a "renaming stack" of physical register names. A physical register may be freed when its name is popped off the renaming stack AND the instruction that produces it enters the ROB. A single state bit will do. The latter of the two events will free place the physical register back on the free list.

The key optimization is that PUSH just shares the previously allocated physical register. PUSH, POP, and PUSH_IM don't need to enter the execution section at all. Here's a nice student solution.

Renaming:

Register renaming for this architecture should be no more difficult than any other. The real difference is that a stack of register NAMES will be maintained rather than actual registers. This could be easily maintained using an SRAM and a counter pointing to the NAME entry for the TOS.

Issue & Operand Fetch:

For instructions operating on the TOS:

The register names of the operands must be fetched from the name stack (described above) and then used to index the physical register file.

The TOS should also decrease and the registers could be marked as "consumed" ✓

(see the solution on freeing registers).


For push: Values marked as written are ready, those not written will be broadcast on the CDB.

The TOS + offset would give a new index into the name stack allowing us to find the physical register with the source data good

push-im? This should not affect TOS and "it should not mark that physical register as "consumed" ✓

For operations which write a result:

The TOS should be incremented and the new TOS entry in the name stack should be filled with whatever ALLOCATE() gives us.



Physical registers can be freed when they are consumed (as detailed above) AND written, that is they have been written back to by the CDB.

This machine will stall when it runs out of physical registers, the reservation station for the current instruction is busy or the ROB is full, essentially when the instruction has nowhere to go. In the case of this code it is when the ROB will fill up first as the longer fadd instructions delay things, however given a deep enough ROB and a pipelined (or fast) memory and fadd this code could execute with a CPI of 1.

In this case the number of parallel iterations may be limited by the number of FUs / reservation stations, especially since I did not believe that there are many fadd or memory units.

However the primary limitation in this design is issue rate. Stack architectures tend to have high instruction counts compared to register/register machines like the R10000. This will result in the situation where each microinstruction can actually perform multiple instructions. For example

```
push @4  
push @4  
sub
```

could easily be handled in one microinstruction, leading me to believe that the issue rate will be the primary bottleneck, and that some kind of superscalar or the ability to translate multiple instructions into one microinstruction will be useful.

Note: I have assumed branch prediction is in use. Perhaps simply "static taken."