

12 BONUS: Branch Prediction [30 points]

Assume a machine with a two-bit global history register (GHR) shared by all branches, which starts with Not Taken, Not Taken (2'b00). Each pattern history table entry (PHTE) contains a 2-bit saturating counter. The saturating counter values are as follows:

2'b00 - Strongly Not Taken
 2'b01 - Weakly Not Taken
 2'b10 - Weakly Taken
 2'b11 - Strongly Taken

Assume the following piece of code runs on this machine. The code has two branches (labeled B1 and B2). When we say that a branch is taken, we mean that the code inside the curly brackets is executed. For the following questions, assume that this is the only block of code that will ever be run, and the loop-condition branch (B1) is resolved first in the iteration before the if-condition branch (B2).

```
for (int i = 0; i < 1000000; i++) { /* B1 */
    /* TAKEN PATH for B1 */
    if (i % 3 == 0) { /* B2 */
        j[i] = k[i] - 1; /* TAKEN PATH for B2 */
    }
}
```

- (a) [20 points] Is it possible to observe that the branch predictor mispredicts 100% of the times in the first 5 iterations of the loop? If yes, fill in the table below with all possible initial values each entry can take. We represent Not Taken with N, and Taken with T.

Table 3: PHT

PHT Entry	Value
TT	01
TN	00
NT	01
NN	00 or 01

Show your work here.

Yes, it is possible.

The pattern after 5 iterations: TTTNTNTTTN.

In order to be more clear, we add indices to each branch outcome in the pattern above, to represent their positions in the pattern: T₁ T₂ T₃ N₄ T₅ N₆ T₇ T₈ T₉ N₁₀

- For GHR=NN, the only observed branch is T₁. Therefore, the PHTE for NN has to be either 00 or 01 so that the branch predictor mispredicts the taken branch.
- For GHR=TT, the observed branches are T₃ N₄ T₉ N₁₀. The PHTE for TT has to be initialized to 01 in order to cause the predictor to always mispredict. This way, each N and T moves the saturating counter to their respective direction. This will cause misprediction for the next branch which is always in the opposite direction.
- For GHR=TN, the observed branches are T₅ T₇. Thus, the initial PHTE value for TN has to be 00 to mispredict both taken branches.
- For GHR=NT, the observed branches are T₂ N₆ T₈. Similar to the TT entry, NT's PHTE has to be initialized 01.

- (b) [10 points] At steady-state, we observe the following pattern which repeats over time: TTTNTN, with T representing Taken, and N representing Not Taken. When GHR pattern equals to NT or TT, the predictor will observe that the branch outcome will be either T or N. Therefore, no matter what the initial values for these two entries are in the pattern history table (PHT), only one of the branches can be predicted correctly. Thus prediction accuracy will never reach 100%. Explain how using local history registers instead of the global history register will help bring the prediction accuracy up to 100% during the steady state, by showing what each PHTE will saturate to.

For the outer loop, we will keep observing all Ts, and the counters will be set to 2'b11 for TT and lead to 100% accuracy for this branch.
The second branch will keep observing this repeated pattern: TNN. So entry TN will be saturated to 2'b00, entry NN will saturate to 2'b11, and entry NT will saturate to 2'b00.