



---

## Technique to Calculate Day of Week

---

*Author: Tan Beng Hai  
Microchip Technology Inc.*

### INTRODUCTION

Basically, there are two kinds of electronic systems that come with a built-in calendar. The first kind of system is used mainly to display a calendar for a user's convenience. Examples of these systems are digital watches, computers, VCRs and TVs with on-screen display features. The second kind of system is required to know whether a given date is a weekend or weekday. Examples of such a system are multi-rate meters (such as a phone bill meter) and electronic pricing systems, where the weekend rate and the weekday rate are different.

In order to build an electronic calendar into the system, the designer needs to write a piece of software that will be able to determine the day (Sunday, Monday, ..., Saturday) of the week when a date is input into the system. This routine is the basic component of an electronics calendar.

This Technical Brief provides a technique to find the exact day for a given date input.

### THEORY OF CALCULATION

The method used to calculate the day of week is a straight forward and simple one. This method makes use of 31 December 1989 as a reference point. The reason why this date was chosen as a reference point is because it was on the last day of the week (Sunday), and also on the last day of a year (this makes it easy to calculate the number of days since the next day/date will be first/first). One day after this date was Monday, and two days after this date was Tuesday, and so on.

The date given will be N days after the 31st December 1989, and if the number N is divided by the number of days in a week (7), the return will correspond to a specific day of the week. For this application, 0 corresponds to Sunday, 1 to Monday, and so on till 6 corresponds to Saturday. Therefore, when a date is given, the number of days from the date given after the 31 December can be calculated. Then the division of the number by 7 will give a remainder, which will correspond to the day of the week that the system required.

### DESCRIPTION OF SOFTWARE

This application note provides two routines for the calculation of the day of the week. One is written in ANSI C and the other is written in assembly language using a PIC16C54 microcontroller.

In these routines, the number of days after 31 December 1989 is calculated and stored in a register called `AccValue`. There are a total of three steps involved in getting the number of days.

The first step is to find out the difference in years, and convert the difference into days. A 16-bit counter, `TempYear`, is used as a temporary counter and is initialized to the year 1990. The routine will keep comparing the contents of `TempYear` to the year (`CurrentYear` in the 'C' software) that is input in the software. If the `TempYear` value is less than the year value, `TempYear` will be increased by 1 until the contents of `TempYear` match the year given.

The `AccValue` will be increased by 1 (instead of 365, because  $365 \text{MOD} 7 = 1$ ) or by 2 (if `TempYear` is a leap year) for each comparison in which the `TempYear` value is less than the year value.

The second step involves calculating the number of days that have elapsed between the first day (inclusive) of that year and the first day of the month given. The number of days elapsed is calculated and pre-stored in a table. This value is retrieved with respect to the input month and added to the `AccValue`.

The way to calculate the pre-stored value is as follows; for January there is less than one month elapsed, therefore the value stored is 0. For February, the month passed is only 1 (January) and the value stored is  $31 \text{MOD} 7$ , which is 3. For March, 2 months have passed, (January and February), so the value stored is  $(28+31) \text{MOD} 7$ , which is 3.


The third step involves adding the day given to the `AccValue`. The `AccValue` is then divided by 7, and the remainder gives the result corresponding to the day of week.

Figure 1 is a flowchart of the software routine.

The software here will only work if the input given ranges from 1 January 1990 to 31 December 2099.

The software does not check for the use of erroneous dates such as 29 February 1998, or 32 March 1999.

FIGURE 1: APPLICATION FLOWCHART



## APPENDIX A: PIC16C54 ASSEMBLY CODE

```

ListP=16C54
;
;*****
;
PCL      equ    02h
STATUS   equ    03h
;
#define   Z      STATUS,2
#define   C      STATUS,0
;
YearHi    equ    10h           ;Store the Upper byte of Year
YearLw    equ    11h           ;Store the Lower byte of year
Month     equ    12h           ;Store the Month(1 for January, 2 for February and so on)
Day       equ    13h           ;Store the Day
AccValue  equ    14h
TempA     equ    15h
TempB     equ    16h
TempYearHi equ    15h
TempYearLw equ    16h
Lbyte     equ    17h
Hbyte     equ    18h
Ltemp     equ    19h
Htemp     equ    1Ah
Temp      equ    1Bh
;
    org 0x00
;*****
; Test program for GetDayOfWeek
; The End Result willbe stored in AccValue
;*****
;
main      movlw    19h           ;Set Date as 21 September 1998
          movwf    TempA
          movlw    98h
          movwf    TempB
          movlw    9
          movwf    Month
          movlw    D'21'
          movwf    Day
;
          call     BCDtoBin      ;Convert the 4-digit BCD Year to 16bit int value
;
          movfw    Lbyte
          movwf    YearLw
;
          movfw    Hbyte
          movwf    YearHi
;
          call     GetDayOfWeek  ;Calculate Day
;
Loop      gotoLoop
;
;*****
; Accumulated Value for Month
; This routine return the remainder value when
; number of days summed up and divided by 7
;*****
;
GetMonthValueaddwfPCL,1
          nop
          retlw    0             ;January
          retlw    3             ;February, %(31/7) = 3
          retlw    3             ;March, Remaider for (3+28)/7
          retlw    6             ;April, (3+31)/7
          retlw    1             ;May, (6+30)/7

```

```

        retlw 4           ;June, (1+31)/7
        retlw 6           ;July, %(4+30)/7= 6
        retlw 2           ;August, %(6+31/7) = 2
        retlw 5           ;September, %(2+31)/7=4
        retlw 0           ;October, %(5+30)/7=6
        retlw 3           ;November, (0+31)/7=3
        retlw 5           ;December, (3+30)/7=5
;
;*****
;
;       Routine : GetDayOfWeek
;*****
;
GetDayOfWeekclrAccValue
        call    CheckValidInput
        btfss   Z           ;Is input Valid ?
        retlw   08
;
        movlw   0C6h         ;Set the Temp counter to 1990(Decimal)
        movwf   TempYearLw
        movlw   07
        movwf   TempYearHi
;
GetDay_0      call    CompYear      ;Check is Year > Temp counter
        btfsc   Z
        goto    GetDay_1          ;Year = Temp
;
;Year is > Temp Year
;
        incf    AccValue,1
        call    IsLeapYear        ;Check is TempYear = Leap Year
        btfsc   Z                 ;Is Leap Year ?
        incf    AccValue,1        ;Yes !
;
        call    IncTemp
        goto    GetDay_0
;
GetDay_1      movlw.3
        subwf   Month,W           ;Check is Month > February ?
        btfss   C
        goto    GetDay_2          ;No !
;
        call    IsLeapYear        ;Check for Leap year
        btfss   Z
        goto    GetDay_2          ;Not Leap Year!
        incf    AccValue,1
;
GetDay_2      movf   Month,w
        call    GetMonthValue
        addwf   AccValue,1        ;Sum the AccValue with Month Value
        movf    Day,w
        addwf   AccValue,1        ;Sum the AccValue with Day Value
        call    Modula_7          ;AccValue%7
        retlw   0
;
;*****
;
;       Routine: Check Valid Input for 1990-2099
;       (equivalent to 07C6h - 0833h)
;       If Input Valid, return Valid = 1
;       Else Valid = 0
;*****
;
CheckValidInput movlw   07h
        subwf   YearHi,w
        btfss   C
        goto    NotValid         ;YearHi is < 07h
;

```

```

                btfss    Z
                goto     CheckValid_0    ;YearHi not equal to 07h
;
;YearHi is = 07h Check For Year low
;
                movlw    0C6h
                subwf     YearLw,w
                btfss     C
                goto     NotValid        ;YearLw is <90
;
ValidYear      bsf       Z
                retlw     0              ;Year is valid
;
;YearHi is greater 07h, check for YearHi=08h
;
CheckValid_0   movlw     08h
                subwf     YearHi,w
                btfss     Z
                goto     NotValid        ;YearHi is > 20
;
;YearHi is 20, check for YearLw < or = 33
;
                movlw     34h
                subwf     YearLw,w
                btfss     C              ;is YearLw end with Hex value ?
                goto     ValidYear       ;Not a valid value
;
NotValid       bcf       Z
                retlw     0
;
;*****
;       Routine: Modula_7
;       Register: ACC
;       Output: Remainder of Acc/7
;*****
;
Modula_7       movlw     .7
                subwf     AccValue,w
                btfss     C
                goto     Modula_70
;
;Contents of Acc > 7
;
                movlw     .7
                subwf     AccValue,1
                goto     Modula_7
;
Modula_70      movf       AccValue,w
                movwf     Temp
                retlw     0
;
;*****
;       Routine : CompYear
;       ReturnZ=1 if Year > TempYear
;       Else return 0
;*****
;
CompYear       movf       YearHi,w
                subwf     TempYearHi,w
                btfss     Z
                retlw     0              ;YearHi > TempYearHi
;
                movfw     YearLw
                subwf     TempYearLw,w
                retlw     0
;

```

```
;*****
;
;       Routine: IsLeapYear
;       Return Z=1 if TempYear is Leap year
;       Else Return 0
;*****
;
IsLeapYear      btfsc   TempYearLw,0
                goto    NotLeapYear
;
                btfsc   TempYearLw,1
                goto    NotLeapYear
;
                bsf     Z
                retlw   0
;
NotLeapYear     bcf     Z
                retlw   0
;
;*****
;       Routine: IncTemp
;       Increment The Temporary Counter
;*****
;
IncTemp         incfsz  TempYearLw,1
                retlw   0
;
                incf    TempYearHi,1
                retlw   0
;
;*****
;       Routine : BCDtoBin
;       This routine convert 4-Digit BCD value(D3D2D1D0)
;       into 16Bit Binary code
;       input : 2 digit High Byte is stored in TempA
;              2 digit Low byte is store in TempB
;       Output: Hbyte:Lbyte
;       For more on the BCD to Bin conversion please refer
;       to AN544
;*****
;
BCDtoBin        clr     Htemp
                clr     Ltemp
                clr     Lbyte
                clr     Hbyte
;
                swapf   TempA,w           ;D3*10
                call    Mpy10
;
                movfw   TempA             ;[(D3*10)+D2]*10
                call    Mpy10
;
                swapf   TempB,w           ;{[(D3*10)+D2]*10+D1}*10
                call    Mpy10
;
                movfw   TempB             ;
                andlw   0x0f
;
                addwf   Lbyte,1           ;{[(D3*10)+D2]*10+D1}*10+D4
                btfsc   C
                incfH   byte,1
                retlw   0
;
```

```

;*****
;      Routine : Mpy10
;      This routine multiply the value store in W register by 10
;      Theory : Let say the input is N,
;      1st, Store the product of 2*N into Temporary register
;      2nd, Multiply the value N by 8, (8*N) and store in Hbyte and Lbyte
;      3rd, Sum up the value obtained in 1st and 2nd steps
;      The whole process is equivalent to  $2*N+8*N = N(2+8) = 10*N$ 
;*****
;
Mpy10      andlw    0x0f
           addwf    Lbyte,1      ;2*N and store the product in temp
           btfsc    C
           incf     Hbyte,1
;
           bcf      C
           rlf      Lbyte,w
           movwf    Ltemp
           rlf      Hbyte,W
           movwf    Htemp
;
           bcf      C            ;8*N
           rlf      Lbyte,1
           rlf      Hbyte,1
;
           bcf      C
           rlf      Lbyte,1
           rlf      Hbyte,1
;
           bcf      C
           rlf      Lbyte,1
           rlf      Hbyte,1
;
           movfw    Ltemp        ;8*N+2*N =10*N
           addwf    Lbyte,1
           movfw    Htemp
           addwf    Hbyte,1
           retlw    0
;
;*****
;
END

```

## APPENDIX B: C IMPLEMENTATION

```
#include<P17C756.H>

#defineOK1
#defineError8

charGetDayofWeek();
charCheckValidInput(unsigned int);
charIsLeapYear(int);

rom      constunsigned charTable[13]={0,0,3,3,6,1,4,6,2,5,0,3,5};

unsigned intCurrentYear;
unsigned charMonth,Day;

/*****
 * Test Program for the routine GetDayofWeek()
 *****/
voidmain(){

    charTemp;

    CurrentYear = 1998;/*Date : 21 September 1998*/
    Month      = 9;
    Day        = 21;

    Temp = GetDayofWeek();/*Result stored in Temp*/
    do{
    }while(1);
}

/*****
 * GetDayofWeek
 * This routine calculate the Day(Sunday, Monday,...Saturday) of
 * week when a Date(year, Month, Day) is given.
 * Input : Year, Month and Day which in this routine is used
 * as global variable.
 * Output Variable : 0 to 6(which correspond to Sunday to Saturday
 * respectively) if the input is acceptable, else a value 8 is return
 *****/
charGetDayofWeek(){

    unsigned intTempYear;
    unsigned charAccValue, Temp;

    if(CheckValidInput(CurrentYear)!=OK)/* Return Error if input not Valid*/
        return Error;

    TempYear = 1990;/*Comparation start with year 1990*/
    AccValue = 0;/*Init AccValue to 0*/

    /* If TempYear is a leap year AccValue +2, else AccValue+1 */

    while(TempYear != CurrentYear){
        AccValue++;
        if(IsLeapYear(TempYear))
            AccValue++;
        TempYear++;
    }

    if(Month > 2){
        if(IsLeapYear(TempYear)==1)
            AccValue++;
    }
}
```



```

    AccValue += Table[Month];
    AccValue += Day;

    AccValue= AccValue%7;

    return(AccValue);
}

/*****
* CheckValidInput
* Return a '1' if the input is within the required range. Else
* return a '0'.
*
* Input Variable : 16Bit Unsigned Int
* Output Variable : '1' if input ranges between 1990 & 2099 inclusively
*****/
charCheckValidInput(unsigned int Input){

    if(Input>=1990 && Input<=2099 )
        returnOK;
    else
        return !OK;

}

/*****
* IsLeapYear
* Return a '1' if the input is a leap year. Else return a '0'
*
* Input Variable : 16Bit Unsigned Int
* Output Variable : '1' if is a leap year, else '0'.
*****/
charIsLeapYear(int Year){

    Year=Year&0x0003;
    if(Year==0)
        return 1;
    else
        return0;

}
/*****/

```



## WORLDWIDE SALES AND SERVICE

### AMERICAS

#### Corporate Office

Microchip Technology Inc.  
2355 West Chandler Blvd.  
Chandler, AZ 85224-6199  
Tel: 480-786-7200 Fax: 480-786-7277  
Technical Support: 480-786-7627  
Web Address: <http://www.microchip.com>

#### Atlanta

Microchip Technology Inc.  
500 Sugar Mill Road, Suite 200B  
Atlanta, GA 30350  
Tel: 770-640-0034 Fax: 770-640-0307

#### Boston

Microchip Technology Inc.  
5 Mount Royal Avenue  
Marlborough, MA 01752  
Tel: 508-480-9990 Fax: 508-480-8575

#### Chicago

Microchip Technology Inc.  
333 Pierce Road, Suite 180  
Itasca, IL 60143  
Tel: 630-285-0071 Fax: 630-285-0075

#### Dallas

Microchip Technology Inc.  
4570 Westgrove Drive, Suite 160  
Addison, TX 75248  
Tel: 972-818-7423 Fax: 972-818-2924

#### Dayton

Microchip Technology Inc.  
Two Prestige Place, Suite 150  
Miamisburg, OH 45342  
Tel: 937-291-1654 Fax: 937-291-9175

#### Detroit

Microchip Technology Inc.  
Tri-Atria Office Building  
32255 Northwestern Highway, Suite 190  
Farmington Hills, MI 48334  
Tel: 248-538-2250 Fax: 248-538-2260

#### Los Angeles

Microchip Technology Inc.  
18201 Von Karman, Suite 1090  
Irvine, CA 92612  
Tel: 949-263-1888 Fax: 949-263-1338

#### New York

Microchip Technology Inc.  
150 Motor Parkway, Suite 202  
Hauppauge, NY 11788  
Tel: 631-273-5305 Fax: 631-273-5335

#### San Jose

Microchip Technology Inc.  
2107 North First Street, Suite 590  
San Jose, CA 95131  
Tel: 408-436-7950 Fax: 408-436-7955

### AMERICAS (continued)

#### Toronto

Microchip Technology Inc.  
5925 Airport Road, Suite 200  
Mississauga, Ontario L4V 1W1, Canada  
Tel: 905-405-6279 Fax: 905-405-6253

### ASIA/PACIFIC

#### Hong Kong

Microchip Asia Pacific  
Unit 2101, Tower 2  
Metroplaza  
223 Hing Fong Road  
Kwai Fong, N.T., Hong Kong  
Tel: 852-2-401-1200 Fax: 852-2-401-3431

#### Beijing

Microchip Technology, Beijing  
Unit 915, 6 Chaoyangmen Bei Dajie  
Dong Erhuan Road, Dongcheng District  
New China Hong Kong Manhattan Building  
Beijing 100027 PRC  
Tel: 86-10-85282100 Fax: 86-10-85282104

#### India

Microchip Technology Inc.  
India Liaison Office  
No. 6, Legacy, Convent Road  
Bangalore 560 025, India  
Tel: 91-80-229-0061 Fax: 91-80-229-0062

#### Japan

Microchip Technology Intl. Inc.  
Benex S-1 6F  
3-18-20, Shinyokohama  
Kohoku-Ku, Yokohama-shi  
Kanagawa 222-0033 Japan  
Tel: 81-45-471-6166 Fax: 81-45-471-6122

#### Korea

Microchip Technology Korea  
168-1, Youngbo Bldg. 3 Floor  
Samsung-Dong, Kangnam-Ku  
Seoul, Korea  
Tel: 82-2-554-7200 Fax: 82-2-558-5934

#### Shanghai

Microchip Technology  
RM 406 Shanghai Golden Bridge Bldg.  
2077 Yan'an Road West, Hong Qiao District  
Shanghai, PRC 200335  
Tel: 86-21-6275-5700 Fax: 86 21-6275-5060

### ASIA/PACIFIC (continued)

#### Singapore

Microchip Technology Singapore Pte Ltd.  
200 Middle Road  
#07-02 Prime Centre  
Singapore 188980  
Tel: 65-334-8870 Fax: 65-334-8850

#### Taiwan

Microchip Technology Taiwan  
10F-1C 207  
Tung Hua North Road  
Taipei, Taiwan  
Tel: 886-2-2717-7175 Fax: 886-2-2545-0139

### EUROPE

#### United Kingdom

Arizona Microchip Technology Ltd.  
505 Eskdale Road  
Wokingham Triangle  
Wokingham  
Berkshire, England RG41 5TU  
Tel: 44 118 921 5858 Fax: 44-118 921-5835

#### Denmark

Microchip Technology Denmark ApS  
Regus Business Centre  
Lautrup høj 1-3  
Ballerup DK-2750 Denmark  
Tel: 45 4420 9895 Fax: 45 4420 9910

#### France

Arizona Microchip Technology SARL  
Parc d'Activite du Moulin de Massy  
43 Rue du Saule Trapu  
Batiment A - 1er Etage  
91300 Massy, France  
Tel: 33-1-69-53-63-20 Fax: 33-1-69-30-90-79


#### Germany

Arizona Microchip Technology GmbH  
Gustav-Heinemann-Ring 125  
D-81739 München, Germany  
Tel: 49-89-627-144 0 Fax: 49-89-627-144-44

#### Italy

Arizona Microchip Technology SRL  
Centro Direzionale Colleoni  
Palazzo Taurus 1 V. Le Colleoni 1  
20041 Agrate Brianza  
Milan, Italy  
Tel: 39-039-65791-1 Fax: 39-039-6899883

11/15/99



Microchip received QS-9000 quality system certification for its worldwide headquarters, design and wafer fabrication facilities in Chandler and Tempe, Arizona in July 1999. The Company's quality system processes and procedures are QS-9000 compliant for its PICmicro® 8-bit MCUs, KEELoc® code hopping devices, Serial EEPROMs and microperipheral products. In addition, Microchip's quality system for the design and manufacture of development systems is ISO 9001 certified.

All rights reserved. © 1999 Microchip Technology Incorporated. Printed in the USA. 11/99 Printed on recycled paper.

Information contained in this publication regarding device applications and the like is intended for suggestion only and may be superseded by updates. No representation or warranty is given and no liability is assumed by Microchip Technology Incorporated with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Use of Microchip's products as critical components in life support systems is not authorized except with express written approval by Microchip. No licenses are conveyed, implicitly or otherwise, under any intellectual property rights. The Microchip logo and name are registered trademarks of Microchip Technology Inc. in the U.S.A. and other countries. All rights reserved. All other trademarks mentioned herein are the property of their respective companies.