

Name: Saranya Aluru

Roll No: 2520080012

```
mysql> USE OrderPractice;
Database changed
mysql> CREATE TABLE orders (
  ->     ord_no INT PRIMARY KEY,
  ->     purch_amt DECIMAL(10,2),
  ->     ord_date DATE,
  ->     customer_id INT,
  ->     salesman_id INT
  -> );
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> DESC orders;
```

Field	Type	Null	Key	Default	Extra
ord_no	int	NO	PRI	NULL	
purch_amt	decimal(10,2)	YES		NULL	
ord_date	date	YES		NULL	
customer_id	int	YES		NULL	
salesman_id	int	YES		NULL	

```
5 rows in set (0.01 sec)
```

```
mysql> INSERT INTO orders VALUES
-> (70001,150.50,'2012-10-05',3005,5002),
-> (70009,270.65,'2012-09-10',3001,5005),
-> (70002,65.26,'2012-10-05',3002,5001),
-> (70004,110.50,'2012-08-17',3009,5003),
-> (70007,948.50,'2012-09-10',3005,5002),
-> (70005,2400.60,'2012-07-27',3007,5001),
-> (70008,5760.00,'2012-09-10',3002,5001),
-> (70010,1983.43,'2012-10-10',3004,5006),
-> (70003,2480.40,'2012-10-10',3009,5003),
-> (70012,250.45,'2012-06-27',3008,5002),
-> (70011,75.29,'2012-08-17',3003,5007),
-> (70013,3045.60,'2012-04-25',3002,5001);
```

Query OK, 12 rows affected (0.01 sec)

Records: 12 Duplicates: 0 Warnings: 0

```
mysql> SELECT * FROM orders;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70004	110.50	2012-08-17	3009	5003
70005	2400.60	2012-07-27	3007	5001
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005
70010	1983.43	2012-10-10	3004	5006
70011	75.29	2012-08-17	3003	5007
70012	250.45	2012-06-27	3008	5002
70013	3045.60	2012-04-25	3002	5001

12 rows in set (0.00 sec)

```
mysql> SELECT *
```

```
mysql> SELECT *  
-> FROM orders  
-> WHERE purch_amt > 2000;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

4 rows in set (0.01 sec)

```
mysql> SELECT *  
-> FROM orders  
-> WHERE ord_date = '2012-09-10';
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005

3 rows in set (0.00 sec)

```
mysql> SELECT *
-> FROM orders
-> WHERE salesman_id = 5001;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70002	65.26	2012-10-05	3002	5001
70005	2400.60	2012-07-27	3007	5001
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001

4 rows in set (0.00 sec)

```
mysql> SELECT *
-> FROM orders
-> ORDER BY purch_amt DESC;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70008	5760.00	2012-09-10	3002	5001
70013	3045.60	2012-04-25	3002	5001
70003	2480.40	2012-10-10	3009	5003
70005	2400.60	2012-07-27	3007	5001
70010	1983.43	2012-10-10	3004	5006
70007	948.50	2012-09-10	3005	5002
70009	270.65	2012-09-10	3001	5005
70012	250.45	2012-06-27	3008	5002
70001	150.50	2012-10-05	3005	5002
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70002	65.26	2012-10-05	3002	5001

12 rows in set (0.00 sec)

```
mysql> SELECT *
-> FROM orders
-> ORDER BY ord_date;
```

ord_no	purch_amt	ord_date	customer_id	salesman_id
70013	3045.60	2012-04-25	3002	5001
70012	250.45	2012-06-27	3008	5002
70005	2400.60	2012-07-27	3007	5001
70004	110.50	2012-08-17	3009	5003
70011	75.29	2012-08-17	3003	5007
70007	948.50	2012-09-10	3005	5002
70008	5760.00	2012-09-10	3002	5001
70009	270.65	2012-09-10	3001	5005
70001	150.50	2012-10-05	3005	5002
70002	65.26	2012-10-05	3002	5001
70003	2480.40	2012-10-10	3009	5003
70010	1983.43	2012-10-10	3004	5006

12 rows in set (0.00 sec)

```
mysql> SELECT SUM(purch_amt) AS total_revenue
-> FROM orders;
```

total_revenue
17541.18

1 row in set (0.01 sec)

```
mysql> SELECT COUNT(*) AS total_orders  
-> FROM orders;
```

```
+-----+  
| total_orders |  
+-----+  
|          12 |  
+-----+  
1 row in set (0.01 sec)
```

```
mysql> SELECT salesman_id,  
-> SUM(purch_amt) AS total_sales  
-> FROM orders  
-> GROUP BY salesman_id;
```

```
+-----+-----+  
| salesman_id | total_sales |  
+-----+-----+  
|          5002 |      1349.45 |  
|          5001 |     11271.46 |  
|          5003 |      2590.90 |  
|          5005 |       270.65 |  
|          5006 |      1983.43 |  
|          5007 |       75.29 |  
+-----+-----+  
6 rows in set (0.00 sec)
```

```
mysql> SELECT AVG(purch_amt) AS average_order  
-> FROM orders;
```

```
+-----+  
| average_order |  
+-----+  
| 1461.765000 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> SELECT MAX(purch_amt) AS highest_order  
-> FROM orders;
```

```
+-----+  
| highest_order |  
+-----+  
| 5760.00 |  
+-----+  
1 row in set (0.02 sec)
```

```
mysql> SELECT MIN(purch_amt) AS lowest_order  
-> FROM orders;
```

```
+-----+  
| lowest_order |  
+-----+  
| 65.26 |  
+-----+  
1 row in set (0.00 sec)
```

```
mysql> SELECT customer_id,  
->      SUM(purch_amt) AS total_purchase  
-> FROM orders  
-> GROUP BY customer_id;
```

customer_id	total_purchase
3005	1099.00
3002	8870.86
3009	2590.90
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3008	250.45

8 rows in set (0.00 sec)

```
mysql> SELECT customer_id,  
->      MAX(purch_amt) AS highest_purchase  
-> FROM orders  
-> GROUP BY customer_id;
```

customer_id	highest_purchase
3005	948.50
3002	5760.00
3009	2480.40
3007	2400.60
3001	270.65
3004	1983.43
3003	75.29
3008	250.45

8 rows in set (0.00 sec)


```
mysql> SELECT salesman_id,  
->      SUM(purch_amt) AS total_sales  
-> FROM orders  
-> GROUP BY salesman_id  
-> HAVING SUM(purch_amt) > 3000;  
+-----+-----+  
| salesman_id | total_sales |  
+-----+-----+  
|          5001 |      11271.46 |  
+-----+-----+  
1 row in set (0.00 sec)
```



```
mysql> SELECT customer_id,  
->      SUM(purch_amt) AS total_purchase  
-> FROM orders  
-> GROUP BY customer_id  
-> HAVING SUM(purch_amt) > 2500;  
+-----+-----+  
| customer_id | total_purchase |  
+-----+-----+  
|          3002 |      8870.86 |  
|          3009 |      2590.90 |  
+-----+-----+  
2 rows in set (0.00 sec)
```

```
mysql> SELECT customer_id,  
->      COUNT(*) AS total_orders  
-> FROM orders  
-> GROUP BY customer_id  
-> HAVING COUNT(*) > 1;
```

customer_id	total_orders
3005	2
3002	3
3009	2

3 rows in set (0.02 sec)

```
mysql> SELECT customer_id,  
->      SUM(purch_amt) AS total_purchase  
-> FROM orders  
-> GROUP BY customer_id  
-> HAVING SUM(purch_amt) > 1000  
-> ORDER BY total_purchase DESC;
```

customer_id	total_purchase
3002	8870.86
3009	2590.90
3007	2400.60
3004	1983.43
3005	1099.00

5 rows in set (0.00 sec)

```
mysql> SELECT customer_id,
->         MAX(purch_amt) AS max_purchase
-> FROM orders
-> GROUP BY customer_id
-> HAVING MAX(purch_amt) BETWEEN 2000 AND 6000;
```

customer_id	max_purchase
3002	5760.00
3009	2480.40
3007	2400.60

3 rows in set (0.02 sec)

```
mysql> SELECT salesman_id,
->         COUNT(*) AS total_orders
-> FROM orders
-> GROUP BY salesman_id
-> HAVING COUNT(*) >= 2;
```

salesman_id	total_orders
5002	3
5001	4
5003	2

3 rows in set (0.00 sec)

```
mysql> SELECT ord_date,
->         MAX(purch_amt) AS highest_purchase
-> FROM orders
-> GROUP BY ord_date
-> HAVING MAX(purch_amt) > 2000;
```

ord_date	highest_purchase
2012-10-10	2480.40
2012-07-27	2400.60
2012-09-10	5760.00
2012-04-25	3045.60

4 rows in set (0.00 sec)