

Cross-Domain JavaScript Source File Inclusion (Systemic)

Assessment Identifier: **WS-DYN-07** | Assessment Type: **Dynamic** | Date: **September 08, 2026**

Severity: LOW	CVSS: 3.7	CWE: CWE-829
OWASP: A08:2021 - Software and Data Integrity Failures	WASC ID: 15	Confidence: Medium
Target / Component: Frontend Analytics Integration	Affected URL: https://www.worldmonitor.app/	Parameter: https://abacus.worldmonitor.app/script.js

1. Description

The page includes one or more script files from a third-party domain. Loading JavaScript files from third-party domains introduces trust dependencies on external systems that are not directly under the control of the primary application domain.

2. Steps to Reproduce

- Send an HTTP GET request to https://www.worldmonitor.app/.
- Inspect the HTML response body returned by the server.
- Locate any <script> elements loading scripts from cross-domain origins (e.g., https://abacus.worldmonitor.app/script.js).

3. Controlled Proof of Concept

HTML Evidence:

```

<script async defer src="https://abacus.worldmonitor.app/script.js"
data-website-id="e8800335-c853-46a8-8497-c993ed2f68bc"
data-domains="worldmonitor.app,www.worldmonitor.app,happy.worldmonitor.app"
nonce="wm-static-bootstrap"></script>

```

Verification: Host abacus.worldmonitor.app differs from primary domain www.worldmonitor.app.

4. Business & Security Impact

Including scripts from cross-domain sources creates a reliance on external server security. If the third-party domain hosting the script is compromised or hijacked, an attacker could manipulate the hosted script content to execute malicious code within the context of the primary application users, leading to cross-site scripting (XSS), data interception, or session theft.

5. Remediation Recommendations

Primary Fix: Host critical scripts locally on the primary domain or apply Subresource Integrity controls.

- Ensure JavaScript source files are loaded from trusted sources, and the sources cannot be controlled by end users of the application.
- Host critical scripts locally on the same origin domain whenever feasible.
- Implement Subresource Integrity (SRI) attributes (e.g., integrity="sha384-...") on any external scripts that must be included from external domains to ensure their integrity is validated before execution.

6. Evidence & Validation




Figure 1: Matched Proof-of-Concept Screenshot for Vulnerability #7 (7/poc-1.png)

Authorization & Safety Compliance: This security assessment scan was conducted strictly under authorized parameters in accordance with ethical hacking standards. All validations and safe proof-of-concept tests were non-destructive. No persistent modifications or sensitive data exfiltration occurred.