

Rajalakshmi Engineering College

Name: Saranya Vimalanathan
Email: 240701620@rajalakshmi.edu.in
Roll no: 240701620
Phone: 9789689339
Branch: REC
Department: CSE - Section 9
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 3_PAH

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

Egath is participating in a coding hackathon, and one of the challenges requires him to work with an array of integers. The task is to remove exactly one element from the array such that the sum of the remaining elements is a prime number.

Help Egath find the first possible prime sum by removing one element or determining if no such prime sum can be achieved.

Input Format

The first line of input consists of an integer N, representing the number of elements in the array.

The second line consists of N space-separated integers, representing the array elements.

Output Format

If removing one element results in a prime sum, print the sum.

If no such prime sum can be achieved by removing exactly one element, print "No valid prime sum found".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 3

1 2 3

Output: 5

Answer

// You are using Java

```
import java.util.Scanner;
```

```
public class Main {
```

```
    public static boolean isPrime(int num) {  
        if (num <= 1) return false;  
        if (num == 2) return true;  
        if (num % 2 == 0) return false;  
        for (int i = 3; i * i <= num; i += 2) {  
            if (num % i == 0) return false;  
        }  
        return true;  
    }
```

```
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int N = sc.nextInt();  
        int[] arr = new int[N];
```

```

int totalSum = 0;
for (int i = 0; i < N; i++) {
    arr[i] = sc.nextInt();
    totalSum += arr[i];
}

boolean found = false;

for (int i = 0; i < N; i++) {
    int sumWithout = totalSum - arr[i];
    if (isPrime(sumWithout)) {
        System.out.println(sumWithout);
        found = true;
        break;
    }
}

if (!found) {
    System.out.println("No valid prime sum found");
}

sc.close();
}
}

```

Status : Correct

Marks : 10/10

2. Problem Statement

Priya is building a system to automate image transformations using matrix operations. To do this, she needs to multiply two matrices representing pixel data and transformation rules.

Help Priya perform matrix multiplication and print the resulting matrix if the operation is valid.

Input Format

The first line of input consists of two int values, representing the number of rows R1 and columns C1 of the first matrix.

The next $R1 \times C1$ integers represent the elements of the first matrix.

The next line consists of two int values, representing the number of rows $R2$ and columns $C2$ of the second matrix.

The next $R2 \times C2$ integers represent the elements of the second matrix.

Output Format

If matrix multiplication is possible, print $R1$ lines, each containing $C2$ space-separated int values representing the resulting matrix.

Otherwise, print "Matrix multiplication not possible".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 2 3

1 2 3

4 5 6

3 2

7 8

9 10

11 12

Output: 58 64

139 154

Answer

// You are using Java

```
import java.util.Scanner;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int R1 = sc.nextInt();  
        int C1 = sc.nextInt();  
        int[][] matrix1 = new int[R1][C1];
```

```
for (int i = 0; i < R1; i++) {  
    for (int j = 0; j < C1; j++) {  
        matrix1[i][j] = sc.nextInt();  
    }  
}
```

```
int R2 = sc.nextInt();  
int C2 = sc.nextInt();  
int[][] matrix2 = new int[R2][C2];  
for (int i = 0; i < R2; i++) {  
    for (int j = 0; j < C2; j++) {  
        matrix2[i][j] = sc.nextInt();  
    }  
}
```

```
if (C1 != R2) {  
    System.out.println("Matrix multiplication not possible");  
} else {  
    int[][] result = new int[R1][C2];
```

```
    for (int i = 0; i < R1; i++) {  
        for (int j = 0; j < C2; j++) {  
            int sum = 0;  
            for (int k = 0; k < C1; k++) {  
                sum += matrix1[i][k] * matrix2[k][j];  
            }  
            result[i][j] = sum;  
        }  
    }
```

```
    for (int i = 0; i < R1; i++) {  
        for (int j = 0; j < C2; j++) {  
            System.out.print(result[i][j] + " ");  
        }  
        System.out.println();  
    }  
}
```

```
        sc.close();  
    }  
}
```

Status : Correct

Marks : 10/10

3. Problem Statement

Eminem is a billiard player who enjoys playing billiards and also likes solving mathematical puzzles. He notices that the billiard balls on the table are arranged in a grid, and he is curious to find the sum of the numbers written on each ball.

Write a program to find the sum of all the numbers written on each ball in the grid.

Input Format

The first line of input consists of an integer N, representing the number of rows.

The second line consists of an integer M, representing the number of columns.

The following lines N lines consist of M space-separated integers, representing the numbers written on each ball.

Output Format

The output prints an integer representing the sum of all the numbers written on each ball.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3

3

1 2 3

4 5 6

7 8 9

Output: 45

Answer

// You are using Java

```
import java.util.Scanner;
```

```
public class Main {  
    public static void main(String[] args) {  
        Scanner sc = new Scanner(System.in);
```

```
        int N = sc.nextInt();  
        int M = sc.nextInt();
```

```
        int sum = 0;
```

```
        for (int i = 0; i < N; i++) {  
            for (int j = 0; j < M; j++) {  
                sum += sc.nextInt();  
            }  
        }
```

```
        System.out.println(sum);
```

```
        sc.close();  
    }  
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

In a customer loyalty program, reward points are logged in a sorted array as customers make transactions. Occasionally, due to system errors, duplicate entries for the same transaction may appear. To ensure accurate reward calculations, it's crucial to remove these duplicates from the list.

Write a program to process the array of reward points, removing any duplicates while preserving the order of unique entries. The program should then display the cleaned list of unique reward points and the total count of these unique points.

Input Format

The first line of input consists of an integer N, representing the number of reward points.

The second line consists of N space-separated integers, representing the reward points in sorted order.

Output Format

The first line of output prints the cleaned list of unique reward points separated by a space.

The second line of output prints an integer representing the total count of unique reward points.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 3
100 100 200
Output: 100 200
2

Answer

```
// You are using Java
import java.util.Scanner;

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int N = sc.nextInt();
        int[] arr = new int[N];
```



```
for (int i = 0; i < N; i++) {  
    arr[i] = sc.nextInt();  
}
```

```
int[] unique = new int[N];  
int count = 0;
```

```
for (int i = 0; i < N; i++) {  
    if (i == 0 || arr[i] != arr[i - 1]) {  
        unique[count] = arr[i];  
        count++;  
    }  
}
```

```
for (int i = 0; i < count; i++) {  
    System.out.print(unique[i] + " ");  
}  
System.out.println();
```

```
System.out.println(count);
```

```
sc.close();  
}
```

Status : Correct

Marks : 10/10