

# **L-MARK®**

## The reliable tubing & label printer

# **LK-320**



## *Convenient and practical*

- Light enough to carry and use anywhere (only 1.5kg)
- Automatically prints and cuts to your selected tag length
- All functions can be performed by pressing only one key, simple operation, anyone can use it right away
- QWERTY style keyboard allows fast data entry

### ■ LK-320 Cable ID Printer Specifications

|                            |                                                       |
|----------------------------|-------------------------------------------------------|
| Model                      | LK-320                                                |
| Mode of printing           | Thermal transfer printing                             |
| Resolution                 | 300dpi                                                |
| Printing character height  | 1.3mm—8mm                                             |
| Max number of input pages  | 198                                                   |
| Sleeve tube size printable | Φ2.5—Φ6                                               |
| label size printable       | 6mm、9mm、12mm                                          |
| Printing speed             | 11.5mm/sec(with half-cut)                             |
| Display                    | LCD, white color background, displaying up to 3 lines |
| Characters printable       | Chinese, English, number, symbol                      |
| Entry method               | Standard 64-key                                       |
| Memory                     | About 50,000 characters                               |
| Material cutting method    | Automatic half-cutting                                |
| Power supply               | DC 12V 2A                                             |
| Ambient requirements       | Operation: Temp 15℃~35℃                               |
|                            | Relative humidity 10%~85% (without condensation)      |
|                            | Storage: Temp 5℃~35℃                                  |
|                            | Relative humidity 10%~85% (without condensation)      |
| Overall dimensions         | 265(L)×198(W)×90(H)                                   |
| Weight                     | About 1.5kg                                           |

Specifications are subject to change without notice for product improvement



- Maintenance services are carried out on the basis of customers bringing the repair center. The period of free-of-charge maintenance services under the warranty is one year from the date of purchase.
- The presence of grit, grease, or scratches on the tube or label tape may prevent correct printing.
- The minimum period that replacement parts for maintenance and repair will be kept is seven years from the time the product is discontinued.
- It can not insure to print normally if does not use original ribbon.

### ■ Consumables

| Commodity    | Description                                  | Product Code | Package          |
|--------------|----------------------------------------------|--------------|------------------|
| Labels       | Label cassette tape (White 6mm)              | LM406WL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (White 9mm)              | LM409WL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (White 12mm)             | LM412WL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Yellow 6mm)             | LM406YL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Yellow 9mm)             | LM409YL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Yellow 12mm)            | LM412YL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Silver 6mm)             | LM406SL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Silver 9mm)             | LM409SL      | 5pcs(8m×5)/box   |
|              | Label cassette tape (Silver 12mm)            | LM412SL      | 5pcs(8m×5)/box   |
| Ink ribbons  | Ribbon cassette (black)                      | LM33B        | 5pcs(80m×5)/box  |
|              | Ribbon cassette (white)                      | LM33W        | 5pcs(80m×5)/box  |
|              | Ribbon cassette (red)                        | LM33R        | 5pcs(80m×5)/box  |
| Shrink tubes | 2:1 heat shrink tube cassette (White 3.0mm)  | LM-SS30W     | 5pcs(2.5m×5)/box |
|              | 2:1 heat shrink tube cassette (Yellow 3.0mm) | LM-SS30Y     | 5pcs(2.5m×5)/box |
|              | 2:1 heat shrink tube cassette (White 5.2mm)  | LM-SS52W     | 5pcs(2m×5)/box   |
|              | 2:1 heat shrink tube cassette (Yellow 5.2mm) | LM-SS52Y     | 5pcs(2m×5)/box   |
|              | 2:1 heat shrink tube cassette (White 6.8mm)  | LM-SS68W     | 5pcs(2m×5)/box   |
| Cutter       | 2:1 heat shrink tube cassette (Yellow 6.8mm) | LM-SS68Y     | 5pcs(2m×5)/box   |
|              | Cutter (cutter holder and cutting blade)     | LM-02-10     | 2pcs/box         |



Label tape



Ribbon cassette

#### Caution



Please read the instruction manual thoroughly before using the LK-320 and be sure to use it only according to the instructions. Only operate the LK-320 using the power supply and voltage rating stated in the manual.

**L-MARK®**

**LABEL & MARK INDUSTRIES COMPANY**

<http://www.lmark.net>