

Stability and delay analysis of delay tolerant networks with random message arrivals

Sarath Yasodharan ¹

Vineeth Bala Sukumaran ² Chandramani Singh ¹

¹Indian Institute of Science, Bangalore


²Indian Institute of Space Science and Technology, Trivandrum

COMSNETS, 2017

Outline


- 1 System model
- 2 Stability analysis
- 3 Delay analysis
- 4 Future work

System model




- A source node, a destination node and N mobile nodes.

System model




- A source node, a destination node and N mobile nodes.
- Mobility model: $\exp(\beta)$ intermeeting times between pairs of nodes, independent across node pair.

System model



- A source node, a destination node and N mobile nodes.
- Mobility model: $\exp(\beta)$ intermeeting times between pairs of nodes, independent across node pair.
- Packets arrive to the source at the points of a Poisson point process of rate λ .

System model



- A source node, a destination node and N mobile nodes.
- Mobility model: $\exp(\beta)$ intermeeting times between pairs of nodes, independent across node pair.
- Packets arrive to the source at the points of a Poisson point process of rate λ .
- Routing protocol: Two-hop relaying.

System model

- Messages are delay-sensitive; needs fast delivery.

System model

- Messages are delay-sensitive; needs fast delivery.
- Source makes K copies of each message, and transmits to first K susceptible relays it meets.

System model

- Messages are delay-sensitive; needs fast delivery.
- Source makes K copies of each message, and transmits to first K susceptible relays it meets.
- A message is delivered to the destination if any one of the infected relays with a copy of the message meets the destination.

System model

- Messages are delay-sensitive; needs fast delivery.
- Source makes K copies of each message, and transmits to first K susceptible relays it meets.
- A message is delivered to the destination if any one of the infected relays with a copy of the message meets the destination.
- Assumptions:
 - A relay can hold at most one packet.
 - Source does not meet the destination.
 - No feedback mechanism for acknowledging message delivery.

System model

- Messages are delay-sensitive; needs fast delivery.
- Source makes K copies of each message, and transmits to first K susceptible relays it meets.
- A message is delivered to the destination if any one of the infected relays with a copy of the message meets the destination.
- Assumptions:
 - A relay can hold at most one packet.
 - Source does not meet the destination.
 - No feedback mechanism for acknowledging message delivery.
- Goal:
 - What is the maximum arrival rate λ that the system can support?
 - How does end-to-end delay depend on the system parameters?

Stability analysis

- $Q(t)$: Number of packets in the source buffer at time t (counts each copy of a message; a single un-served message gives $Q(t) = K$).

Stability analysis

- $Q(t)$: Number of packets in the source buffer at time t (counts each copy of a message; a single un-served message gives $Q(t) = K$).
- $R(t)$: Number of infected relays at time t .

Stability analysis

- $Q(t)$: Number of packets in the source buffer at time t (counts each copy of a message; a single un-served message gives $Q(t) = K$).
- $R(t)$: Number of infected relays at time t .
- $\{(Q(t), R(t)), t \geq 0\}$ is a discrete-time Markov process on $\mathbb{Z}_+ \times \{0, 1, \dots, N\}$.

Stability analysis

- $Q(t)$: Number of packets in the source buffer at time t (counts each copy of a message; a single un-served message gives $Q(t) = K$).
- $R(t)$: Number of infected relays at time t .
- $\{(Q(t), R(t)), t \geq 0\}$ is a discrete-time Markov process on $\mathbb{Z}_+ \times \{0, 1, \dots, N\}$.
- Stability threshold:

$$\lambda^* = \sup\{\lambda : \{(Q(t), R(t)), t \geq 0\} \text{ is recurrent}\}.$$

Stability analysis

- Transition rates of the process $\{(Q(t), R(t)), t \geq 0\}$ for $i, j > 0$:
 -

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

Stability analysis

- Transition rates of the process $\{(Q(t), R(t)), t \geq 0\}$ for $i, j > 0$:

-

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

-

$$(0, j) \longrightarrow \begin{cases} (K, j), & \text{at rate } \lambda \\ (0, j - 1), & \text{at rate } j\beta \end{cases}$$

Stability analysis

- Transition rates of the process $\{(Q(t), R(t)), t \geq 0\}$ for $i, j > 0$:

-

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

-

$$(0, j) \longrightarrow \begin{cases} (K, j), & \text{at rate } \lambda \\ (0, j - 1), & \text{at rate } j\beta \end{cases}$$

- $(0, 0) \rightarrow (K, 0)$ at rate λ

Stability analysis

- Transition rates of the process $\{(Q(t), R(t)), t \geq 0\}$ for $i, j > 0$:

-

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

-

$$(0, j) \longrightarrow \begin{cases} (K, j), & \text{at rate } \lambda \\ (0, j - 1), & \text{at rate } j\beta \end{cases}$$

- $(0, 0) \rightarrow (K, 0)$ at rate λ

Theorem

The stability threshold of the source queue is $\lambda^ = \frac{N\beta}{2K}$.*

- Proof via verifying conditions for recurrence in ¹

¹H. Keston, Recurrent criteria for multidimensional Markov chains and multi-dimensional linear birth and death processes, Adv. App. Prob., 1976

Stability analysis: Two general cases

- Source-destination meetings are permitted.
- Transition rates:

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (i - 1, j), & \text{at rate } \beta \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

Theorem

The stability threshold of the source queue is

$$\lambda^* = \frac{(N + 2)\beta}{2K}.$$

Stability analysis: Two general cases

- Source-destination meetings are permitted.
- When a source-destination meeting occurs, all copies of the present message are discarded from the source buffer.
- Transition rates:

$$(i, j) \longrightarrow \begin{cases} (i + K, j), & \text{at rate } \lambda \\ (qK, j), & \text{at rate } \beta \\ (i, j - 1), & \text{at rate } j\beta \\ (i - 1, j + 1), & \text{at rate } (N - j)\beta \end{cases}$$

where $i = qK + r$, $1 \leq r \leq K$, $q \in \mathbb{N}$.

Theorem

Let

$$\lambda_1 = \frac{(N + 2)\beta}{2K}, \text{ and } \lambda_2 = \frac{(N + 2K)\beta}{2K}.$$

Then, the queue is stable for any rate λ such that $\lambda < \lambda_1$, and the queue is unstable for any rate λ such that $\lambda > \lambda_2$.

- Stability threshold is linearly proportional to the number of relay nodes N , and inversely proportional to the redundancy parameter K .


Remarks

- Stability threshold is linearly proportional to the number of relay nodes N , and inversely proportional to the redundancy parameter K .
- For a fixed N , more number of relay nodes are infected with the same packet as we increase K , which reduces the stability threshold.

- Stability threshold is linearly proportional to the number of relay nodes N , and inversely proportional to the redundancy parameter K .
- For a fixed N , more number of relay nodes are infected with the same packet as we increase K , which reduces the stability threshold.
- For a fixed K , packets can be delivered quickly if we have more number of relay nodes which results in higher stability threshold.

Delay analysis

- Delay components: Delivery delay ($D_{d,i}$), end-to-end delay ($D_{e,i}$) and queueing delay ($D_{q,i}$).



Delay analysis: Single relay case

- $N = 1$. Source queue can be modelled by an $M/G/1$ queue with special service for the first customer.

Delay analysis: Single relay case

- $N = 1$. Source queue can be modelled by an $M/G/1$ queue with special service for the first customer.
- During a busy period, service time is

$$X = \sum_{k=1}^K (E_{k,1} + E_{k,2}).$$



Delay analysis: Single relay case

- $N = 1$. Source queue can be modelled by an $M/G/1$ queue with special service for the first customer.
- During a busy period, service time is

$$X = \sum_{k=1}^K (E_{k,1} + E_{k,2}).$$



- During an idle period, service time is

$$X^* = \begin{cases} E_{1,2} + \sum_{k=2}^K (E_{k,1} + E_{k,2}), w.p. \frac{\beta}{\beta + \lambda}, \\ \sum_{k=1}^K (E_{k,1} + E_{k,2}), w.p. \frac{\lambda}{\beta + \lambda}. \end{cases}$$

Delay analysis: Single relay case

Theorem

The average queueing delay \overline{d}_q is given by

$$\overline{d}_q = \frac{2\overline{X}^* + \lambda((\overline{X}^*)^2 - \overline{X}^2)}{2(1 - \lambda\overline{X} + \lambda\overline{X}^*)} + \frac{\overline{X}^2}{2(1 - \lambda\overline{X})}.$$

Delay analysis: Single relay case

Theorem

The average queueing delay \overline{d}_q is given by

$$\overline{d}_q = \frac{2\overline{X}^* + \lambda((\overline{X}^*)^2 - \overline{X}^2)}{2(1 - \lambda\overline{X} + \lambda\overline{X}^*)} + \frac{\overline{X}^2}{2(1 - \lambda\overline{X})}.$$

- Assuming the service time of first customer to an empty queue to be distributed as X ,

$$\overline{d}_q = \frac{\lambda\overline{X}^2}{2(1 - \lambda\overline{X})} + \overline{X}.$$

where $\overline{X} = \frac{2K}{\beta}$ and $\overline{X}^2 = \frac{2K}{\beta^2} + \frac{4K^2}{\beta^2}$.

Delay analysis: Single relay case

Theorem

The average queueing delay \overline{d}_q is given by

$$\overline{d}_q = \frac{2\overline{X}^* + \lambda((\overline{X}^*)^2 - \overline{X}^2)}{2(1 - \lambda\overline{X} + \lambda\overline{X}^*)} + \frac{\overline{X}^2}{2(1 - \lambda\overline{X})}.$$

- Assuming the service time of first customer to an empty queue to be distributed as X ,

$$\overline{d}_q = \frac{\lambda\overline{X}^2}{2(1 - \lambda\overline{X})} + \overline{X}.$$

where $\overline{X} = \frac{2K}{\beta}$ and $\overline{X}^2 = \frac{2K}{\beta^2} + \frac{4K^2}{\beta^2}$.

- $\overline{d}_q \rightarrow \infty$ as $\lambda \rightarrow \frac{\beta}{2K}$.

Delay analysis: Single relay case

Theorem

The average queueing delay \overline{d}_q is given by

$$\overline{d}_q = \frac{2\overline{X^*} + \lambda((\overline{X^*})^2 - \overline{X^2})}{2(1 - \lambda\overline{X} + \lambda\overline{X^*})} + \frac{\overline{X^2}}{2(1 - \lambda\overline{X})}.$$

- Assuming the service time of first customer to an empty queue to be distributed as X ,

$$\overline{d}_q = \frac{\lambda\overline{X^2}}{2(1 - \lambda\overline{X})} + \overline{X}.$$

where $\overline{X} = \frac{2K}{\beta}$ and $\overline{X^2} = \frac{2K}{\beta^2} + \frac{4K^2}{\beta^2}$.

- $\overline{d}_q \rightarrow \infty$ as $\lambda \rightarrow \frac{\beta}{2K}$.
- Average delivery delay is $\frac{1}{\beta}$.

Delay analysis: Single relay case

Theorem

The average queueing delay \overline{d}_q is given by

$$\overline{d}_q = \frac{2\overline{X^*} + \lambda((\overline{X^*})^2 - \overline{X^2})}{2(1 - \lambda\overline{X} + \lambda\overline{X^*})} + \frac{\overline{X^2}}{2(1 - \lambda\overline{X})}.$$


- Assuming the service time of first customer to an empty queue to be distributed as X ,

$$\overline{d}_q = \frac{\lambda\overline{X^2}}{2(1 - \lambda\overline{X})} + \overline{X}.$$

where $\overline{X} = \frac{2K}{\beta}$ and $\overline{X^2} = \frac{2K}{\beta^2} + \frac{4K^2}{\beta^2}$.

- $\overline{d}_q \rightarrow \infty$ as $\lambda \rightarrow \frac{\beta}{2K}$.
- Average delivery delay is $\frac{1}{\beta}$.
- $K = 1$ gives the minimum \overline{d}_q .


Simulation results: single relay case



- Stability threshold $\lambda^* = \frac{N\beta}{2K} = 0.25$

Simulation results: single relay case

- $K = 3$



- $\lambda_1^* = 0.0416, \lambda_2^* = 0.083$

Delay analysis: Multiple relays

- Multiserver $M^{[K]}/G/N$ queueing model. Each relay $r \in \{1, 2, \dots, N\}$ is a server.

Delay analysis: Multiple relays

- Multiserver $M^{[K]}/G/N$ queueing model. Each relay $r \in \{1, 2, \dots, N\}$ is a server.
- No closed-form expression for average queueing delay.²

²V. Gupta et al., On the inapproximability of M/G/K: why two moments of job size distribution are not enough, *Queueing Systems*, 2010

Delay analysis: Multiple relays

- Multiserver $M^{[K]}/G/N$ queueing model. Each relay $r \in \{1, 2, \dots, N\}$ is a server.
- No closed-form expression for average queueing delay. ²
- Approximate by $M^{[K]}/G/1$ system with service times scaled by $\frac{1}{N}$.

²V. Gupta et al., On the inapproximability of M/G/K: why two moments of job size distribution are not enough, *Queueing Systems*, 2010

Delay analysis: Multiple relays

- Multiserver $M^{[K]}/G/N$ queueing model. Each relay $r \in \{1, 2, \dots, N\}$ is a server.
- No closed-form expression for average queueing delay. ²
- Approximate by $M^{[K]}/G/1$ system with service times scaled by $\frac{1}{N}$.
- When arrival rate λ is close to $\frac{N\beta}{2K}$, a susceptible relay always finds a work load. The service time is

$$X = E_{1,1} + E_{1,2}.$$

²V. Gupta et al., On the inapproximability of M/G/K: why two moments of job size distribution are not enough, *Queueing Systems*, 2010

Delay analysis: Multiple relays

- Multiserver $M^{[K]}/G/N$ queueing model. Each relay $r \in \{1, 2, \dots, N\}$ is a server.
- No closed-form expression for average queueing delay. ²
- Approximate by $M^{[K]}/G/1$ system with service times scaled by $\frac{1}{N}$.
- When arrival rate λ is close to $\frac{N\beta}{2K}$, a susceptible relay always finds a work load. The service time is

$$X = E_{1,1} + E_{1,2}.$$

- Approximate average queueing delay:

$$\overline{d_q} = \frac{\lambda \overline{(X^*)^2}}{2(1 - K\lambda\overline{X})} + K\overline{X},$$

$$\text{where } \overline{X} = \frac{2}{N\beta}, \overline{(X^*)^2} = (\overline{X^2} - (\overline{X})^2)K + K^2(\overline{X})^2, \overline{X^2} = \frac{2}{N\beta^2} + \frac{4}{N^2\beta^2}.$$

²V. Gupta et al., On the inapproximability of M/G/K: why two moments of job size distribution are not enough, *Queueing Systems*, 2010

Delay analysis: Multiple relays

- Simplification yields

$$\overline{d_q} = \frac{\lambda \left[\frac{2K}{N\beta^2} + \frac{4K^2}{N^2\beta^2} \right]}{2(1 - \frac{2K\lambda}{N\beta})} + \frac{2K}{N\beta}.$$

Delay analysis: Multiple relays

- Simplification yields


$$\overline{d_q} = \frac{\lambda \left[\frac{2K}{N\beta^2} + \frac{4K^2}{N^2\beta^2} \right]}{2(1 - \frac{2K\lambda}{N\beta})} + \frac{2K}{N\beta}.$$

- Heuristic correction based on simulation results: $\frac{2K}{N^2\beta^2}$ instead of $\frac{2K}{N\beta^2}$.

$$\overline{d_q} = \frac{\lambda \left[\frac{2K}{N^2\beta^2} + \frac{4K^2}{N^2\beta^2} \right]}{2(1 - \frac{2K\lambda}{N\beta})} + \frac{2K}{N\beta}.$$

Simulation results


- $N = 20, K = 5$



- $\lambda_1^* = 0.3, \lambda_2^* = 0.5$

Simulation results


- $N = 20, \beta = 0.5$



- $\lambda_1^* = 0.5, \lambda_2^* = 1$

Delivery delay vs. number of copies


- $\lambda = 0.45, \beta = 1$



- An optimal value of K at with delivery delay is minimum.


End-to-end delay vs. number of copies

- $\lambda = 0.45, \beta = 1$



Tradeoff: Queueing delay and delivery delay

- $\lambda = 0.45$, and $\beta = 1$



- Queueing delay $\overline{d_q}$ increases monotonically with K . Tradeoff between $\overline{d_q}$ and $\overline{d_d}$ for $K \in \{1, 2, \dots, K^*\}$.

Future work

- Extension to multiple source-destination pairs.
- Relay nodes can carry more than one packet at a time.
- Behaviour for large number of relay nodes.

Thank you