Status	Finished
Started	Friday, 30 October 2026, 12:22 AM
Completed	Friday, 30 October 2026, 12:30 AM
Duration	8 mins 21 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

- a. readline() ✓
- b. line()
- c. readlines(1)
- d. read(1)

The correct answer is: readline()

Question **2**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

- a. infile = open(file = “a.txt”, “r”)
- b. infile = open(file = “a.txt”, “r”)
- c. infile = open(file, “a.txt”, “r”)
- d. infile = open(“a.txt”, “r”) ✓

The correct answer is:
infile = open(“a.txt”, “r”)

Question **3**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. read(size) ✓
- b. readline()
- c. readlines()
- d. readchar()

The correct answer is: read(size)

Question **4**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. w
b. a
c. r
d. r+ ✓

The correct answer is: r+

Question **5**

Correct

Mark 1.00 out of 1.00

file_object.seek(offset [, reference_point])

What is the default, the value of reference_point?

a. 0 ✓
b. garbage
c. 1
d. 2
e. null

The correct answer is:
0

Question **6**

Correct

Mark 1.00 out of 1.00

What does the flush() method do in file handling?

a. Deletes the file content
b. Flushes the internal buffer to the file ✓
c. Closes the file
d. Moves the file cursor to the beginning

The correct answer is: Flushes the internal buffer to the file

Question **7**

Incorrect

Mark 0.00 out of 1.00

Which method is used to sets the position of a file pointer

a. tell()
b. ftell()
c. seek()
d. fseek() ✗

The correct answer is: seek()

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. current()
b. locate()
c. position()
d. tell() ✓

The correct answer is: tell()

Question **9**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. An error is raised ✓
b. An empty file object is returned
c. The operation is ignored
d. A new file is created

The correct answer is: An error is raised

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for writing in binary format?

a. rb
b. r+
c. w
d. wb ✓

The correct answer is: wb

Question **11**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. shrink()
b. reduce()
c. resize()
d. truncate() ✓

The correct answer is: truncate()

Question **12**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. openfile()
b. file()
c. open_file()
d. open() ✓

The correct answer is: open()

Question **13**

Incorrect

Mark 0.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints each line of the file

b. Prints the first 10 characters of the file

c. Prints an error message ✗

d. Prints the entire content of the file

The correct answer is: Prints the entire content of the file

Question **14**

Correct

Mark 1.00 out of 1.00

Which method can be used to read all lines of a file into a list?

a. readlist()

b. read()

c. readlines() ✓

d. readline()

The correct answer is: readlines()

Question **15**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. Hello

b. Hello, world! ✓

c. An error is raised

d. world

The correct answer is: Hello, world!

Status	Finished
Started	Monday, 2 November 2026, 3:04 PM
Completed	Monday, 2 November 2026, 5:04 PM
Duration	2 hours
Grade	**3.00** out of 10.00 (**30**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Create a Python program to write to a specific line in a text file, replacing the existing content of that line.

Description:

1. **Input:**
   - A text file with multiple lines.
   - A line number to write to.
   - New content for the specified line.
2. **Output:**
   - The updated file with the specified line replaced by the new content in file "output.txt".

Example:

- **Input File Content:**

  "Line one.
  Line two.
  Line three.
  Line four."
  2

  Updated line two.

Output:

Line one.
Updated line two.
Line three.
Line four.

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	`input1.txt`
	`2`
	`Updated line two.`
		`Line one.`
		`Updated line two.`
		`Line three.`
		`Line four.`

Answer: (penalty regime: 0 %)

```
filename = input()
line_number = int(input())
new_content = input()

with open(filename, 'r') as file:
    lines = file.readlines()

lines[line_number - 1] = new_content + '\n'

with open('output.txt', 'w') as file:
    file.writelines(lines)
```

	Test	Input	Expected	Got	

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		`input1.txt`
		`2`
		`Updated line two.`
			`Line one.`
			`Updated line two.`
			`Line three.`
			`Line four.`
				`Line one.`
				`Updated line two.`
				`Line three.`
				`Line four.`
					✓

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		`input2.txt`
		`2`
		`Line B Updated.`
			`Line A.`
			`Line B Updated.`
			`Line C.`
				`Line A.`
				`Line B Updated.`
				`Line C.`
					✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Create a Python program to delete a specific line from a text file based on a given line number.

Description:

1. **Input:**
   - A text file with multiple lines.
   - A line number to delete.
2. **Output:**
   - The updated file with the specified line removed in file "output.txt".

Example:

- **Input File Content:**

  "Line one.
  Line two.
  Line three.
  Line four."
  2

  Updated line two.

Output:

Line one.
Line three.
Line four.

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	input1.txt
	2
		Line one.
		Line three.
		Line four.

Answer: (penalty regime: 0 %)

```
filename = input()
line_number = int(input())

with open(filename, 'r') as file:
    lines = file.readlines()

del lines[line_number - 1]

with open('output.txt', 'w') as file:
    file.writelines(lines)
```

	Test	Input	Expected	Got	

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		input1.txt
		2
			Line one.
			Line three.
			Line four.
				Line one.
				Line three.
				Line four.
					✓

	Test	Input	Expected	Got	

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		input2.txt
		3
			Line A.
			Line B.
				Line A.
				Line B.
					✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Write a Python program to reverse the contents of a specific line in a text file based on a given line number.

Description:

1. **Input:**
   - A text file with multiple lines.
   - A line number to reverse.
2. **Output:**
   - The updated file with the specified line's contents reversed in file "output.txt".

Example:

- **Input File Content:**

  "Line one.
  Line two.
  Line three.
  Line four."
  3

Output:

Line one.
Line two.
eerht eniL.
Line four.

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	`input1.txt`
	`3`
		`Line one.`
		`Line two.`
		`eerht eniL.`
		`Line four.`

Answer: (penalty regime: 0 %)

```
filename = input()
line_number = int(input())

with open(filename, 'r') as file:
    lines = file.readlines()

line = lines[line_number - 1].rstrip('\n')
lines[line_number - 1] = line[:-1][::-1] + line[-1] + '\n'

with open('output.txt', 'w') as file:
    file.writelines(lines)
```

	Test	Input	Expected	Got	

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		input1.txt
		3
			Line one.
			Line two.
			eerht eniL.
			Line four.
				Line one.
				Line two.
				eerht eniL.
				Line four.
					✓

✓	`with open('output.txt', 'r') as file:`
	`  text = file.read()`
	`  print(text)`
		input2.txt
		2
			Line A.
			B eniL.
			Line C.
				Line A.
				B eniL.
				Line C.
					✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Not answered

Mark 0.00 out of 1.00

Write a Python program to count the frequency of each word in a given text file.

Description:

1. **Input:**
   - String as input.
2. **Output:**
   - A list of words with their corresponding frequency count to be write in a file "output.txt"

Example:

- **Input File Content:**

  apple orange apple banana apple orange

Output:

apple: 3
orange: 2
banana: 1

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	`apple orange apple banana apple orange`	`apple: 3`
		`banana: 1`
		`orange: 2`

Answer: (penalty regime: 0 %)

```
1
```

Question **5**

Not answered

Mark 0.00 out of 1.00

Create a Python program to find the longest word in a text file.

- **Input:**
  - A text file containing multiple lines of text.
- **Output:**
  - The longest word in the file.

For example:

Input	Result
input1.txt	Longest word: containing

Answer: (penalty regime: 0 %)

```
1
```

Question **6**

Not answered

Mark 0.00 out of 1.00

Write a Python program to append a new line at a specific position in a text file, shifting existing lines down.

Description:

1. **Input:**
   - A text file with multiple lines.
   - A line number to insert the new line at.
   - New content for the new line.
2. **Output:**
   - The updated file with the new line inserted at the specified position, shifting the existing lines down in file "output.txt".

Example:

- **Input File Content:**

  "Line one.
  Line two.
  Line three.
  Line four."
  3

  Inserted line..

Output:

Line one.
Line two.
Inserted line.
Line three.
Line four.

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	`input1.txt`
	`3`
	`Inserted line.`
		`Line one.`
		`Line two.`
		`Inserted line.`
		`Line three.`
		`Line four.`

Answer: (penalty regime: 0 %)

```
1
```

Question **7**

Not answered

Mark 0.00 out of 1.00

Develop a Python program to identify and print all palindrome words from a given text file.

Description:

1. **Input:**
   - A text file containing multiple words.
2. **Output:**
   - A list of palindrome words found in the file name as 'output.txt'.

For example:

Test	Input	Result

`with open('output.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	input1.txt	madam
		arora
		malayalam

Answer: (penalty regime: 0 %)

```
1
```

Question **8**

Not answered

Mark 0.00 out of 1.00

Develop a Python program to read a specific line from a text file based on a given line number.

Description:

1. **Input:**
   - A text file with multiple lines.
   - A line number to read.
2. **Output:**
   - The content of the specified line.

input1.txt:

Line one.
Line two.
Line three.
Line four.

For example:

Input	Result
input1.txt 3	Line three.

Answer: (penalty regime: 0 %)

```
1
```

Question **9**

Not answered

Mark 0.00 out of 1.00

Develop a Python program to copy the contents of one file to another file.

Description:

1. **Input:**
   - Source file and destination file names.
2. **Output:**
   - The content of the source file copied to the destination file.

For example:

Test	Input	Result

`with open('output1.txt', 'r') as file:`
`  text = file.read()`
`  print(text)`
	`input1.txt`
	`output1.txt`
		`This is the source file.`
		`It contains multiple lines of text.`
		`Here is another line.`

Answer: (penalty regime: 0 %)

```
1
```

Question **10**

Not answered

Mark 0.00 out of 1.00

Develop a Python program to read a text file and count the total number of words in the file.

Description:

1. **Input:**
   - A text file containing several lines of text.
   - File name you should get as input.
2. **Output:**
   - The total number of words in the file.

For example:

Input	Result
input2.txt	Total words: 14
input3.txt	Total words: 15

Answer: (penalty regime: 0 %)

```
1
```