

Commonsense Reasoning Guiding Deep Learning for Transparent Decision Making in Robotics

Mohan Sridharan¹ and **Tiago Mota**²

¹University of Birmingham, UK m.sridharan@bham.ac.uk, <https://www.cs.bham.ac.uk/~sridharm/> ²The University of Auckland, NZ




Research Questions

- How best to enable robots to **represent** and **reason** with **qualitative** and **quantitative** descriptions of incomplete knowledge and uncertainty?
“Books are usually in the library”
“I am 90% certain robotics book is in the library”
- How best to enable robots to **learn interactively** and **cumulatively** from **sensor inputs** and limited human feedback?
Camera images, verbal cues, different surfaces
“Robot with weak arm cannot lift heavy box”
- How best to enable designers to **understand** the robots’ behavior and to establish that it **satisfies desirable properties**?
“Why did you go to the kitchen?”
“How likely is it that the engineer is in the office?”

Core Ideas and Inspiration

- Cognitive systems** inspired by **human cognition** and **motor control**.
- Theories of **intention**, **affordance**, **explanation**, **observation**.
- Qualitative** and **quantitative** reasoning at **different abstractions**; **tight coupling** between **logician**, **statistician**, and **creative explorer**.
- Interactive** and **cumulative** learning of **relevant** concepts.

Architecture Overview



Architecture combines strengths of **non-monotonic logical reasoning**, **probabilistic reasoning**, and **interactive learning**.

Illustrative Domain

Robot Assistant (RA) domain:

- Find and move objects to places or people.
- Humans have *role* (**engineer**, **manager**); objects have **attributes**.
- Estimate **occlusion of objects**, **stability of structures**.
- Answer explanatory questions in simulated and real-world scenarios.



Coarse Resolution Domain Representation

- System description** \mathcal{D}_C with **sorted signature** Σ_C and **axioms**.

- Σ_C has **sorts**, **statics**, and **fluents**. For RA domain:
 $next_to(place, place), loc(thing) = place, stable(object), in_hand(robot, object), obj_relation(relation, object, object)$
- Σ_C has **actions**. For RA domain:
 $move(robot, place), pickup(robot, object), putdown(robot, object), exo.move(object, place)$
- Axioms**: constraints, causal laws, executability conditions.
 $move(robot_1, Pl) \text{ causes } loc(robot_1) = Pl$
 $loc(O) = Pl \text{ if } loc(robot_1) = Pl, in_hand(robot_1, O)$
 $obj_relation(above, A, B), I \text{ if } obj_relation(below, B, A), I$
 $impossible \text{ pickup}(robot_1, Ob_1) \text{ if } obj_relation(below, Ob_1, Ob_2)$
- History \mathcal{H}_C with **prioritized defaults** in initial state.
initial default $loc(X) = library \text{ if } book(X)$
initial default $loc(X) = office \text{ if } book(X), loc(X) \neq library$

- Compute **answer sets** of CR-Prolog program $\Pi(\mathcal{D}_C, \mathcal{H}_C)$.
- Non-monotonic logical reasoning** essential for robotics+AI.


Theory of Affordances and Intentions

- Affordance**: attributes of object(s)+agent(s) with reference to actions.
- Unexpected success/failure; model **intentional actions**, observations.
- Principles of **persistence**, **non-procrastination**, and **relevance**.
- Expand \mathcal{D}_C and \mathcal{H}_C ; **mental fluents and actions**; axioms for action effects, start/stop activities; model **attempted actions**.

Fine Resolution Domain Representation


- Refinement**: describe (\mathcal{D}_C) at finer resolution (\mathcal{D}_F) .
- Theory of observation**: knowledge fluents + actions.
- Randomize** and **zoom** to $\mathcal{D}_{FR}(T)$ for $T = \langle \sigma_1, a^H, \sigma_2 \rangle$.
- Formal relationships** between descriptions. Separation of concerns.
- Probabilistic model** of uncertainty in sensing and actuation.
- Fine-resolution execution with $\mathcal{D}_{LR}(T)$ and probabilities, e.g., **POMDP policy**, probabilistic grasping. Add coarse-resolution outcomes to \mathcal{H} .

Interactive (Deep) Learning




- Incomplete knowledge; **unexpected** or **sub-optimal** outcomes.
- Labeled samples; limited human time and expertise; delayed outcomes.
- Incrementally learn** previously unknown **actions**, **axioms**.

- Generalize from human **verbal descriptions**: “Robot is labeling **big textbook**”, “Robot labeled **small fragile cup**”: $label(R, O) \text{ causes } labeled(O)$
- Relevance** and relational inference guide **active exploration** or **reactive execution** with knowledge or **reinforcement**.
- Reason with knowledge for estimation tasks. If not successful, **reasoning guides deep learning** with automatically identified ROIs.
- Represent learned model’s behavior in (**decision tree**); **cumulative learning** and construct new axioms.




$\neg stable(A) \text{ if } obj_relation(above, A, B), surface(B, irregular)$
 $impossible \text{ grasp}(rob_1, C) \text{ if } weight(C, heavy), arm(rob_1, electro)$

Theory of Explanations and VQA



- Characterize explanations: **abstraction**, **specificity**, **verbosity**.
- Methodology** for constructing explanations **interactively**.
- Visual Question Answering (VQA)**.



- Complementary strengths of **non-monotonic logical reasoning**, **deep learning**, and **inductive learning**.

Experimental Results


- Actions and axioms learned with **high precision and recall**.

	Precision	Recall
Strict	69.2%	78.3%
Relaxed	96%	95.1%


- Precision and recall of **retrieving relevant literals** for explanations with and without learned axioms.

	Precision		Recall	
Query Type	Without	With	Without	With
Plan description	78.54%	100%	67.52%	100%
Why X?	76.29%	95.25%	66.75%	95.25%
Why not X?	96.61%	96.55%	64.04%	100%
Belief	96.67%	99.02%	95.6%	100%

- Desired accuracy (stability, occlusion) with **lower training complexity**.



- Minimal and correct plans** with learned knowledge.



Conclusions + Future Work

- Step-wise refinement** simplifies design and implementation, **increases confidence** in behavior, **promotes scalability**.
- Precise relationship** between descriptions at different resolutions.
- Reasoning directs **interactive learning** of domain dynamics.
- Explanations at desired **level of abstraction**.
- Explore **interplay between reasoning and learning** in other domains.

Acknowledgements

Research threads pursued in collaboration with Ben Meadows, Tiago Mota, Heather Riley, Rocío Gomez, Michael Gelfond, Shiqi Zhang, and Jeremy Wyatt, with support from the U.S. ONR awards N00014-13-1-0766, N00014-17-1-2434 and N00014-20-1-2390, the AOARD award FA2386-16-1-4071, and the U.K. EPSRC award EP/S032487/1.

References

- Mohan Sridharan, Michael Gelfond, Shiqi Zhang and Jeremy Wyatt. **REBA: Refinement-based Architecture for Knowledge Representation and Reasoning in Robotics**. In *Journal of Artificial Intelligence Research*, 65:87-180, 2019.
- Tiago Mota, Mohan Sridharan and Ales Leonardis. **Integrated Commonsense Reasoning and Deep Learning for Transparent Decision Making in Robotics**. In *Springer Nature Computer Science Journal*, 2(4):1-18, 2021.
- Mohan Sridharan and Ben Meadows. **Knowledge Representation and Interactive Learning of Domain Knowledge for Human-Robot Interaction**. In *Advances in Cognitive Systems Journal*, 7:77-96, 2018.
- Heather Riley and Mohan Sridharan. **Integrating Non-monotonic Logical Reasoning and Inductive Learning With Deep Learning for Explainable Visual Question Answering**. In *Frontiers in Robotics and AI, special issue on Combining Symbolic Reasoning and Data-Driven Learning for Decision-Making*, Volume 6, 2019.
- Mohan Sridharan and Ben Meadows. **Theory of Explanation for Human-Robot Collaboration**. In the *Knstliche Intelligenz Journal*, 33(4):331-342, December 2019.