



Configure Terraform provider.tf

This Terraform now defaults to store state on S3. As such the `./provider.tf` must both be configured with the S3 bucket and S3 bucket region you choose to store state in. If you don't have an explicit bucket for storing state you may use the same 'utility bucket' that is used in the TFVAR 's3_bucket_name' at the top-level of this repo.

Note you can't put variables in the provider backend config, which is why this note is here.

Persistent Storage Deployment Example

```
module "cnq_storage" {
  source = "git::https://github.com/Qumulo/aws-terraform-cnq.git?ref=v6.2/persistent-storage"

  # ***** Required *****
  # ***** Terraform Variables *****
  # deployment_name                - Any <=32 character name for the
  deployment_name                 deployment. Set on first apply. Changes are ignored after that to
  #                               prevent unintended resource destruction.
  #                               - All infrastructure will be tagged
  #                               with the Deployment Name and a unique 11 digit alphanumeric suffix.
  deployment_name = "my-storage-deployment-name"

  # ***** AWS Variables *****
  # aws_region                    - AWS region to deploy the cluster
  aws_region                   persistent storage buckets in. For example us-west-2 or us-east-1.
  #                               The S3 buckets deployed must be in
  #                               the same region you plan to deploy the Qumulo cluster in.
  aws_region = "us-west-2"

  # ***** Qumulo Storage Variables *****
  # prevent_destroy              - Prevent accidentally destroying
  prevent_destroy              non-empty buckets with Terraform. If applied true, this must be set to
  #                               false, applied, and then a destroy may be performed.
  # soft_capacity_limit          - The capacity limit for all buckets
  soft_capacity_limit         combined. Specified in TB, 50TB to 50000TB (50PB). Default is 500TB.
  #                               You can always increase the soft limit in the future.
  prevent_destroy = false
  soft_capacity_limit = 500

  # ***** Misc *****
  # tags                        - Additional tags to add to all
  tags                       created resources. Often used for billing, departmental tracking,
  #                               chargeback, etc.
  #                               If you add an additional tag with
  #                               the key 'Name' it will be ignored. All infrastructure is tagged with the
```

```
'Name=deployment_unique_name'.
#                                     Example: tags = { "key1" =
"value1", "key2" = "value2" }
# s3_log_bucket_name                - The target bucket name for S3
logging. Default is null which disables logging. Setting other than null
enables logging to the target bucket.
# s3_log_bucket_prefix              - The target bucket prefix for S3
logging. Default is 'log/'
tags                                = null
s3_log_bucket_name                  = null
s3_log_bucket_prefix                = "log/"
}

output "outputs_cnq_storage" {
  value = module.cnq_storage
}
```

Terraform Documentation

 **Note:** This repository uses documentation generated with Terraform-Docs.

Requirements

Name	Version
terraform	>= 1.1.2
aws	~> 5.32
null	~> 3.1
random	~> 3.1

Inputs

Name	Description	Type	Default	Required
aws_region	AWS region	string	n/a	yes
deployment_name	Name for this Terraform deployment. This name plus 11 random alphanumeric characters will be used for all resource names where appropriate.	string	n/a	yes
prevent_destroy	Prevent the accidental destruction of non-empty buckets with Terraform.	bool	true	no
s3_log_bucket_name	The target bucket name for S3 logging	string	null	no

Name	Description	Type	Default	Required
s3_log_bucket_prefix	The target bucket prefix for S3 logging	string	"log/"	no
soft_capacity_limit	Soft capacity limit for all buckets combined: 50TB to 50000TB (50PB).	number	500	no
tags	OPTIONAL: Additional global tags	map(string)	null	no

Outputs

Name	Description
bucket_names	Names of the S3 buckets created
deployment_unique_name	The unique name for this Persistent Storage deployment. Referenced for the CNQ Cluster deployment.
prevent_destroy	Prevent the accidental destruction of non-empty buckets with Terraform.
soft_capacity_limit	Soft capacity limit for all buckets combined

About This Repository

This repository uses the [MIT license](#). All contents Copyright © 2024 [Qumulo, Inc.](#), except where specified. All trademarks are property of their respective owners.

For more information about this repository, contact [Dack Busch](#) and [Gokul Kupparaj](#).