

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		

11	For double coat plastering, second coat applied after proper curing of first coat		
12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		

11	For double coat plastering, second coat applied after proper curing of first coat		
12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		

11	For double coat plastering, second coat applied after proper curing of first coat		
12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		

11	For double coat plastering, second coat applied after proper curing of first coat		
12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature:

PAARISHIV HOMES

Plastering Checklist

Name of work:

Date:

Agreement number:

MB Pg No:

Name of Contractor:

MB Serial No:

Location:

Sl. No	Check Point	Status (OK/Not OK)	Remarks
1	Surface cleaned of dust, loose mortar, and debris before plastering		
2	All holes, joints, and chases filled and cured before plastering		
3	Brick/block joints properly raked to receive plaster		
4	Masonry cured at least 7 days before plastering		
5	Scaffolding is stable and does not touch the wall surface		
6	Plaster mix prepared in correct ratio as per drawing/spec		
7	Sand used is clean, well-graded, and silt-free		
8	Water used is clean/potable		
9	Plaster thickness as per specification (generally 12mm / 15mm / 20mm)		
10	Single coat thickness does not exceed 12 mm		
11	For double coat plastering, second coat applied after proper curing of first coat		

12	Mortar used within 30 minutes of mixing		
13	Plaster surface kept rough for receiving the second coat or finishing coat		
14	Levels, line, and plumb checked with straight edge & spirit level like Button Mark.		
15	Corners, edges, and junctions kept straight, neat, and true		
16	Curing of plaster started after 24 hours and continued for 7 days minimum		
17	No cracks, honeycombs, or hollow patches visible on plaster surface		
18	Electrical/Plumbing chase work completed before plastering		
19	Final surface smooth, even, and ready for painting/finishing		
20	Before the ceiling and column plastering the surface should be Hacked .		
21	The fiber mesh should be used among concrete, brick work and electrical point chasing areas.		

Checked By:

Name:

Signature:

Verified By:

Name:

Signature: