```java
class Threads extends Thread{

    String s; int time;

    Threads(String s, int time){

        this.s = s;

        this.time = time;

    }

    public void run(){

        try{

            while(true){

                System.out.println(s);

                Thread.sleep(time * 1000);

            }

        }

        catch(InterruptedException ie){

            System.out.println("Thread occurs: " + ie);

        }

    }

}

public class LP8{

    public static void main(String[] args) {

        Threads t1 = new Threads("BMS College of Engineering", 10);

        Threads t2 = new Threads("CSE", 2);


        t1.start();

        t2.start();

    }

}
```

```
C:\Users\Sarim Ali\OneDrive\Desktop\OOPs>java LP8
CSE
BMS College of Engineering
CSE
CSE
CSE
CSE
BMS College of Engineering
CSE
CSE
CSE
CSE
CSE
BMS College of Engineering
CSE
```

Write a prgm which creates two threads, one thread display
"BMS College of Engineering" once every 10 seconds & another
displaying "CSE" once every 2 seconds.

```
class Threads extends Thread {
    String s; int time;
    Threads (String s, int time) {
        this.s = s;
        this.time = time;
    }
    public void run() {
        try {
            while (true) {
                System.out.println(s);
                Thread.sleep(time * 1000);
            }
        }
        catch (InterruptedException ie) {
            System.out.println("Thread occurs: " + ie);
        }
    }
}
public class Lab {
    public static void main (String[] args) {
        Threads t1 = new Threads ("BMS College of Engineering", 10);
        Threads t2 = new Threads ("CSE", 2);
        t1.start();
        t2.start();
    }
}
```

Output:- BMS College of Engineering
          CSE
          CSE
          CSE
          CSE
          CSE
          BMS College of Engineering
          CSE
          CSE
          CSE
          CSE