EXAMINER DEFENSE HANDBOOK & 9-SLIDE PRESENTER GUIDE

Biological Treatment of Textile Dyeing Effluent: CSTR vs. PFR Digital Twin

9-Slide Presenter Script (with Welcome & Thank You Slides), Deep Chemical Reaction Kinetics, Multi-Physics Hydrodynamics & Examiner Q&A Guide

Comprehensive oral defense manual based on Fogler Chemical Reaction Engineering (CRE) methodology, Metcalf & Eddy wastewater engineering fundamentals, and the Bangladesh Department of Environment (DoE) ECR Schedule-10 standards.

PRESENTED BY GROUP MEMBERS (5):

1. **Sarim Sadman Rafio** — Slides 1–2 (Welcome, ETP Architecture & 3D Digital Twin)
2. **Kazi Farhan Hasan** — Slide 3 (Dual-Limitation Monod-Haldane Kinetics & Arrhenius Coupling)
3. **Md. Zinnuraine** — Slides 4–5 (Levenspiel Sizing & 1D Spatial PFR DO Sag ODEs)
4. **Azizia Binta Sayeed** — Slide 6 (Fogler RTD E(θ), Toxic Dye Shock & 25-Day Startup)
5. **Sabikun Nahar Anika** — Slides 7–9 (TEA/LCA Carbon Parity, Final Verdict & Closing Q&A)

Live Digital Twin & Slide Deck: https://textile-bioreactor-digital-twin.vercel.app

Design Parameters: $Q_0 = 1,000\ \mathrm{m^3/d}$, $S_0 = 750\ \mathrm{mg/L}$, $S_e \leq 75\ \mathrm{mg/L}$ (90% conversion), $\theta_c = 5.0\ \mathrm{d}$, $T = 32^{\circ}\mathrm{C}$

Key Findings: PFR saves 68% active liquid volume ($158.9\ \mathrm{m^3}$ vs. $490.5\ \mathrm{m^3}$, $3.09\times$), but suffers Pass-1 Entrance DO Sag ($0.56\ \mathrm{mg/L}$) and filamentous bulking without Tapered Aeration. Recommended design: 4-Stage Hybrid Cascade ($9.12/10$).

Group Members: 1. Sarim Sadman Rafio • 2. Kazi Farhan Hasan • 3. Md. Zinnuraine • 4. Azizia Binta Sayeed • 5. Sabikun Nahar Anika

Textile Bioreactor Digital Twin — Examiner Defense Handbook | Page 1

SLIDE 1 / 09

Welcome & Research Group Introduction (`S1`)

Presenter: *1. Sarim Sadman Rafio*

🎯 CORE IDEA OF SLIDE 1

CORE OBJECTIVE

Warmly welcome the honorable faculty examiners and audience, introduce all **5 group members**, and frame the central Chemical Reaction Engineering (CRE) research question of our interactive Digital Twin.

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Keep Slide 1 (`S1`) on screen in **`16:9 Fullscreen`** mode as the team steps up to the podium.
- Point out the **5 Group Members Showcase Card** on the right and the live-running **3D ETP Plant Preview** underneath it.
- Click **`Start Technical Deck ➔`** (or press the `→` arrow key) to transition to Slide 2.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~45 SECONDS)

WORD-FOR-WORD SCRIPT

*""Assalamu Alaikum and a very warm welcome to our respected faculty examiners and fellow classmates. Thank you for joining our Chemical Reaction Engineering design defense on the **Comparative Design of CSTR and PFR Bioreactors for Industrial Textile Dyeing Effluent**. Allow me to introduce our 5-member research and engineering team: I am **Sarim Sadman Rafio**, joined by **Kazi Farhan Hasan**, **Md. Zinnuraine**, **Azizia Binta Sayeed**, and **Sabikun Nahar Anika**. Rather than presenting static screenshots, we are presenting directly from our live 60-frames-per-second Multi-Physics Digital Twin—where every equation, 3D vessel, Levenspiel integral, and spatial ODE profile responds in real time. Let us begin with the industrial problem on Slide 2." ---"*

SLIDE 2 / 09

Industrial Problem & ETP Architecture (S2)

Presenter: *1. Sarim Sadman Rafio*

🎯 CORE IDEA OF SLIDE 2

CORE OBJECTIVE

Introduce the real-world industrial engineering problem in the **Gazipur–Narayanganj textile wet-processing corridor** of Bangladesh and show the complete 8-stage Effluent Treatment Plant (ETP) in the live 3D simulation.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **COD Fractionation Theory ($\mathrm{TCOD} = \mathrm{bCOD} + \mathrm{nbCOD}$):**

- Raw textile dyeing wastewater has a Total Chemical Oxygen Demand (TCOD) of $1,100$–$1,400\ \mathrm{mg/L}$, composed of recalcitrant non-biodegradable azo chromophores (nbCOD) and biodegradable organic substrates (bCOD: starch sizing, acetic acid, polyvinyl alcohol, and cleaved dye intermediates).
- **Why Physico-Chemical Pre-Treatment (`CHEM-001`) Precedes the Bioreactor:** Ferrous sulfate ($\mathrm{FeSO_4}$) and lime ($\mathrm{Ca(OH)_2}$) coagulation destabilizes colloidal dye micelles via **DLVO charge neutralization** and sweep flocculation, removing nbCOD and adjusting pH from 10.5 to 7.2–7.8 so downstream aerobic heterotrophs receive purely biodegradable substrate ($S_0 = 750\ \mathrm{mg\ bCOD/L}$).

1. **Decoupling Hydraulic Retention Time (τ) from Solids Retention Time (θ_c):**

- In a simple chemostat without recycle, biomass leaves at the liquid flow rate, forcing $\theta_c = \tau$. Because heterotrophic bacteria grow slowly, operating without recycle requires an impractically huge tank.
- By adding a **Secondary Clarifier (`CLR-201/202`)** and **Return Activated Sludge (`RAS` , recycle ratio $R = Q_r/Q_0 = 0.40$)**, we trap and recycle microorganisms. This decouples the **Biomass Residence Time ($\theta_c = 5.0\ \mathrm{days}$)** from the **Liquid Hydraulic Retention Time ($\tau = V/Q_0 \approx 3.8$–$11.8\ \mathrm{hours}$)**, concentrating active biomass to $X_b \approx 3,877\ \mathrm{mg\ VSS/L}$.

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Click `Load Baseline Textile ETP (32°C)` on the slide controls to ensure baseline conditions ($Q_0 = 1000\ \mathrm{m^3/d}$, $S_0 = 750\ \mathrm{mg/L}$, $S_e = 75\ \mathrm{mg/L}$, $\theta_c = 5.0\ \mathrm{d}$, $T = 32^\circ\mathrm{C}$).
- Slowly orbit the **3D Digital Twin** on the right side from left (`INF-001` Raw Intake) to right (`OUTFALL-001` Treated River Outfall) so the audience sees the transparent flanged glass pipes and internal flowing water transitioning from dark indigo dye to clear emerald water.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~60 SECONDS)

WORD-FOR-WORD SCRIPT

*""Assalamu Alaikum / Good morning to the respected examiners. Our project presents a full-scale Chemical Reaction Engineering Digital Twin for the biological treatment of textile dyeing effluent in Bangladesh. Export-oriented knit and woven dyeing mills discharge roughly $1,000\ \mathrm{m^3/day}$ of warm, alkaline wastewater loaded with $750\ \mathrm{mg/L}$ of biodegradable COD (S_0), reactive azo dyes, and hydrolyzed starch sizing. Under the Bangladesh Department of Environment (DoE) ECR Schedule-10 mandate, we must achieve a 90% reduction down to $S_e \leq 75\ \mathrm{mg/L}$ before river discharge. On the right, you see our live 3D multi-physics plant. Raw indigo-dyed wastewater enters at `INF-001` , undergoes $\mathrm{FeSO_4/Lime}$ coagulation (`CHEM-001`) to strip non-biodegradable chromophores, flow equalization (`EQ-001`), and fine rotary screening (`SCR-001`) before splitting into our two competing biological reactors: an **Ideal Back-Mixed CSTR (`CSTR-101`)** and a **4-Pass Baffled Serpentine Plug Flow Reactor (`PFR-102`)**, followed by secondary clarifiers (`CLR-201/202`), tertiary filtration (`FLT-301`), and compliant discharge (`OUTFALL-001`). By recycling settled biomass via the RAS loop ($R = 0.40$), we decouple liquid residence time (τ) from biological Solids Retention Time ($\theta_c = 5.0\ \mathrm{days}$)."*"

❓ ANTICIPATED EXAMINER QUESTIONS FOR SLIDE 2

EXAMINER VIVA DEFENSE

Q: Write the sludge mass balance that defines Solids Retention Time (θ_c).

A: $\theta_c = \frac{\text{Total Active Biomass in Reactor}}{\text{Biomass Wasted per Day}} = \frac{V \cdot X_b}{Q_w \cdot X_r + (Q_0 - Q_w) \cdot X_e}$. Assuming negligible solids in the clarified overflow ($X_e \approx 0$), $\theta_c = \frac{V \cdot X_b}{Q_w \cdot X_r}$.

Q: Why is an Equalization Tank (`EQ-001`) placed upstream of the bioreactors?

A: Textile dyeing is a batch process (scouring, bleaching, dyeing, rinsing). Without equalization, sudden pH, temperature, and concentration spikes would violate steady-state operation and shock the microbial consortium. ---

SLIDE 3 / 09

Dual-Limitation Monod-Haldane Kinetics & Arrhenius Coupling (S3)

Presenter: *2. Kazi Farhan Hasan*

🎯 CORE IDEA OF SLIDE 3

CORE OBJECTIVE

Explain the biochemical rate law governing microbial growth (μ) and substrate consumption ($-r_s$), including **dual substrate limitation** (organic carbon S + dissolved oxygen DO), **Arrhenius thermal scaling**, and **Haldane toxic substrate inhibition** at high dye loads.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Briggs-Haldane / Michaelis-Menten Enzyme Derivation of Monod Kinetics:**

- Monod kinetics is the whole-cell macroscopic analog of Michaelis-Menten enzyme kinetics ($E + S \rightleftharpoons ES \rightarrow E + P$).
- **Order of Reaction Transition:**
- **High Substrate ($S \gg K_S$):** All microbial permease/enzyme active sites are saturated. $\frac{S}{K_S+S} \approx 1 \implies \mu \approx \mu_{\max}$, so substrate degradation is **Apparent Zero-Order** ($-r_s = \frac{\mu_{\max}}{Y} X_b \propto S^0$).
- **Low Substrate ($S \ll K_S$):** Active sites are mostly empty. $\frac{S}{K_S+S} \approx \frac{S}{K_S} \implies -r_s = \left(\frac{\mu_{\max} X_b}{Y K_S}\right) S$, so degradation is **Apparent First-Order** ($-r_s \propto S^1$).
- **Our Exit Condition ($S_e = 75\ \mathrm{mg/L}, K_S = 60\ \mathrm{mg/L}$):** Since S_e and K_S are of the same magnitude ($\frac{75}{60+75} = 0.556$), our bioreactor operates in the **Mixed-Order Transition Regime**.

1. **Haldane Uncompetitive Substrate Inhibition (S^2/K_I):**

- At excessive azo-dye / aromatic loads ($S > 1,200\ \mathrm{mg/L}$), a second substrate molecule binds to the enzyme-substrate complex ($ES + S \rightleftharpoons ESS_{\text{inactive}}$), yielding the Haldane denominator $K_S + S + \frac{S^2}{K_I}$.
- **Critical Peak Substrate Concentration (S^*):** Taking $\frac{d\mu}{dS} = 0$ gives the exact substrate concentration where growth rate peaks before inhibition takes over:

$$S_{\text{peak}} = \sqrt{K_S \cdot K_I} = \sqrt{60 \times 1200} = 268.3\ \mathrm{mg/L}$$

1. **Modified Van 't Hoff-Arrhenius Temperature Dependency:**

- Over the mesophilic biological range ($15^\circ\mathrm{C}$–$38^\circ\mathrm{C}$), the exponential Arrhenius activation energy law $k(T) = Ae^{-E_a/RT}$ is linearized around $T_{\text{ref}} = 20^\circ\mathrm{C}$ as:

$$\mu_{\max}(T) = \mu_{\max}(20^\circ\mathrm{C}) \cdot \theta_\mu^{T-20} \quad (\theta_\mu = 1.072), \qquad k_d(T) = k_d(20^\circ\mathrm{C}) \cdot \theta_{kd}^{T-20} \quad (\theta_{kd} = 1.040)$$

1. **True Yield (Y) vs. Observed Yield (Y_{obs}) via Endogenous Respiration (k_d):**

- Not all synthesized biomass survives; cells oxidize their own cellular mass for maintenance energy at rate $k_d \cdot X_b$:

$$r_{g,\text{net}} = \mu X_b - k_d X_b = (-r_s) \cdot Y_{\text{obs}}, \qquad Y_{\text{obs}} = \frac{Y}{1 + k_d \cdot \theta_c}$$

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Point to the **solid celadon curve** (standard Dual-Monod) vs. the **dashed ochre curve** (Haldane dye-inhibited growth, peaking at $S_{\text{peak}} = 268\ \mathrm{mg/L}$) on the right-hand SVG chart.
- Click `Test Winter/Monsoon Cool (22°C)` or drag the **Temperature (T) slider** from $32^\circ\mathrm{C}$ down to $22^\circ\mathrm{C}$ and back up to $36^\circ\mathrm{C}$. Watch $\mu_{\max}(T)$ shift live.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~60 SECONDS)

WORD-FOR-WORD SCRIPT

Textile Bioreactor Digital Twin — Examiner Defense Handbook | Page 5

*""Moving to Slide 2, we formulate the biochemical reaction rate law. Unlike elementary chemical reactions, aerobic biodegradation follows a **Dual-Limitation Monod-Haldane model**:*

$$\mu(S, \mathrm{DO}, T) = \mu_{\max}(T) \cdot \left(\frac{S}{K_S + S + S^2/K_I} \right) \cdot \left(\frac{\mathrm{DO}}{K_{OH} + \mathrm{DO}} \right), \qquad -r_s = \frac{\mu}{Y} X_b$$

*Theoretically, this equation captures three fundamental regimes: when $S \gg K_S$, the reaction is apparent zero-order; when $S \approx K_S = 60\ \mathrm{mg/L}$, it shifts toward first-order; and when $S > S_{\mathrm{peak}} = \sqrt{K_S K_I} = 268\ \mathrm{mg/L}$, uncompetitive Haldane inhibition from toxic dye aromatics causes the dashed ochre rate curve to bend downward. Furthermore, because textile vats discharge warm water at $32^\circ\mathrm{C}$, Van 't Hoff-Arrhenius scaling ($\theta_T = 1.072$) boosts $\mu_{\max}$ from $3.20\ \mathrm{d}^{-1}$ at $20^\circ\mathrm{C}$ to $4.92\ \mathrm{d}^{-1}$ **at** $32^\circ\mathrm{C}$. Watch the graph on the right as I lower the temperature slider to $22^\circ\mathrm{C}$—the growth curve drops toward the red dashed washout line ($1/\theta_c + k_d$).""*

❓ ANTICIPATED EXAMINER QUESTIONS FOR SLIDE 3

EXAMINER VIVA DEFENSE

Q: Why do we include endogenous decay ($k_d = 0.088\ \mathrm{d}^{-1}$ at $32^\circ\mathrm{C}$) in the model?

A: Microorganisms require ATP for cell maintenance, motility, and osmotic regulation against Glauber's salt ($\mathrm{Na_2SO_4}$) in textile wastewater. Endogenous decay reduces the true yield $Y = 0.45\ \mathrm{mg\ VSS/mg\ bCOD}$ to an observed yield $Y_{\mathrm{obs}} = \frac{Y}{1 + k_d \theta_c} = 0.312\ \mathrm{mg\ VSS/mg\ bCOD}$ at $\theta_c = 5\ \mathrm{d}$, which reduces excess waste sludge production while increasing oxygen demand. ---

SLIDE 4 / 09

Levenspiel Reciprocal-Rate Sizing (S4)

Presenter: *3. Md. Zinnuraine*

🎯 CORE IDEA OF SLIDE 4

CORE OBJECTIVE

Use **Fogler Chapter 2 Mole Balance & Levenspiel Sizing** ($\frac{-1}{r_s}$ vs. Conversion X) to prove mathematically and visually why the **CSTR requires** $490.5\ \mathrm{m}^3$ ($\tau = 11.8\ \mathrm{h}$) while the **PFR requires only** $158.9\ \mathrm{m}^3$ ($\tau = 3.8\ \mathrm{h}$)—a $3.09\times$ **volumetric advantage** at 90% removal.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Fogler General Mole/Mass Balance Derivation:**

- Starting from $\mathrm{In} - \mathrm{Out} + \mathrm{Generation} = \mathrm{Accumulation}$ at steady state ($\frac{dN_S}{dt} = 0$) with fractional conversion $X = \frac{S_0 - S}{S_0}$ and mass feed rate $F_{S0} = Q_0 S_0$:
- **Ideal CSTR Algebraic Design Equation:**

$$F_{S0} - F_{S0}(1 - X_e) + r_s(S_e)V_{\mathrm{CSTR}} = 0 \implies \frac{V_{\mathrm{CSTR}}}{F_{S0}} = \frac{\tau_{\mathrm{CSTR}}}{S_0} = X_e \cdot \left(\frac{-1}{r_s(X_e)}\right)$$

Geometrically on a plot of $\left(\frac{-1}{r_s}\right)$ vs. X, V_{CSTR} is the **Rectangle** of width X_e and height $\left(\frac{-1}{r_s}\right)_{X_e}$.

- **Ideal PFR Differential Design Equation:**

$$F_{S0}\,dX = (-r_s)\,dV \implies \frac{V_{\mathrm{PFR}}}{F_{S0}} = \frac{\tau_{\mathrm{PFR}}}{S_0} = \int_0^{X_e} \left(\frac{-1}{r_s(X)}\right) dX$$

Geometrically, V_{PFR} is the **Area Under the Curve** from $X = 0$ to $X = X_e$.

1. **Closed-Form Analytical Integration of Monod PFR vs. CSTR Ratio:**

- Assuming constant X_b (enforced by high recycle ratio R) and substituting $-r_s = k_{\mathrm{eff}}\frac{S}{K_S + S}$ where $S = S_0(1 - X)$:

$$\tau_{\mathrm{CSTR}} = \frac{S_0 - S_e}{k_{\mathrm{eff}}}\left(1 + \frac{K_S}{S_e}\right), \qquad \tau_{\mathrm{PFR}} = \frac{1}{k_{\mathrm{eff}}}\left[(S_0 - S_e) + K_S \ln\left(\frac{S_0}{S_e}\right)\right]$$

- Dividing the two gives the exact dimensionless theoretical **Volume Ratio Equation**:

$$\frac{V_{\mathrm{CSTR}}}{V_{\mathrm{PFR}}} = \frac{(S_0 - S_e)\left(1 + \frac{K_S}{S_e}\right)}{(S_0 - S_e) + K_S \ln\left(\frac{S_0}{S_e}\right)}$$

- Notice the physical insight: the first term $(S_0 - S_e)$ is the **Zero-Order contribution**, and the second term involving K_S is the **First-Order Monod penalty**!

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Hover your cursor across the **Levenspiel Plot** on the right from $X = 0$ to $X = 0.90$ to highlight the difference between the **Terracotta CSTR Rectangle** and the **Pine/Celadon PFR Integral Area**.
- Click `Demo High Target Sₑ = 300 mg/L`, let the examiners see the ratio drop to $1.59\times$, and then drag S_e back to $75\ \mathrm{mg/L}$ ($3.09\times$).

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~75 SECONDS)

WORD-FOR-WORD SCRIPT

*""Slide 4 presents our core steady-state sizing result derived from Fogler's Chapter 2 Mole Balances using the **Levenspiel Plot** ($\frac{-1}{r_s}$ vs. conversion $X = \frac{S_0 - S}{S_0}$). From the CSTR design equation $V_{\text{CSTR}} = F_{S0} \cdot X_e \cdot (-1/r_s)_{\text{exit}}$, complete back-mixing forces the entire tank volume to operate at the lowest exit concentration $S_e = 75\ \text{mg/L}$ ($X = 0.90$). Because $S_e = 75\ \text{mg/L}$ is comparable to $K_S = 60\ \text{mg/L}$, the Monod factor $\frac{S}{K_S + S}$ drops to 0.556, pushing the reciprocal rate $\frac{-1}{r_s}$ to its peak at the top-right corner. Thus, the CSTR requires the **entire terracotta rectangle: $\mathbf{490.5}\ \text{m}^3$** ($\tau = 11.8\ \text{hours}$). In contrast, the PFR differential balance $V_{\text{PFR}} = F_{S0} \int_0^{X_e} (-1/r_s)\, dX$ integrates smoothly under the curve from $S_0 = 750\ \text{mg/L}$ to $75\ \text{mg/L}$, requiring only the **shaded integral area: $\mathbf{158.9}\ \text{m}^3$** ($\tau = 3.8\ \text{hours}$)—a $3.09\times$ **volume reduction**. To prove the reaction-order theory live, watch when I click `Demo High Target Sₑ = 300 mg/L`: when $S_e \gg K_S$, the term $K_S/S_e \to 0$, Monod kinetics stays in the **zero-order saturation regime**, the Levenspiel curve flattens horizontally, and the volume ratio drops to $1.59\times$!""*

❓ ANTICIPATED EXAMINER QUESTIONS FOR SLIDE 4

EXAMINER VIVA DEFENSE

Q: Define the First Damköhler Number (Da_I) for this bioreactor.

A: $\text{Da}_I = \frac{\text{Characteristic Reaction Rate}}{\text{Convective Mass Flow Rate}} = \frac{(\mu_{\max}/Y) X_b \cdot V}{Q_0 S_0} = \frac{\mu_{\max} X_b \tau}{Y S_0}$. To achieve 90% conversion ($X = 0.90$), a back-mixed CSTR requires a $3.09\times$ higher Damköhler number ($\tau_{\text{CSTR}} = 11.77\ \text{h}$) than a PFR ($\tau_{\text{PFR}} = 3.81\ \text{h}$). ---

SLIDE 5 / 09

1D Spatial PFR ODEs & The Entrance Dissolved Oxygen Sag Trap (S5)

Presenter: *3. Md. Zinnuraine*

🎯 CORE IDEA OF SLIDE 5

CORE OBJECTIVE

Reveal the critical **gas-liquid mass transfer trap of a standard PFR**: solving the coupled 1D spatial Runge-Kutta (RK4) ODEs along the channel ($z/L \in [0, 1]$) uncovers a dangerous **Entrance Dissolved Oxygen (DO) Sag** in Pass 1—and show how **Tapered Aeration** solves it.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Two-Film Gas-Liquid Mass Transfer Theory (Whitman, 1923) & Oxygen Balance:**

- Oxygen is sparingly soluble in water ($\mathrm{DO_{sat}} \approx 7.3\ \mathrm{mg/L}$ at $32^{\circ}\mathrm{C}$ via Henry's Law, adjusted by wastewater salinity/surfactant factor $\alpha \approx 0.85, \beta \approx 0.95$).
- The volumetric oxygen transfer rate (OTR) across fine-bubble air diffusers is controlled by liquid-film resistance:

$$\mathrm{OTR} = k_L a \cdot (\mathrm{DO_{sat}} - \mathrm{DO})$$

- Meanwhile, the biological **Oxygen Uptake Rate (OUR)** is the sum of growth-associated oxidation and endogenous respiration (where $1.42\ \mathrm{g\ O_2/g\ VSS}$ is the theoretical COD of bacterial cells $\mathrm{C_5H_7O_2N}$):

$$\mathrm{OUR}(z) = \left(\frac{1 - 1.42Y}{Y}\right) \mu(z) X_b(z) + 1.42 k_d X_b(z)$$

- Combining OTR and OUR along the PFR plug-flow coordinate $d\tau = \frac{dV}{Q_0}$ yields the spatial Dissolved Oxygen differential equation:

$$\frac{d(\mathrm{DO})}{d\tau} = \underbrace{k_L a(z)(\mathrm{DO_{sat}} - \mathrm{DO})}_{\text{Gas-Liquid Supply (OTR)}} - \underbrace{\mathrm{OUR}(S(z), \mathrm{DO}(z), X_b(z))}_{\text{Microbial Demand (OUR)}}$$

1. **Kinetic Selection Theory of Filamentous Sludge Bulking (Chudoba, 1973):**

- Why does Pass-1 hypoxia ($\mathrm{DO} = 0.56\ \mathrm{mg/L} < 1.0\ \mathrm{mg/L}$) ruin clarifier settling ($\mathrm{SVI} = 165\ \mathrm{mL/g}$)?
- Filamentous bacteria (*Sphaerotilus natans*, *Microthrix parvicella*) have a high surface-area-to-volume ratio and a lower oxygen half-saturation constant ($K_{OH,\mathrm{fil}} \approx 0.05\ \mathrm{mg/L}$) than healthy floc-forming *Zoogloea* bacteria ($K_{OH,\mathrm{floc}} \approx 0.20\ \mathrm{mg/L}$).
- Consequently, when Pass-1 DO drops to $0.56\ \mathrm{mg/L}$, filaments outgrow floc-formers, extending bridges between flocs that prevent compaction in the secondary clarifier!

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Drag the **Virtual Sonde Probe (z/L)** slider across the plot on the right from $z/L = 0.0$ to $z/L = 0.20$ to point out where the DO curve dips to $0.56\ \mathrm{mg/L}$.
- Click `Tapered k_La (Engineered Fix)` at the top of the right panel! Watch minimum DO rise above $1.15\ \mathrm{mg/L}$ and SVI drop into the healthy settling regime.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~70 SECONDS)

WORD-FOR-WORD SCRIPT

""Slide 5 examines coupled gas-liquid mass transfer and spatial reaction kinetics along the PFR by solving the 3-state ODE system $\frac{dS}{d\tau}, \frac{dX_b}{d\tau}, \frac{d(\mathrm{DO})}{d\tau}$ via 4th-order Runge-Kutta integration. By Two-Film Mass Transfer Theory, oxygen supply is $\mathrm{OTR} = k_L a(\mathrm{DO_{sat}} - \mathrm{DO})$, while microbial oxygen demand is $\mathrm{OUR} = \frac{1-1.42Y}{Y}\mu X_b + 1.42 k_d X_b$, where 1.42 is the stoichiometric oxygen equivalent of $\mathrm{C_5H_7O_2N}$ biomass. At the PFR entrance ($z/L = 0.05$–0.25

), high substrate $S_0 = 750\ \mathrm{mg/L}$ drives maximum OUR that exceeds uniform aeration ($k_La = 150\ \mathrm{d^{-1}}$), causing bulk DO to sag to $0.56\ \mathrm{mg/L}$. By Chudoba's Kinetic Selection Theory, low DO favors low-K_{OH} filamentous bacteria (Sphaerotilus natans) over floc-formers, causing filamentous sludge bulking ($\mathrm{SVI} = 165\ \mathrm{mL/g}$). When I click `Tapered k_La (Engineered Fix)`*, we grade diffuser density spatially ($1.65\times$ at the inlet, $0.45\times$ at the exit) so $\mathrm{OTR}(z)$ matches $\mathrm{OUR}(z)$—eliminating the DO sag at zero extra blower energy!""*

❓ ANTICIPATED EXAMINER QUESTIONS FOR SLIDE 5

EXAMINER VIVA DEFENSE

Q: Why is the stoichiometric coefficient $1.42\ \mathrm{mg\ O_2/mg\ VSS}$ used in the oxygen balance?

A: The empirical molecular formula of active heterotrophic biomass is $\mathrm{C_5H_7O_2N}$ ($\mathrm{MW} = 113\ \mathrm{g/mol}$). Complete oxidation to $\mathrm{CO_2}$, $\mathrm{H_2O}$, and $\mathrm{NH_3}$ follows $\mathrm{C_5H_7O_2N + 5O_2 \rightarrow 5CO_2 + 2H_2O + NH_3}$, requiring $\frac{5\times32}{113} = \frac{160}{113} = 1.416 \approx 1.42\ \mathrm{g\ O_2}$ per gram of VSS. ---

SLIDE 6 / 09

Non-Ideal Flow, RTD $E(\theta)$, Toxic Dye Shock & 25-Day Startup (S6)

Presenter: *4. Azizia Binta Sayeed*

🎯 CORE IDEA OF SLIDE 6

CORE OBJECTIVE

Bridge ideal textbook reactors to real industrial hydrodynamics using **Fogler Residence Time Distribution** $E(\theta)$, **Axial Dispersion (**Pe**)**, **Tanks-in-Series (**N**-CSTR cascade)**, **Intraparticle Bio-Floc Reaction-Diffusion (Thiele Modulus** ϕ**)**, **2-Hour Toxic Dye Shock Buffering**, and **25-Day Startup & Washout ODEs**.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Fogler Residence Time Distribution (**$E(\theta)$**) & Tanks-in-Series Theory (Ch. 16 & 17):**

- Because real baffled basins have turbulent eddies, corner dead zones, and axial back-mixing, fluid elements take different times t to exit. Normalized by $\theta = t/\tau$:
- **Ideal CSTR (**$N = 1$**):** $E(\theta) = e^{-\theta}$ (variance $\sigma_\theta^2 = 1$).
- N **Equal CSTRs-in-Series:**

$$E(\theta) = \frac{N(N\theta)^{N-1}}{(N-1)!}e^{-N\theta}, \qquad \sigma_\theta^2 = \frac{1}{N}$$

As $N \to \infty$, $\sigma_\theta^2 \to 0$ and $E(\theta) \to \delta(\theta - 1)$ (Ideal Plug Flow).

1. **Axial Dispersion Model & Bodenstein / Peclet Number (**Pe**):**

- Governed by the 1D advection-dispersion equation with dispersion coefficient D_a $[\mathrm{m}^2/\mathrm{s}]$:

$$\mathrm{Pe} = \frac{u \cdot L}{D_a} = \frac{\text{Advective Transport}}{\text{Axial Dispersion}}$$

- For small-to-moderate dispersion, the variance equivalence between Axial Dispersion and Tanks-in-Series is $\sigma_\theta^2 = \frac{2}{\mathrm{Pe}} \approx \frac{1}{N} \implies N \approx \frac{\mathrm{Pe}}{2}$.

1. **Intraparticle Bio-Floc Reaction-Diffusion & Thiele Modulus (**ϕ**, Fogler Ch. 12):**

- Shown in Card 4 of the `CREExperimentsPanel`: activated sludge bacteria live inside porous spherical bio-flocs of radius $R_f \approx 60\ \mu\mathrm{m}$ with effective oxygen diffusivity $D_{\text{eff}} \approx 1.2 \times 10^{-9}\ \mathrm{m}^2/\mathrm{s}$.
- The **Thiele Modulus (**ϕ**)** compares surface reaction rate to internal pore diffusion rate:

$$\phi = R_f\sqrt{\frac{k_v}{D_{\text{eff}}}}, \qquad \eta = \frac{3}{\phi^2}(\phi\coth\phi - 1)$$

where η is the **Internal Effectiveness Factor**. When bulk DO is low, DO drops to zero inside the core of the floc, creating an internal anoxic micro-zone!

1. **Biomass Washout Bifurcation (**$\theta_{c,\min}$**):**

- From the unsteady CSTR biomass ODE $\frac{dX_b}{dt} = \left(\mu(S) - \frac{1}{\theta_c} - k_d\right)X_b$, a non-trivial steady state ($X_b > 0$) exists if and only if $\theta_c > \theta_{c,\min}$, where:

$$\frac{1}{\theta_{c,\min}} = \mu(S_0, \mathrm{DO}) - k_d \implies \theta_{c,\min} \approx 0.42\ \text{days (at } 32^\circ\mathrm{C})$$

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- On the `Fogler RTD E(θ) & Dye Shock Cannon` view, drag **Tanks-in-Series (**N**)** and point out both the **Toxic Shock-Load Cannon** (Card 2) and the **Bio-Floc Reaction-Diffusion Micro-Profile** (Card 4).

Textile Bioreactor Digital Twin — Examiner Defense Handbook | Page 11

- Switch to `25-Day Startup & Washout ODEs`, drag **Sludge Age (θ_c)** down to 0.35 d to trigger washout live, then restore $\theta_c = 5.0$ d.

WORD-FOR-WORD SPEAKING SCRIPT (~75 SECONDS)

WORD-FOR-WORD SCRIPT

*""Slide 6 integrates four advanced Chemical Reaction Engineering concepts: non-ideal RTD $E(\theta)$, intraparticle bio-floc diffusion, dynamic shock buffering, and startup bifurcation. First, in Card 1 on the right, we compare Ideal CSTR exponential decay $E(\theta) = e^{-\theta}$ against the N-Tanks-in-Series distribution $E(\theta) = \frac{N(N\theta)^{N-1}}{(N-1)!}e^{-N\theta}$ and the Axial Dispersion model ($\mathrm{Pe} = uL/D_a$). At $N = 4$ stages, variance drops to $\sigma_\theta^2 = 1/N = 0.25$. Second, Card 2 demonstrates **Dynamic Shock Buffering**: during a 2-hour factory dye vat dump ($2,200$ mg/L), the CSTR's back-mixed residence time distribution dilutes the spike immediately below 75 mg/L, whereas the PFR propagates an unattenuated plug that triggers Haldane inhibition and severe effluent violation. Third, Card 4 solves the spherical reaction-diffusion equation inside a single 60 μm microbial bio-floc using the **Thiele Modulus (ϕ)** and internal effectiveness factor (η). Finally, switching to `25-Day Startup & Washout ODEs`, we see that biomass requires $3 \times \theta_c \approx 15$ days to reach steady state, and dropping θ_c below the transcritical bifurcation point $\theta_{c,\min} = 0.42$ days causes complete microbial washout.""*

ANTICIPATED EXAMINER QUESTIONS FOR SLIDE 6

EXAMINER VIVA DEFENSE

Q: What is the physical meaning of the Thiele Modulus (ϕ) and Effectiveness Factor (η) in your bio-floc plot?

A: The Thiele Modulus $\phi = R_f\sqrt{\text{Reaction Rate}/\text{Diffusion Rate}}$ measures whether substrate/oxygen conversion is limited by intrinsic microbial kinetics ($\phi \ll 1, \eta \approx 1$) or by internal pore diffusion through the extracellular polymeric substances (EPS) matrix of the floc ($\phi \gg 1, \eta \approx 3/\phi$). ---

Textile Bioreactor Digital Twin — Examiner Defense Handbook | Page 12

SLIDE 7 / 09

Techno-Economic Analysis (TEA) & Life Cycle Assessment (LCA) (S7)

Presenter: *5. Sabikun Nahar Anika*

🎯 CORE IDEA OF SLIDE 7

CORE OBJECTIVE

Prove via **Macroscopic Electron-Balance Thermodynamics** why a $3.09\times$ smaller PFR uses the **EXACT SAME aeration electricity** as a CSTR, and explain why the PFR's internal serpentine baffle walls make its civil concrete CAPEX slightly higher.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Thermodynamic Conservation of Electron Equivalents (Why Volume $\neq$ Energy):**

- By definition, $1\ \text{kg}$ of bCOD removed represents $1\ \text{kg}$ of O_2 electron-equivalent demand.
- Across any control volume removing daily substrate mass $\Delta M_S = Q_0(S_0 - S_e) = 675\ \text{kg bCOD/day}$ at fixed $\theta_c = 5.0\ \text{d}$, the removed electrons must either go into **New Net Biomass ($1.42 \cdot \Delta X_{\text{net}}$)** or be transferred to **Dissolved Oxygen (RO_2 $[\text{kg O}_2/\text{d}]$)**:

$$\text{RO}_2 = Q_0(S_0 - S_e) \cdot (1 - 1.42Y_{\text{obs}}) = Q_0(S_0 - S_e) \cdot \left(1 - \frac{1.42Y}{1 + k_d\theta_c}\right)$$

- Notice that **Reactor Volume (V) does NOT appear anywhere in this equation!** Because both CSTR and PFR have identical Q_0, S_0, S_e, Y, k_d, and θ_c, both consume the exact same stoichiometric oxygen ($878.9\ \text{kg O}_2/\text{day}$) and blower electricity ($488.3\ \text{kWh/day}$ at $\text{SAE} = 1.8\ \text{kg O}_2/\text{kWh}$).

1. **Civil Structural Mechanics of Baffled Rectangular Basins vs. Single Tanks:**

- A single square/cylindrical CSTR has only 4 outer perimeter walls (or 1 circular hoop-stress wall).
- A 4-pass serpentine PFR requires **3 internal full-length reinforced-concrete dividing baffle walls**. Each internal wall must be structurally reinforced with steel rebar on both faces to withstand full hydrostatic bending moment ($M = \frac{1}{6}\gamma_w H^3$) when an adjacent channel is dewatered for diffuser maintenance—increasing concrete volume ($195\ \text{m}^3$ vs. $168\ \text{m}^3$) and formwork cost.

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Point to the **Stacked Daily Electrical Demand Bar** on the right (76% Aeration Blowers, 14% Mechanical Mixing, 10% Pumping).
- Highlight the **Reinforced Concrete** and **Civil & Mech CAPEX** rows in the live comparison table.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~60 SECONDS)

WORD-FOR-WORD SCRIPT

*""Slide 7 answers a classic chemical engineering design paradox: if the PFR is $3.09\times$ smaller in volume than the CSTR, why isn't its electricity bill $3\times$ lower? By the **Macroscopic Electron-Equivalent Mass Balance**, total daily oxygen demand is $\text{RO}_2 = Q_0(S_0 - S_e)(1 - 1.42Y_{\text{obs}})$. Every gram of bCOD removed must either be assimilated into wasted biomass ($1.42Y_{\text{obs}}$) or oxidized by molecular O_2. Because reactor volume V does not appear in this thermodynamic conservation law, both reactors require the exact same stoichiometric oxygen transfer and blower power ($488.3\ \text{kWh/day}$, or 76% of total ETP power), resulting in identical specific energy ($0.642\ \text{kWh/m}^3$) and carbon emissions ($394.8\ \text{kg CO}_2\text{e/day}$). Furthermore, while the PFR holds less water, its 4-pass serpentine geometry requires **three internal reinforced-concrete baffle walls** designed for hydrostatic bending loads, raising concrete requirement to $195\ \text{m}^3$ ($\$141,200$ CAPEX) vs. $168\ \text{m}^3$ ($\$129,600$ CAPEX) for the unbaffled CSTR."*
---"

SLIDE 8 / 09

Final Engineering Recommendation & Multi-Criteria Verdict (S8)

Presenter: *5. Sabikun Nahar Anika*

🎯 CORE IDEA OF SLIDE 8

CORE OBJECTIVE

Synthesize all kinetic, hydrodynamic, mass-transfer, and economic principles into a **Weighted Multi-Criteria Engineering Decision Matrix** and recommend the **4-Stage Hybrid Cascade with Tapered Aeration**.

📚 UNDERLYING CRE & PROCESS ENGINEERING THEORY (KNOW BEFOREHAND)

CRE & MASS-TRANSFER THEORY

1. **Why $N = 4$ Staged CSTRs-in-Series Is the Theoretical Industrial Sweet Spot:**

- **Volumetric Efficiency:** From Fogler's N-CSTR cascade curve, going from $N = 1$ to $N = 4$ recovers 82% **of the theoretical volume savings** between a single CSTR and an infinite-stage ideal PFR ($N = \infty$). Adding more than 4 baffles yields diminishing volumetric returns while increasing hydraulic headloss and concrete wall cost.
- **Metabolic Selector Effect (Preventing Filamentous Bulking):** A 4-stage compartmentalized cascade creates a controlled substrate gradient ($S_1 > S_2 > S_3 > S_4$) that acts as a **kinetic selector** favoring floc-forming bacteria, while **Tapered Aeration** (k_La : $240 \rightarrow 170 \rightarrow 115 \rightarrow 75\ \mathrm{d}^{-1}$) prevents Pass-1 hypoxia.
- **Lead-Stage Dilution Buffer:** Sizing Stage 1 slightly larger (e.g., 40% of total volume) provides CSTR-like dilution against Haldane substrate inhibition during sudden dye dumps.

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Show the **Multi-Criteria CRE Engineering Scorecard** where the **4-Stage Hybrid (Tapered)** wins with $9.12/10$.
- Advance to **Slide 9 (S9)** for the team thank-you and live examiner Q&A.

🎙️ WORD-FOR-WORD SPEAKING SCRIPT (~55 SECONDS)

WORD-FOR-WORD SCRIPT

*""On Slide 8, we synthesize our reaction engineering analysis into a practical industrial design for Bangladesh's textile sector. A **Single Ideal CSTR** offers excellent shock dilution and uniform* DO *(*$2.15\ \mathrm{mg/L}$*), but suffers a* $3.09\times$ *Levenspiel volume penalty (*$490.5\ \mathrm{m^3}$*). Conversely, a **Uniform PFR** minimizes liquid volume (*$158.9\ \mathrm{m^3}$*), but suffers Pass-1 oxygen sag (*$\mathrm{DO} = 0.56\ \mathrm{mg/L}$*), filamentous bulking (*$\mathrm{SVI} = 165\ \mathrm{mL/g}$*), and zero dilution buffering against Haldane dye inhibition. Therefore, our quantitative decision matrix proves that the optimal reactor is a **4-Stage Compartmentalized Hybrid Cascade (*$N = 4$ ***CSTRs-in-series,*** $V_{\mathrm{total}} \approx 215\ \mathrm{m^3}$***) paired with Tapered Fine-Bubble Aeration (*k_La ***graded from*** 240 ***to*** $70\ \mathrm{d}^{-1}$***) and*** $R = 0.40$ ***RAS recycle—achieving a weighted score of*** $9.12/10$*."---"*

SLIDE 9 / 09

Thank You Everyone & Live Examiner Q&A Defense (S9)

Presenters: *All 5 Group Members (1. Sarim Sadman Rafio, 2. Kazi Farhan Hasan, 3. Md. Zinnuraine, 4. Azizia Binta Sayeed, 5. Sabikun Nahar Anika)*

🎯 CORE IDEA OF SLIDE 9

CORE OBJECTIVE

Express gratitude to the faculty examiners and audience, display the **5-Member Team Sign-Off Roster**, and keep the **Live Q&A Switcher** active so any technical question can be answered with live simulations directly from Slide 9.

🖱️ WHAT TO DO ON SCREEN (CHOREOGRAPHY)

ON-SCREEN LIVE ACTION

- Keep Slide 9 (`S9`) displayed while the examiners ask questions.
- Use either the **top-right visual switcher** (`Thank You & Team Roster` , `Live 3D Plant` , `Levenspiel Plot` , `Axial DO Profiles`) or the **bottom quick-jump buttons** (`S2` – `S8`) to demonstrate any parameter change requested by the examiners.

🎙️ WORD-FOR-WORD CLOSING SCRIPT (~30 SECONDS)

CORE OBJECTIVE

> *"To conclude on Slide 9, on behalf of our entire 5-member group—**Sarim Sadman Rafio**, **Kazi Farhan Hasan**, **Md. Zinnuraine**, **Azizia Binta Sayeed**, and **Sabikun Nahar Anika**—thank you everyone for your time and attention. We now welcome your questions and invite the examination panel to test any live operating scenario on our Digital Twin."*

EXAMINER VIVA REFERENCE

Essential quantitative metrics, dimensionless numbers, and thermodynamic relationships to cite during tough technical questions from examiners.

Theoretical Concept	Governing Formula	Physical Meaning & Value in Our Project
1st Damköhler Number (Da_I)	$\mathrm{Da}_I = \frac{(\mu_{\max}/Y)X_b\tau}{S_0}$	Ratio of surface/volumetric reaction rate to convective feed rate. Higher Da_I required in CSTR ($3.09\times$) than PFR for $X = 0.90$.
Peclet / Bodenstein Number (Pe)	$\mathrm{Pe} = \frac{uL}{D_a} \approx 2N$	Ratio of plug-flow advection to axial turbulent dispersion. $\mathrm{Pe} \to 0$ is CSTR; $\mathrm{Pe} \to \infty$ is ideal PFR; our 4-pass basin has $\mathrm{Pe} \approx 30$.
Thiele Modulus (ϕ) & Effectiveness (η)	$\phi = R_f\sqrt{\frac{k_v}{D_{\mathrm{eff}}}}, \quad \eta = \frac{3}{\phi^2}(\phi\coth\phi - 1)$	Ratio of intraparticle bio-floc reaction rate to pore diffusion across a $R_f = 60\ \mu\mathrm{m}$ microbial floc.
Haldane Inhibition Peak (S_{peak})	$S_{\mathrm{peak}} = \sqrt{K_S \cdot K_I}$	Substrate level where $\frac{d\mu}{dS} = 0$. For $K_S = 60$, $K_I = 1200\ \mathrm{mg/L}$, growth peaks at $268.3\ \mathrm{mg/L}$ and declines above it.
Critical Washout SRT ($\theta_{c,\min}$)	$\theta_{c,\min} = [\mu(S_0, \mathrm{DO}, T) - k_d(T)]^{-1}$	Transcritical bifurcation limit below which all bacteria wash out ($X_b = 0$). Equals 0.42 days at $32^\circ\mathrm{C}$.
Observed vs. True Yield (Y_{obs})	$Y_{\mathrm{obs}} = \frac{Y}{1 + k_d\theta_c}$	Accounts for endogenous cell respiration ($k_d = 0.088\ \mathrm{d}^{-1}$), reducing $Y = 0.45$ to $Y_{\mathrm{obs}} = 0.312\ \mathrm{mg\ VSS/mg\ bCOD}$.
Stoichiometric Oxygen Demand (RO_2)	$\mathrm{RO}_2 = Q_0(S_0 - S_e)(1 - 1.42Y_{\mathrm{obs}})$	Electron-equivalent conservation law proving why CSTR and PFR require identical blower energy ($488.3\ \mathrm{kWh/d}$).