

Operator-Aware Mixed-Precision Tolerance Calibration for Tensor Kernels

Dipankar Sarkar^[0000–0001–5431–6367]

Arizona State University, USA
dsarkar3@asu.edu

Abstract. Most tensor-kernel correctness tests go through a fixed-shape allclose-style check with hand-picked absolute and relative tolerances. The thresholds are copied across the corpus and rarely revisited. We mine the element-wise error distribution of every test case from accumulated cloud GPU runs across the 26-entry gpuemu corpus and 2 dtypes (8,076 result rows). We then ask one empirical question. What absolute tolerance would the kernel itself, observed under its correct implementation, justify? The answer is much tighter than the current hand-picked atol. The largest tightening is attention.triton fp16 at $2,184\times$. Restricted to the seven LLM-style buggy variants for which the corpus ships a paired correct counterpart, calibrated per-(op, dtype) tolerances raise bug-detection recall from 73.2% (1,805 of 2,467) to 82.4% (2,034 of 2,467), an absolute gain of 9.3 percentage points (+229 new detections). The control false-positive count rises from 0 to 20 out of 1,882 correct-control cases (+1.1 percentage points).

Keywords: mixed precision · tolerance calibration · ULP error · Triton · kernel testing

1 Introduction

Mixed-precision kernels (fp16, bfloat16, fp32) ship in every modern deep-learning system [1,5]. Their correctness is judged against a higher-precision reference with absolute and relative tolerances:

```
torch.allclose(out, ref, atol= $\varepsilon$ , rtol= $\delta$ ).
```

The tolerances ε and δ are operator and dtype specific in principle. In practice they are uniform across an entire benchmark. KernelBench [6] uses `atol=1e-5`, `rtol=1e-2`. GEAK [9] uses a per-op shortlist. These hand-picked values serve well most of the time. The cost of getting them wrong is asymmetric.

Too loose. Real bugs slip through. We quantify the gap below at 9.3 percentage points of recall on the gpuemu buggy corpus [7].

Too tight. Correct kernels at the edge of the tolerance band flap as flaky failures and get disabled in CI.

This paper makes the trade-off measurable and proposes a one-shot calibration that improves both axes at once. The contributions are three.

1. A measurement instrument. The validator of the companion artefact [7] records the full element-wise error distribution per test case: count, num-exceeding, abs error percentiles, rel error envelope, ULP envelope. The full schema is listed in Section 3.1. The data is rich enough to drive the calibration below.
2. A calibration protocol. For each (op, dtype) we compute the p95 of `max_abs` across passing cases of the correct kernel and multiply by a 1.5 safety factor. We then apply this calibrated atol to every variant in the op family, including the LLM-style buggy ones, and re-classify.
3. An empirical result on 8,076 result rows. Calibrated atol recovers an additional 229 buggy-kernel detections across the seven paired buggy variants. Recall goes from 73.2% to 82.4% (+9.3 percentage points). The cost is a net increase of 20 control false positives (from 0 to 20 out of 1,882 correct-control cases, +1.1 percentage points).

2 Related Work

Mixed-precision tolerances in practice. The PyTorch mixed-precision documentation [1] describes the dynamic grad-scaler workaround for fp16 and recommends fp32 master copies for accumulation, but offers no per-op tolerance guidance for correctness testing. The BF16 study of Kalamkar et al. [5] establishes BF16’s range advantage but does not address kernel-level tolerance setting. V-ABFT [4] and recent componentwise error analyses [3] develop analytical bounds for matmul accumulation but require operator-specific derivation.

Heuristic calibration. El Arar et al. [3] propose generating positive matrices of representative sizes, computing relative verification error across 100k trials, and setting thresholds to the observed maximum plus a 20% safety margin. Our protocol differs in three respects. The workload is the actual fuzz corpus, not synthetic positive matrices. We use p95 with $1.5\times$ safety, robust to single-case outliers. We evaluate the recall improvement on a seeded-buggy corpus rather than reporting only the calibrated threshold.

DL library testing. FreeFuzz [10], DocTer [11], DeepREL [2], and NablaFuzz [12] use cross-backend or metamorphic oracles to find logical bugs without per-op atol. They avoid the calibration problem but can only flag bugs that change the comparison-against-another-implementation result. Calibrated atol is complementary. It tightens the same-implementation reference oracle that is the only option when there is no other backend (e.g., a new Triton kernel).

3 Method

3.1 Captured distribution

The `gpuemu` validator populates an `ErrorStats` record on every validation. The record carries eleven fields: `count`, the number of element comparisons;

`num_exceeding`, the count exceeding the per-(op, dtype) tolerance; the abs-error envelope (`max_abs`, `mean_abs`) and percentiles (`p50_abs`, `p90_abs`, `p99_abs`); the rel-error pair (`max_rel`, `mean_rel`); and the ULP pair (`max_ulp`, `mean_ulp`).

ULP distance for fp16 and bf16 is computed in the native 16-bit ordered representation. For fp32 and fp64 it is computed in 32-bit and 64-bit respectively. NaN and Inf inputs saturate ULP to `u64::MAX`. All values ride the same JSON protocol that delivers the verdict, so the calibration data is a free side product of every run.

3.2 Calibration protocol

For each correct kernel in an op family (e.g., `softmax_triton` in the softmax family) and each dtype:

```
passing_abs = [ row.max_abs for row in results
                if row.kernel == K_correct and row.dtype == DT
                and row.passed ]
proposed_atol = percentile(passing_abs, 95) * 1.5
```

We then apply `proposed_atol` to every kernel in the family, both correct and buggy, and recount.

The $1.5\times$ safety multiplier is a single fixed hyperparameter. A formal sensitivity sweep across $1.25\times$ to $2.0\times$ is noted as a v2 follow-up in Section 6.

3.3 Calibration source mapping

The mapping from a buggy variant to its correct counterpart is currently hard-coded by naming convention in the calibration script (for example, the `softmax_llm_buggy` variant maps to `softmax_triton`). A future revision should read a `calibrate-against` field from each kernel’s metadata file.

3.4 Assumptions

The calibration depends on four assumptions.

1. The corpus contains at least one correct kernel per op family. The calibration percentile is meaningful only over correct samples. The 26-entry gpuemu corpus satisfies this by construction.
2. The fp64 reference is the ground truth for each (op, dtype) pair. The error distribution we calibrate against is therefore the kernel’s intrinsic error against fp64.
3. The 1,882 correct-control cases are representative of the operator’s typical workload. The corpus spans boundary and regular shapes plus three value distributions (uniform, NaN-injected, adversarial), which we judge representative for the LLM-Triton class.
4. The $1.5\times$ safety multiplier is set a priori. A formal sensitivity sweep is a v2 follow-up.

4 Evaluation

Data. 8,076 result rows accumulated from cloud GPU runs of the 26-entry gpuemu corpus at 2 dtypes (16 controls plus 10 LLM-style buggy variants; see the companion paper [7] for the canonical corpus table). Each correct-kernel (op, dtype) cell produces a calibration sample. The headline below is restricted to the seven buggy variants that ship a paired correct counterpart. The full tightening table spans 14 (op, dtype) cells with a finite calibrated tolerance (Table 2). Runs captured on RTX 3060 between 2026-05-27 and 2026-06-11; all error-stats payloads persist to a Backblaze B2 bucket.

Headline. Applying $p_{95} \times 1.5$ from each correct kernel as the calibrated atol changes the verdict on the corpus as shown in Table 1.

Table 1. Calibrated atol vs current per-op atol, seven paired-buggy subset.

metric	current	calibrated
Buggy flagged	1,805 / 2,467 (73.2%)	2,034 / 2,467 (82.4%)
FP on controls	0 / 1,882 (0.0%)	20 / 1,882 (1.1%)
Largest tightening	5.0e−2	2.29e−5 (2,184×)

That is 9.3 percentage points of recall on the seven paired-buggy subset, at the cost of 20 net new control false positives. The 20 new failures cluster on (op, dtype) cells where the kernel’s typical max-abs error is small enough that the calibrated p95 tightens below a few hand-picked outliers (layernorm fp32 and fp16, sigmoid_triton fp16, softmax fp16, rmsnorm_triton fp16, and a couple of matmul cells). Table 2 reports the per-(op, dtype) tightening factor on representative entries.

Table 2. Tightening factor per (op, dtype), selected entries from 14 total.

op	dtype	current atol	calibrated	tightening
attention_triton	fp16	5.0e−2	2.29e−5	2,184×
tanh_triton	fp16	5.0e−2	4.58e−5	1,092×
softmax_triton	fp16	2.0e−2	2.29e−5	874×
elu_triton	fp32	1.0e−4	1.79e−7	559×
gelu_triton	fp32	1.0e−4	7.15e−7	140×
matmul	fp32	5.0e−2	9.16e−4	55×
layernorm	fp32	1.0e−4	1.36e−5	7×

Medians are between 100× and 200×, which suggests hand-picked tolerances are routinely chosen with a wide safety margin that swallows real bugs.




Fig. 1. Tightening factor (current / calibrated atol), log scale. Bars right of 1.0 mark current tolerances looser than calibration.

Per-buggy-kernel recall improvement under calibrated atol (selected entries) is in Table 3.

Table 3. Per-buggy-kernel recall, current vs calibrated atol, selected entries.

buggy kernel	dtype	current	calibrated
softmax_llm_buggy	fp16	30% (90/301)	45% (135/301)
softmax_llm_buggy	fp32	29% (80/280)	62% (173/280)
softmax_triton_buggy	fp16	28% (62/219)	66% (145/219)
softmax_triton_buggy	fp32	61% (108/176)	61% (108/176)
silu_triton_buggy	fp16	95% (168/177)	99% (176/177)
gelu_triton_buggy	fp16	96% (181/188)	96% (181/188)
rmsnorm_triton_buggy	fp32	100% (141/141)	100% (141/141)

The largest recall gains are on the shape-dependent tail-mask bugs (softmax-*). These are exactly the cases where the hand-picked atol was wide enough to mask the bug at most shapes.

5 Discussion

Calibration interacts with input generation [8]. When boundary fuzzing already catches every case of a uniformly wrong bug (gelu_triton_buggy, for example),

tightening atol changes nothing. The calibration’s value is concentrated on shape-dependent bugs and on dtypes where the hand-picked atol was guessed pessimistically.

The $1.5\times$ safety multiplier could be replaced with an analytical bound from the operator’s known error structure. Examples are $O(K \cdot \varepsilon_{\text{dtype}})$ for matmul accumulation and $O(N \cdot \varepsilon_{\text{dtype}})$ for reductions. That upgrade would replace empirical calibration with an operator-aware error model. The measurement infrastructure (the validator’s `ErrorStats` record) supports it directly. We leave the model fit to future work.

6 Limitations

The calibration is per-(op, dtype) atol only. A magnitude-scaled (`atol + rtol · |r|`) variant would track output magnitude and would likely tighten further on operators whose output range varies across shapes (matmul, l2norm).

The $1.5\times$ safety factor was fixed a priori. A formal sensitivity sweep across $1.25\times$ to $2.0\times$ and a leave-one-run-out validation against held-out runs are noted follow-ups for a v2 of this paper.

All data is from a single GPU model (RTX 3060). Distribution shift across GPU generations, especially across SM_80 vs SM_90, is unstudied here. The companion paper [7] reports identical verdicts across five GPU classes on the correctness oracle, which suggests the calibration would carry across, but we have not measured the per-GPU error distribution directly.

7 Conclusion

A one-shot p95-from-controls calibration turns hand-picked per-op atol from a coarse rule of thumb into a measured envelope. The calibration uses the error distribution the validator already records on every run. On the seven paired-buggy subset of the gpuemu corpus, it recovers 9.3 percentage points of bug-detection recall ($1,805 \rightarrow 2,034$ of 2,467), at the cost of 20 net new control false positives ($0 \rightarrow 20$ of 1,882, +1.1 pp). The calibration itself runs in seconds against accumulated run records. The headline tightening factors (median roughly $200\times$, up to $2,184\times$ on attention_triton fp16) suggest hand-picked tolerances across the LLM-kernel ecosystem are routinely far looser than the operator’s intrinsic error envelope.

Artefact. The corpus, the calibration script (`analysis/p2.calibrate.py`), and the replay tool that fetches each cited run record are bundled in the public `gpuemu-corpus` package at <https://github.com/sarkar-dipankar/gpuemu-corpus>. The validator daemon that records the `ErrorStats` distribution is at <https://github.com/Skelf-Research/gpuemu>.

License. This preprint is released under CC-BY 4.0.

References

1. Ahmed, S., et al.: What every user should know about mixed precision training in PyTorch. PyTorch blog (2022), <https://pytorch.org/blog/what-every-user-should-know-about-mixed-precision-training-in-pytorch/>, updated November 2024
2. Deng, Y., Yang, C., Wei, A., Zhang, L.: Fuzzing deep-learning libraries via automated relational API inference. In: Proc. 30th ACM Joint Eur. Softw. Eng. Conf. and Symp. Found. Softw. Eng. (ESEC/FSE). pp. 44–56 (2022). <https://doi.org/10.1145/3540250.3549085>
3. El Arar, E.-M., Filip, S.-I., Mary, T., Riccietti, E.: Mixed precision accumulation for neural network inference guided by componentwise forward error analysis. arXiv preprint (2025), <https://arxiv.org/abs/2503.15568>
4. Gao, Y., Hua, Q., Chen, Z.: V-ABFT: Variance-based adaptive threshold for fault-tolerant matrix multiplication in mixed-precision deep learning. arXiv preprint (2026), <https://arxiv.org/abs/2602.08043>
5. Kalamkar, D., Mudigere, D., Mellempudi, N., Das, D., Banerjee, K., Avancha, S., Vooturi, D.T., Jammalamadaka, N., Huang, J., Yuen, H., Yang, J., Park, J., Heinecke, A., Georganas, E., Srinivasan, S., Kundu, A., Smelyanskiy, M., Kaul, B., Dubey, P.: A study of BFLOAT16 for deep learning training. arXiv preprint (2019), <https://arxiv.org/abs/1905.12322>
6. Ouyang, A., Guo, S., Arora, S., Zhang, A.L., Hu, W., Ré, C., Mirhoseini, A.: KernelBench: Can LLMs write efficient GPU kernels? arXiv preprint (2025), <https://arxiv.org/abs/2502.10517>
7. Sarkar, D.: The correctness illusion in LLM-generated GPU kernels. arXiv preprint (2026), <https://arxiv.org/abs/2606.20128>
8. Sarkar, D.: Test-input generation for tensor programs: What actually finds kernel bugs (2026), manuscript in preparation. Reproducibility artefacts at <https://github.com/sarkar-dipankar/gpuemu-corpus>.
9. Wang, J., Joshi, V., Majumder, S., Xu Chao, Ding, B., Liu, Ziqiong, Brahma, P.P., Li, D., Liu, Zicheng, Barsoum, E.: GEAK: Introducing Triton kernel AI agent & evaluation benchmarks. arXiv preprint (2025), <https://arxiv.org/abs/2507.23194>
10. Wei, A., Deng, Y., Yang, C., Zhang, L.: Free lunch for testing: Fuzzing deep-learning libraries from open source. In: Proc. 44th Int. Conf. Software Engineering (ICSE). pp. 995–1007 (2022). <https://doi.org/10.1145/3510003.3510041>, <https://arxiv.org/abs/2201.06589>
11. Xie, D., Li, Y., Kim, M., Pham, H.V., Tan, L., Zhang, X., Godfrey, M.W.: DocTer: Documentation-guided fuzzing for testing deep learning API functions. In: Proc. 31st ACM SIGSOFT Int. Symp. Software Testing and Analysis (ISSTA). pp. 176–188 (2022). <https://doi.org/10.1145/3533767.3534220>, <https://arxiv.org/abs/2109.01002>
12. Yang, C., Deng, Y., Yao, J., Tu, Y., Li, H., Zhang, L.: Fuzzing automatic differentiation in deep-learning libraries. In: Proc. 45th Int. Conf. Software Engineering (ICSE). pp. 1174–1186 (2023). <https://doi.org/10.1109/ICSE48619.2023.00105>, <https://arxiv.org/abs/2302.04351>