

Test-Input Generation for Tensor Programs: What Actually Finds Kernel Bugs

Dipankar Sarkar^[0000-0001-5431-6367]

Arizona State University, USA
dsarkar3@asu.edu

Abstract. Test-input generation for tensor kernels is folkloric. Most projects pick a representative shape and dtype, run a fixed-shape allclose-style check, and ship. We make the choices explicit and measure them. Using the gpuemu op-schema-aware seeded fuzzer [7], we evaluate seven test-generation strategies across a 26-op corpus (16 correct controls and 10 LLM-style buggy variants seeded with documented transcription patterns) on an RTX 3060 GPU instance. Strategies vary the shape candidate set, the dtype mix, and the input value distribution. We report each strategy on two axes: bug recall and control false-positive (FP) rate. Boundary-only shape sampling is the operationally safe winner: 78% recall on the 10 buggy kernels with 0% FP on the 16 controls. Adversarial value sampling reaches higher recall (99%) but inflates control FP to 94% because the strategy injects NaN and Inf inputs and the validator’s NaN check fires on every kernel that propagates them, not only on buggy kernels. On the two softmax tail-mask bugs the “regular” strategy (no boundary shapes) catches 0%, while boundary raises recall to 100% and 62% respectively. That gap is the clearest single signal in the data. The corpus result is about which seeded bug patterns each strategy catches, not about the bug rate of any specific deployed LLM.

Keywords: kernel testing · fuzzing · boundary value analysis · Triton · LLM-generated code

1 Introduction

Generated GPU kernels from recent benchmarks [4,10,6,2] are tested by an oracle that takes inputs from somewhere. Where is rarely documented and almost never compared. The “regular shape” default (one shape per operator, one dtype, uniform random values) is the convenient choice, but it has two empirically measured failure modes.

Shape-dependent bugs. Tail-mask leak in reductions and accumulator overwrite in matmul only surface at specific boundary shapes (e.g., $H = 3$, $K = 1$). A test at $H = 256$, $K = 16$ cannot see them.

Magnitude-sensitive bugs. Overflow with extreme values, and special-case handling for zero, Inf, and NaN, only surface under input distributions that include those values.

This paper measures both gaps and quantifies what each strategy buys. The contributions are four.

1. A strategy taxonomy for tensor-kernel test-input generation, exposed as switchable knobs on the gpuemu fuzzer [7]. The knobs are the shape candidate set (boundary, regular, or default mix), the dtype set, and the value distribution (Uniform, NaNInjected, or Adversarial).
2. A controlled ablation across 26 ops, 7 strategies, and 8 iterations per (strategy, kernel), 1,456 cases on a single RTX 3060.
3. A ranked table that reports each strategy on both recall (on the 10 buggy kernels) and control FP rate (on the 16 correct kernels). Adversarial reaches 99% recall but 94% FP. Boundary reaches 78% recall at 0% FP. The “regular” strategy loses an entire bug class (0% recall on tail-mask bugs).
4. A measured explanation of the recall-FP trade-off for the adversarial and NaN-injected strategies. Both inject non-finite inputs, both inflate FP, and the inflation traces to the validator’s NaN check rather than to genuine output divergence.

2 Related Work

Boundary-value testing. A classical software-testing principle dating to Myers [3]. The highest defect density sits at the boundaries of input partitions. Modern coverage-guided fuzzers (AFL, libFuzzer) implement variants of this. For tensor kernels the analogue is *shape boundaries* (1, prime, power of two ± 1) and *value boundaries* (0, subnormal, near fp-max, $\pm \text{Inf}$, NaN).

DL library fuzzing. FreeFuzz [11], DocTer [12], DeepREL [1], and NablaFuzz [13] all fuzz the API layer of TensorFlow, PyTorch, and JAX. Their generation strategies are mostly value mutational and they evaluate at the API level, not the kernel level. Coverage-guided variants [5] focus on syntactic coverage of the API surface, not the operator’s input domain. None of them publish a per-strategy ablation of the kind below.

Kernel-level metamorphic testing. A few works derive metamorphic relations for specific operators (e.g., softmax shift-invariance), but the practice has not propagated to the LLM-kernel ecosystem.

LLM-kernel benchmarks. The benchmarks [4,10,6,2,9] are usually one-shape, one-dtype. KernelBench’s [4] correctness oracle is `torch.allclose` on the reference shape. Without varied inputs an entire class of bugs is invisible. This is the gap we measure.

3 Method

3.1 Strategy parameters

A strategy is a triple (`op_schema`, `dtypes`, `value_distribution`) applied uniformly to every (`op`, `iter`) under the strategy.

op_schema a per-input shape generator. Each op ships a native schema (mixed boundary and regular candidates). A strategy can override the candidate set for any dim. For example **boundary** restricts H to $\{1, 3, 7\}$ and **regular** restricts H to $\{128, 256, 512\}$.

dtypes a list of dtypes to round-robin across iters.

value_distribution how the fuzzer fills tensor values. **Uniform** samples $U[-10, 10]$ (default). **NaNInjected** replaces 5% of float elements with NaN, $\pm\text{Inf}$, or 0. **Adversarial** samples equal-weight across five dtype-aware buckets: 0; very small (near the dtype’s tiny value, subnormal for fp32 and fp16); large (max divided by 10); wide-uniform $U[-10^3, 10^3]$; and non-finite ($\pm\text{Inf}$, NaN).

3.2 The seven strategies evaluated

Table 1 lists the seven strategies. All seven share the same operator corpus and the same per-op tolerances. Only the test-input generator changes.

Table 1. The seven strategies evaluated in the ablation.

strategy	op_schema	dtypes	value_distribution
default	native	native	Uniform
boundary	$H \in \{1, 3, 7\}$	native	Uniform
regular	$H \in \{128, 256, 512\}$	native	Uniform
single.dtype_f32	native	{float32}	Uniform
single.dtype_f16	native	{float16}	Uniform
nan_injected	native	native	NaNInjected
adversarial	native	native	Adversarial

3.3 Bookkeeping

The driver (`drivers/p3_strategies.py`) records per (strategy, op, iter) the verdict, dtype, shape, layout, `failure_kind`, and `error_stats`. It also records time-to-first-failure (in seconds) per (strategy, op) as a wall-clock efficiency metric.

3.4 Assumptions

The ablation depends on four assumptions.

1. The 16 controls are correct kernels (human-written Triton or numpy stand-ins). The companion paper [7] establishes their correctness on the gpuemu oracle.
2. The 10 buggy variants are author-seeded with documented LLM transcription patterns. They are not pulled from real LLM-generated outputs.

3. Tolerances are fixed per (op, dtype) across all seven strategies. The companion paper [8] addresses the tolerance question separately. Mixing the calibration step in here would conflate two effects.
4. The Python client decodes received tensors as contiguous, so layout-only strategies (transposed, strided) are nominal at the client boundary. The daemon-side fuzzer correctly varies strides but the kernel sees contiguous data.

4 Evaluation

Setup. RTX 3060, image `pytorch/pytorch:2.4.0-cuda12.4-cudnn9-devel`. 7 strategies $\times$ 26 ops $\times$ 8 iters = 1,456 cases. Run id `run-20260611-101922-4dcac1` on Backblaze B2.

Headline: recall and control FP per strategy. Each strategy ran the same 10 buggy kernels and the same 16 controls at 8 iterations per (strategy, kernel). That gives 80 buggy cases and 128 control cases per strategy. Table 2 reports both axes.

Table 2. Per-strategy recall (10 buggy $\times$ 8 iters = 80) and control FP rate (16 correct $\times$ 8 = 128).

strategy	bug recall	control FP
adversarial	79/80 (99%)	120/128 (94%)
nan_injected	75/80 (94%)	93/128 (73%)
boundary	62/80 (78%)	0/128 (0%)
single.dtype.f32	59/80 (74%)	0/128 (0%)
single.dtype.f16	59/80 (74%)	3/128 (2%)
default	57/80 (71%)	0/128 (0%)
regular	51/80 (64%)	0/128 (0%)

Killer finding: shape-dependent bugs vanish under “regular”. Table 3 reports per-kernel recall on four shape-sensitive bugs under each of four strategies. Regular sampling catches 0% of the two tail-mask bugs. Boundary sampling catches them at 100% and 62% respectively.

Table 3. Recall on shape-dependent buggy kernels, four strategies, 8 iters per cell.

buggy kernel	default	boundary	regular	adversarial
softmax_llm_buggy	25%	100%	0%	100%
softmax_triton_buggy	38%	62%	0%	100%
attention_triton_buggy	50%	25%	38%	100%
matmul_triton_buggy	62%	75%	50%	88%




Fig. 1. Bug recall (%) per (strategy, buggy kernel), 8 iters each. Strategy order matches Table 1 (default top, adversarial bottom).

Why adversarial and NaN-injected inflate FP. Both strategies inject NaN, Inf, and subnormal values into inputs. Correct kernels that propagate NaN to their output trip the validator’s `check_nan` flag, which marks the case as a failure even though the reference kernel produces the same NaN on the same input. The 120/128 adversarial FPs and the 93/128 NaN-injected FPs are therefore validator artefacts of strict NaN handling under non-finite inputs, not genuine output divergence on correct kernels. The four strategies that do not inject non-finite inputs (boundary, regular, default, single_dtype_f32) all preserve precision at 0 FP. The single_dtype_f16 strategy registers 3 FPs out of 128, all on the same fp16-borderline operator. The headline operational recommendation is therefore boundary as the safe default; adversarial as a high-recall complement only when the downstream consumer can itself disregard NaN-output-on-NaN-input failures.

5 Discussion

The strategy ranking is operator-dependent. The bug families split into three groups.

Uniform-magnitude bugs (gelu missing 0.5, silu β confusion, rmsnorm and l2norm missing `sqrt`, leaky_relu wrong α) are caught at 100% by every strategy. The bug is shape and value independent, so any input reveals it.

Shape-dependent tail-mask bugs (softmax) need the right boundary shape. Regular sampling at $H \in \{128, 256, 512\}$ (all powers of two relative to BLOCK) catches 0% of them.

Magnitude-sensitive bugs (attention without $1/\sqrt{D}$ saturates softmax differently at different value scales; matmul `acc=` variants behave differently with extreme accumulators) need value-distribution diversity. Adversarial value sampling has the highest raw recall on these, but the same value injection that catches the bug also drives the control FP rate to 94%.

A two-stage operational recipe. The strategies split naturally into a gate and a triage pass. Stage one is the gate: `boundary` shape sampling on every kernel. It catches 78% of seeded bugs and produces zero false alarms on controls, which is what a CI pipeline needs from a pass/fail signal. Stage two is the triage pass: `adversarial` or `nan_injected` run on kernels that the gate already flagged, or on kernels under code review. The triage pass should not feed back into a pass/fail gate until the validator stops counting NaN-output as a failure when the reference kernel produces the same NaN on the same input. In a real testing pipeline the operator does not know in advance which kernels are buggy, so the recipe is: gate with boundary, escalate to adversarial under human review or after the validator change lands.

6 Limitations

The `nan_injected` and `adversarial` strategies dominate the raw recall ranking, but the same input distribution that raises buggy-kernel failure counts also raises control failures through the validator’s strict `check_nan` flag. We are not yet able to separate “true output divergence on a buggy kernel” from “non-finite input propagated to output and flagged by the validator” inside the existing fail signal. A validator change that treats NaN-output as a pass when the reference kernel produces the same NaN on the same input would split the two and let these strategies report their bug-discovery recall without the FP inflation. We treat that as a follow-up in the `gpuemu` project rather than re-running the ablation here.

Strategies vary only the candidate set per dim and the dtype and value distribution. Layout strategies (non-contiguous strided, transposed) are not yet exercised end to end because the Python client decodes received tensors as contiguous.

The bug corpus is author-seeded with documented LLM transcription patterns. We have not yet fuzzed LLM-generated kernels directly.

Iter count per (strategy, kernel) is modest (8). A larger sweep would tighten confidence intervals on the per-bug recall numbers.

7 Conclusion

Test-input generation is not a fixed cost. It is a knob that swings kernel bug recall by 35 percentage points (64% under regular shapes to 99% under adversarial values). The data argues for one cheap change and one operationally aware one.

Always include boundary shapes in the per-op schema. Without them, an entire class of tail-mask bugs is invisible to the oracle (0% recall on `softmax.*_buggy`

under regular sampling, up to 100% under boundary sampling). This costs nothing to flip.

Treat adversarial value sampling as a high-recall complement, not a default. Adversarial reaches 99% raw recall, but on the current validator it also flags 94% of correct controls as failures because non-finite inputs cascade through correct kernels and trip the NaN check. Either fix the validator to ignore NaN-output when the reference also produces NaN on the same input, or restrict the adversarial pass to diagnostic triage on kernels already flagged by the boundary gate or under code review.

On the gpuemu corpus the boundary knob alone pushes bug recall from 71% under `default` to 78% at 0% control FP. The `adversarial` knob reaches 99% recall but only becomes a safe default after the validator stops flagging NaN-output as a failure when the reference produces the same NaN on the same input. Until then, treat boundary as the operational gate and adversarial as a diagnostic pass on suspected-buggy targets.

Artefact. The corpus, the strategy driver (`drivers/p3_strategies.py`), the per-strategy table generator (`analysis/p3_strategy_table.py`), and the replay tool that fetches the cited run record are bundled in the public `gpuemu-corpus` package at <https://github.com/sarkar-dipankar/gpuemu-corpus>. The validator daemon is at <https://github.com/Skelf-Research/gpuemu>.

License. This preprint is released under CC-BY 4.0.

References

1. Deng, Y., Yang, C., Wei, A., Zhang, L.: Fuzzing deep-learning libraries via automated relational API inference. In: Proc. 30th ACM Joint Eur. Softw. Eng. Conf. and Symp. Found. Softw. Eng. (ESEC/FSE). pp. 44–56 (2022). <https://doi.org/10.1145/3540250.3549085>
2. Dong, J., Yang, Y., Liu, T., Wang, Y., Qi, F., Tarokh, V., Rangadurai, K., Yang, S.: STARK: Strategic team of agents for refining kernels. arXiv preprint (2025), <https://arxiv.org/abs/2510.16996>
3. Myers, G.J.: The Art of Software Testing. Wiley (1979)
4. Ouyang, A., Guo, S., Arora, S., Zhang, A.L., Hu, W., Ré, C., Mirhoseini, A.: KernelBench: Can LLMs write efficient GPU kernels? arXiv preprint (2025), <https://arxiv.org/abs/2502.10517>
5. Qin, F., Naziri, M.M.A., Ai, H., Dutta, S., d’Amorim, M.: Evaluating the effectiveness of coverage-guided fuzzing for testing deep learning library APIs. arXiv preprint (2025), <https://arxiv.org/abs/2509.14626>
6. Ran, D., Xie, S., Ji, M., Liu, A., Wu, M., Cao, Y., Guo, Y., Yu, H., Li, L., Hu, Y., Yang, W., Xie, T.: KernelBand: Steering LLM-based kernel optimization via hardware-aware multi-armed bandits. arXiv preprint (2025), <https://arxiv.org/abs/2511.18868>
7. Sarkar, D.: The correctness illusion in LLM-generated GPU kernels. arXiv preprint (2026), <https://arxiv.org/abs/2606.20128>

8. Sarkar, D.: Operator-aware mixed-precision tolerance calibration for tensor kernels (2026), manuscript in preparation. Reproducibility artefacts at <https://github.com/sarkar-dipankar/gpuemu-corpus>.
9. Wang, Han, Zhang, J., Jiang, K., Wang, Haoxu, Chen, J., Zhu, J.: KernelBenchX: A comprehensive benchmark for evaluating LLM-generated GPU kernels. arXiv preprint (2026), <https://arxiv.org/abs/2605.04956>
10. Wang, J., Joshi, V., Majumder, S., Xu Chao, Ding, B., Liu, Ziqiong, Brahma, P.P., Li, D., Liu, Zicheng, Barsoum, E.: GEAK: Introducing Triton kernel AI agent & evaluation benchmarks. arXiv preprint (2025), <https://arxiv.org/abs/2507.23194>
11. Wei, A., Deng, Y., Yang, C., Zhang, L.: Free lunch for testing: Fuzzing deep-learning libraries from open source. In: Proc. 44th Int. Conf. Software Engineering (ICSE). pp. 995–1007 (2022). <https://doi.org/10.1145/3510003.3510041>, <https://arxiv.org/abs/2201.06589>
12. Xie, D., Li, Y., Kim, M., Pham, H.V., Tan, L., Zhang, X., Godfrey, M.W.: DocTer: Documentation-guided fuzzing for testing deep learning API functions. In: Proc. 31st ACM SIGSOFT Int. Symp. Software Testing and Analysis (ISSTA). pp. 176–188 (2022). <https://doi.org/10.1145/3533767.3534220>, <https://arxiv.org/abs/2109.01002>
13. Yang, C., Deng, Y., Yao, J., Tu, Y., Li, H., Zhang, L.: Fuzzing automatic differentiation in deep-learning libraries. In: Proc. 45th Int. Conf. Software Engineering (ICSE). pp. 1174–1186 (2023). <https://doi.org/10.1109/ICSE48619.2023.00105>, <https://arxiv.org/abs/2302.04351>