Headless Logs API Docs

TODO: submit this to public docs

Reading Headless Application Build Logs and Runtime Logs

Kibo's Hosted Headless application platform exposes two distinct log types for your application: **Build Logs** and **Runtime Logs**. This guide explains what each log type contains, how to retrieve them via API, and how to interpret the results.

> **Prerequisite:** Your Kibo site must be linked to a Hosted Headless application before using any of the APIs described below. All requests require a valid Bearer (JWT) authentication token.

Overview

Log Type	What it captures	API
Build Log	Step-by-step output from a specific build job on a branch	`GET /platform/appdev/headless-app/builds/{branchName}/logs/{jobId}`
Runtime Log	Application output generated while your headless app is live	`GET /platform/appdev/headless-app/logs/runtime`

To work with build logs, you'll typically follow a two-step flow:

1. **List build jobs** for a branch to find the `jobId` you want to inspect.
2. **Fetch the build log** for that specific `jobId`.

Runtime logs can be retrieved directly and filtered by date.

Step 1 — List Build Jobs for a Branch

Before you can read a build log, you need the `jobId` of the build you want to inspect. Use the **Get Application Build Jobs** API to list all builds for a given branch.

Endpoint

```
GET /api/platform/appdev/headless-app/builds/{branchName}
```

Path Parameters

Parameter	Required	Description
`branchName`	Yes	The name of the source code branch (e.g., `main`, `staging`)

Query Parameters

Parameter	Default	Max	Description
`maxResults`	20	100	Number of build job records to return
`nextToken`	—	—	Pagination token returned by a previous response
`responseFields`	—	—	Comma-separated list of fields to include in the response

Example Request

```
GET /api/platform/appdev/headless-app/builds/main?maxResults=10
Authorization: Bearer {your_token}
```

Example Response

```
{
  "nextToken": "abc123paginationtoken",
  "jobs": [
    {
      "jobId": "build-job-001",
      "status": "SUCCEEDED",
      "commitId": "a3f9e12c",
      "commitTime": "2025-01-15T14:32:00Z",
      "startTime": "2025-01-15T14:33:01Z",
      "endTime": "2025-01-15T14:40:45Z"
    },
    {
      "jobId": "build-job-002",
      "status": "FAILED",
      "commitId": "b7d2a44e",
      "commitTime": "2025-01-14T09:10:00Z",
      "startTime": "2025-01-14T09:11:02Z",
      "endTime": "2025-01-14T09:14:30Z"
    }
  ]
}
```

Response Fields

Field	Description
`nextToken`	Pass this value as `nextToken` in your next request to retrieve the following page of results
`jobs[].jobId`	The unique identifier for the build job — **use this to retrieve the build log**
`jobs[].status`	The result of the build (e.g., `SUCCEEDED`, `FAILED`, `IN_PROGRESS`)
`jobs[].commitId`	The source control commit that triggered the build
`jobs[].commitTime`	When the commit was made
`jobs[].startTime`	When the build started

`jobs[].endTime`	When the build completed

Step 2 — Retrieve a Build Log

Once you have a `jobId`, use the **Get Application Build Log** API to retrieve the step-by-step log output for that build.

Endpoint

```
GET /api/platform/appdev/headless-app/builds/{branchName}/logs/{jobId}
```

Path Parameters

Parameter	Required	Description
`branchName`	Yes	The name of the source code branch
`jobId`	Yes	The build job identifier from Step 1

Query Parameters

Parameter	Description
`responseFields`	Comma-separated list of fields to include in the response

Example Request

```
GET /api/platform/appdev/headless-app/builds/main/logs/build-job-002
Authorization: Bearer {your_token}
```

Example Response

```
{
  "jobId": "build-job-002",
  "steps": [
    {
      "stepName": "INSTALL_DEPENDENCIES",
      "status": "SUCCEEDED",
      "logUrl": "https://logs.example.com/build-job-002/install",
      "startTime": "2025-01-14T09:11:02Z",
      "endTime": "2025-01-14T09:12:30Z"
    },
    {
      "stepName": "BUILD",
      "status": "FAILED",
      "logUrl": "https://logs.example.com/build-job-002/build",
      "startTime": "2025-01-14T09:12:31Z",
      "endTime": "2025-01-14T09:14:30Z"
    }
  ]
}
```

Response Fields

Field	Description
`jobId`	Confirms the build job this log corresponds to
`steps`	An ordered list of the build stages that ran during this job

`steps[].stepName`	The name of the build stage (e.g., `INSTALL_DEPENDENCIES`, `BUILD`)
`steps[].status`	The result of that step (`SUCCEEDED` or `FAILED`)
`steps[].logUrl`	A URL to access the detailed log output for that step
`steps[].startTime`	When this step started
`steps[].endTime`	When this step ended

Reading a Build Log

To diagnose a failed build:

1. Find the **first step with** `"status": "FAILED"` — this is where the build broke.
2. Open the `logUrl` for that step to view the detailed output.
3. Look for error messages, missing dependencies, or compilation errors in the output.
4. Cross-reference the `commitId` (from Step 1) with your source control history to see what changed in that commit.

Retrieving Runtime Logs

Runtime logs capture output from your headless application while it is running in the hosted environment. These logs are available as downloadable files, organized by date and time.

Endpoint

```
GET /api/platform/appdev/headless-app/logs/runtime
```

Query Parameters

Parameter	Default	Max	Description
`prefix`	—	—	Date filter in `yyyy-mm-dd-hh` format. Supports partial dates (see examples below)
`maxResults`	20	100	Number of log records to return
`nextToken`	—	—	Pagination token returned by a previous response
`responseFields`	—	—	Comma-separated list of fields to include in the response

Date Prefix Examples

`prefix` value	Matches
`2025`	All logs from the year 2025

`2025-01`	All logs from January 2025
`2025-01-15`	All logs from January 15, 2025
`2025-01-15-14`	All logs from 2:00 PM on January 15, 2025

Example Request — Filter to a specific day

```
GET /api/platform/appdev/headless-app/logs/runtime?prefix=2025-01-15&maxResults=50
Authorization: Bearer {your_token}
```

Example Response

```
{
  "nextToken": "xyz789paginationtoken",
  "prefix": "2025-01-15",
  "maxResults": 50,
  "isTruncated": true,
  "logs": [
    {
      "key": "2025-01-15-14-app-runtime.log",
      "logUrl": "https://logs.example.com/presigned-url/runtime-log-1",
      "size": 204800,
      "lastModified": "2025-01-15T15:00:00Z"
    },
    {
      "key": "2025-01-15-15-app-runtime.log",
      "logUrl": "https://logs.example.com/presigned-url/runtime-log-2",
      "size": 102400,
      "lastModified": "2025-01-15T16:00:00Z"
    }
  ]
}
```

Response Fields

Field	Description
`nextToken`	Pass this value as `nextToken` in your next request to retrieve additional results
`prefix`	Confirms the date filter that was applied
`maxResults`	Confirms the page size that was applied
`isTruncated`	`true` means more results exist — use `nextToken` to paginate through them
`logs[].key`	The log file identifier, which encodes the date and hour of the log
`logs[].logUrl`	A time-limited URL to download the log file. **Valid for 4 hours** from when the response was received
`logs[].size`	Size of the log file in bytes
`logs[].lastModified`	The last time this log file was updated

Paginating Through Runtime Logs

When `isTruncated` is `true`, there are more results available. Retrieve the next page by passing the `nextToken` from the current response:

```
GET /api/platform/appdev/headless-app/logs/runtime?prefix=2025-01-15&nextToken=xyz789paginationtoken
Authorization: Bearer {your_token}
```

Continue until `isTruncated` is `false` or `nextToken` is absent.

API Reference

API	Reference
Get Application Build Jobs	docs.kibocommerce.com
Get Application Build Log	docs.kibocommerce.com
Get Runtime Logs	docs.kibocommerce.com