R: How to make multiple plots in a graph using unique IDs

Asked 1 year, 7 months ago Modified 1 year, 7 months ago Viewed 194 times 🚼 Part of R Language Collective



I have a dataframe df with 4 unique UID - 1001,1002,1003,1004.

I want to write a user-defined function in R that does the following:





Ð

1. Plots Turbidity against Time for each unique UID. Turbidity values are the ones in the Time_1, Time_2 and Time_3 columns. For example, UID = 1001 will have 4 plots in one graph

	Gen	Site	Type	UID	Time_1	Time_2	Time_3
1	М	FRX	L	1001	100.78	150.78	250.78
5	F	FRX	L	1001	149.02	208.07	308.07
9	М	FRX	R	1001	106.78	146.87	346.87
13	F	FRX	R	1001	129.02	229.28	329.28

- 2. Add a legend to each graph such as M-L, F-L, M-R, and F-R (from columns Gen and Type)
- 3. Add a title to each graph. For example- UID: 1001
- 4. Export the graphs as pdf or jpeg or tiff pdf files 4 graphs per page

```
# dataset
Site <- rep('FRX',length(gen))</pre>
UID <-
c(1001,1002,1003,1004,1001,1002,1003,1004,1001,1002,1003,1004,1001,1002,1003,1004)
c(100.78,112.34,108.52,139.19,149.02,177.77,79.18,89.10,106.78,102.34,128.52,119.19,
Time_2 < -
c(150.78,162.34,188.53,197.69,208.07,217.76,229.48,139.51,146.87,182.54,189.57,199.9
c(250.78,262.34,288.53,297.69,308.07,317.7,329.81,339.15,346.87,382.54,369.59,399.97
df <- data.frame(Gen, Site, Type, UID, Time_1, Time_2, Time_3)</pre>
```


My attempt

```
library(ggplot2)
library(tidyr)
# See below for my thoughts/attempt- I am open to other R libraries and
approaches
```

```
graphplotter <-function(x){</pre>
    # 1. Convert from wide to long
    data_long <- gather(df, time, turbidity, Time_1:Time_3, factor_key=TRUE)</pre>
    data_long
    #2. plot for each unique UID- 1001 to 1004 and add legend
    basic <- ggplot(datalong, aes(time, turbidity, shape=Tree)) + geom_point() +</pre>
geom_line()
    basic + theme(
    legend.position = c(.95, .95),
    legend.justification = c("right", "top"),
    legend.box.just = "right",
    legend.margin = margin(6, 6, 6, 6)
    #3. add title
    print(basic+ labs( title= "UID: 1001, Tubidity against time", y="turbidity",
x = "Time in hours"))
    #4. export as pdf
    pdf("turbdity-time.pdf")
    par(mfrow = c(2, 2)) ## set the layout to be 2 by 2
    sapply(1:4, function(i) plot(basic[,i]))
    dev.off()
}
```

I want all four graphs to look something like this (ignore the circumference and age, should be turbidity and time).

Thanks



```
2
```








```
Ð
```

```
graphplotter <-function(x){
    x %>%
    gather(., time, turbidity, Time_1:Time_3, factor_key=TRUE) %>%
    mutate(label = (paste0(Gen, "-", Type))) %>%
    #group_by(UID) %>%
    ggplot(aes(color = label)) + geom_point(aes(time, turbidity, shape = label,
group = label)) +
    geom_line(aes(time, turbidity, group = label)) + facet_wrap(~UID) + theme(
        legend.position = c(1, 1),
        legend.justification = c("right", "top"),
        legend.box.just = "right",
        legend.margin = margin(1, 1, 1, 1),
        legend.text = element_text(size = 7))
}
graphplotter(df)
```



Share Edit Follow Flag

edited Sep 14, 2021 at 5:34

answered Sep 14, 2021 at 1:22



- @Park..This looks very good (thanks a bunch!), how can I make `F-L`, F-R, M-L and M-R plots have 4 different colors? nasa313 Sep 14, 2021 at 5:11 /
- @nasa313 colors for points or lines? I edit code for both of them Park Sep 14, 2021 at 5:13 🖍

- This is exactly what I want(Thanks a lot.) one last thing, in the 1002 graph the label/legend is blocking the tip of the plots (I just uploaded the image of the graph in the original question). Can we move the label/legend outside of the graph or just make it smaller? nasa313 Sep 14, 2021 at 5:29
- @nasa313 | edit my code, changing legend.margin and add legend.text | You may change thoseoptions and legend.position to change location of legend Park Sep 14, 2021 at 5:35