



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Worksheet 4

Student Name: Sarthak Arora

Branch: BE-CSE

Semester: 5TH

Subject Name: ADBMS

UID: 23BCS12984

Section/Group: KRG2-B

Date of Performance: 08/09/25

Subject Code: 23CSP-333

FUNCTIONAL DEPENDENCIES_-

Q1. Consider a relation R having attributes as R(ABCD), functional dependencies are given below:

AB→C, C→D, D→A

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Sol: -

B is missing on the right-side of given functional dependencies, so it is sure that it must be the part of every candidate key.

Closures: -

$AB^+ = \{A, B, C, D\} \rightarrow AB$ is a key.

$BC^+ = \{A, B, C, D\} \rightarrow BC$ is a key.

$BD^+ = \{A, B, C, D\} \rightarrow BD$ is a key.

Candidate keys: - (BA, BC, BD)

Prime attributes: - A, B, C, D

Non-prime attributes: -

None

Normal Form: 3NF

**Q2. Relation R(ABCDE) having functional dependencies as
: $A \rightarrow D$, $B \rightarrow A$, $BC \rightarrow D$, $AC \rightarrow BE$**

Identify the set of candidate keys possible in relation R. List all the set of prime and non-prime attributes.

Sol: -

C is missing on right-side so it must be a part of every candidate key.

Closures-

$AC^+ = \{A, B, C, D, E\} \Rightarrow AC$ is a key

$BC^+ = \{A, B, C, D, E\} \Rightarrow BC$ is a key

Candidate keys: - (AC, BC)

Prime Attributes: - A, B, C

Non-prime Attributes: - D, E

Normal Form: 1NF

Q3. Consider a relation R having attributes as R(ABCDE), functional dependencies are given below:

$B \rightarrow A$, $A \rightarrow C$, $BC \rightarrow D$, $AC \rightarrow BE$

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Sol: -

Closures -

$A^+ = \{A, C, B, E, D\} = \{A, B, C, D, E\} \Rightarrow A$ is a key

$B^+ = \{A, B, C, D, E\} \Rightarrow B$ is a key

Any superset of A or B is a super key but not minimal. No other single attribute has a closure of all attributes (e.g. $C+C^++C^+$ doesn't expand). So, there are no other candidate keys.

Candidate keys: - (A, B)

Prime attributes: - A, B

Non-prime attributes: - C, D,
E

Normal Form: BCNF

Q4. Consider a relation R having attributes as R(ABCDEF), functional dependencies are given below:

A \rightarrow BCD, BC \rightarrow DE, B \rightarrow D, D \rightarrow A

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Sol: -

Closures-

$AF^+= \{A, B, C, D, E, F\} \Rightarrow \mathbf{AF}$ is a key.

$BF^+= \{A, B, C, D, E, F\} \Rightarrow \mathbf{BF}$ is a key.

$DF^+= \{A, B, C, D, E, F\} \Rightarrow \mathbf{DF}$ is a key.

Check minimality: none of A, B, or D alone determine F; F alone does not determine the rest. Thus AF, BF and DF are minimal (no proper subset is a key).

Candidate Keys: - (AF, BF, DF)

Prime attributes: - A, B, D, F

Non-prime attributes: - C, E

Normal form: - 1 NF

5. Designing a student database involves certain dependencies which are listed below: $X \rightarrow Y$

$WZ \rightarrow X$

$WZ \rightarrow Y$

$Y \rightarrow W$

$Y \rightarrow X$

$Y \rightarrow Z$

Identify the set of candidate keys possible in student database. List all the set of prime and non prime attributes.

Sol: -

Closures: -

$X^+ = \{X, Y, W, Z\} \Rightarrow X$ determines all attributes.

$Y^+ = \{Y, W, X, Z\} \Rightarrow Y$ determines all attributes.

$WZ^+ = \{W, Z, X, Y\} \Rightarrow WZ$ determines all attributes.

Singletons W^+ and Z^+ do **not** expand to all attributes (no FD gives others from W or Z alone), so W and Z are not keys individually.

WZ is a key and minimal because neither WW nor ZZ alone is a key.

Candidate keys: - (X, Y, WZ)

Prime attributes: - X, Y, W, Z

Normal Form: BCNF

6. Debix Pvt Ltd needs to maintain database having dependent attributes ABCDEF. These attributes are functionally dependent on each other for

which functionally dependency set F given as: $\{A \rightarrow BC, D \rightarrow E, BC \rightarrow D, A \rightarrow D\}$

Consider a universal relation $R_1(A, B, C, D, E, F)$ with functional dependency set F, also all attributes are simple and take atomic values only. Find the highest normal form along with the candidate keys with prime and non-prime attribute.

Sol: -

A does **not** appear on any RHS \rightarrow A cannot be determined by other attributes \rightarrow **A must be in every candidate key.**

F does **not** appear on any RHS \rightarrow F cannot be determined by other attributes \rightarrow **F must be in every candidate key.**

So every candidate key must include both A and F.

Closures: -

- $A^+ = \{A, B, C, D, E\}$, A^+ does not include FFF.
- $AF^+ = A^+ \cup \{F\} = \{A, B, C, D, E, F\}$. Hence AF determines all attributes \rightarrow AF is a super key.

Minimality: neither AAA alone nor FFF alone is a key, so AF is minimal.

No other minimal combination can omit either A or F (both are required), so AF is the only candidate key.

Candidate key: -(AF)

Prime attributes: -A, F

Non-prime attributes: -
B,C, D, E

Normal Form: - 1NF