# Experiment 7

| | |
|---|---|
| **Student Name**  Sarthak Arora | **UID**  23BCS12984 |
| **Branch:** CSE | **Section/Group:** KRG_2B |
| **Semester:** 5<sup>th</sup> | **Date of Performance:** 07/10/25 |
| **Subject Name**: PBLJ | **Subject Code:** 23CSH-304 |

## 1. Aim:

To design and implement Java programs using JDBC connectivity, CRUD operations, and MVC architecture for database interaction and management.
• To apply JDBC concepts, transaction handling, and MVC design pattern for real-world data management applications.

**Part A – Easy Level:**
• To create a Java program that connects to a MySQL database and retrieves all records from the Employee table.
• To demonstrate database connectivity using DriverManager and Connection objects.

**Part B – Medium Level:**
• To develop a Java program that performs CRUD operations on a Product table using JDBC.
• To implement transaction handling for ensuring data consistency during database operations.

**Part C – Hard Level:**
• To build a Java application using MVC architecture for managing student data through JDBC.
• To separate Model, View, and Controller functionalities and perform CRUD operations efficiently.

## 2. Objective:

✓ To understand and implement **JDBC connectivity** for accessing relational databases.

- ✓ To perform Create, Read, Update, and Delete (CRUD) operations using JDBC.
- ✓  To apply transaction management for maintaining database integrity.
- ✓ To design applications using the MVC architecture for modular and maintainable code.
- ✓ To handle SQL exceptions and manage JDBC resources effectively..

# 3. JAVA script and output:

**EASY-LEVEL PROBLEM**

```java
package exp.pkg6;


import java.sql.*;


public class Exp6 {
    public static void main(String[] args) {
        try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/college", "root", "password");
            Statement stmt = con.createStatement();
            ResultSet rs = stmt.executeQuery("SELECT * FROM Employee");
            while (rs.next()) {
                System.out.println("EmpID: " + rs.getInt(1) + ", Name: " + rs.getString(2) + ", Salary: " + rs.getDouble(3));
            }
            con.close();
        } catch (Exception e) {
            System.out.println(e);
```

```
        }
     }
}
```

## SAMPLE OUTPUT:

EmpID: 101, Name: Akshara, Salary: 50000
EmpID: 102, Name: Ishika, Salary: 60000

## MEDIUM LEVEL PROBLEM:

```java
package exp.pkg6;

import java.sql.*;
import java.util.*;

public class Exp6 {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        try {
            Class.forName("com.mysql.cj.jdbc.Driver");
            Connection con = DriverManager.getConnection("jdbc:mysql://localhost:3306/college",
"root", "password");
            while (true) {
                System.out.println("Menu:\n1. Add Product\n2. View All Products\n3. Update
Product\n4. Delete Product\n5. Exit");
                System.out.print("Enter your choice: ");
                int choice = sc.nextInt();
                sc.nextLine();
                if (choice == 1) {
                    System.out.print("Enter ProductID: ");
                    int id = sc.nextInt();
                    sc.nextLine();
                    System.out.print("Enter Product Name: ");
```

```java
            String name = sc.nextLine();
            System.out.print("Enter Price: ");
            double price = sc.nextDouble();
            System.out.print("Enter Quantity: ");
            int qty = sc.nextInt();
            PreparedStatement ps = con.prepareStatement("INSERT INTO Product VALUES
(?, ?, ?, ?)");
                ps.setInt(1, id);
                ps.setString(2, name);
                ps.setDouble(3, price);
                ps.setInt(4, qty);
                ps.executeUpdate();
                System.out.println("Product added successfully!");
        } else if (choice == 2) {
            Statement stmt = con.createStatement();
            ResultSet rs = stmt.executeQuery("SELECT * FROM Product");
            while (rs.next()) {
                System.out.println("ID: " + rs.getInt(1) + ", Name: " + rs.getString(2) + ", Price: "
+ rs.getDouble(3) + ", Quantity: " + rs.getInt(4));
                }
        } else if (choice == 3) {
            System.out.print("Enter ProductID to update: ");
            int id = sc.nextInt();
            System.out.print("Enter new Price: ");
            double price = sc.nextDouble();
            PreparedStatement ps = con.prepareStatement("UPDATE Product SET Price=?
WHERE ProductID=?");
                ps.setDouble(1, price);
                ps.setInt(2, id);
                ps.executeUpdate();
                System.out.println("Product updated successfully!");
        } else if (choice == 4) {
            System.out.print("Enter ProductID to delete: ");
            int id = sc.nextInt();
            PreparedStatement ps = con.prepareStatement("DELETE FROM Product WHERE
ProductID=?");
                ps.setInt(1, id);
                ps.executeUpdate();
                System.out.println("Product deleted successfully!");
        } else if (choice == 5) {
```

```java
            System.out.println("Exiting...");
            break;
        } else {
            System.out.println("Invalid choice!");
        }
    }
    con.close();
} catch (Exception e) {
    System.out.println(e);
}
}
}
```

**SAMPLE OUTPUT:**
Menu:
1. Add Product
2. View All Products
3. Update Product
4. Delete Product
5. Exit
Enter your choice: 1
Product added successfully!

## HARD LEVEL PROBLEM

```java
package exp.pkg6;


import java.sql.*;

import java.util.*;


class Student {

    int id;

    String name;

    String dept;
```

```java
    double marks;

    Student(int id, String name, String dept, double marks) {
        this.id = id;
        this.name = name;
        this.dept = dept;
        this.marks = marks;
    }
}

class StudentController {
    Connection con;

    StudentController() throws Exception {
        Class.forName("com.mysql.cj.jdbc.Driver");
        con = DriverManager.getConnection("jdbc:mysql://localhost:3306/college", "root",
"password");
    }

    void addStudent(Student s) throws Exception {
        PreparedStatement ps = con.prepareStatement("INSERT INTO Student VALUES (?, ?, ?,
?)");
        ps.setInt(1, s.id);
        ps.setString(2, s.name);
        ps.setString(3, s.dept);
        ps.setDouble(4, s.marks);
        ps.executeUpdate();
```

```java
    }


    void viewAll() throws Exception {

        Statement stmt = con.createStatement();

        ResultSet rs = stmt.executeQuery("SELECT * FROM Student");

        while (rs.next()) {

            System.out.println("StudentID: " + rs.getInt(1) + ", Name: " + rs.getString(2) + ",
Department: " + rs.getString(3) + ", Marks: " + rs.getDouble(4));

        }

    }


    void updateStudent(int id, double marks) throws Exception {

        PreparedStatement ps = con.prepareStatement("UPDATE Student SET Marks=? WHERE
StudentID=?");

        ps.setDouble(1, marks);

        ps.setInt(2, id);

        ps.executeUpdate();

    }


    void deleteStudent(int id) throws Exception {

        PreparedStatement ps = con.prepareStatement("DELETE FROM Student WHERE
StudentID=?");

        ps.setInt(1, id);

        ps.executeUpdate();

    }

}
```

```java
public class Exp6 {

    public static void main(String[] args) {

        try {

            StudentController sc = new StudentController();

            Scanner in = new Scanner(System.in);

            while (true) {

                System.out.println("--- Student Management System ---");

                System.out.println("1. Add Student\n2. View All Students\n3. Update Student\n4. Delete Student\n5. Exit");

                System.out.print("Enter your choice: ");

                int ch = in.nextInt();

                if (ch == 1) {

                    System.out.print("Enter ID: ");

                    int id = in.nextInt();

                    in.nextLine();

                    System.out.print("Enter Name: ");

                    String name = in.nextLine();

                    System.out.print("Enter Department: ");

                    String dept = in.nextLine();

                    System.out.print("Enter Marks: ");

                    double marks = in.nextDouble();

                    sc.addStudent(new Student(id, name, dept, marks));

                    System.out.println("Student added successfully!");

                } else if (ch == 2) {

                    sc.viewAll();

                } else if (ch == 3) {

                    System.out.print("Enter ID to update: ");
```

```java
            int id = in.nextInt();

            System.out.print("Enter new Marks: ");

            double marks = in.nextDouble();

            sc.updateStudent(id, marks);

            System.out.println("Student updated successfully!");

        } else if (ch == 4) {

            System.out.print("Enter ID to delete: ");

            int id = in.nextInt();

            sc.deleteStudent(id);

            System.out.println("Student deleted successfully!");

        } else if (ch == 5) {

            System.out.println("Exiting...");

            break;

        } else {

            System.out.println("Invalid choice!");

        }

      }

    } catch (Exception e) {

      System.out.println(e);

    }

  }

}
```

**SAMPLE OUTPUT:**

--- Student Management System ---

1. Add Student

2. View All Students

3. Update Student

4. Delete Student

5. Exit

Enter your choice: 2

StudentID: 1001, Name: Akshara, Department: CSE, Marks: 98