

Assembly - Macros

Writing a macro is another way of ensuring modular programming in assembly language.

- A macro is a sequence of instructions, assigned by a name and could be used anywhere in the program.
- In NASM, macros are defined with **%macro** and **%endmacro** directives.
- The macro begins with the %macro directive and ends with the %endmacro directive.

The Syntax for macro definition –

```
%macro macro_name number_of_params  
<macro body>  
%endmacro
```

Where, number_of_params specifies the number parameters, macro_name specifies the name of the macro.

The macro is invoked by using the macro name along with the necessary parameters. When you need to use some sequence of instructions many times in a program, you can put those instructions in a macro and use it instead of writing the instructions all the time.

For example, a very common need for programs is to write a string of characters in the screen. For displaying a string of characters, you need the following sequence of instructions –

```
mov     edx,len      ;message length  
mov     ecx,msg      ;message to write  
mov     ebx,1        ;file descriptor (stdout)  
mov     eax,4        ;system call number (sys_write)  
int     0x80         ;call kernel
```

In the above example of displaying a character string, the registers EAX, EBX, ECX and EDX have been used by the INT 80H function call. So, each time you need to display on screen, you need to save these registers on the stack, invoke INT 80H and then restore the original value of the registers from the stack. So, it could be useful to write two macros for saving and restoring data.

We have observed that, some instructions like IMUL, IDIV, INT, etc., need some of the information to be stored in some particular registers and even return values in some specific register(s). If the program was already using those registers for keeping important data, then the existing data from these registers should be saved in the stack and restored after the instruction is executed.

Example

Following example shows defining and using macros –

```
; A macro with two parameters
; Implements the write system call

%macro write_string 2
    mov    eax, 4
    mov    ebx, 1
    mov    ecx, %1
    mov    edx, %2
    int    80h
%endmacro

section .text
    global _start                ;must be declared for using gcc

_start:                          ;tell linker entry point
    write_string msg1, len1
    write_string msg2, len2
    write_string msg3, len3

    mov    eax,1                ;system call number (sys_exit)
    int    0x80                ;call kernel

section .data
msg1 db 'Hello, programmers!',0xA,0xD
len1 equ $ - msg1

msg2 db 'Welcome to the world of,', 0xA,0xD
len2 equ $- msg2

msg3 db 'Linux assembly programming! '
len3 equ $- msg3
```

[Live Demo](#)

When the above code is compiled and executed, it produces the following result –

Hello, programmers!
Welcome to the world of,
Linux assembly programming!