

DELIVERABLES

Documentation of functional and non-functional requirements

Functional Requirement

1. Users must be able to compare neighbourhoods.

1.1 Users must select neighbourhoods.

- 1.1.1 The system must display a list of available neighbourhoods, drawn from the URA Planning Areas defined in the Data Dictionary.
- 1.1.2 The user must select a neighbourhood.
- 1.1.2.1 The user must select at least 2, maximus 4 neighbourhoods to compare.

1.2 Users may specify their preferences.

- 1.2.1 The system must display the five comparison factors defined in the Data Dictionary.
- 1.2.2 The user may specify the importance of public transport.
- 1.2.2.1 The importance value must be expressed on a scale of 0 (not important) to 10 (essential).
- 1.2.3 The user may specify the importance of greenery.
 - 1.2.3.1 The importance value must be expressed on a scale of 0 (not important) to 10 (essential).
- 1.2.4 The user may specify the importance of healthcare.
 - 1.2.4.1 The importance value must be expressed on a scale of 0 (not important) to 10 (essential).
- 1.2.5 The user may specify the importance of amenities.
- 1.2.5.1 The importance value must be expressed on a scale of 0 (not important) to 10 (essential).
- 1.2.6 The user may specify the importance of housing.
- 1.2.6.1 The importance value must be expressed on a scale of 0 (not important) to 10 (essential).
- 1.2.7 Where a user does not specify an importance value for a comparison factor, the system must apply a default weight of 5.

1.3 Users must be able to view neighbourhood comparisons.

- 1.3.1 The system must retrieve relevant government data for the selected neighbourhoods.

- 1.3.2 The system must process the retrieved data.
- 1.3.3 The system must calculate a category score for each selected neighbourhood.
- 1.3.3.1 Where data for a comparison factor is unavailable for a selected neighbourhood, the system must indicate this to the user rather than substituting a default score.
- 1.3.4 The system must calculate an overall score for each selected neighbourhood.
- 1.3.5 The system must rank the selected neighbourhoods by overall score.
- 1.3.5.1 Where two or more neighbourhoods receive an equal overall score, the system must display them as joint-ranked rather than arbitrarily ordering them.

1.4 Users must receive a neighbourhood recommendation.

- 1.4.1 The system must identify the highest-scoring neighbourhood.
- 1.4.2 The system must display the recommended neighbourhood.
- 1.4.2.1 The displayed recommendation must include the comparison factors that contributed most to the recommended neighbourhood's score.

1.5 Users may answer additional preference questions.

- 1.5.1 The system must ask an additional preference question when a selected neighbourhood's data for a comparison factor exceeds a defined threshold (e.g. population density above 5).
- 1.5.2 The user may provide a response to an additional preference question.
- 1.5.2.1 Where the user does not respond to an additional preference question, the system must proceed using a default value of 5 for that factor's scoring.
- 1.5.3 The system must incorporate the user's response into the scoring process.

1.6 Users must be able to view comparison results visually.

- 1.6.1 The system must display category scores.
- 1.6.2 The system must display overall scores.
- 1.6.3 The system must display comparison results using charts.
- 1.6.4 The system must display the selected neighbourhoods' locations on a map, subject to the Map/Geocoding Service decision (see the companion Use Case Model).

2. The system must maintain up-to-date neighbourhood data.

2.1 The system must periodically refresh neighbourhood data from the Government Data Source.

- 2.1.1 The refresh interval must be 3 months.

2.2 Where the Government Data Source is unavailable during a scheduled refresh, the system must continue operating using the most recent successful data snapshot.

Non-Functional Requirement

Category	Requirement
Usability	80% of first-time users shall be able to complete a full neighbourhood comparison — selecting neighbourhoods, setting preferences, and viewing a recommendation — without external help, within 10 minutes.
Performance	The system shall display comparison results within 30 seconds of the user confirming their preferences, given neighbourhood data has already been retrieved and cached.
Reliability	The system shall handle invalid user input and an unavailable data source without crashing or terminating unexpectedly.
Supportability	The system shall be built from modular components, such that a new comparison factor or neighbourhood data source can be added without modifying the core scoring engine. (Renamed from “Maintainability” to match the syllabus term — same intent.)
Scalability	The system should continue to meet the Performance target above as the number of tracked neighbourhoods and comparison factors grows.
Accuracy	Given the same input data and preference weights, a manual recalculation using the documented scoring formula shall match the system's computed score within exact to 1 decimal place (± 0.05) tolerance.
Transparency	The system shall display enough information about how a recommendation was calculated (per 1.4.3) that a user can identify which comparison factors drove the result.


Compatibility	The system shall operate correctly on the latest two versions of standard desktop web browsers (e.g. Chrome, Firefox, Edge, Safari).
Security	The system shall not require account creation and shall not collect personally identifiable information; preference weights are held only for the current session.

Data Dictionary:

Term	Definition
Neighbourhood	A URA Planning Area, used by the system as the geographical unit for selecting and comparing locations in Singapore.
Comparison Factor	One of the five criteria the system uses to evaluate and compare neighbourhoods: public transport, greenery, healthcare, amenities, and housing.
User Preference	A value from 0 (not important) to 10 (essential) that a user assigns to a Comparison Factor, representing how much that factor should influence a neighbourhood's Overall Neighbourhood Score.
Neighbourhood Data	Information about a neighbourhood's public transport, greenery, healthcare, amenities, and housing, obtained from the Government Data Source.
Category Score	A value from 0 to 10 representing how well a neighbourhood performs on a single Comparison Factor, before User Preference values are applied.
Overall Neighbourhood Score	The weighted combination of a neighbourhood's Category Scores and the user's Preference values, used to rank the selected neighbourhoods.
Recommendation	The selected neighbourhood with the highest Overall Neighbourhood Score, together with the Comparison Factors that contributed most to that score.
Additional Preference Question	A follow-up question the system asks about a notable characteristic of a selected neighbourhood — such as population density — that is not captured by the standard Comparison Factors.

Government Data Source	data.gov.sg and other government agency APIs (e.g. URA, LTA, NParks, MOH) from which Neighbourhood Data is retrieved.
-------------------------------	---

Use Case Diagram:



Use Case Description

Use Case ID:	UC-1		
Use Case Name:	Set Category Preferences		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (initiating)
Description:	The User assigns an importance value to each comparison factor, producing the weight set that all scoring is based on.
Preconditions:	The User has launched the app and the five comparison factors defined in the Data Dictionary are available for display (FR 1.2.1).
Postconditions:	Every comparison factor holds an importance value for the current session — either specified by the User or the default weight applied under FR 1.2.7.
Priority:	High
Frequency of Use:	Once per session; revisable at any time, including after results have been shown.
Flow of Events:	1. User opens the preferences screen. 2. System displays the five comparison factors defined in the Data Dictionary (FR 1.2.1). 3. User specifies an importance value from 0 (not important) to 10 (essential) for one or more factors (FR 1.2.2–1.2.6 and their bounds). 4. System applies the default weight 5 to any factor the User left unspecified (FR 1.2.7). 5. System stores the weight set for the session. 6. System I whether any selected neighbourhood has a notable trait relative to the weight set; if so, the extension point at this step invokes UC-2.
Alternative Flows:	A1 — User revises a weight after results have been displayed: system stores the revised weight set and UC-4 re-runs against it; returns to step 5.
Exceptions:	E1 — The comparison factor list fails to load: system displays a retry prompt and the use case terminates with no stored weight set.

Includes:	None.
Special Requirements:	The weighting control mechanism is fixed point allocation.
Assumptions:	Weights are independent of one another, and the scoring model treats preferences as compensatory — a low score on one factor can be offset by a high score on another.
Notes and Issues:	Extension point "notable trait detected" at step 6; extended by UC-2 under the guard [notable trait detected]. An earlier draft blocked confirmation until at least one factor carried a non-zero weight. FR 1.2.7's default-weight rule supersedes that: a fully unspecified weight set is now valid, so the block has been removed.

Use Case ID:	UC-2		
Use Case Name:	Answer Clarifying Preference Question		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (initiating)
Description:	When a selected neighbourhood's data for a comparison factor exceeds a defined threshold, the system asks a plain-language follow-up question and folds the answer into scoring.
Preconditions:	UC-1 is in progress or complete, and at least one selected neighbourhood's data for a comparison factor exceeds the defined threshold — for example population density above 5(FR 1.5.1).
Postconditions:	The User's response, or the default value applied under FR 1.5.2.1 where no response is given, is recorded and available to UC-6's scoring.
Priority:	Medium
Frequency of Use:	Conditional; 0 to n times per session, depending on the neighbourhoods selected.
Flow of Events:	1. System detects that a selected neighbourhood's data for a comparison factor exceeds the defined threshold (FR 1.5.1). 2. System asks a plain-language question, e.g. "Would you mind high population density?" 3. User provides a response (FR 1.5.2). 4. System incorporates the response into the scoring process (FR 1.5.3). 5. Control returns to UC-1.
Alternative Flows:	A1 — User dismisses the question without answering: system proceeds using the default value 5 for that factor's scoring (FR 1.5.2.1) and returns to UC-1 at step 5.

Exceptions:	None identified. This use case has no unrecoverable failure mode — every path returns control to UC-1.
Includes:	None.
Special Requirements:	Both the threshold that triggers the question and the default value applied when it goes unanswered are 5.
Assumptions:	One follow-up question per flagged factor is sufficient, and the answer adjusts that factor's contribution to the score rather than acting as a hard filter that excludes a neighbourhood outright.
Notes and Issues:	«extend» of UC-1 at extension point "notable trait detected"; guard condition [notable trait detected]. Must not be merged into UC-1's main flow — it runs only when the condition holds, never unconditionally.

Use Case ID:	UC-3		
Use Case Name:	Select Neighbourhoods to Compare		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (initiating)
Description:	The User chooses the set of neighbourhoods (URA Planning Areas) that the comparison will be run over.
Preconditions:	At least one successful data refresh has completed (UC-7), so a list of available neighbourhoods exists in the local store.
Postconditions:	Between 2 to 4 neighbourhoods are selected and held for the current session.
Priority:	High
Frequency of Use:	Once per session; revisable at any time.
Flow of Events:	1. System displays the list of available neighbourhoods, drawn from the URA Planning Areas defined in the Data Dictionary (FR 1.1.1). 2. User selects a neighbourhood (FR 1.1.2). 3. User repeats step 2 until between 2 to 4 neighbourhoods are selected (FR 1.1.2.1). 4. System stores the selection for the session.
Alternative Flows:	A1 — User deselects a neighbourhood: system removes it from the selection and returns to step 2. A2 — User attempts to proceed with fewer than two neighbourhoods selected: system blocks and prompts for a second selection (FR 1.1.2.1); returns to step 2.

Exceptions:	E1 — The neighbourhood list fails to load: system displays a retry prompt and the use case terminates with no stored selection.
Includes:	None.
Special Requirements:	The upper bound on how many neighbourhoods may be compared at once is 4.
Assumptions:	A URA Planning Area is the unit of comparison, and every Planning Area is a plausible candidate unless an inclusion rule says otherwise.
Notes and Issues:	Open issue: whether non-residential Planning Areas (e.g. Central Water Catchment) appear in the list at all. Without an inclusion rule the comparison set may contain areas nobody would be choosing between.

Use Case ID:	UC-4		
Use Case Name:	View Neighbourhood Ranking & Recommendation		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (initiating)
Description:	The User requests the comparison; the system scores and ranks the selected neighbourhoods and presents the highest-scoring one as the recommendation, with the factors that drove it.
Preconditions:	UC-3 has produced between 2 and 4 selected neighbourhoods, and UC-1 has produced a complete weight set (User-specified or defaulted).
Postconditions:	The selected neighbourhoods are displayed in rank order, with the highest-scoring one shown as the recommendation together with the comparison factors that contributed most to its score.
Priority:	High
Frequency of Use:	Every session; re-runs whenever the weight set or the selection changes.
Flow of Events:	1. User requests the comparison. 2. System retrieves the relevant government data for the selected neighbourhoods from the local store (FR 1.3.1). 3. System processes the retrieved data (FR 1.3.2). 4. System invokes UC-6 to compute a category score per factor and an overall score for each selected neighbourhood (FR 1.3.3, FR 1.3.4). 5. System ranks the selected neighbourhoods by overall score (FR 1.3.5). 6. System identifies the highest-scoring neighbourhood (FR 1.4.1). 7. System displays the recommended neighbourhood together with the comparison factors that contributed most to its score (FR 1.4.2, FR 1.4.2.1). 8. System invokes UC-9 to display the results visually.

Alternative Flows:	A1 — Two or more neighbourhoods share the top overall score: system displays them as joint-ranked rather than arbitrarily ordering them (FR 1.3.5.1); continues at step 7.
Exceptions:	E1 — UC-6 cannot produce a score for a selected neighbourhood because data for a comparison factor is unavailable: system indicates the unavailable factor to the User rather than substituting a default score (FR 1.3.3.1), and continues ranking the remaining neighbourhoods. E2 — No successful data refresh has ever completed and no seed data exists: there is nothing to score against; the use case terminates with a message to the User.
Includes:	UC-6 Compute Neighbourhood Scores UC-9 View Comparison Results Visually
Special Requirements:	Results must be displayed within 30 seconds of the User confirming preferences, given that neighbourhood data has already been retrieved and cached (Performance NFR).
Assumptions:	The overall score is a weighted sum of category scores, and the output is presented as the best match for the stated preferences rather than as an objective quality ranking of the towns.
Notes and Issues:	Extended by UC-5 at extension point "user requests explanation" (step 7), under the guard [user requests explanation]. This is the model's one goal-level use case — the reason a User opens the app at all. Every other use case exists in service of it.

Use Case ID:	UC-5		
Use Case Name:	View Score Explanation		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (initiating)
Description:	The User opens a fuller breakdown of how a displayed neighbourhood's overall score was arrived at.
Preconditions:	UC-4 has displayed a ranking and a recommendation.
Postconditions:	The User has seen the per-factor contributions behind the displayed score. No stored state changes.
Priority:	High
Frequency of Use:	Optional; 0 to n times per session, at the User's discretion.

Flow of Events:	1. User requests the explanation for a displayed neighbourhood. 2. System displays that neighbourhood's category scores (FR 1.6.1) and its overall score (FR 1.6.2). 3. System displays how each comparison factor contributed to the overall score, ordered by size of contribution. 4. Control returns to the ranking displayed by UC-4.
Alternative Flows:	A1 — Data for a comparison factor was unavailable for this neighbourhood: the explanation states that the factor was excluded rather than showing it as a zero contribution (FR 1.3.3.1); continues at step 4.
Exceptions:	None identified. Every path returns control to UC-4.
Includes:	None.
Special Requirements:	The explanation must contain enough information for a User to identify which comparison factors drove the result (Transparency NFR). Contributions are ranked by weighted contribution, calculated as the recommended neighbourhood's category score $\times$ the User's importance weight for that factor. The three largest contributions are displayed to the User.
Assumptions:	Users read the explanation to sanity-check a recommendation, not to re-derive the arithmetic themselves.
Notes and Issues:	«extend» of UC-4; guard condition [user requests explanation]. Optional by definition — it never executes unless the User asks for it, which is why it is an extend and not an include.

Use Case ID:	UC-6		
Use Case Name:	Compute Neighbourhood Scores		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (via UC-4). This use case is never triggered directly by an actor.
Description:	Computes a category score for each comparison factor and a weighted overall score for each selected neighbourhood.
Preconditions:	A weight set exists (UC-1), a selection of neighbourhoods exists (UC-3), and locally stored neighbourhood data is available (UC-7, or the retained snapshot from UC-8).
Postconditions:	Each selected neighbourhood holds a category score per comparison factor and one overall score, returned to UC-4.
Priority:	High
Frequency of Use:	Every time UC-4 runs, including on every change to the weight set.

Flow of Events:	1. System reads the stored neighbourhood data for each selected neighbourhood from the local store. 2. System normalises each comparison factor's raw data into a category score from 0 to 10 (FR 1.3.3). 3. System multiplies each category score by the User's importance value for that factor, or by the default weight where none was specified (FR 1.2.7). 4. System sums the weighted category scores into one overall score for the neighbourhood (FR 1.3.4). 5. System repeats steps 1–4 for each selected neighbourhood and returns the scores to UC-4.
Alternative Flows:	A1 — The most recent refresh failed for one dataset: system uses the last-known-good value retained by UC-8 for that factor and continues at step 2.
Exceptions:	E1 — Data for a comparison factor is unavailable for a neighbourhood: system omits that factor from the neighbourhood's overall score and flags it as unavailable rather than substituting a default score (FR 1.3.3.1).
Includes:	None.
Special Requirements:	A manual recalculation using the documented scoring formula must equal the system's computed score to 1 decimal place (Accuracy NFR). Category scores are derived by percentile rank across all in-scope Planning Areas, scaled to 0–10 and computed during data refresh. Spatial aggregation is defined per comparison factor: proximity from the Planning Area centroid to the nearest facilities for sparse facility types (healthcare, public transport), and facility density for abundant types (greenery, amenities).
Assumptions:	Category scores are comparable across factors once normalised, and preferences are compensatory and linear so that a weighted sum is a defensible model.
Notes and Issues:	«include» of UC-4 — it always executes when UC-4 runs, which is why it carries no guard condition. Read only from the local store, never live from the Government Data Source. This is what keeps the Performance NFR achievable.

Use Case ID:	UC-7		
Use Case Name:	Refresh Government Neighbourhood Data		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	Initiating actor: NULL (system-triggered on a schedule). Participating actor: Government Data Source.
---------------	---

Description:	On a schedule, the system fetches current extracts from the Government Data Source, validates them, and replaces the local data snapshot.		
Preconditions:	A prior data snapshot exists, or seed data has been loaded manually for the first run.		
Postconditions:	The local per-factor, per-Planning-Area store is no older than the refresh interval and carries a refresh timestamp.		
Priority:	High		
Frequency of Use:	Periodic; refresh interval 3 months (FR 2.1.1).		
Flow of Events:	1. System wakes on schedule (FR 2.1). 2. System requests the current extract for each tracked dataset from the Government Data Source. 3. System validates each response against the expected schema. 4. System writes the validated data into the local store, replacing the previous snapshot. 5. System records the refresh timestamp.		
Alternative Flows:	A1 — One dataset's endpoint has changed or moved: system retains the previous snapshot for that dataset only, logs the failure, and continues refreshing the remaining datasets; returns to step 2 for the next dataset.		
Exceptions:	E1 — The Government Data Source is unavailable during the scheduled refresh: UC-8 is invoked and the system continues operating on the most recent successful snapshot (FR 2.2). E2 — No successful refresh has ever completed and no seed data exists: the app has nothing to score against; UC-4 and UC-6 cannot run until this is resolved manually.		
Includes:	None.		
Special Requirements:	The refresh interval and the per-dataset schema contracts are 3 months, pending a decision on endpoint stability.		
Assumptions:	data.gov.sg dataset IDs and API versions remain stable between refreshes, and a stale but valid snapshot is preferable to no data at all.		
Notes and Issues:	The initiating actor is NULL — no user triggers this use case. A "Scheduler" actor must not be introduced to stand in for the trigger, as a scheduler is internal to the system and not an external entity. Extended by UC-8 at extension point "data source unavailable".		

Use Case ID:	UC-8		
Use Case Name:	Serve Last-Known-Good Snapshot		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	Initiating actor: NULL (system-triggered). No human actor participates.
Description:	When a scheduled refresh cannot reach the Government Data Source, the system keeps serving the most recent successful snapshot so that comparisons remain available.
Preconditions:	A scheduled refresh (UC-7) has failed to reach the Government Data Source, and at least one successful snapshot exists in the local store.
Postconditions:	The previous snapshot remains the active data set, the app continues to serve comparisons, and the failed refresh attempt is logged with its timestamp.
Priority:	High
Frequency of Use:	Conditional; only when a scheduled refresh fails.
Flow of Events:	1. System detects that the Government Data Source did not respond, or returned an invalid response, during a scheduled refresh. 2. System retains the most recent successful snapshot as the active data set (FR 2.2). 3. System logs the failed refresh attempt and its timestamp. 4. System continues serving comparisons from the retained snapshot.
Alternative Flows:	A1 — Only some datasets failed: system retains the previous snapshot for those datasets only and keeps the newly refreshed data for the rest; continues at step 3.
Exceptions:	E1 — No successful snapshot has ever been stored: there is nothing to fall back to, and the app cannot serve comparisons until a refresh succeeds or seed data is loaded manually.
Includes:	None.
Special Requirements:	Whether the age of the served snapshot is surfaced to the User, and after how long a stale snapshot should be treated as unusable, are 12 months.
Assumptions:	Government data changes slowly enough that a snapshot one refresh interval out of date still supports a defensible comparison.
Notes and Issues:	«extend» of UC-7; guard condition [data source unavailable]. Added to cover FR 2.2, which previously had no use case representing it in the model.

Use Case ID:	UC-9		
Use Case Name:	View Comparison Results Visually		
Created By:	SC2006 Team 5	Last Updated By:	SC2006 Team 5
Date Created:	8 Sep 2026	Date Last Updated:	8 Sep 2026

Actor:	User (via UC-4). Participating actor: Map / Geocoding Service.
---------------	--

Description:	Presents the comparison as scores and charts, and shows the selected neighbourhoods' locations on a map.
Preconditions:	UC-4 has produced category scores and overall scores for the selected neighbourhoods.
Postconditions:	The User has been shown category scores, overall scores, a chart view of the comparison, and the selected neighbourhoods plotted on a map.
Priority:	High
Frequency of Use:	Every time UC-4 runs.
Flow of Events:	1. System displays the category scores for each selected neighbourhood (FR 1.6.1). 2. System displays the overall score for each selected neighbourhood (FR 1.6.2). 3. System displays the comparison results using charts (FR 1.6.3). 4. System requests map tiles, and any coordinates it does not already hold, from the Map / Geocoding Service. 5. System displays the selected neighbourhoods' locations on the map (FR 1.6.4).
Alternative Flows:	A1 — The Map / Geocoding Service is unreachable: system displays the score and chart views without the map, states that the map is unavailable, and completes the use case.
Exceptions:	E1 — No scores are available for any selected neighbourhood: there is nothing to chart or plot; the use case terminates and UC-4 reports the failure to the User.
Includes:	None.
Special Requirements:	Category scores for each comparison factor are displayed as a grouped horizontal bar chart (one group per factor, one bar per selected neighbourhood), with overall scores shown as a separate bar chart. Neighbourhood locations are rendered from locally held Planning Area boundary geometry; no external map tile service is used, so no external request volume or cost is incurred.
Assumptions:	Planning Area boundary geometry is held locally from the government boundary dataset; the Map / Geocoding Service supplies map tiles and, where a source dataset lacks coordinates, geocoding.
Notes and Issues:	«include» of UC-4 — it always executes when UC-4 runs, which is why it carries no guard condition. Added to cover FR 1.6, which previously had no use case representing it in the model. The Map / Geocoding Service association sits here rather than on UC-6, because the external service is needed for display, not for scoring arithmetic.

UI Mockups

N

NeighbourFit · SG

1 Select

2 Preferences

3 Results

Requirement tags

Which neighbourhoods are you weighing up?

Pick between two and 4 planning areas to compare. You can change the set any time.

UC-3 Select NeighbourhoodsFR 1.1.1 · list from URA Planning AreasFR 1.1.2.1 · 2 to [TBD] areas

Search planning areas...

Clementi

URA Planning Area

Tampines

URA Planning Area

Queenstown

URA Planning Area

Jurong West

URA Planning Area

Woodlands

URA Planning Area

Bishan

URA Planning Area

Ang Mo Kio

URA Planning Area

Bedok

URA Planning Area

Punggol

URA Planning Area

Selected (3/4)

Clementi

Tampines

Queenstown

Ready to compare 3 areas.

Set preferences

UC-3 · A2 blocks < 2 selected

Demo controls

Toggle the alternate flows the use cases describe — for showing graders the edge cases, not part of the everyday UI.

List load error (UC-3 · E1)

Clarifying question (UC-2)

Map unavailable (UC-9 · A1)

Note: Queenstown is seeded with missing healthcare data, so the results screen also shows the "unavailable ≠ zero" behaviour (FR 1.3.3.1) without any toggle.

SC2006 Software Engineering · Lab 1 UI mockup · Neighbourhood Comparison App · Team 5. Screens are illustrative; values are placeholder data.

How much does each factor matter to you?

Slide each factor from 0 (not important) to 10 (essential). Anything you leave untouched uses a default weight of 5.

UC-1 Set Category Preferences

FR 1.2.1 · five factors

FR 1.2.2~1.2.6 · scale 0~10

FR 1.2.7 · default weight

? One quick question

Tampines is fairly dense. Would higher population density bother you?

Yes, I'd prefer quieter

No, that's fine

Skip

UC-2 «extend» · FR 1.5

skip → default [TBD] (FR 1.5.2.1)

Public transport

5



Not important

Essential

Using default weight of 5 — move the slider to set your own.

Greenery

5



Not important

Essential

Using default weight of 5 — move the slider to set your own.

Healthcare

5



Not important

Essential

Using default weight of 5 — move the slider to set your own.

Amenities

5



Not important

Essential

Using default weight of 5 — move the slider to set your own.

Housing

5



Not important

Essential

Using default weight of 5 — move the slider to set your own.

[← Back](#)[See results](#)

Demo controls

Toggle the alternate flows the use cases describe — for showing graders the edge cases, not part of the everyday UI.

[List load error \(UC-3 · E1\)](#)[Clarifying question \(UC-2\)](#)[Map unavailable \(UC-9 · A1\)](#)

Note: **Queenstown** is seeded with missing healthcare data, so the results screen also shows the “unavailable ≠ zero” behaviour (FR 1.3.3.1) without any toggle.

Here's how they compare

Ranked by how well each area fits the preferences you set.

[UC-4 View Ranking & Recommendation](#)[UC-9 «include» Visual Results](#)[UC-6 «include» Compute Scores](#)[★ Best fit for you](#)

Tampines

Highest overall score across your 3 areas


Driven by [Amenities](#) [Healthcare](#) [Public transport](#)

8
out of 10

[FR 1.4.2.1 · top contributing factors](#)


Overall ranking

Weighted score for each area · tap a name for the breakdown.

[FR 1.3.5 rank](#)[FR 1.3.3.1 unavailable ≠ zero](#)[FR 1.3.5.1 joint rank](#)


Factor profiles

Category scores (0–10) per factor, before your weights.

[FR 1.6.1–1.6.3 · charts](#)

On the map

Where your selected areas sit across Singapore.

[FR 1.6.4 · locations on map](#)[UC-9 · Map/Geocoding Service](#)[← Adjust preferences](#)[Change areas](#)

Demo controls

Toggle the alternate flows the use cases describe — for showing graders the edge cases, not part of the everyday UI.

[List load error \(UC-3 · E1\)](#)[Clarifying question \(UC-2\)](#)[Map unavailable \(UC-9 · A1\)](#)

Note: **Queenstown** is seeded with missing healthcare data, so the results screen also shows the “unavailable ≠ zero” behaviour (FR 1.3.3.1) without any toggle.

Here's how they compare

Ranked by how well each area fits the preferences you set.

UC-4 View Ranking & Recommendation

UC-9 «include» Visual Results

UC-6 «include» Compute Scores

★ Best fit for you

Tampines

Highest overall score across your 3 areas

Driven by Amenities Healthcare

FR 1.4.2.1 · top contributing factors

Overall ranking

Weighted score for each area · tap a name to see details

1	Tampines	
2	Queenstown	7.6
	Healthcare data unavailable — left out of the score	
3	Clementi	7.5

FR 1.3.5 rank

FR 1.3.3.1 unavailable ≠ zero

FR 1.3.5.1 joint rank

Queenstown

Why it scored 7.6 — factors ordered by contribution.


Public transport	score 9 × weight 5
Amenities	score 8.5 × weight 5
Greenery	score 6.9 × weight 5
Housing	score 5.8 × weight 5

Healthcare data isn't available for Queenstown, so it was left out of the score rather than counted as zero.

UC-5 «extend» View Score Explanation

Transparency NFR

8
out of 10



■ Clementi ■ Tampines ■ Queenstown

FR 1.6.1~1.6.3 · charts

Your PDF report on the AI's critique of your Use Case diagram and requirements

AI critique:

Prompt:

[/mattpocock-skills:grill-me](#) this is a lab project under the course software engineering and here are the ideas and deliverables. What do you think and give some critiques.

Response:

No existing project directory for this, so I'm grilling the documents as written.

Quick verdict before the questions: the *scoping* work is genuinely good — defining "neighbourhood" as a URA Planning Area is the right call and is the kind of thing that earns marks. The requirements numbering is clean and the Data Dictionary is real. But the whole document has a hole in the middle: **it never defines how a Category Score comes to exist.** Every hard question in this project lives in the gap between "MRT exits GeoJSON" and "8.5". Right now the doc says "The system must process the retrieved data" (1.3.2) and then a 0–10 number appears. That's the project. Everything else is a UI over a weighted sum you could write in ten minutes.

Also flagging four concrete defects to fix regardless of how you answer below: (a) the Transparency NFR cites "per 1.4.3", which doesn't exist — you renumbered to 1.4.2.1; (b) Schools appears in your Step-1 mockup but the requirements and Data Dictionary say five factors; (c) 1.3.3.1 (don't substitute a score for missing data) directly contradicts 1.3.4/1.3.5 (compute an overall score and rank) — with a factor missing, you cannot produce a comparable overall score, and the doc doesn't say what happens; (d) 1.3.5.1 promises joint ranking on equal scores, but with floating-point weighted sums exact ties never occur, so as written that requirement is unreachable code.

? Q1 — What is actually being graded, and what stack are you locked into?: "API classes → Data models → Data processing → Scoring → UI" reads like a Java/UML SE course deliverable, but your Compatibility NFR says desktop web browsers. Those imply very different projects. Which is it — Java desktop/OOP with a class diagram as a deliverable, or a web app? And is the grading weighted

toward the *documentation* (requirements, use cases, class diagrams, test plans) or toward a working artefact? This decides whether a geospatial join is even feasible for you, because the library situation differs sharply by language.

→ Tell me the mandated language and the full deliverable list. If it's free choice, I'd say Python + a thin web UI: Shapely/GeoPandas make the point-in-polygon work a non-issue, which is otherwise the single biggest technical risk in this project.

? Q2 – Live API at runtime, or a build-time snapshot committed to the repo?: FR 2.1 mandates periodic refresh from the Government Data Source, and 2.2 mandates fallback to the last snapshot. Consider what you're buying. These datasets change roughly annually (planning-area boundaries, MRT exits, park locations); HDB resale is the only monthly one. Meanwhile data.gov.sg's newer download API is poll-based — you initiate a download, poll for readiness, then fetch a URL — which is fiddly, rate-limited, and will fail during your demo at some point.

The alternative: an offline ETL script (`refresh_data.py`) that hits the APIs, does the spatial joins, and writes a versioned `neighbourhoods.json` snapshot into the repo. The app reads only the snapshot. You still *demonstrate* API integration — the script is the API integration — and you keep FR 2.2's spirit while making Performance and Reliability trivially satisfiable and your demo network-independent.

→ Snapshot. Rewrite 2.1 as "the system shall provide a documented data-refresh procedure that regenerates the neighbourhood dataset from the Government Data Source". A refresh interval you can't demonstrate is a requirement you'll be asked to justify and can't.

? Q3 – Is a Category Score relative to the neighbourhoods the user selected, or absolute across all of Singapore?: This is the most consequential unstated decision in the document and it has no comfortable answer.

Relative to selection (min-max across the 2–N chosen areas): the winner always scores 10 and the loser always 0, so scores are readable, but they're unstable — add Woodlands as a fourth option and Clementi's transport score silently changes. Users find this deeply weird, and it makes your Accuracy NFR harder to state.

Absolute across all planning areas (each area is normalised once, against the national min/max, at ETL time): scores are stable, cacheable, and honest. The cost is that comparing three mature towns gives you the clustered, meaningless-looking numbers in your own example table — 9.2 vs 9.0 vs 8.8 — where the visible spread is noise. Note that your mock table is itself evidence of the problem: every value sits between 7.5 and 9.2, so the weights barely matter and the ranking is decided by rounding.

→ Absolute, computed at ETL time — but normalise against percentile rank across planning areas rather than min-max. Percentile spreads the mid-range out (so Clementi and Tampines actually separate) and kills outlier domination, where one extreme area like Downtown Core squashes everyone else into 8–9. Then say so explicitly in the Data Dictionary: "Category Score: the neighbourhood's percentile rank among all in-scope neighbourhoods on that factor, scaled 0–10."

? Q4 — What shape is the underlying metric: count inside the boundary, density, or distance to nearest?: Right now "Neighbourhood Data" is undefined, and the three options give different answers.

Count inside the polygon is the obvious one and is wrong for sparse facilities. Singapore has roughly 20 public hospitals across ~55 planning areas, so most areas score a hard zero on healthcare and the factor becomes near-binary noise. It also ignores that a Clementi resident uses the hospital in Queenstown.

Density (per km² or per 1,000 residents) fixes size bias but breaks on planning areas with negligible population, and per-km² rewards tiny dense areas absurdly.

Distance from the area's centroid to the nearest N facilities is what "how good is healthcare here" actually means, handles cross-boundary use correctly, and never produces a structural zero.

→ Mix by factor, and document why: proximity for sparse facilities (healthcare, MRT), density for abundant ones (amenities, parks). Use a population-weighted centroid if you can get subzone population, plain polygon centroid if not — and note the limitation, because a plain centroid for a coastal or odd-shaped area can land somewhere nobody lives.

? Q5 — Which planning areas are in scope?: There are ~55 planning areas, and a substantial number have essentially no residents — Western Water Catchment, Central Water Catchment, Tuas,

Changi Bay, Marina South, Simpang, Lim Chu Kang, the North-Eastern Islands. If you ingest the URA dataset wholesale (which was the appeal of the approach), your dropdown offers users the option to move to a reservoir, and – more damagingly under Q3 – those areas sit in the normalisation baseline and drag the distribution.

→ Filter to residential planning areas using a population threshold from the SingStat / data.gov.sg residents-by-planning-area dataset (say, $\geq 5,000$ residents), and state the rule in your scope assumptions. That's defensible, automatic, and it demonstrates a documented inclusion criterion, which reads better than a hand-picked list.

? Q6 – Which direction is "good" for Housing, and how do you handle the HDB town mismatch?:

Two problems bundled here. First, direction: for a buyer, cheaper is better; if you score housing so that expensive = high, you're rewarding the thing the user wants to avoid. Your requirements never say. Second – and this one will bite you in implementation – the HDB resale-price dataset is keyed by **HDB town**, not URA planning area. They are not the same set: HDB has "KALLANG/WHAMPOA" and "CENTRAL AREA"; URA has separate Kallang and Novena and Downtown Core. Some planning areas have no HDB stock at all. So "join housing to planning area" needs a hand-written mapping table plus a policy for unmapped areas. There's also a confound: median resale price mostly measures *flat size mix*, so Sengkang's 5-room-heavy stock looks expensive next to Bishan's 3-room-heavy stock.

→ Define housing as *affordability* (lower median price → higher score), control for flat type by fixing on a single type (4-room, the most widely available) so you're comparing like with like, and ship an explicit `hdb_town → planning_area` mapping file as a documented project artefact. Areas with no 4-room resale transactions in the window become genuine missing data – which is exactly the case 1.3.3.1 needs to handle, and which Q3/Q4 don't rescue you from.

? Q7 – Does FR 1.5, the Additional Preference Question, survive?: As written it's a conditional mid-flow question triggered when some data value crosses a threshold, whose answer is then "incorporated into the scoring process" by an unspecified mechanism, with an unspecified default when unanswered. It also breaks your Accuracy NFR ("a manual recalculation using the documented scoring formula shall match"), because the formula now changes shape depending on the data. For the marginal value of asking "do you mind crowds?", it's a whole subsystem.

➡ Cut it, and replace it with population density as a plain sixth comparison factor with a user-chosen direction ("prefer quieter" / "prefer livelier" / "don't care"). Same insight, no conditional logic,, and it slots into the existing weighted formula unchanged. If your course rewards demonstrating conditional/alternate flows in a use case model, keep 1.5 in the *use case model* as an extension, not in the scoring engine.

Answer these and I'll take the next round: missing-data policy, weight normalisation (right now all-5s and all-10s give identical rankings but triple the overall score – and all-zeros divides by zero), what "contributed most" should actually mean in the explanation, and rewriting the NFRs into things you can actually verify in a lab report.

Prompt:

before we move on, can you also give some critiques to our use case diagram

Response:

Happy to – and this one is worth doing carefully, because the diagram and the FR document are graded together and a grader's fastest source of marks-off is an inconsistency *between* two of your deliverables.

What's genuinely right

All five dependency arrows point the correct way – «include» from base to included, «extend» from extension to base. That is the single most commonly reversed thing in student use case diagrams and you got all five right. Primary actor on the left, supporting external systems on the right, is also the correct convention. And you resisted the urge to draw sequence into the diagram (no arrows implying "select neighbourhoods *then* set preferences"), which is correct – use case diagrams model goals, not flow. If a grader asks why there's no ordering, that's your answer.

The structural problem: this is functional decomposition, not use cases

A use case is a **complete goal that delivers observable value to an actor**. Apply that test:

- **UC-3 Select Neighbourhoods to Compare** — the user selects three names and... nothing happens. No value delivered.
- **UC-1 Set Category Preferences** — moves some sliders. Nothing happens. No value delivered.
- **UC-6 Compute Neighbourhood Scores** — the user cannot observe this at all. It's a function call.

These aren't use cases, they're *steps inside one use case*: "Compare Neighbourhoods". This is the classic anti-pattern (Larman calls it "use cases at the wrong level"; some courses call it the "CRUD trap") and it's specifically what SE lab rubrics look for.

The tell for UC-6 is the «include» arity: **an «include» used by exactly one base use case is not reuse, it's decomposition.** «include» exists so that two or more base use cases can share behaviour. UC-6 is included once. Same for UC-9.

UC-9 is worse — it duplicates UC-4. "View Neighbourhood Ranking & Recommendation" and "View Comparison Results Visually" are the same interaction. The user looks at one screen. You've drawn one use case as two.

➡ Collapse UC-1, UC-3, UC-4, UC-6, UC-9 into **one** use case: **"Compare Neighbourhoods"**. The selecting, weighting, computing and displaying all become numbered steps in that use case's *description* — which is a separate deliverable you're writing anyway, so nothing is lost. The detail moves to where detail belongs.

The counter-pressure is real, so name it: a diagram with two bubbles can look thin, and some tutors want to see a fuller diagram. Don't solve that by re-adding steps — solve it by adding genuine *alternate goals* (below).

UC-8 is the weakest element

«extend» means: *optional* behaviour that adds to a base which remains meaningful and complete without it. "Serve Last-Known-Good Snapshot" fails that test three ways.

1. **It isn't optional-and-additive, it's a failure substitute.** The base didn't complete and something else happened instead. That's an alternate flow in a use case description ("4a. *Data source unavailable: the system retains the existing snapshot and logs the failure*"), not a bubble.

2. **It's attached to the wrong base.** Serving a snapshot serves the *user viewing a comparison*, not the refresh job.
3. **Under the Q2 architecture you just accepted, it's the normal path.** The app *always* reads the committed snapshot. There is no fallback because there's no runtime fetch to fall back from.

➡ Delete UC-8. Fold it into UC-7's alternate flow.

initiating actor: NULL is your diagram telling you something

That annotation isn't UML, and the reason you had to invent it is the real issue: **a use case with no initiator isn't a use case**. Under Q2, UC-7 does have an initiator — a person running `python -m etl.refresh` from the command line.

➡ Add a second actor, **Maintainer** (or Developer), on the left, associated with UC-7. Rename UC-7 to **"Refresh Neighbourhood Data Snapshot"**. The annotation goes away and the diagram becomes true. This also correctly shows that your system has two distinct users with different goals, which is a *legitimate* way to make the diagram richer.

Three inconsistencies with your own FR document

These are the marks-off ones, because they're checkable by anyone reading both documents.

1. UC-5 contradicts FR 1.4.2.1. Your FR says the displayed recommendation **must include** the contributing comparison factors. Your diagram says the explanation is an «`extend`», condition `[user requests explanation]` — i.e. optional, on demand. Both cannot be true. Your Transparency NFR sides with the FR. ➡ Decide, then make both documents agree. My recommendation: the top-line explanation is *always shown* (part of the base use case, per 1.4.2.1), and the detailed per-factor breakdown stays as the «`extend`» on request. Then reword 1.4.2.1 to distinguish the two.

2. The Map/Geocoding Service actor should be deleted. Q12 settled that you render boundaries locally from the committed GeoJSON. There is no external mapping service. An external actor on the diagram that doesn't exist in the design is a straightforward error — and it drags the "subject to the Map/Geocoding Service decision" hedge in FR 1.6.4 along with it. Both go.

3. UC-2 goes with FR 1.5. Same reasoning as Q7. Population density becomes an ordinary comparison factor with no conditional question, so the `[notable trait detected]` extension disappears.

But you *should* replace it with a better «extend», because the Q8 decision hands you a real one:

«extend» [comparison factor has no data for a selected neighbourhood] → the system notifies the user and excludes that factor from the comparison.

That's a genuine conditional branch, it's user-observable, it's tied to behaviour you're actually building, and unlike UC-2 you can demonstrate it live by selecting Bukit Timah.

Two presentation notes

The three grouping rectangles aren't UML packages – a package is a folder shape with a tab. As plain nested rectangles inside the system boundary they can read as sub-system boundaries. Either draw them as proper packages or drop them; with a tightened diagram you won't need them. And the UC numbering is scrambled relative to the layout (UC-3 sits above UC-1, UC-9 between UC-6 and UC-5) – renumber in reading order once the content settles.

What the revised diagram looks like

Actors: User (left), Maintainer (left), Government Data Source (right). *Map/Geocoding Service:* deleted.

ID	Use case	Actor	Relationships
UC-1	Compare Neighbourhoods	User	—
UC-2	View Detailed Score Breakdown	—	«extend» → UC-1 [user requests breakdown]
UC-3	Refresh Neighbourhood Data Snapshot	Maintainer, Government Data Source	—

Three bubbles. If that's too spare for your rubric, the honest ways to add goal-level use cases – not steps – are: "Save / Share a Comparison" (a real second user goal, if you build it), and splitting UC-1

into "*Compare Neighbourhoods*" and "*Browse a Single Neighbourhood's Profile*" if you support looking at one area without comparing. Both are genuine goals. Adding "Select Neighbourhoods" back is not.

I can produce this as a proper rendered diagram once you've answered Q8–Q13, since the missing-data extension and the map decision both land in it.
