



◆ OFFENSIVE SECURITY SERIES ◆

iOS SETUP

Palera1n, SSH, frida-ios-dump, Burp & SSL Bypass

Palera1n · Checkra1n · SSH · Frida · Objection · Burp · IPA Extract

Palera1n JB

SSH Root

Frida iOS

frida-ios-dump

Burp Proxy

SSL Unpin

JB Bypass

RedTeamGarage (RTG) | Offensive Security Education

<https://www.redteamgarage.com/>

LEGAL DISCLAIMER

This guide is produced by RedTeamGarage (RTG) for educational purposes only. All techniques must ONLY be used on systems you own or have explicit written authorisation to test. RTG assumes zero liability for any misuse of this material.

**TABLE OF CONTENTS**

iOS SETUP — Palera1n, SSH, frida-ios-dump, Burp & SSL Bypass

01.	JAILBREAKING WITH PALERA1N
02.	SSH VIA USB + VERIFY FRIDA
03.	FRIDA-IOS-DUMP — DECRYPT IPA
04.	BURP PROXY + SSL PINNING BYPASS
05.	iOS SETUP CHEAT SHEET



01 — PALERA1N JAILBREAK

iOS 15+ Jailbreak

```
Palera1n - iOS 16 Jailbreak

# Jailbreak iOS with Palera1n (iOS 15+, A12+)
(kali)-[~]
kali $ sudo ./palera1n-linux-x86_64 -l
palera1n - A complete and utter jailbreak
palera1n version 2.0.0 (20230601.030545.1bbaade)
[*] A16 device in Normal mode
[*] Platform: arm64e
Put your device into DFU mode:
[*] Hold volume down button...
[*] While still holding volume down, hold power button for 4 seconds...
[*] Release power button, keep holding volume down for 10 more seconds.
[*] Device entered DFU mode
[*] Booting pali ramdisk...
[*] Jailbreak complete! Install Sileo/Cydia.
```

Figure: Palera1n jailbreaks iPhone running iOS 16 on A16 chip — Sileo/Cydia ready



02 — SSH & FRIDA

USB SSH + Frida Verify

```
SSH via USB + Verify Frida

# SSH to device via USB (iProxy forwarding)
(kali)-[~]
kali $ iproxy 2222 22 &
[1] 12345

(kali)-[~]
kali $ ssh -p 2222 root@localhost
The authenticity of host '[localhost]:2222' can't be established.
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added '[localhost]:2222' to the list of known hosts.
root@localhost's password:
iPhone:~ root#

# CRITICAL - change default SSH password immediately!
(kali)-[~]
kali $ passwd
Changing password for root.
New password:
Retype new password:
passwd: password updated successfully

# Verify Frida installed on device (from Frida Cydia repo)
(kali)-[~]
kali $ frida-ps -U | head -5
  PID  Name
  ----  ----
    128  backboardd
    129  CommCenter
  12847  com.target.bankingapp
```

Figure: iProxy forwards USB, SSH connects as root, default password changed, Frida active



03 — IPA EXTRACTION

Decrypt & Pull IPA

```
frida-ios-dump - Decrypt & Extract IPA

# Extract (decrypt) IPA from App Store app
(kali)-[~]
kali $ python3 dump.py com.target.bankingapp
[*] Get the target application
[*] Dumping com.target.bankingapp
Start the target app com.target.bankingapp
[*] Start get memory data
[*] Dump memory from: 0x0000000100000000 to: 0x00000001001f0000
[*] Dump memory from: 0x00000001d000c000 to: 0x00000001d01f0000
[*] Memory dump completed
[*] Generating ipa file
[+] Saved to /var/root/com.target.bankingapp.ipa

# Pull IPA to Kali
(kali)-[~]
kali $ scp -P 2222 root@localhost:/var/root/com.target.bankingapp.ipa .
com.target.bankingapp.ipa          100%  18MB  4.2MB/s   00:04

# Verify decryption (cryptid should be 0)
(kali)-[~]
kali $ unzip -q com.target.bankingapp.ipa -d ipa_extracted && otool -l ipa_extracted/Payload/BankingApp.app/BankingAp
p | grep cryptid
cryptid 0 - decrypted successfully!
```

Figure: frida-ios-dump decrypts App Store IPA, cryptid=0 confirms successful decryption



04 — BURP & SSL

Proxy + Pinning Bypass

```

Burp Proxy + iOS SSL Pinning Bypass

# Configure Burp proxy on iOS
# Settings → WiFi → (i) → HTTP Proxy → Manual: ATTACKER_IP:8080
# Browse http://burpsuite → download cert → install profile
# Settings → General → About → Certificate Trust Settings → enable full trust

# Bypass SSL pinning with objection
(kali)-[~]
kali $ objection -g com.target.bankingapp explore
Using USB device `iPhone`
Agent injected and responds ok!
com.target.bankingapp on (iOS: 16.7.5) [usb] #

(kali)-[~]
kali $ ios sslpinning disable
(agent) Loaded security framework
(agent) Disabling TrustKit via hook
(agent) SecTrustEvaluate() replaced with nop
(agent) NSURLSession SSL pinning disabled
(agent) AFNetworking SSL pinning disabled
(agent) Pinning disabled successfully
```

Figure: Burp CA trusted, objection disables all iOS SSL pinning methods — traffic intercepted



05 — CHEAT SHEET

Quick Reference

Palera1n jailbreak	<code>sudo ./palera1n-linux-x86_64 -l</code> (put in DFU mode first)
Checkra1n jailbreak	<code>sudo ./checkra1n -c</code> (A11 and older, iOS 12-14)
SSH via USB	<code>iproxy 2222 22</code> & then <code>ssh -p 2222 root@localhost</code>
Default SSH password	alpine – CHANGE IMMEDIATELY with <code>passwd</code>
Install Frida	Add repo: https://build.frida.re in Cydia/Sileo → install Frida
List processes	<code>frida-ps -U</code>
Attach objection	<code>objection -g com.pkg.name explore</code>
SSL unpin iOS	<code>ios sslpinning disable</code>
JB bypass	<code>ios jailbreak disable</code>
Burp proxy iOS	Settings → WiFi → HTTP Proxy → Manual: ATTACKER_IP:8080
Install Burp CA	Browse http://burpsuite → download → Settings → install → trust
Extract IPA	<code>python3 dump.py com.pkg.name (frida-ios-dump)</code>
Pull IPA	<code>scp -P 2222 root@localhost:/var/root/app.ipa .</code>
Verify decryption	<code>otool -l BinaryName grep cryptid</code> (0 = decrypted)
Get container path	<code>objection > env</code>
Download file	<code>file download /path/to/file</code> (in objection)



CONNECT WITH REDTEAMGARAGE (RTG)

The Community. The Knowledge. The Edge.



Official Website	https://www.redteamgarage.com/
Telegram	https://t.me/redteamgarage
LinkedIn	https://www.linkedin.com/company/redteamgarage-rtg

RTG MISSION

Real-world offensive security training - practical, no fluff, built for serious learners.

Build the most comprehensive red team technique library available anywhere.

Train the next generation of elite offensive security professionals globally.

© RedTeamGarage (RTG). All content for educational and authorized security testing only.