
OKAWA MAGNETIC PUMP





ML SERIES MAGNETIC DRIVING PUMP HAS A SEAL-LESS STRUCTURE, NEVER LEAK. It can be widely used in various application. Applied corrosion resistant material, such as GFRPP, CFRETFE. It is suitable for photo industry, plating, PCB industry, etc.

Specification

Model	CURVE	HOSE		THREADED		Max Flow	Top Head	Standard			Power	
		Inlet (≡)	Outlet (IIII)	In*Out (inch)	Union (IIII)	(L/min)	(M)	Flow (L/min)	Head (M)	Gravity	Output (W)	Phase
ML-3R	a	14	14	G1/2*G1/2	_	8.5	1	3	0.8	<1.1	3	1
ML-3RZ	b	14	14	G1/2*G1/2	-	5.8	2.1	3.5	1.5	<1.1	3	1
ML-10R	c	14	14	G1/2*G1/2	==	12	1.5	6		<1.1	10	£
ML-20R	d	14	14	G3/4*G3/4	13mm	17	2.4	8	1.5	<1.1	20	
ML-20R	e	18	18	G3/4*G3/4	16mm	28	3.1	17	2	<1.1	20	1
ML-20RX	f	26	26	G1*G1	20mm	47	1.8	30	1	<1.1	20	1
ML-20RZ	9	18	18	G3/4*G3/4	13mm	11	4.9	7	4	<1.1	20	1
ML-45R	h	20	20	G3/4*G3/4	16mm	35	3.8	16	2.5	<1.1	45	- 1
ML-45RX	1	26	26	G1*G1	20mm	62	2.9	32	2	<1.1	45	1
ML-45RZ	1	18	18	G3/4*G3/4	13mm	15	8	11	6	<1.1	45	1
ML-65R	k	20	20	G3/4*G3/4	16mm	45	4.6	22	4	<1.1	65	1
ML-65RX	1	26	26	G1*G1	20mm	78	3.3	48	2	<1.1	65	1
ML-65RZ	m	22	22	G3/4*G3/4	16mm	22	10	10	8	<1.1	65	1
ML-65RY	n	22	22	G3/4*G3/4	16mm	13	11.5	8	10	<1.1	65	1
ML-90R	0	26	26	G1*G1	20mm	65	5,8	30	4	<1.2	90	1or3
ML-90RX	р	26	26	G1*G1	20mm	70	8.2	48	4	<1.2	90	1or3
ML-150R	q	26	26	G1*G1	20mm	86	6.7	53	4	<1.2	150	1or3
ML-250R	r	26	26	G1*G1	20mm	125	8.6	65	6.5	<1.3	250	1or3
ML-250RX	s	26	26	G1*G1	20mm	135	11.7	65	9	<1.3	250	1or3
ML-250RZ	t	26	26	G1 ¹ /4*G11/4	32mm	180	9	110	5	<1.3	250	1or3
ML-370R	U	26	26	G1 ¹ /2*G11/2	36mm	230	10.5	150	6	<1.3	370	1or3

Struction

