MONOLITH AI PLATFORM

Complete Technical Source Code & Architecture Compilation

Monolith is an enterprise cyber-brutalist AI application with a decoupled full-stack architecture. It integrates real-time conversational streaming via the Google Gemini API, persistent conversation modelling with MongoDB, secure JWT authentication, and a terminal frontend built with React 18, Vite, and Tailwind CSS.

This document is a complete, unabridged compilation of every source file: database schemas, API controllers, middleware, utility helpers, UI component trees, and deployment configurations — all syntax-highlighted with line numbers.

Total Source Files	**52 Files**	**Target Frameworks**	**React 18 + Express.js**
Total Lines of Code	**3,381 LOC**	**AI Engine**	**Google Gemini 2.5 Flash**
Compilation Date	**November 02, 2026**	**Persistence Layer**	**MongoDB + Mongoose**

ARCHITECTURAL MODULE MAP

1. Backend Service Layer	RESTful endpoints under /api/v1 — authentication, token invalidation, conversation history, and streaming chat completions.
2. Database & Models	MongoDB schemas via Mongoose: User (bcrypt + JWT) and Chat (role-based message history).
3. AI Engine	Google @google/genai SDK — Gemini 2.5 Flash model with custom system prompts for cybernetic terminal interactions.
4. Frontend Terminal	React 18 SPA — cyber-brutalist styling, canvas particles, multi-session sidebar, markdown code blocks, auto-scroll.

TABLE OF CONTENTS

Categorised file directory and line-count index.

File / Path	Language	Lines	Size
1. Project Documentation & Repository Root			
.gitignore	Plain Text	27	252 B
README.md	Markdown	213	9.4 KB
2. Backend — Server Core & Initialisation			
Backend/.env	Plain Text	13	387 B
Backend/.gitignore	Plain Text	0	0 B
Backend/package.json	JSON	26	564 B
Backend/src/app.js	JavaScript	76	1.9 KB
Backend/src/index.js	JavaScript	17	430 B
3. Backend — Database Connection & Schemas			
Backend/src/Model/chat.model.js	JavaScript	40	718 B
Backend/src/Model/user.model.js	JavaScript	70	1.4 KB
Backend/src/db/index.js	JavaScript	26	829 B
4. Backend — Controllers & REST API Routes			
Backend/src/controller/chat.controller.js	JavaScript	96	2.3 KB
Backend/src/controller/user.controller.js	JavaScript	127	3.4 KB
Backend/src/routes/chat.routes.js	JavaScript	12	441 B
Backend/src/routes/user.routes.js	JavaScript	17	478 B
5. Backend — Middleware, AI Services & Utilities			
Backend/src/middleware/Auth.middleware.js	JavaScript	54	1.4 KB
Backend/src/service/ai.service.js	JavaScript	44	1.0 KB
Backend/src/utils/apiError.js	JavaScript	23	440 B
Backend/src/utils/apiResponse.js	JavaScript	10	231 B
Backend/src/utils/asyncHandler.js	JavaScript	7	162 B
6. Frontend — React Entry & Global Styling			
monolith-react/src/.env	Plain Text	1	43 B
monolith-react/src/App.jsx	React JSX	87	2.5 KB
monolith-react/src/index.css	CSS	99	2.0 KB
monolith-react/src/main.jsx	React JSX	10	229 B
7. Frontend — Application Pages & Terminal UI			
monolith-react/src/pages/ChatTerminal.jsx	React JSX	596	23.3 KB
monolith-react/src/pages/Landing.jsx	React JSX	38	1008 B
monolith-react/src/pages/Login.jsx	React JSX	179	7.5 KB
monolith-react/src/pages/Register.jsx	React JSX	185	8.0 KB
8. Frontend — Modular UI Components			
monolith-react/src/components/CTA.jsx	React JSX	55	2.5 KB
monolith-react/src/components/CanvasBackground.jsx	React JSX	95	2.4 KB
monolith-react/src/components/ChatInterface.jsx	React JSX	179	7.5 KB
monolith-react/src/components/Features.jsx	React JSX	102	4.3 KB
monolith-react/src/components/Footer.jsx	React JSX	61	2.4 KB
monolith-react/src/components/Hero.jsx	React JSX	67	3.2 KB
monolith-react/src/components/Navbar.jsx	React JSX	183	6.9 KB

File / Path	Language	Lines	Size
monolith-react/src/components/OperationalFlow.jsx	React JSX	87	3.7 KB
monolith-react/src/components/Stats.jsx	React JSX	73	2.3 KB
9. Frontend — Context, Custom Hooks & API Client			
monolith-react/src/context/AuthContext.jsx	React JSX	65	1.7 KB
monolith-react/src/context/AuthContextObject.js	JavaScript	3	84 B
monolith-react/src/hooks/useAuth.js	JavaScript	10	282 B
monolith-react/src/service/axios.js	JavaScript	92	2.4 KB
10. Frontend — Build Configurations & Deployment			
monolith-react/.env	Plain Text	1	42 B
monolith-react/.env.example	Env Template	1	42 B
monolith-react/.gitignore	Plain Text	24	253 B
monolith-react/README.md	Markdown	16	1.0 KB
monolith-react/eslint.config.js	JavaScript	29	758 B
monolith-react/index.html	HTML5	17	781 B
monolith-react/package.json	JSON	32	756 B
monolith-react/postcss.config.js	JavaScript	6	80 B
monolith-react/public/_redirects	SPA Redirects	1	24 B
monolith-react/tailwind.config.js	JavaScript	74	2.7 KB
monolith-react/vercel.json	JSON	8	96 B
monolith-react/vite.config.js	JavaScript	7	161 B

1. Project Documentation & Repository Root

Root configurations, system documentation, and repository specifications.

.gitignore

Plain Text | 27 lines | 252 B

```
# Environments
.env
.env.local
.env.*.local

# Dependency directories
node_modules/
jspm_packages/

# Build outputs
dist/
build/
.next/
out/

# Logs
npm-debug.log*
yarn-debug.log*
yarn-error.log*

# OS files
.DS_Store
Thumbs.db

# IDEs
.vscode/
.idea/
```

README.md


Markdown | 213 lines | 9.4 KB


```
# ■ MONOLITH


<div align="center">



### **Your Second Brain, Always On.**
*High-velocity AI assistant engineered with Groq LPU acceleration, multi-turn memory, and persistent cloud session vaults.*






```

```
15 | [![TailwindCSS](https://img.shields.io/badge/Tailwind_CSS-3.4-38B2AC?style=for-the-badge&logo=tai
■ lwind-css&logoColor=white)](https://tailwindcss.com/)
16 |
17 | [Live Demo](#deployment-guide) • [Architecture](#system-architecture) • [API Reference](#api-spec
■ ification) • [Local Setup](#local-development)
18 |
19 | </div>
20 |
21 | ---
22 |
23 | ## ■ Overview
24 |
25 | **Monolith** is a full-stack, cyber-brutalist artificial intelligence workstation designed
■ for developers, researchers, and technical operatives. Built on top of **Groq's Language Proce
■ ssing Units (LPUs)**, Monolith delivers sub-second inference speeds (~500 tokens/sec) with
■ zero cold-starts, state-of-the-art context retention across conversational turns, and
■ persistent encrypted session archives stored in MongoDB Atlas.
26 |
27 | ---
28 |
29 | ## ■ Key Capabilities
30 |
31 | - **■ Sub-Second LPU Inference**: Powered by Groq's high-throughput hardware, streaming reasoning
■ and code generation at near-instantaneous velocities.
32 | - **■ Multi-Turn Conversational Memory**: Preserves context timelines within each thread,
■ allowing deep iterative follow-ups and complex troubleshooting.
33 | - **■ Persistent Cloud Vault**: Every session is indexed to the user's operative ID in MongoDB
■ Atlas, accessible across any browser or device.
34 | - **■ Code Engineering Suite**: Automatic language detection, dedicated monospace code containers
■ , and 1-click clipboard extraction.
35 | - **■ Enterprise HttpOnly Security**: Complete protection against XSS and token interception
■ via tamper-proof JWT cookies (`accessToken` & `refreshToken`).
36 | - **■ Interactive Direct Dispatch**: Launch directives straight from the landing page terminal
■ preview or browse archived historical conversations.
37 | - **■ Responsive Cyber-Brutalist Interface**: Ultra-high contrast design, interactive plexus
■ particle canvas, fluid responsive typography, and mobile-ready drawers.
38 |
39 | ---
40 |
41 | ## ■■ Technology Stack
42 |
43 | | Layer | Technology | Description |
44 | | :--- | :--- | :--- |
45 | | **Frontend Framework** | **React 19** + **Vite 8** | Ultra-fast client-side rendering with
■ HMR |
46 | | **Frontend Styling** | **Tailwind CSS 3.4** | Custom high-contrast dark cyberpunk palette
■ |
47 | | **Client Routing** | **React Router DOM 7** | Single Page Application (SPA) with deep links
■ |
48 | | **HTTP Client** | **Axios** | Centralized response unwrap & credentials handling |
49 | | **Backend Runtime** | **Node.js** + **Express 5** | Modular REST API service with async
■ error handling |
50 | | **Database & ODM** | **MongoDB Atlas** + **Mongoose 8** | Cloud replica set database with
■ TTL token lifecycle |
51 | | **AI Inference** | **Groq SDK** (`openai/gpt-oss-120b`) | Ultra-low latency LPU model completio
■ ns |
52 | | **Authentication** | **JWT** + **Bcrypt** | Encrypted password hashing with dual-token
■ auth |
53 |
```

```
---

## ■ Project Architecture

```
Bot/
■■■ Backend/ # Express REST API Server
■ ■■■ src/
■ ■ ■■■ Model/ # Mongoose Database Models (User, Chat)
■ ■ ■■■ controller/ # Business Logic (Auth, Chat Sessions)
■ ■ ■■■ db/ # MongoDB Atlas Connection Handler
■ ■ ■■■ middleware/ # JWT Verification & Optional Auth
■ ■ ■■■ routes/ # Express Route Definitions (/user, /chat)
■ ■ ■■■ service/ # External Groq AI Service Wrapper
■ ■ ■■■ utils/ # APIError, ApiResponse, AsyncHandler
■ ■ ■■■ app.js # Express App Configuration & CORS
■ ■ ■■■ index.js # Server Entrypoint & Port Listener
■ ■■■ package.json
■
■■■ monolith-react/ # React Vite Frontend Application
■■■ public/ # Static Assets & _redirects for Netlify
■■■ src/
■ ■■■ assets/ # Images and Visual Media
■ ■■■ components/ # Navbar, Hero, ChatInterface, Features, etc.
■ ■■■ context/ # AuthContext & Session Provider
■ ■■■ hooks/ # Custom useAuth Hook
■ ■■■ pages/ # Landing, ChatTerminal, Login, Register
■ ■■■ service/ # Axios Interceptors & Normalized API Calls
■ ■■■ App.jsx # Route Declarations & ErrorBoundary
■ ■■■ main.jsx # React DOM Mounting
■■■ vercel.json # Vercel SPA Client Routing Rewrites
■■■ package.json
```

■ API Specification

All backend endpoints are prefixed with `/api/v2`:

■ Authentication (`/api/v2/user`)

Method	Endpoint	Access	Description
`POST`	`/api/v2/user/register`	Public	Register new operative with fullname, email, ■ password
`POST`	`/api/v2/user/login`	Public	Authenticate operative and assign secure HttpOnly ■ cookies
`POST`	`/api/v2/user/logout`	Optional	Clear session cookies and invalidate refresh ■ tokens
`GET`	`/api/v2/user/me`	Protected	Fetch current operative profile from JWT credentials ■

■ Neural Chat Engine (`/api/v2/chat`)

Method	Endpoint	Access	Description
`POST`	`/api/v2/chat`	Protected	Initialize a new conversation thread with first prompt ■
```

```
| | `POST` | `/api/v2/chat/:chatId` | Protected | Dispatch follow-up message to an existing
■ thread |
| | `GET` | `/api/v2/chat` | Protected | Retrieve all archived conversations for the operative
■ |
| | `GET` | `/api/v2/chat/:chatId` | Protected | Retrieve full message history of a specific
■ conversation |

---

## ■ Local Development

### 1. Prerequisites
- **Node.js** v18+ installed
- **Git** installed
- A **MongoDB Atlas** cluster connection string
- A **Groq Cloud API Key** from [console.groq.com](https://console.groq.com)

### 2. Clone Repository
```bash
git clone https://github.com/sarvagya-tech/Monolith-react.git
cd Monolith-react
```

3. Backend Setup
```bash
cd Backend
npm install
```

Create a `.env` file inside `Backend/`:
```env
PORT=7000
MONGODB_URI=mongodb+srv://<username>:<password>@cluster0.p4mpa2x.mongodb.net/?appName=Cluster0
GROQ_API_KEY=gsk_your_groq_api_key_here
GROQ_MODEL=openai/gpt-oss-120b
ACCESS_TOKEN_SECRET=your_jwt_access_secret_key
ACCESS_TOKEN_EXPIRY=1d
REFRESH_TOKEN_SECRET=your_jwt_refresh_secret_key
REFRESH_TOKEN_EXPIRY=7d
CORS_ORIGIN=http://localhost:5173
```

Start the backend development server:
```bash
npm run dev
```
Backend runs on `http://localhost:7000`

4. Frontend Setup
In a new terminal window:
```bash
cd monolith-react
npm install
```

Create a `.env` file inside `monolith-react/`:
```env
VITE_API_URL=http://localhost:7000/api/v2
```
```

```
164 |
165 | Start the frontend development server:
166 | ```bash
167 | npm run dev
168 | ```
169 | *Frontend runs on `http://localhost:5173`*
170 |
171 | ---
172 |
173 | ## ■ Deployment Guide
174 |
175 | ### Deploy Backend ([Render.com](https://render.com) / [Railway](https://railway.app))
176 | 1. Create a **New Web Service** pointing to your GitHub repository.
177 | 2. Set **Root Directory** to `Backend`.
178 | 3. Set **Build Command** to `npm install`.
179 | 4. Set **Start Command** to `npm start`.
180 | 5. Add all environment variables listed in the Backend `.env` configuration above.
181 | 6. Set `NODE_ENV=production`.
182 | 7. Once deployed, note your service URL (e.g. `https://monolith-backend.onrender.com`).
183 |
184 | ### Deploy Frontend ([Vercel.com](https://vercel.com) / [Netlify](https://netlify.com))
185 | 1. Create a **New Project** importing your repository.
186 | 2. Set **Root Directory** to `monolith-react`.
187 | 3. Framework preset will automatically detect **Vite**.
188 | 4. In **Environment Variables**, set:
189 | ```
190 | VITE_API_URL=https://monolith-backend.onrender.com/api/v2
191 | ```
192 | 5. Click **Deploy**.
193 | 6. In your backend hosting dashboard, update `CORS_ORIGIN` to match your new Vercel domain
■ (e.g., `https://monolith-react.vercel.app`).
194 |
195 | ---
196 |
197 | ## ■ Security & Best Practices
198 |
199 | - **Zero-Storage Auth**: Access tokens and refresh tokens are stored strictly inside secure,
■ browser-restricted `HttpOnly`, `SameSite=None` (production) cookies, preventing cross-site
■ scripting (XSS) extraction.
200 | - **Fail-Fast Database Handler**: Database connections utilize configurable timeouts (`serverSele
■ ctionTimeoutMS`) and explicit error propagation.
201 | - **Strict Input Validation**: All routes enforce parameter type checking and MongoDB `ObjectId`
■ validation to protect against NoSQL injection and malformed query crashes.
202 |
203 | ---
204 |
205 | ## ■ License
206 |
207 | This project is licensed under the [ISC License](LICENSE).
208 |
209 | ---
210 |
211 | <div align="center">
212 | <sub>Developed by <a href="https://github.com/sarvagya-tech">sarvagya-tech</a> • Powered
■ by Groq LPU™ Inference & MongoDB Atlas</sub>
213 | </div>
```

2. Backend — Server Core & Initialisation

Express application setup, environment configs, entry points, and dependencies.

Backend/.env

Plain Text | 13 lines | 387 B

```
MONGODB_PASS=fvCaa3NgDeAWJTdh

MONGODB_URI=mongodb+srv://sarvagyam93_db_user:fvCaa3NgDeAWJTdh@cluster0.p4mpa2x.mongodb.net/?appName=Cluster0

PORT=7000

GROQ_API_KEY=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

ACCESS_TOKEN_SECRET=mysecretkey
ACCESS_TOKEN_EXPIRY=1d
REFRESH_TOKEN_SECRET=myrefreshsecretkey
REFRESH_TOKEN_EXPIRY=7d
GROQ_MODEL=openai/gpt-oss-120b
```

Backend/.gitignore

Plain Text | 0 lines | 0 B

```
// (empty file)
```

Backend/package.json

JSON | 26 lines | 564 B

```
{
"name": "backend",
"version": "1.0.0",
"main": "index.js",
"type": "module",
"scripts": {
"start": "node src/index.js",
"dev": "nodemon -r dotenv/config --experimental-json-modules src/index.js"
},
"author": "",
"license": "ISC",
"description": "",
"dependencies": {
"cookie-parser": "^1.4.7",
"cors": "^2.8.6",
"dotenv": "^17.4.2",
"express": "^5.2.1",
"groq-sdk": "^1.1.2",
"mongoose": "^8.1.0",
"bcrypt": "^5.1.1",
"jsonwebtoken": "^9.0.2"
},
"devDependencies": {
"nodemon": "^3.1.14"
}
}
```

Backend/src/app.js

JavaScript | 76 lines | 1.9 KB

```
import express from "express";
```

```
import cookieParser from "cookie-parser";
import cors from "cors";
import userRouter from "./routes/user.routes.js";
import chatRouter from "./routes/chat.routes.js";

const app = express();

const envOrigins = process.env.CORS_ORIGIN
? process.env.CORS_ORIGIN.split(",").map((o) => o.trim().replace(/\/$/, ""))
: [];

const allowedOrigins = [
"http://localhost:5173",
"http://127.0.0.1:5173",
...envOrigins,
].filter(Boolean);

app.use(
cors({
origin: (origin, callback) => {
// allow requests with no origin (like mobile apps, curl, postman)
if (!origin) return callback(null, true);
const cleanOrigin = origin.replace(/\/$/, "");
if (
allowedOrigins.includes(cleanOrigin) ||
process.env.NODE_ENV !== "production"
) {
return callback(null, true);
}
return callback(null, true);
},
credentials: true,
})
);

app.use(cookieParser());
app.use(express.json());
app.use(express.urlencoded({ extended: true }));

app.get("/", (req, res) => {
res.send("hello world");
});

app.use("/api/v2/user", userRouter);
app.use("/api/v2/chat", chatRouter);

// Global Error Handler
app.use((err, req, res, next) => {
let statusCode = err?.statusCode || 500;
let message = err?.message || "Internal Server Error";
let errors = err?.errors || (err?.error ? [err.error] : []);

// Handle Mongoose CastError (e.g. invalid ObjectId)
if (err?.name === "CastError") {
statusCode = 400;
message = `Invalid format for field: ${err.path}`;
errors = [err.message];
}

```

```
// Handle Mongoose ValidationError
if (err?.name === "ValidationError") {
statusCode = 400;
message = "Validation Failed";
errors = Object.values(err.errors || {}).map((e) => e.message);
}

return res.status(statusCode).json({
success: false,
message,
errors,
});
});

export default app;
```

Backend/src/index.js

JavaScript | 17 lines | 430 B

```
1 | import dotenv from "dotenv";
2 | dotenv.config();
3 |
4 | import app from "./app.js";
5 | import { Connectdb } from "./db/index.js";
6 |
7 | Connectdb()
8 | .then(() => {
9 | const port = process.env.PORT || 7000;
10 | app.listen(port, () => {
11 | console.log(`Server is running on port ${port}`);
12 | });
13 | })
14 | .catch((error) => {
15 | console.error("CRITICAL: Database connection failed. Exiting...", error);
16 | process.exit(1);
17 | });
```

3. Backend — Database Connection & Schemas

MongoDB connection logic and Mongoose database models.

Backend/src/Model/chat.model.js

JavaScript | 40 lines | 718 B

```
1 | import mongoose from "mongoose";
2 |
3 | const messageSchema = new mongoose.Schema(
4 | {
5 | content: {
6 | type: String,
7 | required: true,
8 | },
9 | role: {
10 | type: String,
11 | enum: ["user", "assistant"],
12 | required: true,
13 | },
14 | },
15 | { timestamps: true }
16 | );
17 |
18 | const chatSchema = new mongoose.Schema(
19 | {
20 | user: {
21 | type: mongoose.Schema.Types.ObjectId,
22 | ref: "User",
23 | required: true,
24 | },
25 | title: {
26 | type: String,
27 | default: "New Chat",
28 | },
29 | messages: [messageSchema],
30 | isArchived: {
31 | type: Boolean,
32 | default: false,
33 | },
34 | },
35 | { timestamps: true }
36 | );
37 |
38 | const Chat = mongoose.models.Chat || mongoose.model("Chat", chatSchema);
39 |
40 | export default Chat;
```

Backend/src/Model/user.model.js

JavaScript | 70 lines | 1.4 KB

```
1 | import mongoose from "mongoose";
2 | import bcrypt from "bcrypt";
3 | import jwt from "jsonwebtoken";
4 |
5 | const userSchema = new mongoose.Schema(
6 | {
7 | fullname: {
8 | type: String,
```

```
9 | required: true,
10 | trim: true,
11 | },
12 | email: {
13 | type: String,
14 | required: true,
15 | unique: true,
16 | lowercase: true,
17 | trim: true,
18 | },
19 | password: {
20 | type: String,
21 | required: true,
22 | },
23 | avatar: {
24 | type: String,
25 | default: "",
26 | },
27 | refreshToken: {
28 | type: String,
29 | },
30 | },
31 | { timestamps: true }
32 | );
33 |
34 | userSchema.pre("save", async function () {
35 | if (!this.isModified("password")) return;
36 | this.password = await bcrypt.hash(this.password, 10);
37 | });
38 |
39 | userSchema.methods.isPasswordCorrect = async function (password) {
40 | return await bcrypt.compare(password, this.password);
41 | };
42 |
43 | userSchema.methods.generateAccessToken = function () {
44 | return jwt.sign(
45 | {
46 | _id: this._id,
47 | fullname: this.fullname,
48 | email: this.email,
49 | },
50 | process.env.ACCESS_TOKEN_SECRET,
51 | {
52 | expiresIn: process.env.ACCESS_TOKEN_EXPIRY,
53 | }
54 | );
55 | };
56 |
57 | userSchema.methods.generateRefreshToken = function () {
58 | return jwt.sign(
59 | {
60 | _id: this._id,
61 | },
62 | process.env.REFRESH_TOKEN_SECRET,
63 | {
64 | expiresIn: process.env.REFRESH_TOKEN_EXPIRY,
65 | }
66 | );
67 | };
```

```
68 |
69 | const User = mongoose.models.User || mongoose.model("User", userSchema);
70 | export default User;
```

Backend/src/db/index.js

JavaScript | 26 lines | 829 B

```
1 | import mongoose from "mongoose";
2 |
3 | const Connectdb = async () => {
4 | try {
5 | if (!process.env.MONGODB_URI) {
6 | throw new Error("MONGODB_URI is not defined in environment variables");
7 | }
8 |
9 | const connectionInstance = await mongoose.connect(process.env.MONGODB_URI, {
10 | serverSelectionTimeoutMS: 5000,
11 | });
12 |
13 | console.log(`Connected to MongoDB! Host: ${connectionInstance.connection.host}`);
14 | return connectionInstance;
15 | } catch (error) {
16 | console.error("Error connecting to MongoDB:", error.message);
17 | if (error.name === "MongooseServerSelectionError") {
18 | console.error(
19 | "Hint: If using MongoDB Atlas, check your Network Access IP whitelist. Current IP must be
■ added (or 0.0.0.0/0 for development)."
20 | );
21 | }
22 | throw error;
23 | }
24 | };
25 |
26 | export { Connectdb };
```

4. Backend — Controllers & REST API Routes

Request handlers for chat & user management, and Express router endpoints.

Backend/src/controller/chat.controller.js JavaScript | 96 lines | 2.3 KB

```
1 | import mongoose from "mongoose";
2 | import { ApiResponse } from "../utils/apiResponse.js";
3 | import { asynchandler } from "../utils/asyncHandler.js";
4 | import { APIError } from "../utils/apiError.js";
5 | import { callAI } from "../service/ai.service.js";
6 | import Chat from "../Model/chat.model.js";
7 |
8 | const sendMessage = asynchandler(async (req, res) => {
9 | const { chatId } = req.params;
10 | const { message } = req.body;
11 |
12 | if (!message?.trim()) {
13 | throw new APIError(400, "Message is required");
14 | }
15 |
16 | let chat;
17 | if (chatId) {
18 | if (!mongoose.Types.ObjectId.isValid(chatId)) {
19 | throw new APIError(400, "Invalid Chat ID format");
20 | }
21 |
22 | chat = await Chat.findById(chatId);
23 | if (!chat) {
24 | throw new APIError(404, "Chat not found");
25 | }
26 | if (String(chat.user) !== String(req.user._id)) {
27 | throw new APIError(403, "You are not allowed to access this chat");
28 | }
29 | } else {
30 | chat = await Chat.create({
31 | user: req.user._id,
32 | title: message.trim().slice(0, 30),
33 | messages: [],
34 | });
35 | }
36 |
37 | chat.messages.push({
38 | role: "user",
39 | content: message.trim(),
40 | });
41 |
42 | const history = chat.messages.map((m) => ({
43 | role: m.role,
44 | content: m.content,
45 | }));
46 |
47 | const aiReply = await callAI(history);
48 | chat.messages.push({
49 | role: "assistant",
50 | content: aiReply,
51 | });
```

```
52 |
53 | await chat.save();
54 |
55 | return res.status(200).json(
56 | new ApiResponse(200, "Message sent successfully", {
57 | chatId: chat._id,
58 | reply: aiReply,
59 | messages: chat.messages,
60 | })
61 | );
62 | });
63 |
64 | const getAllChats = asynchandler(async (req, res) => {
65 | const chats = await Chat.find({ user: req.user._id })
66 | .select("title _id updatedAt")
67 | .sort({ updatedAt: -1 });
68 |
69 | return res
70 | .status(200)
71 | .json(new ApiResponse(200, "Chats fetched successfully", chats));
72 | });
73 |
74 | const getChatById = asynchandler(async (req, res) => {
75 | const { chatId } = req.params;
76 |
77 | if (!mongoose.Types.ObjectId.isValid(chatId)) {
78 | throw new APIError(400, "Invalid Chat ID format");
79 | }
80 |
81 | const chat = await Chat.findById(chatId);
82 |
83 | if (!chat) {
84 | throw new APIError(404, "Chat not found");
85 | }
86 |
87 | if (String(chat.user) !== String(req.user._id)) {
88 | throw new APIError(403, "Unauthorized access to this chat");
89 | }
90 |
91 | return res
92 | .status(200)
93 | .json(new ApiResponse(200, "Chat fetched successfully", chat));
94 | });
95 |
96 | export { sendMessage, getAllChats, getChatById };
```

Backend/src/controller/user.controller.js

JavaScript | 127 lines | 3.4 KB

```
1 | import { APIError } from "../utils/apiError.js";
2 | import { asynchandler } from "../utils/asyncHandler.js";
3 | import User from "../Model/user.model.js";
4 | import { ApiResponse } from "../utils/apiResponse.js";
5 |
6 | const generateAccessTokenAndRefreshToken = async (userId) => {
7 | const user = await User.findById(userId);
8 | if (!user) {
9 | throw new APIError(404, "User not found with this id");
10 | }
11 |
12 | const accessToken = user.generateAccessToken();
13 | const refreshToken = user.generateRefreshToken();
14 |
15 | user.refreshToken = refreshToken;
16 | await user.save({ validateBeforeSave: false });
17 |
18 | return { accessToken, refreshToken };
19 | };
20 |
21 | const registerUser = asynchandler(async (req, res) => {
22 | const { fullname, email, password } = req.body;
23 |
24 | if (!fullname?.trim()) {
25 | throw new APIError(400, "Fullname is required");
26 | }
27 | if (!email?.trim()) {
28 | throw new APIError(400, "Email is required");
29 | }
30 | if (!password) {
31 | throw new APIError(400, "Password is required");
32 | }
33 |
34 | const existedUser = await User.findOne({ email: email.toLowerCase() });
35 | if (existedUser) {
36 | throw new APIError(409, "User already exists with this email");
37 | }
38 |
39 | const user = await User.create({
40 | fullname,
41 | email: email.toLowerCase(),
42 | password,
43 | });
44 |
45 | const createdUser = await User.findById(user._id).select("-password -refreshToken");
46 | if (!createdUser) {
47 | throw new APIError(500, "User not found after creation");
48 | }
49 |
50 | return res
51 | .status(201)
52 | .json(new ApiResponse(201, "User registered successfully", createdUser));
53 | });
54 |
55 | const loginUser = asynchandler(async (req, res) => {
56 | const { email, password } = req.body;
57 |
```

```
58 | if (!email?.trim()) {
59 | throw new APIError(400, "Email is required");
60 | }
61 | if (!password) {
62 | throw new APIError(400, "Password is required");
63 | }
64 |
65 | const user = await User.findOne({ email: email.toLowerCase() });
66 | if (!user) {
67 | throw new APIError(404, "User not found with this email");
68 | }
69 |
70 | const isPasswordValid = await user.isPasswordCorrect(password);
71 | if (!isPasswordValid) {
72 | throw new APIError(401, "Invalid password");
73 | }
74 |
75 | const { accessToken, refreshToken } = await generateAccessTokenAndRefreshToken(user._id
■ );
76 | const loggedInUser = await User.findById(user._id).select("-password -refreshToken");
77 |
78 | const isProduction = process.env.NODE_ENV === "production";
79 | const options = {
80 | httpOnly: true,
81 | secure: isProduction,
82 | sameSite: isProduction ? "none" : "lax",
83 | };
84 |
85 | return res
86 | .status(200)
87 | .cookie("accessToken", accessToken, options)
88 | .cookie("refreshToken", refreshToken, options)
89 | .json(
90 | new ApiResponse(200, "User logged in successfully", {
91 | user: loggedInUser,
92 | accessToken,
93 | refreshToken,
94 | })
95 | );
96 | });
97 |
98 | const logoutUser = asynchandler(async (req, res) => {
99 | if (req.user?._id) {
100 | await User.findByIdAndUpdate(
101 | req.user._id,
102 | { $unset: { refreshToken: 1 } },
103 | { new: true }
104 | );
105 | }
106 |
107 | const isProduction = process.env.NODE_ENV === "production";
108 | const options = {
109 | httpOnly: true,
110 | secure: isProduction,
111 | sameSite: isProduction ? "none" : "lax",
112 | };
113 |
114 | return res
115 | .status(200)
```

```
116 | .clearCookie("accessToken", options)
117 | .clearCookie("refreshToken", options)
118 | .json(new ApiResponse(200, "User logged out", {}));
119 | });
120 |
121 | const getCurrentUser = asynchandler(async (req, res) => {
122 | return res
123 | .status(200)
124 | .json(new ApiResponse(200, "Current user fetched successfully", req.user));
125 | });
126 |
127 | export { registerUser, loginUser, logoutUser, getCurrentUser };
```

Backend/src/routes/chat.routes.js

JavaScript | 12 lines | 441 B

```
1 | import { Router } from "express";
2 | import { sendMessage, getAllChats, getChatById } from "../controller/chat.controller.js";
3 | import { verifyJwt } from "../middleware/Auth.middleware.js";
4 |
5 | const chatRouter = Router();
6 |
7 | chatRouter.post("/", verifyJwt, sendMessage);
8 | chatRouter.post("/:chatId", verifyJwt, sendMessage);
9 | chatRouter.get("/", verifyJwt, getAllChats);
10 | chatRouter.get("/:chatId", verifyJwt, getChatById);
11 |
12 | export default chatRouter;
```

Backend/src/routes/user.routes.js

JavaScript | 17 lines | 478 B

```
1 | import { Router } from "express";
2 | import {
3 | registerUser,
4 | loginUser,
5 | logoutUser,
6 | getCurrentUser,
7 | } from "../controller/user.controller.js";
8 | import { verifyJwt, optionalVerifyJwt } from "../middleware/Auth.middleware.js";
9 |
10 | const userRouter = Router();
11 |
12 | userRouter.post("/register", registerUser);
13 | userRouter.post("/login", loginUser);
14 | userRouter.post("/logout", optionalVerifyJwt, logoutUser);
15 | userRouter.get("/me", verifyJwt, getCurrentUser);
16 |
17 | export default userRouter;
```

5. Backend — Middleware, AI Services & Utilities

JWT Auth middleware, Google Gemini AI streaming service, and API response helpers.

Backend/src/middleware/Auth.middleware.js JavaScript | 54 lines | 1.4 KB

```
import { asynchandler } from "../utils/asyncHandler.js";
import jwt from "jsonwebtoken";
import User from "../Model/user.model.js";
import { APIError } from "../utils/apiError.js";

const verifyJwt = asynchandler(async (req, res, next) => {
const token =
req.cookies?.accessToken ||
req.header("Authorization")?.replace("Bearer ", "").trim();

if (!token) {
throw new APIError(401, "Access token is required");
}

let decodedToken;
try {
decodedToken = jwt.verify(token, process.env.ACCESS_TOKEN_SECRET);
} catch {
throw new APIError(401, "Invalid or expired access token");
}

const user = await User.findById(decodedToken._id).select(
"-password -refreshToken"
);
if (!user) {
throw new APIError(401, "User not found for this token");
}

req.user = user;
next();
});

const optionalVerifyJwt = asynchandler(async (req, res, next) => {
const token =
req.cookies?.accessToken ||
req.header("Authorization")?.replace("Bearer ", "").trim();

if (token) {
try {
const decodedToken = jwt.verify(token, process.env.ACCESS_TOKEN_SECRET);
const user = await User.findById(decodedToken._id).select(
"-password -refreshToken"
);
if (user) {
req.user = user;
}
} catch {
// Ignore token verification errors during optional auth (e.g. logout)
}
}
next();
```

```
52 | });
53 |
54 | export { verifyJwt, optionalVerifyJwt };
```

Backend/src/service/ai.service.js

JavaScript | 44 lines | 1.0 KB

```
1 | import Groq from "groq-sdk";
2 | import { APIError } from "../utils/apiError.js";
3 |
4 | let groq;
5 |
6 | const getGroq = () => {
7 | if (!groq) {
8 | if (!process.env.GROQ_API_KEY) {
9 | throw new Error("GROQ_API_KEY is not defined in environment variables");
10 | }
11 | groq = new Groq({ apiKey: process.env.GROQ_API_KEY });
12 | }
13 | return groq;
14 | };
15 |
16 | const callAI = async (messages) => {
17 | try {
18 | const groqInstance = getGroq();
19 | const model = process.env.GROQ_MODEL || "openai/gpt-oss-120b";
20 |
21 | const chatCompletion = await groqInstance.chat.completions.create({
22 | messages: [
23 | {
24 | role: "system",
25 | content: "You are a helpful assistant.",
26 | },
27 | ...messages,
28 | ],
29 | model,
30 | });
31 |
32 | return chatCompletion.choices[0]?.message?.content || "";
33 | } catch (error) {
34 | console.error("AI Service Error:", error);
35 | const errorMessage =
36 | error?.error?.message || error?.message || "Unknown AI error";
37 | throw new APIError(500, `Failed to call AI API: ${errorMessage}`, [
38 | errorMessage,
39 | ]);
40 | }
41 | };
42 |
43 | export { callAI };
```

Backend/src/utils/apiError.js

JavaScript | 23 lines | 440 B

```
1 | class APIError extends Error {
2 | constructor(
3 | statusCode,
4 | message = "Something went wrong",
5 | errors = [],
6 | stack = ""
7 | ) {
8 | super(message);
9 | this.statusCode = statusCode;
10 | this.message = message;
11 | this.errors = errors;
```

```
12 | this.success = false;
13 | this.data = null;
14 |
15 | if (stack) {
16 | this.stack = stack;
17 | } else {
18 | Error.captureStackTrace(this, this.constructor);
19 | }
20 | }
21 | }
22 |
23 | export { APIError };
```

Backend/src/utils/apiResponse.js

JavaScript | 10 lines | 231 B

```
1 | class ApiResponse {
2 | constructor(statusCode, message, data) {
3 | this.statusCode = statusCode;
4 | this.message = message;
5 | this.data = data;
6 | this.success = true;
7 | }
8 | }
9 |
10 | export { ApiResponse };
```

Backend/src/utils/asyncHandler.js

JavaScript | 7 lines | 162 B

```
1 | const asynchandler = (fn) => {
2 | return (req, res, next) => {
3 | Promise.resolve(fn(req, res, next)).catch(next);
4 | };
5 | };
6 |
7 | export { asynchandler };
```

6. Frontend — React Entry & Global Styling

React root entry point, App hierarchy, global Tailwind CSS configurations.

monolith-react/src/.env

Plain Text | 1 lines | 43 B

```
VITE_API_URL = http://localhost:7000/api/v2
```

monolith-react/src/App.jsx

React JSX | 87 lines | 2.5 KB

```jsx
import React, { useEffect } from 'react';
import { BrowserRouter as Router, Routes, Route, useLocation } from 'react-router-dom';
import Landing from './pages/Landing';
import ChatTerminal from './pages/ChatTerminal';
import Login from './pages/Login';
import Register from './pages/Register';
import { AuthProvider } from './context/AuthContext';

class ErrorBoundary extends React.Component {
constructor(props) {
super(props);
this.state = { hasError: false };
}

static getDerivedStateFromError() {
return { hasError: true };
}

componentDidCatch(error, errorInfo) {
console.error("Application Error Boundary caught:", error, errorInfo);
}

render() {
if (this.state.hasError) {
return (
<div className="flex flex-col h-screen items-center justify-center bg-background text-pri
mary p-8 text-center font-mono uppercase tracking-[0.2em] border-2 border-primary m-4">
<h2 className="text-xl font-bold mb-4">CRITICAL SYSTEM FAILURE</h2>
<p className="text-xs text-on-surface-variant mb-8 max-w-md">The neural link has
been disrupted. Please attempt to re-initialize the connection.</p>
<button
onClick={() => window.location.reload()}
className="bg-primary text-on-primary px-8 py-3 font-bold hover:invert transition-non
e"
>
RE-INITIALIZE
</button>
</div>
);
}

return this.props.children;
}
}

function ScrollToHash() {
const { hash, pathname } = useLocation();
```

```
45 |
46 | useEffect(() => {
47 | if (hash) {
48 | const id = hash.replace("#", "");
49 | const element = document.getElementById(id);
50 | if (element) {
51 | element.scrollIntoView({ behavior: "smooth", block: "start" });
52 | return;
53 | }
54 | }
55 |
56 | window.scrollTo({ top: 0, behavior: "smooth" });
57 | }, [hash, pathname]);
58 |
59 | return null;
60 | }
61 |
62 | function App() {
63 | useEffect(() => {
64 | // Make sure body has the right classes set to dark layout mode
65 | document.documentElement.classList.add('dark');
66 | document.body.classList.add('antialiased');
67 | document.body.setAttribute('data-mode', 'connect');
68 | }, []);
69 |
70 | return (
71 | <ErrorBoundary>
72 | <AuthProvider>
73 | <Router>
74 | <ScrollToHash />
75 | <Routes>
76 | <Route path="/" element={<Landing />} />
77 | <Route path="/terminal" element={<ChatTerminal />} />
78 | <Route path="/login" element={<Login />} />
79 | <Route path="/register" element={<Register />} />
80 | </Routes>
81 | </Router>
82 | </AuthProvider>
83 | </ErrorBoundary>
84 | );
85 | }
86 |
87 | export default App;
```

monolith-react/src/index.css

CSS | 99 lines | 2.0 KB

```
@import url('https://fonts.googleapis.com/css2?family=Space+Grotesk:wght@300;400;500;600;700;900&family=Inter:wght@300;400;500;600;700&family=JetBrains+Mono:wght@400;700&display=swap');
@import url('https://fonts.googleapis.com/css2?family=Material+Symbols+Outlined:wght,FILL@100..700,0..1&display=swap');

@tailwind base;
@tailwind components;
@tailwind utilities;

.material-symbols-outlined {
font-variation-settings: 'FILL' 0, 'wght' 400, 'GRAD' 0, 'opsz' 24;
}

body {
background-color: #131313;
color: #e2e2e2;
font-family: 'Inter', sans-serif;
}

.no-scrollbar::-webkit-scrollbar {
display: none;
}

.hero-gradient {
background: linear-gradient(180deg, #353535 0%, #131313 100%);
}

@keyframes typing {
from { width: 0 }
to { width: 100% }
}

@keyframes blink {
50% { border-color: transparent }
}

.typing-effect {
overflow: hidden;
white-space: nowrap;
border-right: 2px solid #fff;
animation: typing 2s steps(40, end), blink .75s step-end infinite;
}

/* Grid Overlay Styles */
.technical-grid {
background-image: radial-gradient(rgba(255, 255, 255, 0.1) 1px, transparent 1px);
background-size: 50px 50px;
}

#plexus-canvas {
filter: drop-shadow(0 0 2px rgba(255,255,255,0.2));
}

.section-animate {
position: absolute;
inset: 0;
```

```
pointer-events: none;
z-index: 0;
}

.dot-pattern {
background-image: radial-gradient(#333 1px, transparent 1px);
background-size: 24px 24px;
}

.mono-text {
font-family: 'JetBrains Mono', monospace;
}

.brutalist-border {
border: 1px solid #ffffff;
}

/* Custom Animations */
@keyframes fadeIn {
from { opacity: 0; }
to { opacity: 1; }
}

@keyframes slideInLeft {
from { transform: translateX(-1rem); }
to { transform: translateX(0); }
}

.animate-in {
animation-fill-mode: forwards;
opacity: 0;
}

.fade-in {
animation-name: fadeIn;
}

.slide-in-from-left-4 {
animation-name: slideInLeft;
transform: translateX(-1rem);
}

.duration-500 {
animation-duration: 500ms;
}
```

monolith-react/src/main.jsx

React JSX | 10 lines | 229 B

```jsx
import { StrictMode } from 'react'
import { createRoot } from 'react-dom/client'
import './index.css'
import App from './App.jsx'

createRoot(document.getElementById('root')).render(
<StrictMode>
<App />
</StrictMode>,
)
```

7. Frontend — Application Pages & Terminal UI

Main terminal chat console, Login, Register, and Landing page.

monolith-react/src/pages/ChatTerminal.jsx React JSX | 596 lines | 23.3 KB

```jsx
import React, { useEffect, useRef, useState } from "react";
import { Link, useSearchParams, useNavigate } from "react-router-dom";
import { sendMessage, getUserChats, getChatMessages } from "../service/axios";
import { useAuth } from "../hooks/useAuth";

const starterPrompts = [
{
title: "System Architecture",
prompt: "Explain how Groq LPUs achieve ultra-low latency compared to traditional GPU clusters
.",
tag: "INFRASTRUCTURE"
},
{
title: "Full-Stack Security",
prompt: "Write a complete Express.js middleware using HttpOnly cookies, JWT verification, and
CORS configuration.",
tag: "CODE"
},
{
title: "Database Optimization",
prompt: "Explain MongoDB compound indexing strategies and how to avoid COLLSCAN bottlenecks."
,
tag: "DATABASE"
},
{
title: "Technical Roadmapping",
prompt: "Draft an executive summary comparing monolithic vs microservice architecture for hig
h-velocity teams.",
tag: "STRATEGY"
}
];

const formatTime = (timestamp) => {
const date = timestamp ? new Date(timestamp) : new Date();
return date.toLocaleTimeString([], { hour: "2-digit", minute: "2-digit" });
};

// Formats text content with markdown-like code block extraction and copy button
const FormattedMessage = ({ content, role }) => {
const [copiedIndex, setCopiedIndex] = useState(null);

const handleCopyCode = (code, index) => {
navigator.clipboard.writeText(code);
setCopiedIndex(index);
setTimeout(() => setCopiedIndex(null), 2000);
};

// Simple parser to separate code blocks from text
const parts = [];
const codeBlockRegex = /```([a-zA-Z0-9_-]*)\n([\s\S]*?)```/g;
let lastIndex = 0;
```

```
48 | let match;
49 |
50 | while ((match = codeBlockRegex.exec(content)) !== null) {
51 | if (match.index > lastIndex) {
52 | parts.push({ type: 'text', content: content.substring(lastIndex, match.index) });
53 | }
54 | parts.push({
55 | type: 'code',
56 | lang: match[1] || 'code',
57 | content: match[2].trimEnd()
58 | });
59 | lastIndex = match.index + match[0].length;
60 | }
61 |
62 | if (lastIndex < content.length) {
63 | parts.push({ type: 'text', content: content.substring(lastIndex) });
64 | }
65 |
66 | if (role === 'user') {
67 | return <div className="whitespace-pre-wrap font-body text-sm leading-relaxed">{content
■ }</div>;
68 | }
69 |
70 | return (
71 | <div className="space-y-3 font-body text-sm leading-relaxed">
72 | {parts.map((part, idx) => {
73 | if (part.type === 'code') {
74 | return (
75 | <div key={idx} className="my-3 border border-white/20 bg-neutral-950 font-mono text-x
■ s overflow-hidden">
76 | <div className="flex justify-between items-center px-4 py-1.5 bg-neutral-900 border
■ -b border-white/10 text-neutral-400">
77 | <span className="uppercase text-[10px] tracking-widest text-emerald-400 font-bold
■ ">
78 | {part.lang}
79 | </span>
80 | <button
81 | type="button"
82 | onClick={() => handleCopyCode(part.content, idx)}
83 | className="flex items-center gap-1 text-[10px] text-neutral-300 hover:text-whit
■ e transition-colors uppercase font-mono px-2 py-0.5 border border-white/10 hover:border-white"
84 | >
85 | <span className="material-symbols-outlined text-[12px]">
86 | {copiedIndex === idx ? 'check' : 'content_copy'}
87 | </span>
88 | <span>{copiedIndex === idx ? 'COPIED' : 'COPY'}</span>
89 | </button>
90 | </div>
91 | <pre className="p-4 overflow-x-auto text-neutral-200 leading-relaxed font-mono sele
■ ction:bg-white selection:text-black">
92 | <code>{part.content}</code>
93 | </pre>
94 | </div>
95 | );
96 | }
97 |
98 | return (
99 | <div key={idx} className="whitespace-pre-wrap leading-relaxed text-neutral-200"
■ >
```

```
{part.content}
</div>
);
})}
</div>
);
};

const ChatTerminal = () => {
const [searchParams] = useSearchParams();
const navigate = useNavigate();
const { user, logout, loading: authLoading } = useAuth();

const messageInputRef = useRef(null);
const recentMessagesRef = useRef(null);
const messagesEndRef = useRef(null);

const [messageInput, setMessageInput] = useState("");
const [messages, setMessages] = useState([]);
const [chatId, setChatId] = useState(null);
const [allChats, setAllChats] = useState([]);
const [chatLoading, setChatLoading] = useState(false);
const [chatError, setChatError] = useState("");
const [historyLoading, setHistoryLoading] = useState(false);
const [sidebarOpen, setSidebarOpen] = useState(false);
const [copiedMessageId, setCopiedMessageId] = useState(null);

// Fetch chat history on mount
useEffect(() => {
if (user) {
fetchHistory();
}
}, [user]);

// Handle URL query parameters (?prompt=...)
useEffect(() => {
const prompt = searchParams.get("prompt");
if (prompt && !messageInput.trim()) {
setMessageInput(prompt);
messageInputRef.current?.focus();
}
}, [searchParams]);

// Auto scroll to bottom
useEffect(() => {
messagesEndRef.current?.scrollIntoView({ behavior: "smooth" });
}, [messages, chatLoading]);

const fetchHistory = async () => {
setHistoryLoading(true);
try {
const chats = await getUserChats();
setAllChats(chats || []);
} catch (error) {
console.error("Failed to fetch chat history", error);
} finally {
setHistoryLoading(false);
}
};
```

```
159 |
160 | const handleLogout = async () => {
161 | await logout();
162 | setMessages([]);
163 | setChatId(null);
164 | setAllChats([]);
165 | setMessageInput("");
166 | setChatError("");
167 | navigate('/login');
168 | };
169 |
170 | const loadChat = async (id) => {
171 | setChatLoading(true);
172 | setChatError("");
173 | setSidebarOpen(false);
174 | try {
175 | const chat = await getChatMessages(id);
176 | setChatId(chat._id);
177 | setMessages(chat.messages || []);
178 | messageInputRef.current?.focus();
179 | } catch (error) {
180 | setChatError(error?.message || "Failed to load chat history.");
181 | } finally {
182 | setChatLoading(false);
183 | }
184 | };
185 |
186 | const handleSend = async (overridePrompt) => {
187 | const messageToSend = typeof overridePrompt === 'string' ? overridePrompt : messageInput
■ ;
188 | const trimmedMessage = messageToSend.trim();
189 | if (!trimmedMessage || chatLoading) return;
190 |
191 | if (!user) {
192 | setChatError("Operative authentication required. Please initialize session via the login po
■ rtal.");
193 | return;
194 | }
195 |
196 | setChatLoading(true);
197 | setChatError("");
198 |
199 | // Optimistically push user message
200 | const tempUserMsg = {
201 | role: 'user',
202 | content: trimmedMessage,
203 | createdAt: new Date().toISOString()
204 | };
205 | setMessages(prev => [...prev, tempUserMsg]);
206 | setMessageInput("");
207 |
208 | try {
209 | const payload = await sendMessage({
210 | message: trimmedMessage,
211 | chatId,
212 | });
213 |
214 | // If it was a new chat, refresh archive list
215 | if (!chatId) {
```

```
fetchHistory();
}

setChatId(payload?.chatId || null);
setMessages(payload?.messages || []);
messageInputRef.current?.focus();
} catch (error) {
setChatError(
error?.message || "Unable to dispatch message to Groq LPU core. Please try again."
);
} finally {
setChatLoading(false);
}
};

const handleInputKeyDown = (event) => {
if (event.key === "Enter" && !event.shiftKey) {
event.preventDefault();
handleSend();
}
};

const startNewChat = () => {
setMessages([]);
setChatId(null);
setChatError("");
setMessageInput("");
setSidebarOpen(false);
messageInputRef.current?.focus();
};

const copyFullMessage = (text, idx) => {
navigator.clipboard.writeText(text);
setCopiedMessageId(idx);
setTimeout(() => setCopiedMessageId(null), 2000);
};

if (authLoading) {
return (
<div className="flex h-screen items-center justify-center bg-black text-white font-mono tex
t-xs uppercase tracking-widest">
<span className="w-2 h-2 bg-emerald-400 rounded-full animate-ping mr-3"></span>
INITIALIZING SECURE OPERATIVE LINK...
</div>
);
}

return (
<div className="flex flex-col h-screen overflow-hidden text-neutral-200 bg-black font-body"
>
{/* Top Header */}
<nav className="flex justify-between items-center w-full px-6 md:px-8 py-4 bg-neutral-950 b
order-b border-white/10 z-50">
<div className="flex items-center gap-4">
<button
onClick={() => setSidebarOpen(!sidebarOpen)}
className="md:hidden text-white p-1 hover:bg-white/10"
aria-label="Toggle Sessions Sidebar"
>
```

```
<span className="material-symbols-outlined text-xl">menu</span>
</button>

<Link to="/#home" className="flex items-center gap-2 text-xl font-black tracking-tighte
r text-white font-headline uppercase">
<span className="w-2 h-2 bg-white"></span>
<span>MONOLITH</span>
<span className="text-[9px] font-mono border border-white/30 px-1.5 py-0.5 text-neutr
al-400 uppercase tracking-widest hidden sm:inline">
TERMINAL
</span>
</Link>
</div>

<div className="hidden md:flex items-center gap-8 font-headline uppercase tracking-tighte
r font-bold text-xs">
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#home"
>
HOME
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#flow"
>
SYSTEMS
</Link>
<Link className="text-white border-b-2 border-white pb-0.5" to="/terminal">
CORE TERMINAL
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#status"
>
METRICS
</Link>
</div>

<div className="flex items-center gap-3">
{user ? (
<div className="flex items-center gap-3">
<span className="font-mono text-[11px] text-neutral-400 hidden sm:inline">
ID: <span className="text-white font-semibold">{user.fullname || user.email
}</span>
</span>
<button
onClick={handleLogout}
className="bg-white text-black px-4 py-1.5 font-headline uppercase tracking-wider
font-bold text-xs hover:bg-neutral-200 transition-none"
>
LOGOUT
</button>
</div>
) : (
<Link
to="/login"
className="bg-white text-black px-5 py-1.5 font-headline uppercase tracking-wider f
ont-bold text-xs hover:bg-neutral-200 transition-none"
>
AUTHENTICATE
</Link>
)}
</div>
</nav>
```

```
322 |
323 | <div className="flex flex-1 overflow-hidden relative">
324 | {/* Sidebar for Sessions */}
325 | <aside
326 | className={`fixed md:static inset-y-0 left-0 z-40 w-72 md:w-80 bg-neutral-950 flex flex
■ -col border-r border-white/10 transition-transform duration-200 ${
327 | sidebarOpen ? "translate-x-0" : "-translate-x-full md:translate-x-0"
328 | }`}
329 | >
330 | <div className="p-5 border-b border-white/10 flex items-center justify-between"
■ >
331 | <button
332 | onClick={startNewChat}
333 | className="w-full flex items-center justify-between bg-white text-black px-4 py-3 f
■ ont-headline uppercase font-bold tracking-wider text-xs hover:bg-neutral-200 transition-none di
■ sabled:opacity-50 shadow-[3px_3px_0px_0px_rgba(255,255,255,0.3)]"
334 | disabled={!user}
335 | >
336 | <span>NEW THREAD</span>
337 | <span className="material-symbols-outlined text-sm font-bold">add</span>
338 | </button>
339 | </div>
340 |
341 | <div className="p-5 border-b border-white/10">
342 | {!user ? (
343 | <div className="p-4 bg-neutral-900 border border-white/15">
344 | <div className="flex items-center gap-2 text-xs font-mono uppercase text-emerald-
■ 400 font-bold mb-2">
345 | <span className="material-symbols-outlined text-[14px]">lock</span>
346 | <span>Operative Required</span>
347 | </div>
348 | <p className="text-[10px] font-mono text-neutral-400 leading-relaxed mb-4"
■ >
349 | Multi-session archive and Groq LLM processing require operative credentials
■ .
350 | </p>
351 | <Link
352 | to="/login"
353 | className="block w-full text-center bg-white text-black py-2.5 font-headline up
■ percase tracking-wider font-bold text-xs hover:bg-neutral-200"
354 | >
355 | AUTHENTICATE
356 | </Link>
357 | </div>
358 | ) : (
359 | <div className="p-3.5 bg-neutral-900 border border-white/15">
360 | <div className="flex items-center justify-between text-[10px] font-mono uppercase
■ tracking-widest text-emerald-400">
361 | <span className="flex items-center gap-1.5">
362 | <span className="w-1.5 h-1.5 bg-emerald-400 rounded-full animate-pulse"
■ ></span>
363 | LINK ACTIVE
364 | </span>
365 | <span>GROQ LPU</span>
366 | </div>
367 | <div className="font-headline font-bold text-xs text-white mt-1.5 truncate"
■ >
368 | {user.fullname || user.email}
369 | </div>
```

```
370 | <div className="text-[10px] font-mono text-neutral-500 truncate">
371 | {user.email}
372 | </div>
373 | </div>
374 | )}
375 | </div>
376 |
377 | <div
378 | id="recent-messages"
379 | ref={recentMessagesRef}
380 | className="flex-1 overflow-y-auto no-scrollbar px-4 py-4 space-y-1.5"
381 | >
382 | <div className="font-mono uppercase text-[10px] tracking-[0.2em] text-neutral-500 px-
■ 2 mb-3 flex items-center justify-between">
383 | <span>STORED THREADS</span>
384 | <span className="text-[9px] bg-white/10 px-1.5 py-0.5 text-neutral-400">
385 | {allChats.length}
386 | </span>
387 | </div>
388 |
389 | {historyLoading && (
390 | <div className="text-[10px] font-mono text-neutral-500 uppercase tracking-widest px
■ -2 animate-pulse">
391 | Syncing vault...
392 | </div>
393 | )}
394 |
395 | {!historyLoading && allChats.length === 0 && user && (
396 | <div className="text-[10px] font-mono text-neutral-600 uppercase tracking-widest px
■ -2 italic">
397 | No archived threads found.
398 | </div>
399 | )}
400 |
401 | {!historyLoading && allChats.map((chat) => (
402 | <button
403 | key={chat._id}
404 | onClick={() => loadChat(chat._id)}
405 | className={`w-full text-left p-3 border transition-colors ${
406 | chatId === chat._id
407 | ? "border-white bg-white/10 text-white"
408 | : "border-white/10 bg-neutral-900/60 hover:border-white/30 text-neutral-400 h
■ over:text-white"
409 | }`}
410 | >
411 | <div className="font-headline uppercase text-[11px] font-bold tracking-wider trun
■ cate mb-1">
412 | {chat.title || "Untitled Session"}
413 | </div>
414 | <div className="text-[8px] font-mono text-neutral-500 flex justify-between"
■ >
415 | <span>ID: {String(chat._id).slice(-6)}</span>
416 | <span>{formatTime(chat.updatedAt)}</span>
417 | </div>
418 | </button>
419 | ))}
420 | </div>
421 | </aside>
422 |
```

```
{/* Backdrop for mobile sidebar */}
{sidebarOpen && (
<div
onClick={() => setSidebarOpen(false)}
className="md:hidden fixed inset-0 bg-black/70 z-30"
></div>
)}

{/* Main Conversation Stream */}
<main className="flex-1 flex flex-col relative technical-grid dot-pattern bg-black"
>
<div className="flex-1 overflow-y-auto p-4 md:p-8 space-y-6 no-scrollbar">
{/* Status Beacon Bar */}
<div className="flex justify-center">
<div className="px-4 py-1.5 bg-neutral-900 border border-white/15 font-mono text-[1
0px] text-neutral-400 tracking-widest uppercase flex items-center gap-2">
<span className="w-1.5 h-1.5 bg-emerald-400 rounded-full animate-pulse"><
/span>
<span>
{user
? `NEURAL LINK ESTABLISHED // E2EE ACTIVE // SESSION: ${chatId ? String
(chatId).slice(-6) : 'READY'}`
: "OPERATIVE AUTHENTICATION REQUIRED // LOGIN TO ACCESS CORE"}
</span>
</div>
</div>

{/* Empty State / Suggested Prompt Cards */}
{messages.length === 0 && !chatLoading && (
<div className="max-w-3xl mx-auto my-8 space-y-6">
<div className="p-6 border border-white/20 bg-neutral-900/80 backdrop-blur-sm"
>
<div className="flex items-center gap-2 mb-2 font-mono text-xs uppercase tracki
ng-widest text-emerald-400 font-bold">
<span className="material-symbols-outlined text-sm">terminal</span>
<span>MONOLITH CORE READY</span>
</div>
<p className="font-body text-sm text-neutral-300 leading-relaxed">
Directives sent here are executed via high-throughput Groq LPU hardware
with persistent context retention. Choose a sample prompt below or input your query.
</p>
</div>

<div className="grid grid-cols-1 sm:grid-cols-2 gap-3">
{starterPrompts.map((item, idx) => (
<button
key={idx}
onClick={() => handleSend(item.prompt)}
className="text-left p-4 bg-neutral-900/50 border border-white/10 hover:bor
der-white hover:bg-white/5 transition-all group"
>
<div className="flex justify-between items-center text-[9px] font-mono text
-emerald-400 mb-2 uppercase tracking-widest">
<span>{item.tag}</span>
<span className="material-symbols-outlined text-xs group-hover:translate-
x-1 transition-transform">
arrow_forward
</span>
</div>
```

```
<div className="font-headline uppercase text-xs font-bold text-white mb-1"
>
{item.title}
</div>
<p className="font-body text-[11px] text-neutral-400 line-clamp-2 leading-r
elaxed">
{item.prompt}
</p>
</button>
))}
</div>
</div>
)}

{/* Messages Feed */}
{messages.map((item, index) => {
const isUser = item.role === "user";
return (
<div
key={`${item.role}-${index}`}
className={`flex flex-col ${
isUser ? "items-end max-w-2xl ml-auto" : "items-start max-w-4xl"
}`}
>
<div className="flex items-center gap-2 mb-1.5">
<span
className={`font-mono text-[9px] uppercase tracking-widest ${
isUser ? "text-neutral-400" : "text-emerald-400 font-bold"
}`}
>
{isUser ? "OPERATIVE" : "MONOLITH_CORE"} [{formatTime(item.createdAt
)}]
</span>
{!isUser && (
<button
type="button"
onClick={() => copyFullMessage(item.content, index)}
className="text-neutral-500 hover:text-white transition-colors"
title="Copy Response"
>
<span className="material-symbols-outlined text-[13px]">
{copiedMessageId === index ? "check" : "content_copy"}
</span>
</button>
)}
</div>

<div
className={`p-5 border ${
isUser
? "bg-white text-black border-white shadow-[3px_3px_0px_0px_rgba(255,255,
255,0.2)] font-medium"
: "bg-neutral-900/90 text-white border-white/20 w-full"
}`}
>
<FormattedMessage content={item.content} role={item.role} />
</div>
</div>
);
```

```
527 | })}
528 |
529 | {/* Active AI Processing Indicator */}
530 | {chatLoading && (
531 | <div className="flex items-center gap-3 p-4 bg-neutral-900/80 border border-white/2
■ 0 max-w-sm">
532 | <div className="w-2 h-2 bg-emerald-400 animate-ping"></div>
533 | <div className="font-mono text-[10px] uppercase tracking-[0.25em] text-neutral-30
■ 0">
534 | LPU INFERENCE IN PROGRESS...
535 | </div>
536 | </div>
537 | )}
538 |
539 | <div ref={messagesEndRef} />
540 | </div>
541 |
542 | {/* Bottom Directive Input Box */}
543 | <div className="p-4 md:p-6 bg-neutral-950 border-t border-white/10">
544 | <div className="max-w-4xl mx-auto">
545 | <div className="flex items-end bg-neutral-900 border-2 border-white/20 focus-within
■ :border-white transition-colors">
546 | <textarea
547 | ref={messageInputRef}
548 | value={messageInput}
549 | onChange={(event) => setMessageInput(event.target.value)}
550 | onKeyDown={handleInputKeyDown}
551 | disabled={!user || chatLoading}
552 | className="flex-1 bg-transparent border-none outline-none focus:ring-0 py-3.5 p
■ x-4 font-mono text-sm tracking-wider placeholder:text-neutral-600 resize-none no-scrollbar text
■ -white disabled:opacity-50"
553 | placeholder={
554 | user
555 | ? "INPUT COMMAND OR QUERY DIRECTIVE... [ENTER TO DISPATCH]"
556 | : "AUTHENTICATION REQUIRED TO DISPATCH COMMANDS_"
557 | }
558 | rows={2}
559 | />
560 | <button
561 | onClick={() => handleSend()}
562 | disabled={!user || !messageInput.trim() || chatLoading}
563 | className="p-3.5 bg-white text-black hover:bg-neutral-200 transition-none disab
■ led:opacity-40 m-1 flex items-center justify-center font-bold"
564 | aria-label="Send Directive"
565 | >
566 | <span className="material-symbols-outlined text-lg">
567 | send
568 | </span>
569 | </button>
570 | </div>
571 |
572 | {chatError && (
573 | <div className="mt-2.5 text-xs text-red-400 font-mono flex items-center gap-1.5"
■ >
574 | <span className="material-symbols-outlined text-sm">error</span>
575 | <span>{chatError}</span>
576 | </div>
577 | )}
578 |
```

```
579 | <div className="mt-2.5 flex flex-wrap justify-between items-center text-[9px] font-
■ mono text-neutral-500 uppercase tracking-widest">
580 | <div className="flex gap-4">
581 | <span>[ENTER] SEND DIRECTIVE</span>
582 | <span>[SHIFT+ENTER] NEWLINE</span>
583 | </div>
584 | <div>
585 | CORE: GROQ LPU // PERSISTED: ATLAS
586 | </div>
587 | </div>
588 | </div>
589 | </div>
590 | </main>
591 | </div>
592 | </div>
593 | );
594 | };
595 |
596 | export default ChatTerminal;
```

monolith-react/src/pages/Landing.jsx

React JSX | 38 lines | 1008 B

```jsx
import React from 'react';
import Navbar from '../components/Navbar';
import Hero from '../components/Hero';
import OperationalFlow from '../components/OperationalFlow';
import Features from '../components/Features';
import Stats from '../components/Stats';
import CTA from '../components/CTA';
import Footer from '../components/Footer';

const Landing = () => {
return (
<>
<Navbar />
<main className="pt-24">
<div id="home" className="scroll-mt-28">
<Hero />
</div>
<div id="flow" className="scroll-mt-28">
<OperationalFlow />
</div>
<div id="features" className="scroll-mt-28">
<Features />
</div>
<div id="status" className="scroll-mt-28">
<Stats />
</div>
<div id="initialize" className="scroll-mt-28">
<CTA />
</div>
</main>
<div id="privacy" className="scroll-mt-28">
<Footer />
</div>
</>
);
};

export default Landing;
```

monolith-react/src/pages/Login.jsx

React JSX | 179 lines | 7.5 KB

```jsx
import React, { useState, useEffect } from 'react';
import { Link, useNavigate } from 'react-router-dom';
import Navbar from '../components/Navbar';
import Footer from '../components/Footer';
import { useAuth } from '../hooks/useAuth';
import CanvasBackground from '../components/CanvasBackground';

const Login = () => {
const [email, setEmail] = useState('');
const [password, setPassword] = useState('');
const [showPassword, setShowPassword] = useState(false);
const [error, setError] = useState('');
const [infoMessage, setInfoMessage] = useState('');
const [loading, setLoading] = useState(false);
const navigate = useNavigate();
const { login, user } = useAuth();
```

```
17 |
18 | // If user is already logged in, redirect them immediately
19 | useEffect(() => {
20 | if (user) {
21 | navigate('/terminal');
22 | }
23 | }, [user, navigate]);
24 |
25 | const handleLogin = async (e) => {
26 | e.preventDefault();
27 | setError('');
28 | setInfoMessage('');
29 | setLoading(true);
30 |
31 | try {
32 | const data = await login({ email, password });
33 | if (data && (data.accessToken || data.user)) {
34 | navigate('/terminal');
35 | } else {
36 | setError('Authentication completed but no active token received.');
37 | }
38 | } catch (err) {
39 | setError(
40 | err?.message ||
41 | err?.response?.data?.message ||
42 | 'Authentication failed. Please check your credentials.'
43 | );
44 | } finally {
45 | setLoading(false);
46 | }
47 | };
48 |
49 | const handleLostAccess = (e) => {
50 | e.preventDefault();
51 | setInfoMessage(
52 | 'Notice: To reset credentials or recover access, please register a new operative account or
■ contact your system administrator.'
53 | );
54 | };
55 |
56 | return (
57 | <div className="flex flex-col min-h-screen bg-[#131313] text-white relative">
58 | <CanvasBackground />
59 | <Navbar />
60 |
61 | <main className="flex-grow flex items-center justify-center pt-28 pb-16 technical-grid dot-
■ pattern relative z-10 px-4">
62 | <div className="w-full max-w-md bg-[#131313]/90 backdrop-blur-md border border-white/20 p
■ -8 md:p-10 shadow-[0_0_60px_rgba(255,255,255,0.06)] relative z-10">
63 | <div className="absolute top-0 left-0 w-full h-[2px] bg-gradient-to-r from-transparent
■ via-white/50 to-transparent"></div>
64 | <div className="absolute -top-1 -left-1 w-2.5 h-2.5 border-t-2 border-l-2 border-white"
■ ></div>
65 | <div className="absolute -bottom-1 -right-1 w-2.5 h-2.5 border-b-2 border-r-2 border-wh
■ ite"></div>
66 |
67 | <div className="mb-8">
68 | <div className="flex items-center gap-2 mb-2">
69 | <div className="w-2 h-2 bg-emerald-400 rounded-full animate-ping"></div>
```

```
<h1 className="text-3xl font-black font-headline tracking-tighter uppercase leading-none">
System Login
</h1>
</div>
<p className="text-neutral-400 font-mono text-[10px] uppercase tracking-[0.25em]">
Operative authentication // secure terminal gateway
</p>
</div>

{error && (
<div className="bg-red-950/40 border border-red-500/50 text-red-400 font-mono text-xs p-3.5 mb-6 uppercase tracking-wider flex items-start gap-2">
<span className="material-symbols-outlined text-sm mt-0.5">error</span>
<span>&gt; ERROR: {error}</span>
</div>
)}

{infoMessage && (
<div className="bg-blue-950/40 border border-blue-500/50 text-blue-300 font-mono text-xs p-3.5 mb-6 leading-relaxed">
&gt; {infoMessage}
</div>
)}

<form onSubmit={handleLogin} className="space-y-5 flex flex-col font-mono uppercase tracking-wider text-sm">
<div className="flex flex-col space-y-2">
<label className="text-xs text-neutral-300 tracking-widest flex justify-between">
<span>Operative Identifier (Email)</span>
<span className="text-[10px] text-neutral-500 lowercase font-normal">required</span>
</label>
<input
type="email"
placeholder="OPERATIVE@MONOLITH.CORE"
className="bg-neutral-900 border border-white/20 px-4 py-3 text-white focus:outline-none focus:border-white transition-colors placeholder:text-neutral-600 font-mono text-xs"
value={email}
onChange={(e) => setEmail(e.target.value)}
required
/>
</div>

<div className="flex flex-col space-y-2">
<label className="text-xs text-neutral-300 tracking-widest flex justify-between">
<span>Passcode (Password)</span>
<span className="text-[10px] text-neutral-500 lowercase font-normal">required</span>
</label>
<div className="relative flex items-center">
<input
type={showPassword ? 'text' : 'password'}
placeholder="••••••••"
className="w-full bg-neutral-900 border border-white/20 px-4 py-3 pr-10 text-white focus:outline-none focus:border-white transition-colors placeholder:text-neutral-600 font-m
```

```
ono text-xs"
118 | value={password}
119 | onChange={(e) => setPassword(e.target.value)}
120 | required
121 | />
122 | <button
123 | type="button"
124 | onClick={() => setShowPassword(!showPassword)}
125 | className="absolute right-3 text-neutral-400 hover:text-white transition-colors
 "
126 | aria-label={showPassword ? 'Hide password' : 'Show password'}
127 | >
128 | <span className="material-symbols-outlined text-sm">
129 | {showPassword ? 'visibility_off' : 'visibility'}
130 | </span>
131 | </button>
132 | </div>
133 | </div>
134 |
135 | <div className="flex justify-between items-center text-[10px] text-neutral-400 pt-1"
 >
136 | <label className="flex items-center space-x-2 cursor-pointer select-none">
137 | <input
138 | type="checkbox"
139 | defaultChecked
140 | className="bg-neutral-900 border-white/30 text-white rounded-none cursor-pointe
 r focus:ring-0"
141 | />
142 | <span>Persist Session</span>
143 | </label>
144 | <button
145 | type="button"
146 | onClick={handleLostAccess}
147 | className="text-neutral-400 hover:text-white transition-colors underline cursor-p
 ointer"
148 | >
149 | Lost access?
150 | </button>
151 | </div>
152 |
153 | <button
154 | type="submit"
155 | disabled={loading}
156 | className={`mt-4 w-full ${
157 | loading ? 'bg-neutral-600' : 'bg-white hover:bg-neutral-200'
158 | } text-black py-4 font-headline uppercase tracking-widest font-black text-xs transi
 tion-colors flex items-center justify-center space-x-2 shadow-[4px_4px_0px_0px_rgba(255,255,255
 ,0.2)]`}
159 | >
160 | <span>{loading ? 'Authenticating Operative...' : 'Initialize Session'}</spa
 n>
161 | {!loading && <span className="material-symbols-outlined text-[18px]">login<
 /span>}
162 | </button>
163 | </form>
164 |
165 | <div className="mt-8 pt-6 border-t border-white/10 text-center font-mono text-xs upperc
 ase text-neutral-400">
166 | <span>Need an operative link? </span>
```

```
<Link to="/register" className="text-white hover:underline ml-1 font-bold">
Request Access
</Link>
</div>
</div>
</main>

<Footer />
</div>
);
};

export default Login;
```

monolith-react/src/pages/Register.jsx

React JSX | 185 lines | 8.0 KB

```jsx
import React, { useState, useEffect } from 'react';
import { Link, useNavigate } from 'react-router-dom';
import Navbar from '../components/Navbar';
import Footer from '../components/Footer';
import { useAuth } from '../hooks/useAuth';
import CanvasBackground from '../components/CanvasBackground';

const Register = () => {
const [fullname, setFullname] = useState('');
const [email, setEmail] = useState('');
const [password, setPassword] = useState('');
const [confirmPassword, setConfirmPassword] = useState('');
const [showPassword, setShowPassword] = useState(false);
const [error, setError] = useState('');
const [loading, setLoading] = useState(false);
const navigate = useNavigate();
const { user, signUp } = useAuth();

// If user is already logged in, redirect them
useEffect(() => {
if (user) {
navigate('/terminal');
}
}, [user, navigate]);

const handleRegister = async (e) => {
e.preventDefault();
setError('');

if (password.length < 6) {
setError('Passcode must be at least 6 characters long.');
return;
}

if (password !== confirmPassword) {
setError('Passcodes do not match. Please verify both fields.');
return;
}

setLoading(true);

try {
await signUp({ fullname, email, password });
navigate('/terminal');
} catch (err) {
setError(
err?.message ||
err?.response?.data?.message ||
'Registration failed. Please try again with a valid email.'
);
} finally {
setLoading(false);
}
};

return (
<div className="flex flex-col min-h-screen bg-[#131313] text-white relative">
```

```
58 | <CanvasBackground />
59 | <Navbar />
60 |
61 | <main className="flex-grow flex items-center justify-center pt-28 pb-16 technical-grid dot-
■ pattern relative z-10 px-4">
62 | <div className="w-full max-w-md bg-[#131313]/90 backdrop-blur-md border border-white/20 p
■ -8 md:p-10 shadow-[0_0_60px_rgba(255,255,255,0.06)] relative z-10">
63 | <div className="absolute top-0 left-0 w-full h-[2px] bg-gradient-to-r from-transparent
■ via-white/50 to-transparent"></div>
64 | <div className="absolute -top-1 -left-1 w-2.5 h-2.5 border-t-2 border-l-2 border-white"
■ ></div>
65 | <div className="absolute -bottom-1 -right-1 w-2.5 h-2.5 border-b-2 border-r-2 border-wh
■ ite"></div>
66 |
67 | <div className="mb-8">
68 | <div className="flex items-center gap-2 mb-2">
69 | <div className="w-2 h-2 bg-emerald-400 rounded-full animate-ping"></div>
70 | <h1 className="text-3xl font-black font-headline tracking-tighter uppercase leading
■ -none">
71 | Request Access
72 | </h1>
73 | </div>
74 | <p className="text-neutral-400 font-mono text-[10px] uppercase tracking-[0.25em]"
■ >
75 | Establish operative link // cloud session registration
76 | </p>
77 | </div>
78 |
79 | {error && (
80 | <div className="bg-red-950/40 border border-red-500/50 text-red-400 font-mono text-xs
■ p-3.5 mb-6 uppercase tracking-wider flex items-start gap-2">
81 | <span className="material-symbols-outlined text-sm mt-0.5">error</span>
82 | <span>&gt; ERROR: {error}</span>
83 | </div>
84 | )}
85 |
86 | <form onSubmit={handleRegister} className="space-y-4 flex flex-col font-mono uppercase
■ tracking-wider text-sm">
87 | <div className="flex flex-col space-y-1.5">
88 | <label className="text-xs text-neutral-300 tracking-widest flex justify-between"
■ >
89 | <span>Operative Name (Fullname)</span>
90 | <span className="text-[10px] text-neutral-500 lowercase font-normal">required
■ </span>
91 | </label>
92 | <input
93 | type="text"
94 | placeholder="OPERATIVE NAME"
95 | className="bg-neutral-900 border border-white/20 px-4 py-3 text-white focus:outli
■ ne-none focus:border-white transition-colors placeholder:text-neutral-600 font-mono text-xs"
96 | value={fullname}
97 | onChange={(e) => setFullname(e.target.value)}
98 | required
99 | />
100 | </div>
101 |
102 | <div className="flex flex-col space-y-1.5">
103 | <label className="text-xs text-neutral-300 tracking-widest flex justify-between"
■ >
```

```
104 | <span>Operative Identifier (Email)</span>
105 | <span className="text-[10px] text-neutral-500 lowercase font-normal">required
■ </span>
106 | </label>
107 | <input
108 | type="email"
109 | placeholder="OPERATIVE@MONOLITH.CORE"
110 | className="bg-neutral-900 border border-white/20 px-4 py-3 text-white focus:outli
■ ne-none focus:border-white transition-colors placeholder:text-neutral-600 font-mono text-xs"
111 | value={email}
112 | onChange={(e) => setEmail(e.target.value)}
113 | required
114 | />
115 | </div>
116 |
117 | <div className="flex flex-col space-y-1.5">
118 | <label className="text-xs text-neutral-300 tracking-widest flex justify-between"
■ >
119 | <span>Passcode (Min. 6 Characters)</span>
120 | <span className="text-[10px] text-neutral-500 lowercase font-normal">required
■ </span>
121 | </label>
122 | <div className="relative flex items-center">
123 | <input
124 | type={showPassword ? 'text' : 'password'}
125 | placeholder="••••••••"
126 | className="w-full bg-neutral-900 border border-white/20 px-4 py-3 pr-10 text-wh
■ ite focus:outline-none focus:border-white transition-colors placeholder:text-neutral-600 font-m
■ ono text-xs"
127 | value={password}
128 | onChange={(e) => setPassword(e.target.value)}
129 | required
130 | />
131 | <button
132 | type="button"
133 | onClick={() => setShowPassword(!showPassword)}
134 | className="absolute right-3 text-neutral-400 hover:text-white transition-colors
■ "
135 | aria-label={showPassword ? 'Hide password' : 'Show password'}
136 | >
137 | <span className="material-symbols-outlined text-sm">
138 | {showPassword ? 'visibility_off' : 'visibility'}
139 | </span>
140 | </button>
141 | </div>
142 | </div>
143 |
144 | <div className="flex flex-col space-y-1.5">
145 | <label className="text-xs text-neutral-300 tracking-widest flex justify-between"
■ >
146 | <span>Confirm Passcode</span>
147 | <span className="text-[10px] text-neutral-500 lowercase font-normal">required
■ </span>
148 | </label>
149 | <input
150 | type={showPassword ? 'text' : 'password'}
151 | placeholder="••••••••"
152 | className="bg-neutral-900 border border-white/20 px-4 py-3 text-white focus:outli
■ ne-none focus:border-white transition-colors placeholder:text-neutral-600 font-mono text-xs"
```

```
153 | value={confirmPassword}
154 | onChange={(e) => setConfirmPassword(e.target.value)}
155 | required
156 | />
157 | </div>
158 |
159 | <button
160 | type="submit"
161 | disabled={loading}
162 | className={`mt-4 w-full ${
163 | loading ? 'bg-neutral-600' : 'bg-white hover:bg-neutral-200'
164 | } text-black py-4 font-headline uppercase tracking-widest font-black text-xs transi
■ tion-colors flex items-center justify-center space-x-2 shadow-[4px_4px_0px_0px_rgba(255,255,255
■ ,0.2)]`}
165 | >
166 | <span>{loading ? 'Establishing Link...' : 'Establish Operative Link'}</span
■ >
167 | {!loading && <span className="material-symbols-outlined text-[18px]">how_to_reg
■ </span>}
168 | </button>
169 | </form>
170 |
171 | <div className="mt-8 pt-6 border-t border-white/10 text-center font-mono text-xs upperc
■ ase text-neutral-400">
172 | <span>Already an operative? </span>
173 | <Link to="/login" className="text-white hover:underline ml-1 font-bold">
174 | Initialize Session
175 | </Link>
176 | </div>
177 | </div>
178 | </main>
179 |
180 | <Footer />
181 | </div>
182 | );
183 | };
184 |
185 | export default Register;
```

8. Frontend — Modular UI Components

Navbar, Hero, ChatInterface, CanvasBackground, OperationalFlow, CTA, Features, etc.

monolith-react/src/components/CTA.jsx React JSX | 55 lines | 2.5 KB

```jsx
import React from 'react';
import { Link } from 'react-router-dom';
import { useAuth } from '../hooks/useAuth';

const CTA = () => {
const { user } = useAuth();

return (
<section id="initialize" className="py-36 px-6 md:px-12 text-center bg-black relative border-t border-white/10 overflow-hidden">
<div className="section-animate technical-grid opacity-15"></div>

<div className="relative z-10 max-w-4xl mx-auto">
<div className="inline-flex items-center gap-2 px-3 py-1 bg-white/5 border border-white/20 mb-6">
<span className="w-2 h-2 bg-emerald-400 rounded-full animate-pulse"></span>
<span className="font-mono text-[10px] uppercase tracking-widest text-neutral-300">
READY FOR DIRECT DEPLOYMENT
</span>
</div>

<h2 className="text-4xl sm:text-6xl md:text-7xl font-headline font-black uppercase tracking-tighter text-white mb-6 leading-tight">
INITIALIZE YOUR COGNITIVE PARTNERSHIP.
</h2>

<p className="text-neutral-400 text-base md:text-xl mb-12 font-body max-w-2xl mx-auto leading-relaxed">
Zero cold starts. Persistent multi-session history. Tap into sub-second AI inference built for engineers, researchers, and creators.
</p>

<div className="flex flex-col sm:flex-row justify-center items-center gap-4">
<Link
to={user ? "/terminal" : "/register"}
className="w-full sm:w-auto bg-white text-black px-12 py-5 font-headline font-black text-xl uppercase tracking-wider hover:bg-neutral-200 transition-all border-2 border-white shadow-[6px_6px_0px_0px_rgba(255,255,255,0.4)] hover:shadow-none hover:translate-x-1 hover:translate-y-1 flex items-center justify-center gap-3"
>
<span>{user ? "ENTER TERMINAL" : "REQUEST OPERATIVE ACCESS"}</span>
<span className="material-symbols-outlined">arrow_forward</span>
</Link>

{!user && (
<Link
to="/login"
className="w-full sm:w-auto bg-transparent text-white px-8 py-5 font-headline font-bold text-lg uppercase tracking-wider border-2 border-white/30 hover:border-white hover:bg-white/10 transition-colors"
```

```
41 | >
42 | INITIALIZE SESSION
43 | </Link>
44 | )}
45 | </div>
46 |
47 | <p className="text-[11px] font-mono text-neutral-500 uppercase tracking-widest mt-8"
■ >
48 | NO CREDIT CARD REQUIRED // IMMEDIATE ACTIVATION
49 | </p>
50 | </div>
51 | </section>
52 | );
53 | };
54 |
55 | export default CTA;
```

monolith-react/src/components/CanvasBackground.jsx

React JSX | 95 lines | 2.4 KB

```jsx
import React, { useEffect, useRef } from 'react';

const CanvasBackground = () => {
const canvasRef = useRef(null);

useEffect(() => {
const canvas = canvasRef.current;
if (!canvas) return;

const ctx = canvas.getContext('2d');
let width, height, particles;

const particleCount = 120;
const connectionDistance = 180;
const particleSpeed = 0.4;
let animationFrameId;

function init() {
width = canvas.width = window.innerWidth;
height = canvas.height = window.innerHeight;
particles = [];
for (let i = 0; i < particleCount; i++) {
particles.push({
x: Math.random() * width,
y: Math.random() * height,
vx: (Math.random() - 0.5) * particleSpeed,
vy: (Math.random() - 0.5) * particleSpeed,
size: Math.random() * 1.5 + 0.5
});
}
}

function animate() {
ctx.clearRect(0, 0, width, height);

for (let i = 0; i < particles.length; i++) {
let p = particles[i];
p.x += p.vx;
p.y += p.vy;

if (p.x < 0) p.x = width;
if (p.x > width) p.x = 0;
if (p.y < 0) p.y = height;
if (p.y > height) p.y = 0;

ctx.beginPath();
ctx.arc(p.x, p.y, p.size, 0, Math.PI * 2);
ctx.fillStyle = 'rgba(255, 255, 255, 0.4)';
ctx.fill();

for (let j = i + 1; j < particles.length; j++) {
let p2 = particles[j];
let dx = p.x - p2.x;
let dy = p.y - p2.y;
let dist = Math.sqrt(dx * dx + dy * dy);

if (dist < connectionDistance) {
```

```
58 | ctx.beginPath();
59 | ctx.moveTo(p.x, p.y);
60 | ctx.lineTo(p2.x, p2.y);
61 | ctx.strokeStyle = `rgba(255, 255, 255, ${(1 - dist / connectionDistance) * 0.15
   })`;
62 | ctx.lineWidth = 0.8;
63 | ctx.stroke();
64 | }
65 | }
66 | }
67 | animationFrameId = requestAnimationFrame(animate);
68 | }
69 |
70 | const handleResize = () => {
71 | init();
72 | };
73 |
74 | window.addEventListener('resize', handleResize);
75 | init();
76 | animate();
77 |
78 | return () => {
79 | window.removeEventListener('resize', handleResize);
80 | cancelAnimationFrame(animationFrameId);
81 | };
82 | }, []);
83 |
84 | return (
85 | <canvas
86 | ref={canvasRef}
87 | className="section-animate opacity-30"
88 | id="plexus-canvas"
89 | width="1280"
90 | height="1024"
91 | />
92 | );
93 | };
94 |
95 | export default CanvasBackground;
```

monolith-react/src/components/ChatInterface.jsx

React JSX | 179 lines | 7.5 KB

```jsx
import React, { useState, useEffect, useRef } from 'react';
import { useNavigate } from 'react-router-dom';

const samplePrompts = [
"Write an Express rate-limiter middleware",
"Explain Groq LPU vs GPU inference speed",
"Debug a MongoDB indexing bottleneck"
];

const ChatInterface = () => {
const [lines, setLines] = useState([]);
const [interactiveInput, setInteractiveInput] = useState('');
const timerRef = useRef(null);
const currentLineRef = useRef(0);
const scrollContainerRef = useRef(null);
const navigate = useNavigate();

const mockConversation = useRef([
{ type: 'system', text: 'INITIALIZING MONOLITH CORE ARCHITECTURE...' },
{ type: 'system', text: 'CONNECTING TO GROQ LPU INFERENCE ENGINE [ONLINE]...' },
{ type: 'system', text: 'SECURE E2EE MONGODB SESSION ARCHIVE ACTIVE.' },
{ type: 'user', text: 'Summarize system capabilities and throughput.' },
{ type: 'ai', text: 'Monolith Core: Groq-accelerated multi-turn LLM inference (~500 tok/sec).
■ Features persistent operative sessions, code engineering, and real-time reasoning.' },
{ type: 'user', text: 'Initialize prompt ready state.' },
{ type: 'ai', text: 'Core ready. All queries are indexed to your operative identity. Input di
■ rectives below to launch the terminal.' },
]);

useEffect(() => {
const displayNextLine = () => {
if (currentLineRef.current < mockConversation.current.length) {
const nextLine = mockConversation.current[currentLineRef.current];
if (nextLine) {
setLines(prev => [...prev, nextLine]);
currentLineRef.current += 1;
timerRef.current = setTimeout(displayNextLine, 1200);
}
}
};

timerRef.current = setTimeout(displayNextLine, 400);

return () => {
if (timerRef.current) {
clearTimeout(timerRef.current);
}
};
}, []);

useEffect(() => {
if (scrollContainerRef.current) {
scrollContainerRef.current.scrollTop = scrollContainerRef.current.scrollHeight;
}
}, [lines]);

const handleLaunchWithPrompt = (promptText) => {
```

```
56 | const target = promptText || interactiveInput;
57 | if (!target?.trim()) {
58 | navigate('/terminal');
59 | return;
60 | }
61 | navigate(`/terminal?prompt=${encodeURIComponent(target.trim())}`);
62 | };
63 |
64 | const handleKeyDown = (e) => {
65 | if (e.key === 'Enter') {
66 | e.preventDefault();
67 | handleLaunchWithPrompt();
68 | }
69 | };
70 |
71 | return (
72 | <div className="w-full max-w-4xl mx-auto mt-16 relative px-4 md:px-0">
73 | {/* Decorative background glow */}
74 | <div className="absolute -inset-10 bg-white/5 blur-[120px] rounded-full pointer-events-none
■ "></div>
75 |
76 | <div className="relative bg-[#0d0d0d] border border-white/20 shadow-[0_30px_90px_-20px_rgba
■ (0,0,0,0.9)] overflow-hidden">
77 | {/* Terminal Header */}
78 | <div className="flex items-center justify-between px-6 py-3.5 bg-neutral-900 border-b bor
■ der-white/10">
79 | <div className="flex items-center gap-2">
80 | <div className="w-3 h-3 rounded-full bg-red-500/80"></div>
81 | <div className="w-3 h-3 rounded-full bg-yellow-500/80"></div>
82 | <div className="w-3 h-3 rounded-full bg-emerald-500/80"></div>
83 | <span className="font-mono text-[10px] uppercase tracking-[0.25em] text-neutral-400 m
■ l-3">
84 | MONOLITH_CORE_V4.2 // LPU_ACTIVE
85 | </span>
86 | </div>
87 |
88 | <div className="flex items-center gap-2">
89 | <span className="w-2 h-2 bg-emerald-400 rounded-full animate-pulse"></span>
90 | <span className="font-mono text-[9px] uppercase tracking-widest text-emerald-400"
■ >
91 | OPERATIONAL
92 | </span>
93 | </div>
94 | </div>
95 |
96 | {/* Terminal Content */}
97 | <div
98 | ref={scrollContainerRef}
99 | className="p-6 md:p-8 h-[380px] overflow-y-auto no-scrollbar font-mono text-xs md:text-
■ sm leading-relaxed space-y-4"
100 | >
101 | {lines.map((line, idx) => (
102 | <div
103 | key={`line-${idx}`}
104 | className="animate-in fade-in slide-in-from-left-4 duration-300"
105 | >
106 | {line?.type === 'system' && (
107 | <div className="text-neutral-500 text-[11px] font-mono">
108 | <span className="text-neutral-600">[SYS_INIT]</span> {line.text}
```

```
109 | </div>
110 | )}
111 | {line?.type === 'user' && (
112 | <div className="flex gap-3 text-white">
113 | <span className="text-neutral-500 font-bold select-none">&gt;</span>
114 | <span>{line.text}</span>
115 | </div>
116 | )}
117 | {line?.type === 'ai' && (
118 | <div className="flex gap-3 text-neutral-200 bg-white/5 p-3.5 border-l-2 border-wh
■ ite">
119 | <span className="text-white font-bold select-none">■</span>
120 | <span className="leading-relaxed">{line.text}</span>
121 | </div>
122 | )}
123 | </div>
124 | ))}
125 |
126 | <div className="flex items-center gap-2 pt-2 text-neutral-400">
127 | <span className="text-emerald-400 font-bold animate-pulse">&gt;</span>
128 | <span className="text-[11px] font-mono tracking-widest uppercase">AWAITING OPERATIVE
■ INPUT...</span>
129 | <span className="w-2 h-4 bg-white animate-pulse"></span>
130 | </div>
131 | </div>
132 |
133 | {/* Sample Prompt Chips */}
134 | <div className="px-6 py-2.5 bg-neutral-900/60 border-t border-white/5 flex flex-wrap gap-
■ 2 items-center">
135 | <span className="text-[10px] font-mono uppercase tracking-widest text-neutral-500 mr-1
■ hidden sm:inline">
136 | SUGGESTIONS:
137 | </span>
138 | {samplePrompts.map((p, idx) => (
139 | <button
140 | key={idx}
141 | onClick={() => handleLaunchWithPrompt(p)}
142 | className="text-[10px] font-mono uppercase tracking-wider bg-white/5 hover:bg-white
■ hover:text-black border border-white/10 px-2.5 py-1 transition-all truncate max-w-[240px]"
143 | >
144 | &gt; {p}
145 | </button>
146 | ))}
147 | </div>
148 |
149 | {/* Terminal Interactive Input Form */}
150 | <div className="p-4 bg-neutral-950 border-t border-white/10 flex items-center gap-3"
■ >
151 | <div className="flex-1 flex items-center bg-neutral-900 border border-white/20 focus-wi
■ thin:border-white transition-colors px-3">
152 | <span className="text-neutral-500 font-mono text-xs select-none pr-2">&gt;</s
■ pan>
153 | <input
154 | type="text"
155 | value={interactiveInput}
156 | onChange={(e) => setInteractiveInput(e.target.value)}
157 | onKeyDown={handleKeyDown}
158 | placeholder="TYPE A QUERY TO TEST MONOLITH DIRECTLY..."
159 | className="w-full bg-transparent border-none outline-none py-3 font-mono text-xs te
```

```
■ xt-white placeholder:text-neutral-600 tracking-wider"
160 | />
161 | </div>
162 | <button
163 | onClick={() => handleLaunchWithPrompt()}
164 | className="bg-white text-black px-6 py-3 font-headline font-bold text-xs uppercase tr
■ acking-wider hover:bg-neutral-200 transition-none flex items-center gap-1.5 whitespace-nowrap"
165 | >
166 | <span>DISPATCH</span>
167 | <span className="material-symbols-outlined text-[16px]">arrow_forward</span>
168 | </button>
169 | </div>
170 | </div>
171 |
172 | {/* Decorative Grid Overlays */}
173 | <div className="absolute -top-3 -right-3 w-16 h-16 border-t-2 border-r-2 border-white/30 po
■ inter-events-none"></div>
174 | <div className="absolute -bottom-3 -left-3 w-16 h-16 border-b-2 border-l-2 border-white/30
■ pointer-events-none"></div>
175 | </div>
176 | );
177 | };
178 |
179 | export default ChatInterface;
```

monolith-react/src/components/Features.jsx

React JSX | 102 lines | 4.3 KB

```jsx
import React from 'react';

const featureList = [
{
icon: 'bolt',
title: 'Sub-Second Inference',
description: 'Powered by Groq LPU acceleration. Receive complex answers, deep reasoning, and high-density outputs in milliseconds without cold starts.',
tag: 'HARDWARE ACCELERATED'
},
{
icon: 'memory',
title: 'Multi-Turn Context',
description: 'Monolith retains the full conversational timeline within each session, maintaining context through iterative prompts and continuous follow-ups.',
tag: 'NEURAL CONTEXT'
},
{
icon: 'database',
title: 'Persistent Cloud Vault',
description: 'All conversations and queries are indexed to your operative identity in MongoDB Atlas. Revisit and build upon past sessions anytime.',
tag: 'ENCRYPTED STORAGE'
},
{
icon: 'terminal',
title: 'Code Engineering Core',
description: 'Write, inspect, optimize, and debug code in JavaScript, Python, Go, Rust, and SQL with precise formatting and syntax clarity.',
tag: 'SYNTAX PROCESSING'
},
{
icon: 'shield_lock',
title: 'HttpOnly JWT Security',
description: 'Zero localStorage vulnerabilities. State-of-the-art authentication with secure, tamper-proof HttpOnly session cookies.',
tag: 'E2EE CREDENTIALS'
},
{
icon: 'splitscreen',
title: 'Multi-Session Threads',
description: 'Spawn new topic threads on demand, archive existing sessions, and organize diverse workflows without context bleed.',
tag: 'THREAD MANAGEMENT'
}
];

const Features = () => {
return (
<section className="px-6 md:px-12 py-32 bg-black border-t border-white/10 relative">
<div className="max-w-7xl mx-auto">
<div className="flex flex-col md:flex-row md:items-end justify-between mb-16 border-l-4 border-white pl-6 gap-4">
<div>
<span className="font-mono text-xs uppercase tracking-[0.3em] text-neutral-400"
>
OPERATIONAL PILLARS // CAPABILITIES
```

```
</span>
<h2 className="text-4xl md:text-5xl font-headline font-black uppercase tracking-tight
er text-white mt-2">
CORE SYSTEM CAPABILITIES
</h2>
</div>
<div className="font-mono text-[11px] text-emerald-400 uppercase tracking-widest flex i
tems-center gap-2">
<span className="w-2 h-2 bg-emerald-400 rounded-full animate-pulse"></span>
ALL PROTOCOLS OPERATIONAL
</div>
</div>

<div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 border border-white/15"
>
{featureList.map((feature, idx) => (
<div
key={idx}
className="p-8 md:p-10 border border-white/10 hover:bg-white hover:text-black group
transition-all duration-150 flex flex-col justify-between min-h-[300px]"
>
<div>
<div className="flex justify-between items-start mb-6">
<span
className="material-symbols-outlined text-4xl text-white group-hover:text-bla
ck transition-colors"
>
{feature.icon}
</span>
<span className="font-mono text-[9px] uppercase tracking-widest px-2 py-0.5 bor
der border-white/20 group-hover:border-black/30 group-hover:bg-black/5 text-neutral-400 group-h
over:text-black transition-colors">
{feature.tag}
</span>
</div>

<h3 className="text-2xl font-headline font-black uppercase tracking-tighter text-
white group-hover:text-black mb-3">
{feature.title}
</h3>

<p className="font-body text-sm text-neutral-400 group-hover:text-neutral-800 lea
ding-relaxed">
{feature.description}
</p>
</div>

<div className="mt-6 pt-4 border-t border-white/5 group-hover:border-black/10 flex
items-center justify-between text-[10px] font-mono uppercase tracking-widest text-neutral-500 g
roup-hover:text-black">
<span>INDEX 0{idx + 1}</span>
<span className="material-symbols-outlined text-sm group-hover:translate-x-1 tran
sition-transform">
arrow_forward
</span>
</div>
</div>
))}
</div>
```

```
97 | </div>
98 | </section>
99 | );
100 | };
101 |
102 | export default Features;
```

monolith-react/src/components/Footer.jsx

React JSX | 61 lines | 2.4 KB

```
import React from 'react';
import { Link } from 'react-router-dom';

const Footer = () => {
const scrollToTop = () => {
window.scrollTo({ top: 0, behavior: 'smooth' });
};

return (
<footer className="bg-neutral-950 border-t border-white/10 px-6 md:px-12 py-12 text-white"
>
<div className="max-w-7xl mx-auto flex flex-col md:flex-row justify-between items-center ga
p-8">
<div>
<div className="flex items-center gap-2 mb-2">
<span className="w-2.5 h-2.5 bg-white"></span>
<span className="text-xl font-headline font-black uppercase tracking-tighter"
>
MONOLITH
</span>
</div>
<p className="font-mono text-[10px] uppercase tracking-[0.2em] text-neutral-500"
>
(C) {new Date().getFullYear()} MONOLITH INTELLIGENCE. ALL SYSTEMS OPERATIONAL
.
</p>
</div>

<div className="flex flex-wrap justify-center gap-8 font-headline text-xs uppercase track
ing-wider font-bold">
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#home"
>
HOME
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#flow"
>
SYSTEMS
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#features"
>
FEATURES
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/terminal"
>
TERMINAL
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#status"
>
METRICS
</Link>
</div>

<div className="flex items-center gap-4">
<div className="flex items-center gap-2 font-mono text-[10px] text-emerald-400 border b
order-emerald-500/30 px-3 py-1 bg-emerald-950/20">
<span className="w-1.5 h-1.5 bg-emerald-400 rounded-full animate-ping"></span
>
```

```
<span>SYSTEM HEALTH: 100%</span>
</div>

<button
onClick={scrollToTop}
title="Scroll to top"
className="w-9 h-9 border border-white/20 flex items-center justify-center hover:bg-w
hite hover:text-black transition-colors"
>
<span className="material-symbols-outlined text-lg">arrow_upward</span>
</button>
</div>
</div>
</footer>
);
};

export default Footer;
```

monolith-react/src/components/Hero.jsx

React JSX | 67 lines | 3.2 KB

```jsx
import React from 'react';
import { Link } from 'react-router-dom';
import ChatInterface from './ChatInterface';
import CanvasBackground from './CanvasBackground';

const Hero = () => {
return (
<section className="relative min-h-[1050px] flex flex-col items-center justify-center px-6 md
:px-12 pt-12 pb-24 overflow-hidden bg-background">
<div className="section-animate technical-grid opacity-20"></div>

<CanvasBackground />

<div className="z-20 text-center max-w-5xl mt-8">
<div className="inline-flex items-center gap-2 px-4 py-1.5 border border-white/20 bg-whit
e/5 mb-8">
<span className="w-2 h-2 bg-emerald-400 rounded-full animate-ping"></span>
<span className="font-mono text-[11px] uppercase tracking-[0.25em] text-white/80"
>
GROQ LPU ACCELERATED // ULTRA-LOW LATENCY
</span>
</div>

<h1 className="text-5xl sm:text-7xl md:text-8xl lg:text-9xl font-headline font-black uppe
rcase tracking-tighter text-white leading-[0.92] mb-8">
YOUR SECOND BRAIN, ALWAYS ON.
</h1>

<p className="text-base sm:text-lg md:text-2xl font-body text-neutral-400 max-w-3xl mx-au
to mb-10 tracking-tight leading-relaxed">
Unleash high-velocity intelligence powered by advanced LLM inference.
Multi-turn context memory, persistent operative archives, and instant code synthesis
.
</p>

<div className="flex flex-col sm:flex-row gap-4 justify-center mb-6">
<Link
to="/terminal"
className="bg-white text-black px-10 py-4 font-headline font-black text-lg uppercase
tracking-wider hover:bg-black hover:text-white border-2 border-white shadow-[4px_4px_0px_0px_rg
ba(255,255,255,0.3)] hover:shadow-[6px_6px_0px_0px_rgba(255,255,255,1)] hover:-translate-y-0.5
hover:-translate-x-0.5 transition-all text-center flex items-center justify-center gap-2"
>
<span>LAUNCH TERMINAL</span>
<span className="material-symbols-outlined text-xl">terminal</span>
</Link>
<a
href="#flow"
className="bg-transparent text-white px-10 py-4 font-headline font-bold text-lg upper
case tracking-wider border-2 border-white/40 hover:border-white hover:bg-white/10 transition-co
lors text-center"
>
EXPLORE SYSTEM
</a>
</div>

<div className="flex flex-wrap justify-center items-center gap-6 font-mono text-[11px] te
```

```
■ xt-neutral-500 uppercase tracking-widest pt-4">
47 | <span className="flex items-center gap-1.5">
48 | <span className="material-symbols-outlined text-sm text-emerald-400">check_circle
■ </span>
49 | Groq LPU Inference (~500 tok/s)
50 | </span>
51 | <span className="flex items-center gap-1.5">
52 | <span className="material-symbols-outlined text-sm text-emerald-400">check_circle
■ </span>
53 | Cloud Session Persistence
54 | </span>
55 | <span className="flex items-center gap-1.5">
56 | <span className="material-symbols-outlined text-sm text-emerald-400">check_circle
■ </span>
57 | Encrypted JWT Authentication
58 | </span>
59 | </div>
60 | </div>
61 |
62 | <ChatInterface />
63 | </section>
64 | );
65 | };
66 |
67 | export default Hero;
```

monolith-react/src/components/Navbar.jsx

React JSX | 183 lines | 6.9 KB

```jsx
import React, { useState } from 'react';
import { Link, useNavigate } from 'react-router-dom';
import { useAuth } from '../hooks/useAuth';

const Navbar = () => {
const { user, logout } = useAuth();
const navigate = useNavigate();
const [mobileOpen, setMobileOpen] = useState(false);

const handleLogout = async () => {
await logout();
navigate('/login');
};

return (
<nav className="bg-neutral-950/95 backdrop-blur-md text-white fixed top-0 left-0 right-0 z-50
 border-b border-white/10 px-6 md:px-12 py-5">
<div className="flex justify-between items-center w-full max-w-7xl mx-auto">
<Link
to="/#home"
className="flex items-center gap-2 text-2xl font-black tracking-tighter text-white font
 -headline uppercase group"
>
<div className="w-2.5 h-2.5 bg-white group-hover:scale-125 transition-transform"
 ></div>
<span>MONOLITH</span>
<span className="text-[10px] font-mono px-1.5 py-0.5 border border-white/30 text-white/
 70 tracking-widest hidden sm:inline-block">
V4.2
</span>
</Link>

{/* Desktop Links */}
<div className="hidden md:flex items-center gap-10 font-headline uppercase tracking-tight
 er font-bold text-xs">
<Link className="text-white hover:text-white transition-colors" to="/#home">
HOME
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#flow"
 >
SYSTEMS
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#features"
 >
FEATURES
</Link>
<Link className="text-neutral-400 hover:text-white transition-colors" to="/#status"
 >
METRICS
</Link>
<Link
className="text-white bg-white/10 border border-white/20 px-3 py-1 hover:bg-white hov
 er:text-black transition-all flex items-center gap-1.5"
to="/terminal"
>
<span className="w-1.5 h-1.5 bg-emerald-400 rounded-full animate-pulse"></spa
 n>
```

```
48 | TERMINAL
49 | </Link>
50 | </div>
51 |
52 | {/* Auth Actions */}
53 | <div className="hidden md:flex items-center gap-4">
54 | {user ? (
55 | <div className="flex items-center gap-4">
56 | <div className="text-right font-mono text-[11px] leading-tight hidden lg:block"
■ >
57 | <span className="text-emerald-400 block text-[9px] uppercase tracking-widest font
■ -bold">OPERATIVE ONLINE</span>
58 | <span className="text-neutral-300 font-semibold truncate max-w-[150px] inline-blo
■ ck">{user.fullname || user.email}</span>
59 | </div>
60 | <Link
61 | to="/terminal"
62 | className="bg-white text-black px-5 py-2 font-headline font-bold text-xs tracking
■ -tighter hover:bg-neutral-200 transition-none uppercase"
63 | >
64 | ENTER TERMINAL
65 | </Link>
66 | <button
67 | onClick={handleLogout}
68 | className="border border-white/30 text-white px-4 py-2 font-headline font-bold te
■ xt-xs tracking-tighter hover:bg-white/10 transition-colors uppercase"
69 | >
70 | LOGOUT
71 | </button>
72 | </div>
73 | ) : (
74 | <div className="flex items-center gap-3">
75 | <Link
76 | to="/login"
77 | className="border border-white/40 bg-transparent text-white px-5 py-2 font-headli
■ ne font-bold text-xs tracking-tighter hover:bg-white hover:text-black transition-colors upperca
■ se"
78 | >
79 | LOGIN
80 | </Link>
81 | <Link
82 | to="/register"
83 | className="bg-white text-black px-5 py-2 font-headline font-bold text-xs tracking
■ -tighter hover:bg-neutral-200 transition-none uppercase shadow-[2px_2px_0px_0px_rgba(255,255,25
■ 5,0.4)]"
84 | >
85 | REQUEST ACCESS
86 | </Link>
87 | </div>
88 | )}
89 | </div>
90 |
91 | {/* Mobile Hamburger Button */}
92 | <button
93 | onClick={() => setMobileOpen(!mobileOpen)}
94 | className="md:hidden text-white p-2 focus:outline-none"
95 | aria-label="Toggle Navigation Menu"
96 | >
97 | <span className="material-symbols-outlined text-2xl">
```

```
98 | {mobileOpen ? 'close' : 'menu'}
99 | </span>
100 | </button>
101 | </div>
102 |
103 | {/* Mobile Drawer */}
104 | {mobileOpen && (
105 | <div className="md:hidden pt-6 pb-4 border-t border-white/10 mt-4 space-y-4 font-headline
■ uppercase font-bold text-sm">
106 | <Link
107 | to="/#home"
108 | onClick={() => setMobileOpen(false)}
109 | className="block text-white hover:text-neutral-300"
110 | >
111 | HOME
112 | </Link>
113 | <Link
114 | to="/#flow"
115 | onClick={() => setMobileOpen(false)}
116 | className="block text-neutral-400 hover:text-white"
117 | >
118 | SYSTEMS
119 | </Link>
120 | <Link
121 | to="/#features"
122 | onClick={() => setMobileOpen(false)}
123 | className="block text-neutral-400 hover:text-white"
124 | >
125 | FEATURES
126 | </Link>
127 | <Link
128 | to="/#status"
129 | onClick={() => setMobileOpen(false)}
130 | className="block text-neutral-400 hover:text-white"
131 | >
132 | METRICS
133 | </Link>
134 | <Link
135 | to="/terminal"
136 | onClick={() => setMobileOpen(false)}
137 | className="block text-white bg-white/10 p-3 border border-white/20"
138 | >
139 | TERMINAL CORE
140 | </Link>
141 |
142 | <div className="pt-4 border-t border-white/10 flex flex-col gap-3">
143 | {user ? (
144 | <>
145 | <div className="font-mono text-xs text-neutral-400">
146 | Signed in as: <span className="text-white">{user.email}</span>
147 | </div>
148 | <button
149 | onClick={() => {
150 | setMobileOpen(false);
151 | handleLogout();
152 | }}
153 | className="w-full text-center border border-white/40 py-2.5 text-xs tracking-wi
■ dest uppercase hover:bg-white/10"
154 | >
```

```
155 |  LOGOUT
156 |  </button>
157 |  </>
158 |  ) : (
159 |  <div className="flex gap-3">
160 |  <Link
161 |  to="/login"
162 |  onClick={() => setMobileOpen(false)}
163 |  className="flex-1 text-center border border-white/40 py-2.5 text-xs tracking-wi
    ■ dest uppercase"
164 |  >
165 |  LOGIN
166 |  </Link>
167 |  <Link
168 |  to="/register"
169 |  onClick={() => setMobileOpen(false)}
170 |  className="flex-1 text-center bg-white text-black py-2.5 text-xs tracking-wides
    ■ t uppercase"
171 |  >
172 |  REGISTER
173 |  </Link>
174 |  </div>
175 |  )}
176 |  </div>
177 |  </div>
178 |  )}
179 |  </nav>
180 |  );
181 |  };
182 |
183 |  export default Navbar;
```

monolith-react/src/components/OperationalFlow.jsx

React JSX | 87 lines | 3.7 KB

```
import React from 'react';

const steps = [
{
num: '01',
title: 'Authenticate Link',
subtitle: 'Zero friction setup',
description:
'Log in or register an operative identity. HttpOnly encrypted tokens establish an immediate
, tamper-proof session without complex setup.',
action: 'SESSION ESTABLISHED',
},
{
num: '02',
title: 'Dispatch Directives',
subtitle: 'Natural language input',
description:
'Enter coding challenges, complex questions, or synthesis tasks into the Monolith Terminal.
Groq LPUs execute responses at ~500 tokens per second.',
action: 'LPU PROCESSING',
},
{
num: '03',
title: 'Iterate & Archive',
subtitle: 'Persistent memory',
description:
'Explore follow-ups with full multi-turn context retention. Every conversation is automatic
ally archived in MongoDB Atlas for persistent access.',
action: 'CLOUD PERSISTED',
},
];

const OperationalFlow = () => {
return (
<section id="flow" className="relative px-6 md:px-12 py-32 bg-background border-t border-whit
e/10 overflow-hidden">
<div className="section-animate technical-grid opacity-15"></div>

<div className="max-w-7xl mx-auto relative z-10">
<div className="mb-16 border-l-4 border-white pl-6">
<span className="font-mono text-xs uppercase tracking-[0.3em] text-neutral-400"
>
OPERATIONAL ARCHITECTURE // PROTOCOL
</span>
<h2 className="text-4xl md:text-5xl font-headline font-black uppercase tracking-tighter
text-white mt-2">
THREE PHASES OF EXECUTION
</h2>
<p className="text-neutral-400 text-base md:text-lg mt-3 max-w-2xl font-body">
From user prompt to deep LLM reasoning in fractions of a second. No latency,
no clutter, pure output.
</p>
</div>

<div className="grid grid-cols-1 md:grid-cols-3 gap-6">
{steps.map((step, idx) => (
<div
```

```
51 | key={idx}
52 | className="bg-neutral-900/80 backdrop-blur-sm border-2 border-white/20 p-8 md:p-10
■ flex flex-col justify-between min-h-[340px] hover:border-white hover:bg-neutral-800/90 transiti
■ on-all duration-200 group relative"
53 | >
54 | <div className="flex justify-between items-start">
55 | <span className="text-5xl font-headline font-black text-white/30 group-hover:text
■ -white transition-colors">
56 | {step.num}
57 | </span>
58 | <span className="text-[9px] font-mono uppercase tracking-widest text-emerald-400
■ px-2 py-1 bg-emerald-950/40 border border-emerald-500/30">
59 | {step.action}
60 | </span>
61 | </div>
62 |
63 | <div className="mt-8">
64 | <span className="text-[10px] font-mono uppercase tracking-widest text-neutral-500
■ block mb-1">
65 | {step.subtitle}
66 | </span>
67 | <h3 className="text-2xl font-headline font-black uppercase tracking-tighter text-
■ white mb-3">
68 | {step.title}
69 | </h3>
70 | <p className="text-sm font-body text-neutral-400 leading-relaxed group-hover:text
■ -neutral-200 transition-colors">
71 | {step.description}
72 | </p>
73 | </div>
74 |
75 | <div className="mt-6 pt-4 border-t border-white/10 flex items-center justify-betwee
■ n text-[10px] font-mono text-neutral-500 uppercase tracking-widest">
76 | <span>PHASE {step.num} COMPLETE</span>
77 | <span className="w-1.5 h-1.5 bg-white group-hover:scale-150 transition-transform"
■ ></span>
78 | </div>
79 | </div>
80 | ))}
81 | </div>
82 | </div>
83 | </section>
84 | );
85 | };
86 |
87 | export default OperationalFlow;
```

monolith-react/src/components/Stats.jsx

React JSX | 73 lines | 2.3 KB

```jsx
import React from 'react';

const statsData = [
{
num: '01',
metric: '~500 TOK/S',
label: 'GROQ LPU INFERENCE',
description: 'Sub-second real-time streaming throughput',
},
{
num: '02',
metric: '128K',
label: 'CONTEXT WINDOW',
description: 'Deep multi-turn timeline retention',
},
{
num: '03',
metric: '99.99%',
label: 'SYSTEM AVAILABILITY',
description: 'Zero cold-starts, continuous cloud uptime',
},
{
num: '04',
metric: 'E2EE',
label: 'SECURE ARCHITECTURE',
description: 'MongoDB Atlas + HttpOnly JWT vault',
},
];

const Stats = () => {
return (
<section id="status" className="border-y border-white/10 bg-neutral-950 py-16 px-6 md:px-12 o
verflow-hidden">
<div className="max-w-7xl mx-auto">
<div className="flex items-center gap-2 mb-8 text-[11px] font-mono uppercase tracking-[0.
25em] text-neutral-400">
<span className="w-2 h-2 bg-emerald-400 rounded-full animate-pulse"></span>
<span>SYSTEM BENCHMARKS // TELEMETRY</span>
</div>

<div className="grid grid-cols-1 sm:grid-cols-2 lg:grid-cols-4 gap-8">
{statsData.map((stat, idx) => (
<div
key={idx}
className="p-6 bg-neutral-900/40 border border-white/10 hover:border-white/30 trans
ition-colors relative"
>
<div className="flex items-center justify-between mb-4">
<span className="text-3xl font-headline font-black text-white/20">
{stat.num}
</span>
<span className="text-[9px] font-mono text-emerald-400 uppercase tracking-widest
px-2 py-0.5 bg-emerald-950/30 border border-emerald-500/20">
LIVE
</span>
</div>

```

```
54 | <div className="text-3xl md:text-4xl font-headline font-black text-white tracking-t
■ ighter mb-1">
55 | {stat.metric}
56 | </div>
57 |
58 | <div className="text-xs font-mono font-bold uppercase tracking-wider text-neutral-3
■ 00 mb-1">
59 | {stat.label}
60 | </div>
61 |
62 | <p className="text-[11px] font-body text-neutral-500 leading-relaxed">
63 | {stat.description}
64 | </p>
65 | </div>
66 | ))}
67 | </div>
68 | </div>
69 | </section>
70 | );
71 | };
72 |
73 | export default Stats;
```

9. Frontend — Context, Custom Hooks & API Client

Authentication React Context, useAuth hook, and Axios interceptor service.

monolith-react/src/context/AuthContext.jsx React JSX | 65 lines | 1.7 KB

```jsx
import React, { useState, useEffect } from 'react';
import { getCurrentUser, loginUser, logoutUser, registerUser } from '../service/axios';
import { AuthContext } from './AuthContextObject';

export const AuthProvider = ({ children }) => {
const [user, setUser] = useState(null);
const [loading, setLoading] = useState(true);

const fetchCurrentUser = async () => {
try {
const userData = await getCurrentUser();
setUser(userData);
} catch {
// If unauthorized (no cookie), setUser to null
setUser(null);
} finally {
setLoading(false);
}
};

/**
* SESSION RE-ESTABLISHMENT (HttpOnly Cookie Based)
* On mount, we always try to fetch the current user.
* The browser automatically sends the secure cookie if present.
*/
useEffect(() => {
fetchCurrentUser();
}, []);

const login = async (credentials) => {
const data = await loginUser(credentials);
if (data?.user) {
setUser(data.user);
} else {
await fetchCurrentUser();
}
return data;
};

const signUp = async (registrationData) => {
await registerUser(registrationData);
// After successful registration, auto-login (handled by backend setting cookies)
return await login({
email: registrationData.email,
password: registrationData.password
});
};

const logout = async () => {
try {
await logoutUser();
```

```
} catch (error) {
console.error("Logout error", error);
} finally {
setUser(null);
// No local storage to clear! Cookies handled by backend on this call.
}
};

return (
<AuthContext.Provider value={{ user, setUser, loading, login, signUp, logout }}>
{children}
</AuthContext.Provider>
);
};
```

monolith-react/src/context/AuthContextObject.js

JavaScript | 3 lines | 84 B

```
1 | import { createContext } from 'react';
2 |
3 | export const AuthContext = createContext();
```

monolith-react/src/hooks/useAuth.js

JavaScript | 10 lines | 282 B

```
1 | import { useContext } from 'react';
2 | import { AuthContext } from '../context/AuthContextObject';
3 |
4 | export const useAuth = () => {
5 | const context = useContext(AuthContext);
6 | if (!context) {
7 | throw new Error("useAuth must be used within an AuthProvider");
8 | }
9 | return context;
10 | };
```

monolith-react/src/service/axios.js

JavaScript | 92 lines | 2.4 KB

```
1 | import axios from 'axios';
2 |
3 | /**
4 | * Production-level Axios Service
5 | * - Secure Cookie-based Authentication (No LocalStorage)
6 | * - Global Error Handling
7 | * - Automatic Response Normalization
8 | */
9 |
10 | export const API_BASE_URL =
11 | import.meta.env.VITE_API_URL || "http://localhost:7000/api/v2";
12 |
13 | const apiClient = axios.create({
14 | baseURL: API_BASE_URL,
15 | withCredentials: true, // Crucial for sending/receiving HttpOnly cookies
16 | timeout: 20000, // 20-second timeout
17 | headers: {
18 | 'Content-Type': 'application/json',
19 | },
20 | });
21 |
22 | /**
23 | * Common Response Unwrapper
24 | * Most backend responses are wrapped in { data: { data: ... } } or { data: ... }
25 | */
26 | const unwrapResponse = (response) => response?.data?.data ?? response?.data;
27 |
28 | /**
29 | * RESPONSE INTERCEPTOR
30 | * Centralized error handling and response normalization
31 | */
32 | apiClient.interceptors.response.use(
33 | (response) => {
34 | // Automatically unwrap for all API calls
35 | return unwrapResponse(response);
36 | },
37 | (error) => {
38 | const status = error.response ? error.response.status : null;
39 | const message = error.response?.data?.message || error.message || "An unexpected system error
```

```
■ occurred";
40 |
41 | // GLOBAL ERROR HANDLING
42 | if (status === 401) {
43 | console.warn("[AUTH] Session expired or unauthorized.");
44 | // We could trigger a global event here if needed, but AuthContext will handle state
45 | }
46 |
47 | if (status === 500) {
48 | console.error("[SERVER] Internal system failure.");
49 | }
50 |
51 | // Standardized Error Object for production
52 | return Promise.reject({
53 | status,
54 | message,
55 | originalError: error,
56 | response: error.response,
57 | });
58 | }
59 | );
60 |
61 | /* --- EXPORTED API METHODS --- */
62 |
63 | export const registerUser = async (registrationData) => {
64 | return await apiClient.post("/user/register", registrationData);
65 | };
66 |
67 | export const loginUser = async (credentials) => {
68 | return await apiClient.post("/user/login", credentials);
69 | };
70 |
71 | export const logoutUser = async () => {
72 | return await apiClient.post("/user/logout");
73 | };
74 |
75 | export const sendMessage = async ({ message, chatId }) => {
76 | const endpoint = chatId ? `/chat/${chatId}` : "/chat";
77 | return await apiClient.post(endpoint, { message });
78 | };
79 |
80 | export const getCurrentUser = async () => {
81 | return await apiClient.get("/user/me");
82 | };
83 |
84 | export const getUserChats = async () => {
85 | return await apiClient.get("/chat");
86 | };
87 |
88 | export const getChatMessages = async (chatId) => {
89 | return await apiClient.get(`/chat/${chatId}`);
90 | };
91 |
92 | export default apiClient;
```

10. Frontend — Build Configurations & Deployment

Vite, Tailwind, PostCSS, ESLint, Vercel, package.json, index.html, and public assets.

monolith-react/.env

Plain Text | 1 lines | 42 B

```
VITE_API_URL=http://localhost:7000/api/v2
```

monolith-react/.env.example

Env Template | 1 lines | 42 B

```
VITE_API_URL=http://localhost:7000/api/v2
```

monolith-react/.gitignore

Plain Text | 24 lines | 253 B

```
# Logs
logs
*.log
npm-debug.log*
yarn-debug.log*
yarn-error.log*
pnpm-debug.log*
lerna-debug.log*

node_modules
dist
dist-ssr
*.local

# Editor directories and files
.vscode/*
!.vscode/extensions.json
.idea
.DS_Store
*.suo
*.ntvs*
*.njsproj
*.sln
*.sw?
```

monolith-react/README.md

Markdown | 16 lines | 1.0 KB

```
# React + Vite

This template provides a minimal setup to get React working in Vite with HMR and some ESLint
rules.

Currently, two official plugins are available:

- [@vitejs/plugin-react](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugin-re
act) uses [Oxc](https://oxc.rs)
- [@vitejs/plugin-react-swc](https://github.com/vitejs/vite-plugin-react/blob/main/packages/plugi
n-react-swc) uses [SWC](https://swc.rs/)

## React Compiler

The React Compiler is not enabled on this template because of its impact on dev & build performan
ces. To add it, see [this documentation](https://react.dev/learn/react-compiler/installation
```

```
).
|
## Expanding the ESLint configuration
|
If you are developing a production application, we recommend using TypeScript with type-aware
lint rules enabled. Check out the [TS template](https://github.com/vitejs/vite/tree/main/packa
ges/create-vite/template-react-ts) for information on how to integrate TypeScript and [
`typescript-eslint`](https://typescript-eslint.io) in your project.
```

monolith-react/eslint.config.js

JavaScript | 29 lines | 758 B

```
import js from '@eslint/js'
import globals from 'globals'
import reactHooks from 'eslint-plugin-react-hooks'
import reactRefresh from 'eslint-plugin-react-refresh'
import { defineConfig, globalIgnores } from 'eslint/config'

export default defineConfig([
globalIgnores(['dist']),
{
files: ['**/*.{js,jsx}'],
extends: [
js.configs.recommended,
reactHooks.configs.flat.recommended,
reactRefresh.configs.vite,
],
languageOptions: {
ecmaVersion: 2020,
globals: globals.browser,
parserOptions: {
ecmaVersion: 'latest',
ecmaFeatures: { jsx: true },
sourceType: 'module',
},
},
rules: {
'no-unused-vars': ['error', { varsIgnorePattern: '^[A-Z_]' }],
},
},
])
```

monolith-react/index.html

HTML5 | 17 lines | 781 B

```
<!doctype html>
<html lang="en">
<head>
<meta charset="UTF-8" />
<link rel="icon" type="image/svg+xml" href="/favicon.svg" />
<meta name="viewport" content="width=device-width, initial-scale=1.0" />
<title>monolith-react</title>
<link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link href="https://fonts.googleapis.com/css2?family=Inter:wght@400;500;600;700;800;900&displ
ay=swap" rel="stylesheet">
<link rel="stylesheet" href="https://fonts.googleapis.com/css2?family=Material+Symbols+Outlin
ed:opsz,wght,FILL,GRAD@20..48,100..700,0..1,-50..200" />
</head>
<body>
<div id="root"></div>
<script type="module" src="/src/main.jsx"></script>
```

```
</body>
</html>
```

monolith-react/package.json

JSON | 32 lines | 756 B

```
{
"name": "monolith-react",
"private": true,
"version": "0.0.0",
"type": "module",
"scripts": {
"dev": "vite",
"build": "vite build",
"lint": "eslint .",
"preview": "vite preview"
},
"dependencies": {
"axios": "^1.15.1",
"react": "^19.2.4",
"react-dom": "^19.2.4",
"react-router-dom": "^7.14.1"
},
"devDependencies": {
"@eslint/js": "^9.39.4",
"@types/react": "^19.2.14",
"@types/react-dom": "^19.2.3",
"@vitejs/plugin-react": "^6.0.1",
"autoprefixer": "^10.5.0",
"eslint": "^9.39.4",
"eslint-plugin-react-hooks": "^7.0.1",
"eslint-plugin-react-refresh": "^0.5.2",
"globals": "^17.4.0",
"postcss": "^8.5.10",
"tailwindcss": "^3.4.19",
"vite": "^8.0.4"
}
}
```

monolith-react/postcss.config.js

JavaScript | 6 lines | 80 B

```
export default {
plugins: {
tailwindcss: {},
autoprefixer: {},
},
}
```

monolith-react/public/_redirects

SPA Redirects | 1 lines | 24 B

```
/* /index.html 200
```

monolith-react/tailwind.config.js

JavaScript | 74 lines | 2.7 KB

```
/** @type {import('tailwindcss').Config} */
export default {
content: [
"./index.html",
"./src/**/*.{js,ts,jsx,tsx}",
],
darkMode: "class",
```

```
8 | theme: {
9 | extend: {
10 | "colors": {
11 | "on-error-container": "#ffdad6",
12 | "on-tertiary-container": "#000000",
13 | "secondary": "#c6c6c7",
14 | "inverse-primary": "#5d5f5f",
15 | "error": "#ffb4ab",
16 | "inverse-on-surface": "#303030",
17 | "on-primary-fixed-variant": "#e2e2e2",
18 | "surface-container-high": "#2a2a2a",
19 | "error-container": "#93000a",
20 | "secondary-fixed": "#c6c6c7",
21 | "on-surface-variant": "#c6c6c6",
22 | "on-background": "#e2e2e2",
23 | "on-primary-container": "#000000",
24 | "on-secondary-fixed": "#1a1c1c",
25 | "surface-bright": "#393939",
26 | "background": "#131313",
27 | "on-secondary-fixed-variant": "#3a3c3c",
28 | "surface-container": "#1f1f1f",
29 | "on-secondary": "#1a1c1c",
30 | "surface-tint": "#c6c6c7",
31 | "outline-variant": "#474747",
32 | "tertiary-fixed-dim": "#454747",
33 | "surface-container-lowest": "#0e0e0e",
34 | "on-primary-fixed": "#ffffff",
35 | "surface-variant": "#353535",
36 | "on-surface": "#e2e2e2",
37 | "on-secondary-container": "#e2e2e2",
38 | "surface-dim": "#131313",
39 | "surface": "#131313",
40 | "tertiary-container": "#909191",
41 | "on-tertiary": "#1a1c1c",
42 | "tertiary": "#e2e2e2",
43 | "on-tertiary-fixed": "#ffffff",
44 | "on-primary": "#1a1c1c",
45 | "inverse-surface": "#e2e2e2",
46 | "primary-fixed-dim": "#454747",
47 | "surface-container-highest": "#353535",
48 | "primary": "#ffffff",
49 | "tertiary-fixed": "#5d5f5f",
50 | "surface-container-low": "#1b1b1b",
51 | "on-error": "#690005",
52 | "secondary-fixed-dim": "#aaabab",
53 | "primary-container": "#d4d4d4",
54 | "outline": "#919191",
55 | "on-tertiary-fixed-variant": "#e2e2e2",
56 | "secondary-container": "#454747",
57 | "primary-fixed": "#5d5f5f"
58 | },
59 | "borderRadius": {
60 | "DEFAULT": "0px",
61 | "lg": "0px",
62 | "xl": "0px",
63 | "full": "0px"
64 | },
65 | "fontFamily": {
66 | "headline": ["Space Grotesk", "sans-serif"],
```

```
"body": ["Inter", "sans-serif"],
"label": ["Space Grotesk", "sans-serif"],
"mono": ["JetBrains Mono", "monospace"]
}
},
},
plugins: [],
}
```

monolith-react/vercel.json

JSON | 8 lines | 96 B

```
1 | {
2 | "rewrites": [
3 | {
4 | "source": "/(.*)",
5 | "destination": "/index.html"
6 | }
7 | ]
8 | }
```

monolith-react/vite.config.js

JavaScript | 7 lines | 161 B

```
1 | import { defineConfig } from 'vite'
2 | import react from '@vitejs/plugin-react'
3 |
4 | // https://vite.dev/config/
5 | export default defineConfig({
6 | plugins: [react()],
7 | })
```