

- Name: Sarvesh Surve
- List item

 Generate

create a dataframe with 2 columns and 10 rows



Close

```
import numpy as np
from sklearn.model_selection import train_test_split
from sklearn import datasets

def unit_step_func(x):
    return np.where(x > 0 , 1, 0)

class Perceptron:

    def __init__(self, learning_rate=0.01, n_iters=1000):
        self.lr = learning_rate
        self.n_iters = n_iters
        self.activation_func = unit_step_func
        self.weights = None
        self.bias = None

    def fit(self, X, y):
        n_samples, n_features = X.shape

        # init parameters
        self.weights = np.zeros(n_features)
        self.bias = 0

        y_ = np.where(y > 0 , 1, 0)

        for _ in range(self.n_iters):
            for idx, x_i in enumerate(X):
                linear_output = np.dot(x_i, self.weights) + self.bias
                y_predicted = self.activation_func(linear_output)

                # Perceptron update rule
                update = self.lr * (y_[idx] - y_predicted)
                self.weights += update * x_i
                self.bias += update

    def predict(self, X):
        linear_output = np.dot(X, self.weights) + self.bias
        y_predicted = self.activation_func(linear_output)
        return y_predicted

if __name__ == "__main__":

    def accuracy(y_true, y_pred):
        accuracy = np.sum(y_true == y_pred) / len(y_true)
        return accuracy

    X, y = datasets.make_moons(n_samples=150, noise=0.2, random_state=2)
    X_train, X_test, y_train, y_test = train_test_split(
        X, y, test_size=0.2, random_state=123
    )

    p = Perceptron(learning_rate=0.01, n_iters=1000)
    p.fit(X_train, y_train)
    predictions = p.predict(X_test)

    print("Perceptron classification accuracy", accuracy(y_test, predictions))

➞ Perceptron classification accuracy 0.8333333333333334
```

