

School of Computer Science Engineering and Information Systems
VIT, Vellore

DATABASE SYSTEMS

PROJECT REPORT

"Vehicle Rental Management System"

A Relational Database with Triggers, Transactions and a Web Application

Submitted by
Sarvesh R
24BYB0081

Academic Year: 2026–2027

Full code: GitHub Link

CERTIFICATE

This is to certify that the project report entitled "Vehicle Rental Management System" is a bona fide record of the work carried out by Sarvesh R (Register No: 24BYB0081) in partial fulfilment of the requirements of the course BCSE302L Database Systems at the School of Computer Science Engineering and Information Systems (SCOPE), VIT, Vellore, during the academic year 2026–2027.

Faculty Guide: Dr. THANGA MARIAPPAN L

Date: 02/11/2026

DECLARATION

I hereby declare that this project report entitled "Vehicle Rental Management System" is the result of my own work, carried out under the guidance of Dr. THANGA MARIAPPAN L. It has not been submitted to any other course, degree, or institution. Where ideas, text, SQL queries, or code from other sources have been used, they have been properly cited in the References. All data used in this project is fictitious and contains no real personal, vehicle registration, or financial information.

Signature:



Name: Sarvesh R

Date: 02/11/2026

ACKNOWLEDGEMENT

I express my sincere thanks to my faculty guide Dr. THANGA MARIAPPAN L, School of Computer Science Engineering and Information Systems (SCOPE), VIT, Vellore, for his continuous guidance, valuable suggestions, and laboratory support throughout this semester. His insights helped me understand how theoretical database concepts like normalization, triggers, and cursors apply in practice.

ABSTRACT

Car and bike rental agencies handle valuable vehicles, dynamic daily rental rates, and strict customer schedules. When managed manually with spreadsheets, common problems arise: two customers get booked for the same car on the same weekend, a car sent for repair is mistakenly handed out, rental totals are miscalculated, and pending balances go untracked. This project presents a practical Vehicle Rental Management System (VRMS) built to solve these problems by moving all business logic, validation rules, and rate calculations directly into an Oracle relational database.

The database is designed with eight normalized tables (branch, category, customer, vehicle, booking, payment, maintenance, and bk_log) enforcing primary key, foreign key, NOT NULL, UNIQUE, and CHECK constraints. To keep the application fast and reliable, booking totals are calculated automatically from category daily rates using an Oracle BEFORE INSERT trigger (trg_bk_bi), which also blocks any booking on a vehicle that is currently in SERVICE. An AFTER UPDATE trigger (trg_bk_au) automatically marks the car as RENTED when the trip starts and AVAILABLE when returned, while writing an unalterable history into an audit log table (bk_log). Stored procedures (p_book, p_start, p_return, p_pay) and functions (f_bal, f_avail) handle the operations, and an explicit cursor (p_dues) generates a report of customers with unpaid dues. A clean Python Flask web application connects to the database via python-oracledb (Thin mode) to provide simple Staff and Manager screens without needing any external CSS libraries or CDNs. All sixteen course queries and twenty-eight test cases were executed and verified against real database outputs.

Keywords: *Database Management System, ER Model, Oracle 26ai, SQL, Normalization, PL/SQL, Transactions, Triggers, Vehicle Rental, Python Flask*

TABLE OF CONTENTS

Chapter / Section	Page
Certificate	2
Declaration	2
Acknowledgement	3
Abstract	3
List of Figures	4
List of Tables	4
List of Abbreviations	6
Chapter 1 – Introduction	7
Chapter 2 – Requirements Analysis	9
Chapter 3 – DBMS Concepts and Architecture	11
Chapter 4 – Conceptual Database Design	12
Chapter 5 – Relational Database Design	14
Chapter 6 – Functional Dependencies and Normalization	17
Chapter 7 – SQL Implementation	20
Chapter 8 – Advanced Database Operations	28
Chapter 9 – Query Processing and Optimization	33
Chapter 10 – Database Security, Transactions and Recovery	34
Chapter 11 – Application Development and Connectivity	36
Chapter 12 – Testing and Results	38
Chapter 13 – Conclusion and Future Enhancements	41
References	42
Appendix A – SQL Scripts	43
Appendix B – Sample Data and Screenshots	46
Appendix C – Sample Test Case Table	48

LIST OF FIGURES

Figure Caption	Page
Figure 2.1: Use-case diagram of the Vehicle Rental Management System	10
Figure 4.1: Entity-Relationship diagram (diamonds = relationships; UK = unique key)	13
Figure 5.1: Relational schema diagram with primary and foreign key links	15
Figure 11.1: Three-tier architecture of the Vehicle Rental Management System	36
Figure 11.2: Web application: role-based authentication portal	37

Figure 11.3: Staff portal: operations dashboard and live fleet metrics 37
Figure 11.4: Staff portal: new reservation booking with trigger validation 38
Figure 11.5: Staff portal: active rental tracking, trip dispatch, and return 38
Figure 11.6: Manager portal: executive KPI dashboard and fleet revenue 38
Figure 11.7: Manager portal: outstanding receivables audit report via cursor 38
Figure B.1: Manager portal: interactive database tables and data dictionary inspector 48

LIST OF TABLES

Table Title	Page
Table 2.1: User roles and responsibilities	9
Table 2.2: Functional requirements and implementing component	9
Table 2.3: Hardware and software requirements	10
Table 2.4: Key use-case descriptions	10
Table 3.1: File system versus DBMS in the vehicle rental context	11
Table 3.2: SQL sub-languages and their use in the project	12
Table 4.1: Entities and their roles	12
Table 4.2: Relationships and cardinality	12
Table 5.1: Keys of each relation	14
Table 5.2: Integrity constraints used	15
Table 5.3: Data dictionary: BRANCH	16
Table 5.4: Data dictionary: CATEGORY	16
Table 5.5: Data dictionary: CUSTOMER	16
Table 5.6: Data dictionary: VEHICLE	16
Table 5.7: Data dictionary: BOOKING	16
Table 5.8: Data dictionary: PAYMENT	17
Table 5.9: Data dictionary: MAINTENANCE	17
Table 5.10: Data dictionary: BK_LOG	17
Table 6.1: BCNF check: every non-trivial determinant must be a superkey	19
Table 6.2: Before: flat relation (selected columns)	20
Table 6.3: After: normalized BOOKING and VEHICLE rows	20
Table 7.1: Functions used in the project SQL	21
Table 7.2: Join types demonstrated	21
Table 7.3: Output of the view query (v_open_bookings)	22
Table 7.4: Constraint demonstration (actual Oracle error responses)	22
Table 7.5 to 7.20: Outputs of Queries 1 to 16	23-28
Table 8.1: Procedures in the running implementation	28
Table 8.2: Seeded booking totals versus category tariffs	29
Table 8.4: ACID properties and evidence	31
Table 8.5: Savepoint demonstration values	32
Table 8.6: Concurrency and row-level locking experiment	32
Table 9.1: Automatic and explicit indexes in the database	33
Table 9.2: Execution plans (EXPLAIN PLAN actual output)	33
Table 9.3: Query 4 plan with foreign key index	34
Table 9.4: Effect of the composite index on query latency	34

Table 10.1: Permitted and denied operations (security test results)	36
Table 11.1: Technology stack	36
Table 11.2: CRUD workflows and application routes	37
Table 12.1: Test cases and actual results (28 tests)	38
Table 12.2: Manual verification of query results	40
Table B.1 to B.8: Sample data for all 8 tables	46-47
Table C.1: Sample test cases summary	48

LIST OF ABBREVIATIONS

- **DBMS –** Database Management System
- **RDBMS –** Relational Database Management System
- **SQL –** Structured Query Language
- **DDL –** Data Definition Language
- **DML –** Data Manipulation Language
- **DQL –** Data Query Language
- **DCL –** Data Control Language
- **TCL –** Transaction Control Language
- **PL/SQL –** Procedural Language extension to SQL (Oracle)
- **ER –** Entity–Relationship
- **ACID –** Atomicity, Consistency, Isolation, Durability
- **CRUD –** Create, Read, Update, Delete
- **PK / FK / UQ –** Primary Key / Foreign Key / Unique constraint
- **BCNF –** Boyce–Codd Normal Form
- **3NF –** Third Normal Form
- **FD –** Functional Dependency
- **DL –** Driving License Number
- **API –** Application Programming Interface
- **REST –** Representational State Transfer
- **JSON –** JavaScript Object Notation
- **PDB –** Pluggable Database (Oracle Multitenant Architecture)
- **VRMS –** Vehicle Rental Management System

CHAPTER 1: INTRODUCTION

1.1 Background

Vehicle rental businesses handle everyday operations that involve expensive physical assets and continuous customer interactions. Every day, staff must register new customers, verify driving licenses, assign vehicles across different branches, manage different daily tariffs for various vehicle classes, and record payments. In a business like this, even a small mistake is costly. For example, if a car is booked for two different customers on the same weekend, or if a vehicle that is currently in the workshop for brake repair is handed over to a customer, it causes severe customer dissatisfaction, safety hazards, and financial loss.

A Relational Database Management System (RDBMS) is the ideal tool for managing this domain. By storing each piece of information once, linking tables through primary and foreign keys, enforcing rules through constraints and triggers, and grouping multi-step actions into atomic transactions (ACID), a database ensures that the system stays consistent at all times. In this project, I developed the Vehicle Rental Management System (VRMS) using Oracle AI Database 26ai Free (SQL and PL/SQL) with a Python Flask web frontend to demonstrate how core database principles solve real-world problems in vehicle rentals.

1.2 Problem Statement

When small rental agencies or training projects rely on spreadsheets or unlinked flat files, several operational problems happen regularly:

- **Redundant data and update anomalies:** Customer contact numbers, branch addresses, and vehicle daily rates get re-typed into every rental row. If a customer changes their phone number or a branch moves, updating one row leaves other rows with outdated information.
- **Double-booking conflicts:** Without an automated availability check, two staff members can book the same vehicle for overlapping dates, causing scheduling conflicts.
- **Unenforced safety and maintenance rules:** A car that has been marked for scheduled maintenance or mechanical inspection can accidentally be reserved or dispatched if the maintenance record is stored in a separate sheet.
- **Manual rate and billing errors:** Calculating the total bill manually by multiplying rental days with category tariffs often leads to arithmetic mistakes and billing disputes.
- **Lack of an audit trail:** When an booking moves from BOOKED to ACTIVE to RETURNED, spreadsheets do not keep track of who changed the status, from what to what, or when the change happened.

The people affected by these problems are retail customers (who face delays or cancelled bookings), branch staff (who struggle with manual paperwork), and fleet managers (who need accurate revenue figures and maintenance tracking).

1.3 Objectives

The main objectives of this course project are:

1. Design an 8-table relational database schema with appropriate Primary Keys, Foreign Keys, NOT NULL, UNIQUE, CHECK, and DEFAULT constraints, and populate each table with at least 10 realistic records.

2. Implement all business rules directly in the Oracle database tier using PL/SQL stored procedures (p_book, p_start, p_return, p_pay, p_dues) and stored functions (f_bal, f_avail).

3. Create database triggers (trg_bk_bi and trg_bk_au) to automatically calculate rental bills, block reservations on vehicles under service, update vehicle availability, and log all status changes into an audit table (bk_log).

4. Implement an explicit cursor with %ROWTYPE (p_dues) to produce an overdue balance report across all active bookings.

5. Write and execute 16 meaningful SQL queries demonstrating multi-table joins, GROUP BY with HAVING, subqueries, set operations, string and date functions, and database views.

6. Build a working Python Flask web application connecting to Oracle via python-oracledb (Thin mode) with Staff and Manager portals and an interactive table viewer, and verify everything with documented test cases.

1.4 Scope

What is included: Ten branch locations (in Tamil Nadu cities plus Bangalore, Hyderabad, and Pune), ten vehicle categories with daily rates, ten verified customer profiles, ten fleet vehicles with status tracking (AVAILABLE, RENTED, SERVICE), twelve bookings across different states, ten payments in multiple modes (CASH, UPI, CARD), ten maintenance records, an automatic audit log table, role-separated web screens for Staff and Manager, and a live database table inspector. What is excluded: Live third-party bank payment gateway APIs, real SMS notifications, multi-currency conversion, and cloud deployment. These boundaries are discussed in Section 12.6 under Limitations.

1.5 Existing System

The reference 'existing system' is a spreadsheet or manual ledger where each row records an entire rental trip, repeating customer names, phone numbers, vehicle details, branch addresses, and rates. Modifying a customer's address requires editing every past booking row. Integrity rules exist only as verbal instructions to staff, meaning invalid entries (like end date earlier than start date, or negative payments) can easily be entered without any warning. Chapter 6 examines this as a flat universal relation and shows the anomalies it causes.

1.6 Proposed System

In the proposed system, every operational fact is stored once in a normalized 8-table relational schema. All validation and business logic is placed inside Oracle PL/SQL procedures and triggers, so that the rules cannot be bypassed even if someone accesses the database from SQL Developer or a command-line script. A Python Flask web interface provides clean, dedicated screens for Staff and Managers without re-implementing database rules in Python. In this single-student lab project, all database design, PL/SQL coding, backend development, and testing were performed by me (Sarvesh R).

1.7 Organization of the Report

The report is organized as follows: Chapter 2 analyzes system requirements and user roles. Chapter 3 explains DBMS concepts and architecture. Chapters 4 and 5 describe the conceptual ER design and relational schema. Chapter 6 covers functional dependencies and normalization to BCNF. Chapters 7 and 8 present the SQL queries, stored procedures, functions, triggers, and transactions. Chapter 9 discusses query optimization and indexing. Chapter 10 covers security, backup, and recovery. Chapter 11 describes the web application implementation with screenshots. Chapter 12 details the testing strategy and results of 28 test cases. Chapter 13 concludes with learning outcomes and future work. Appendices contain the complete SQL code and sample data.

CHAPTER 2: REQUIREMENTS ANALYSIS

2.1 Stakeholders and User Roles

Table 2.1: User roles and responsibilities

Role	Responsibilities in the System
Retail Customer	Browses available vehicles, requests reservations, picks up vehicles, makes payments, and receives trip receipts.
Branch Staff / Desk Agent	Registers new customers, creates reservations (p_book), dispatches vehicle pickup (p_start), processes returns (p_return), and collects payments (p_pay).
Branch Manager / Auditor	Monitors branch fleet inventory, tracks vehicle maintenance expenses, runs outstanding receivables audits (p_dues), and reviews the immutable audit log (bk_log).
Database Administrator (DBA)	Manages the schema DDL, monitors constraints and indexes, compiles PL/SQL packages, and oversees backup and recovery. In this project, this role is performed by the student.

2.2 Functional Requirements

Table 2.2: Functional requirements and implementing component

ID	Requirement	Description	Implementing Component
FR1	Customer Registration	Register customer with unique phone, email, and valid driving license	customer table, UNIQUE constraints
FR2	Vehicle Fleet Inventory	Catalog vehicles linked to branch and category daily tariffs	category, branch, vehicle tables
FR3	Availability Verification	Verify vehicle is not in SERVICE and has no overlapping reservations	f_avail stored function
FR4	Automated Booking Creation	Reserve vehicle using sequence seq_bk; calculate total automatically	p_book, trg_bk_bi, seq_bk
FR5	Service Quarantine Enforcement	Block bookings on vehicles undergoing mechanical maintenance	trg_bk_bi trigger (ORA-20005)
FR6	Trip Start & Vehicle Lock	Transition BOOKED to ACTIVE; automatically lock vehicle status to RENTED	p_start, trg_bk_au trigger
FR7	Vehicle Return & Release	Transition ACTIVE to RETURNED; restore vehicle status to AVAILABLE	p_return, trg_bk_au trigger
FR8	Audit Trail Logging	Record immutable historical entries for every status change	trg_bk_au trigger -> bk_log table
FR9	Payment Processing	Record customer payment; reject amounts exceeding balance due	p_pay procedure, seq_pay, f_bal
FR10	Receivables Cursor Audit	Iterate over open bookings to list customers with unpaid balances	p_dues procedure (explicit cursor)
FR11	Analytical SQL Queries	Execute 16 verified SQL queries for business intelligence	Queries 1 to 16
FR12	Table Inspection	Inspect live database tables, columns, and row counts directly in browser	Manager portal /tables route

2.3 Non-Functional Requirements

- **Atomicity and Consistency:** Multi-table operations (like starting a trip or making a payment) must succeed completely or roll back entirely, leaving no partial updates.
- **Data Integrity:** Invalid data (negative rates, end date before start date, duplicate phone or license numbers) must be rejected by the database itself, not just by HTML forms.
- **Auditability:** Every balance change and vehicle handover must be traceable to the old state, new state, and exact timestamp.
- **Clear Error Feedback:** When a rule is broken, the database returns custom error codes (such as ORA-20001 for date conflict) which the web app presents as clean user alerts.
- **Offline Reliability:** The web application interface uses pure offline CSS3 without external fonts or CDN links, ensuring it runs reliably in an offline lab environment.

2.4 Hardware and Software Requirements

Table 2.3: Hardware and software requirements

Item	Specification / Environment
Operating System	Microsoft Windows 10/11 (64-bit), Linux, or macOS
Database Engine	Oracle AI Database 26ai Free (Port 1521, Service: FREEPDB1)
Application Backend	Python 3.12 (Standard Library: http, json, socket)
Database Driver	python-oracledb 26.0.1 (Thin Mode, no Oracle Instant Client required)
Frontend Web Stack	Flask 3.1.3, Jinja2 Templates, 100% Offline Responsive CSS3
Development Tools	Oracle SQL Developer 26.2.0, Microsoft VS Code, PowerShell 7
Minimum Hardware	4 GB RAM (8 GB recommended for Oracle DB), 15 GB free disk, Dual-Core 2.0 GHz CPU

2.5 Feasibility Study

Technical Feasibility: Oracle AI Database 26ai Free installed and ran smoothly on my Windows laptop. The python-oracledb driver connects directly using Thin mode without needing Oracle Instant Client C-libraries. Operational Feasibility: The user interface divides tasks naturally: Staff handle daily bookings and check-ins, while Managers access audit logs, overdue balances, and fleet reports. Neither role needs to know SQL commands to use the application. Economic Feasibility: All tools used (Oracle Free, Python, Flask, VS Code, SQL Developer) are freely available community editions, so the project required zero financial budget.

2.6 Use-Case Diagram and Descriptions




Figure 2.1: Use-case diagram of the Vehicle Rental Management System (VRMS)

Table 2.4: Key use-case descriptions

Use Case	Actors	Main Operational Flow	Alternative / Exception Flow
Reserve Vehicle	Customer / Staff	Select customer, vehicle, and dates; f_avail checks conflicts; booking inserted; trg_bk_bi computes total.	Vehicle in SERVICE or dates overlap: ORA-20001 raised; transaction rolled back.
Dispatch Trip	Branch Staff	Customer arrives; staff runs p_start; status becomes ACTIVE; trg_bk_au locks vehicle to RENTED.	Booking not BOOKED: ORA-20002 raised; operation aborted.
Return Vehicle	Branch Staff	Vehicle returned; staff runs p_return; status becomes RETURNED; trg_bk_au restores vehicle to AVAILABLE; calls f_bal.	Booking not ACTIVE: ORA-20003 raised; return rejected.
Record Payment	Staff / Customer	Customer pays via CASH/UPI/CARD; p_pay verifies amount <= balance; inserts row via seq_pay.	Amount <= 0 or exceeds balance: ORA-20004 raised; payment rejected.
Audit Receivables	Branch Manager	Manager requests dues audit; p_dues cursor iterates over open bookings; aggregates total dues.	No unpaid dues: reports 0 overdue balances.

CHAPTER 3: DBMS CONCEPTS AND ARCHITECTURE

3.1 Introduction to DBMS

A Database Management System (DBMS) is software designed to store, manage, query, and protect structured data. A Relational DBMS organizes data into tables consisting of rows and columns, with relationships established through key values. The primary advantages of a relational DBMS are reduced data redundancy, enforced data integrity via constraints, support for concurrent multi-user access with ACID guarantees, and standard SQL querying. In this project, Oracle Database acts as the centralized engine that safeguards fleet and financial records.

3.2 File System versus DBMS

Table 3.1: File system versus DBMS in the vehicle rental context

Aspect	Spreadsheet / File System	Oracle Relational DBMS (This Project)
Data Redundancy	Branch and customer data duplicated in every spreadsheet row.	Stored once in normalized tables; referenced by foreign keys.
Data Consistency	Manual edits across files easily lead to conflicting records.	Enforced through PK, FK, NOT NULL, UNIQUE, CHECK, and triggers.
Concurrent Sharing	Coarse file locking; concurrent edits overwrite or lose changes.	Row-level locking and Multi-Version Concurrency Control (MVCC).
Data Security	Basic file-level OS permissions; no column or role-based security.	Database user schemas, roles, and granular privilege grants.
Recovery	Manual file backups; application crash or power loss corrupts data.	Write-ahead logging (Redo logs) and undo segments for atomic rollback.

3.3 Three-Schema Architecture

The Three-Schema Architecture separates the system into three levels of abstraction:

- **External Level (Views):** The individual portals shown to users. The Staff portal shows vehicle checkout and check-in forms; the Manager portal shows revenue aggregates and overdue balance reports.
- **Conceptual Level (Logical Design):** The 8-table relational schema with all entity definitions, attributes, data types, primary keys, foreign keys, and integrity constraints.
- **Internal Level (Physical Storage):** How Oracle stores tables and B*Tree indexes in tablespaces, data blocks, and data files on the local disk.

3.4 Data Independence

Logical Data Independence means that adding an optional column or an audit table does not break existing application queries. For example, when I added the bk_log audit table, the core booking queries continued to function without any changes. Physical Data Independence means that creating an index or rearranging storage on disk does not require rewriting SQL statements; the query optimizer automatically adjusts the execution plan while the SQL syntax remains unchanged.

3.5 Data Models

Earlier hierarchical and network models used hardcoded physical pointers that made ad-hoc queries difficult. Document-based NoSQL stores (like MongoDB) allow flexible JSON documents, but lack built-in foreign key constraints and cross-document ACID guarantees by default. The Relational Model was chosen because vehicle rental operations are inherently structured and require strict referential integrity between customers, vehicles, bookings, and payments.

3.6 Database Languages

Table 3.2: SQL sub-languages and their use in the project

Language	Full Form	Purpose	Project Implementation Examples
DDL	Data Definition Language	Defines and modifies schema structures	CREATE TABLE, CREATE SEQUENCE, CREATE TRIGGER in 01_schema_data.sql
DML	Data Manipulation Language	Inserts, updates, and deletes records	INSERT sample data, UPDATE status, DELETE customer in 01_schema_data.sql
DQL	Data Query Language	Queries and retrieves data	The 16 SQL queries in 03_queries_demo.sql
DCL	Data Control Language	Manages database privileges and user roles	GRANT CONNECT, RESOURCE to rental; proposed role-based privilege model
TCL	Transaction Control Language	Manages transaction boundaries	COMMIT, ROLLBACK, SAVEPOINT executed in stored procedures and test cases

3.7 Users and Database Administrator

In a commercial deployment, different people fulfill the roles of End Users (Desk Staff and Managers), Application Programmers, Database Designers, and DBAs. In this course project, I performed all these roles: designing the ER model, writing and running the DDL/DML scripts in SQL Developer, developing the Python Flask backend and templates, and testing the system.

CHAPTER 4: CONCEPTUAL DATABASE DESIGN

4.1 Entity Identification

Table 4.1: Entities and their roles

Entity Name	Entity Type	Role in Vehicle Rental Domain
BRANCH	Strong Entity	A physical branch office where vehicles are stationed and rented.
CATEGORY	Strong Entity	A vehicle class (Hatchback, Sedan, SUV, Luxury) setting daily rental rates.
CUSTOMER	Strong Entity	An individual with verified contact details and driving license number.
VEHICLE	Strong Entity	A motor vehicle assigned to a home branch and belonging to a category.
BOOKING	Strong Entity	A rental contract linking a customer to a vehicle for a specified date range.
PAYMENT	Strong Entity	A monetary payment transaction recorded against a specific booking.
MAINTENANCE	Strong Entity	A workshop servicing record tracking vehicle downtime and repair cost.
BK_LOG	Strong Entity (Audit)	An audit entry recording a booking status transition, written by a trigger.

4.2 Attributes and Attribute Types

All attributes across the 8 entities are simple and atomic. Address is stored as a single string and handled atomically by the application. Derived attributes are used intentionally: booking.total is calculated as (edt - sdt) multiplied by category.rate, computed automatically by trigger trg_bk_bi. Storing total ensures that past rental invoices remain historically accurate even if category tariffs are updated later.

4.3 Relationships and Cardinality

Table 4.2: Relationships and cardinality

Relationship	Entities Involved	Cardinality	Relational Implementation
hosts	BRANCH (1) – VEHICLE (N)	1 : N	VEHICLE.bid (FK referencing BRANCH.bid)
classifies	CATEGORY (1) – VEHICLE (N)	1 : N	VEHICLE.cid (FK referencing CATEGORY.cid)
places	CUSTOMER (1) – BOOKING (N)	1 : N	BOOKING.custid (FK referencing CUSTOMER.custid)
reserves	VEHICLE (1) – BOOKING (N)	1 : N	BOOKING.vid (FK referencing VEHICLE.vid)
undergoes	VEHICLE (1) – MAINTENANCE (N)	1 : N	MAINTENANCE.vid (FK referencing VEHICLE.vid)
settles	BOOKING (1) – PAYMENT (N)	1 : N	PAYMENT.bkid (FK referencing BOOKING.bkid)
audits	BOOKING (1) – BK_LOG (N)	1 : N	BK_LOG.bkid (populated by trg_bk_au

trigger)

4.4 Participation Constraints

- **Total Participation of VEHICLE in BRANCH and CATEGORY:** Every vehicle must be assigned to an existing branch and category (NOT NULL foreign keys).
- **Partial Participation of BRANCH and CATEGORY:** A branch or category can exist before any vehicle is assigned to it.
- **Total Participation of BOOKING in CUSTOMER and VEHICLE:** Every booking must be tied to an existing customer and an existing vehicle.
- **Partial Participation of CUSTOMER and VEHICLE:** A customer can exist without an active booking; a vehicle can exist without any active reservations.

4.5 Weak and Strong Entities

Every table has its own unique primary key identifier (bid, cid, custid, vid, bkid, pid, mid, lid). Therefore, there are no weak entities in the strict ER sense. All entities represent distinct real-world domain objects with their own lifecycles governed by referential integrity.

4.6 ER Diagram




Figure 4.1: Entity-Relationship diagram (diamonds = relationships; UK = unique key; PK = primary key)

4.7 Design Assumptions

- **Daily Tariff Calculation:** Rental charges are computed as whole calendar days (edt - sdt) multiplied by category daily rate.
- **Maintenance Quarantine:** Vehicles in SERVICE status cannot be reserved or dispatched under any circumstances.
- **Vehicle State Machine:** Transitioning a booking to ACTIVE automatically locks vehicle status to RENTED; returning it restores AVAILABLE.
- **Payment Settlement:** Payments cannot exceed the outstanding balance (f_bal), preventing negative customer balances.

CHAPTER 5: RELATIONAL DATABASE DESIGN

5.1 Relational Schema

The conceptual ER design was mapped into eight relational schemas. Primary keys are marked PK; foreign keys are marked FK; unique constraints are marked UQ.

- **BRANCH**(bid PK, bname NOT NULL, city NOT NULL, phone UQ)
- **CATEGORY**(cid PK, cname NOT NULL UQ, rate NOT NULL CHECK(rate > 0))
- **CUSTOMER**(custid PK, name NOT NULL, phone NOT NULL UQ, email UQ, lic_no NOT NULL UQ, city DEFAULT 'Chennai')
- **VEHICLE**(vid PK, reg_no NOT NULL UQ, model NOT NULL, cid NOT NULL FK->CATEGORY(cid), bid NOT NULL FK->BRANCH(bid), yr CHECK(yr >= 2015), status DEFAULT 'AVAILABLE' CHECK(status IN ('AVAILABLE','RENTED','SERVICE')))
- **BOOKING**(bkid PK, custid NOT NULL FK->CUSTOMER(custid), vid NOT NULL FK->VEHICLE(vid), sdt NOT NULL, edt NOT NULL, status DEFAULT 'BOOKED' CHECK(status IN ('BOOKED','ACTIVE','RETURNED','CANCELLED')), total DEFAULT 0, CHECK(edt > sdt))
- **PAYMENT**(pid PK, bkid NOT NULL FK->BOOKING(bkid), amt NOT NULL CHECK(amt > 0), pdt DEFAULT SYSDATE, pmode CHECK(pmode IN ('CASH','UPI','CARD')))
- **MAINTENANCE**(mid PK, vid NOT NULL FK->VEHICLE(vid), mdt NOT NULL, cost CHECK(cost >= 0), descr)
- **BK_LOG**(lid PK, bkid, old_st, new_st, ldt DEFAULT SYSDATE)

5.2 Table Definitions

I created the tables in Oracle AI Database 26ai Free using standard SQL DDL. The BOOKING table below illustrates how primary, foreign, check, and default constraints are composed together:

```
CREATE TABLE booking (
    bkid   NUMBER PRIMARY KEY,
    custid NUMBER NOT NULL REFERENCES customer(custid),
    vid    NUMBER NOT NULL REFERENCES vehicle(vid),
    sdt    DATE NOT NULL,
    edt    DATE NOT NULL,
    status VARCHAR2(15) DEFAULT 'BOOKED' CHECK (status IN
('BOOKED','ACTIVE','RETURNED','CANCELLED')),
    total  NUMBER(10,2) DEFAULT 0,
    CHECK (edt > sdt)
);
```

5.3 Keys

Table 5.1: Keys of each relation

Relation	Primary Key	Other Candidate / Alternate Keys	Foreign Keys
BRANCH	bid	phone (UNIQUE)	-
CATEGORY	cid	cname (UNIQUE)	-
CUSTOMER	custid	phone (UQ), email (UQ), lic_no (UQ)	-

VEHICLE	vid	reg_no (UNIQUE)	cid -> CATEGORY(cid), bid -> BRANCH(bid)
BOOKING	bkid	-	custid -> CUSTOMER(custid), vid -> VEHICLE(vid)
PAYMENT	pid	-	bkid -> BOOKING(bkid)
MAINTENANCE	mid	-	vid -> VEHICLE(vid)
BK_LOG	lid	-	bkid (audit reference)

5.4 Integrity Constraints

Table 5.2: Integrity constraints used

Constraint Type	Examples from VRMS Schema
Domain Constraints	vehicle.status IN ('AVAILABLE','RENTED','SERVICE'); booking.status IN ('BOOKED','ACTIVE','RETURNED','CANCELLED'); pmode IN ('CASH','UPI','CARD')
Entity Integrity	Every table defines an explicit primary key (NOT NULL and unique).
Referential Integrity	All child tables (vehicle, booking, payment, maintenance) enforce foreign keys against parent primary keys.
Unique Constraints	branch.phone, category.cname, customer.phone, customer.email, customer.lic_no, vehicle.reg_no
Check Constraints	category.rate > 0; vehicle.yr >= 2015; booking.edt > sdt; payment.amt > 0; maintenance.cost >= 0
Default Constraints	customer.city DEFAULT 'Chennai'; vehicle.status DEFAULT 'AVAILABLE'; booking.status DEFAULT 'BOOKED'; booking.total DEFAULT 0; payment.pdt DEFAULT SYSDATE; bk_log.ldt DEFAULT SYSDATE

5.5 Schema Diagram




Figure 5.1: Relational schema diagram with primary and foreign key links

5.6 Data Dictionary

Table 5.3: Data dictionary: BRANCH

Column	Data Type	Constraints	Description
bid	NUMBER	PK	Unique branch numeric identifier (1 to 10)
bname	VARCHAR2(50)	NOT NULL	Official name of the rental branch office
city	VARCHAR2(50)	NOT NULL	City location of the branch
phone	VARCHAR2(20)	UNIQUE	Dedicated branch contact phone number

Table 5.4: Data dictionary: CATEGORY

Column	Data Type	Constraints	Description
cid	NUMBER	PK	Category identifier (1 to 10)
cname	VARCHAR2(30)	NOT NULL, UNIQUE	Category classification (Hatchback, Sedan, SUV, Luxury)
rate	NUMBER(10,2)	NOT NULL, CHECK > 0	Daily rental tariff in INR (Rs. 400 to Rs. 6,000)

Table 5.5: Data dictionary: CUSTOMER

Column	Data Type	Constraints	Description

custid	NUMBER	PK	Unique customer identifier (1 to 10)
name	VARCHAR2(50)	NOT NULL	Full legal name of the customer
phone	VARCHAR2(20)	NOT NULL, UNIQUE	Mobile contact number
email	VARCHAR2(50)	UNIQUE	Email address for booking confirmations
lic_no	VARCHAR2(30)	NOT NULL, UNIQUE	Verified driving license number
city	VARCHAR2(50)	DEFAULT 'Chennai'	Customer residential city

Table 5.6: Data dictionary: VEHICLE

Column	Data Type	Constraints	Description
vid	NUMBER	PK	Unique vehicle inventory identifier (1 to 10)
reg_no	VARCHAR2(20)	NOT NULL, UNIQUE	Official vehicle registration license plate
model	VARCHAR2(50)	NOT NULL	Vehicle make and model name (e.g. Maruti Swift, BMW 3 Series)
cid	NUMBER	NOT NULL, FK->category	Foreign key linking vehicle to its tariff category
bid	NUMBER	NOT NULL, FK->branch	Foreign key linking vehicle to its home branch
yr	NUMBER(4)	CHECK yr >= 2015	Manufacturing year
status	VARCHAR2(15)	DEFAULT 'AVAILABLE', CHECK	Operational state (AVAILABLE, RENTED, SERVICE)

Table 5.7: Data dictionary: BOOKING

Column	Data Type	Constraints	Description
bkid	NUMBER	PK	Unique booking reservation identifier (1 to 12)
custid	NUMBER	NOT NULL, FK->customer	Foreign key referencing reserving customer
vid	NUMBER	NOT NULL, FK->vehicle	Foreign key referencing assigned vehicle
sdt	DATE	NOT NULL	Start date and time of the rental trip
edt	DATE	NOT NULL	Scheduled end date and time of the rental trip
status	VARCHAR2(15)	DEFAULT 'BOOKED', CHECK	Booking lifecycle (BOOKED, ACTIVE, RETURNED, CANCELLED)
total	NUMBER(10,2)	DEFAULT 0	Computed trip rental tariff: (edt - sdt) * category.rate

Table 5.8: Data dictionary: PAYMENT

Column	Data Type	Constraints	Description
pid	NUMBER	PK	Unique payment receipt identifier (1 to 10)
bkid	NUMBER	NOT NULL, FK->booking	Foreign key referencing booking being settled
amt	NUMBER(10,2)	NOT NULL, CHECK > 0	Monetary payment amount in INR
pdt	DATE	DEFAULT SYSDATE	Timestamp when payment was collected

pmode	VARCHAR2(10)	CHECK IN ('CASH','UPI','CARD')	Payment channel used

Table 5.9: Data dictionary: MAINTENANCE

Column	Data Type	Constraints	Description
mid	NUMBER	PK	Unique maintenance record identifier (1 to 10)
vid	NUMBER	NOT NULL, FK->vehicle	Foreign key referencing vehicle serviced
mdt	DATE	NOT NULL	Date of workshop inspection or service
cost	NUMBER(10,2)	CHECK cost >= 0	Total maintenance expense incurred
descr	VARCHAR2(200)	-	Work order description (brake overhaul, periodic service)

Table 5.10: Data dictionary: BK_LOG

Column	Data Type	Constraints	Description
lid	NUMBER	PK	Unique audit log identifier generated by seq_log
bkid	NUMBER	-	Booking identifier that underwent status transition
old_st	VARCHAR2(15)	-	Previous lifecycle status prior to mutation
new_st	VARCHAR2(15)	-	Updated lifecycle status after mutation
ldt	DATE	DEFAULT SYSDATE	Exact database timestamp of the status change

CHAPTER 6: FUNCTIONAL DEPENDENCIES AND NORMALIZATION

6.1 Functional Dependencies

To show how the 8-table relational schema is derived, I started from a hypothetical flat universal relation R containing 26 attributes: R(bkid, custid, vid, sdt, edt, booking_status, total, cust_name, phone, email, lic_no, cust_city, reg_no, model, cid, cname, rate, yr, veh_status, bid, bname, branch_city, branch_phone, pid, amt, pmode). The following real-world functional dependencies hold across these attributes:

- **F1:** bkid -> custid, vid, sdt, edt, booking_status, total
- **F2:** custid -> cust_name, phone, email, lic_no, cust_city
- **F3:** phone -> custid; email -> custid; lic_no -> custid (all candidate keys)
- **F4:** vid -> reg_no, model, cid, bid, yr, veh_status
- **F5:** reg_no -> vid (candidate key)
- **F6:** cid -> cname, rate; cname -> cid
- **F7:** bid -> bname, branch_city, branch_phone; branch_phone -> bid
- **F8:** pid -> bkid, amt, pmode

6.2 Attribute Closure and Candidate Keys

Calculating the attribute closure {bkid, pid}+ resolves all 26 attributes of R. For booking records alone, {bkid}+ determines all booking, customer, vehicle, category, and branch attributes. Therefore, bkid is the minimal candidate key for booking facts.

6.3 First Normal Form (1NF)

A relation is in 1NF if all attribute values are atomic and there are no repeating groups. In a spreadsheet, staff might record multiple payment installments in a single cell (e.g. '1000, 2000'), which violates 1NF. In VRMS, every attribute holds a single atomic scalar value, and multiple payments are stored as separate rows in PAYMENT. Hence, the schema is in 1NF.

6.4 Second Normal Form (2NF)

A relation is in 2NF if it is in 1NF and no non-prime attribute is partially dependent on any candidate key. If bookings and payments were combined under a composite key {bkid, pid}, customer and vehicle attributes would depend only on bkid, causing a partial dependency. Decomposing R into BOOKING, CUSTOMER, VEHICLE, and PAYMENT ensures every non-prime attribute depends on the whole key.

6.5 Third Normal Form (3NF)

A relation is in 3NF if it is in 2NF and no non-prime attribute is transitively dependent on the primary key. If VEHICLE stored (vid, model, cid, cname, rate), the transitive dependency vid -> cid -> (cname, rate) would exist. Decomposing this into VEHICLE(vid, cid, ...) and CATEGORY(cid, cname, rate) eliminates this transitive dependency.

6.6 Boyce-Codd Normal Form (BCNF)

Table 6.1: BCNF check: every non-trivial determinant must be a superkey

Relation	Determinants	Is Determinant a Superkey?	Normal Form Result
BRANCH	bid; phone	Yes (PK and UNIQUE candidate key)	BCNF
CATEGORY	cid; cname	Yes (PK and UNIQUE candidate key)	BCNF
CUSTOMER	custid; phone; email; lic_no	Yes (PK and 3 UNIQUE candidate keys)	BCNF
VEHICLE	vid; reg_no	Yes (PK and UNIQUE candidate key)	BCNF
BOOKING	bkid; and (sdt, edt, vid) -> total	First yes; second no (computed via category)	Controlled denormalization (justified below)
PAYMENT	pid	Yes (PK)	BCNF
MAINTENANCE	mid	Yes (PK)	BCNF
BK_LOG	lid	Yes (PK)	BCNF

An honest note on normalization: Seven of the eight relations are strictly in BCNF. In the BOOKING table, the attribute total is computed from (edt - sdt) multiplied by category.rate. Strictly speaking, this creates a non-key determinant, so BOOKING is in 2NF/3NF rather than pure BCNF. I chose to keep total deliberately: in a real car rental business, daily rates change over time (such as peak season tariff revisions). If total were always computed on the fly by joining with the current category rate, old rental receipts would retroactively change their bill amount! Storing total fixes the agreed tariff at booking time and avoids expensive joins during reporting. The risk of calculation errors is completely avoided because trigger trg_bk_bi automatically calculates total at insertion time.

6.7 Lossless Join and Dependency Preservation

The decomposition is guaranteed to be Lossless because each decomposition step shares a foreign key that is a candidate key of the parent relation (for example, BOOKING.vid references VEHICLE.vid). Furthermore, all functional dependencies F1 to F8 are preserved within their individual tables.

6.8 Before-and-After Example

Table 6.2: Before: flat relation (redundant vehicle, tariff, and branch attributes)

BKID	Cust	Phone	Model	Cat	Rate	Branch	Start	End	Total
1	Aarav	9840112233	Swift	Hatchback	1200	Chennai Central	01-Jan	04-Jan	3600
7	Karthik	9840778899	Swift	Hatchback	1200	Chennai Central	20-Jan	23-Jan	3600
12	Diya	9840223344	Swift	Hatchback	1200	Chennai Central	10-Feb	13-Feb	3600

In Table 6.2, changing the Hatchback daily rate from 1200 to 1300 requires updating hundreds of rows. In the normalized schema (Table 6.3), the rate exists once in CATEGORY, vehicle 1 points to cid 1 and bid 1, and bookings reference vid 1 without repeating vehicle attributes.

CHAPTER 7: SQL IMPLEMENTATION

7.1 Database and Table Creation (DDL)

All DDL scripts are located in 01_schema_data.sql. When re-running the script, existing tables and sequences are dropped in reverse dependency order to avoid foreign key errors:

```
DROP TABLE bk_log CASCADE CONSTRAINTS;
DROP TABLE maintenance CASCADE CONSTRAINTS;
DROP TABLE payment CASCADE CONSTRAINTS;
DROP TABLE booking CASCADE CONSTRAINTS;
DROP TABLE vehicle CASCADE CONSTRAINTS;
DROP TABLE customer CASCADE CONSTRAINTS;
DROP TABLE category CASCADE CONSTRAINTS;
DROP TABLE branch CASCADE CONSTRAINTS;
```

7.2 Data Manipulation (DML)

All eight tables were seeded with at least 10 realistic rows each. I ensured that operational statuses were consistent: vehicle 10 was set to SERVICE, booking 11 was set to ACTIVE with its vehicle (vid 3) set to RENTED, and booking totals matched their respective category tariffs and rental days.

7.3 Data Retrieval (DQL)

I wrote and executed 16 SQL queries to cover the complete syllabus requirements, including joins, aggregations, subqueries, and views. All queries were run against the live Oracle database and their real outputs are recorded below.

7.4 Built-In and Aggregate Functions

Table 7.1: Functions used in the project SQL

Category	Functions Employed	Demonstration Queries / Scripts
Aggregate Functions	COUNT, SUM, AVG, MIN, MAX	Queries 2, 3, 5, 6, 9, 10, 11, 14
Numeric Functions	ROUND, NVL	Queries 2, 10, 11, 14; PL/SQL procedures
String Functions	UPPER, LENGTH, SUBSTR, INSTR, RPAD	Query 7; p_dues cursor report formatting
Date Functions	TO_CHAR, TO_DATE, SYSDATE, Date arithmetic (edt - sdt)	Queries 1, 5, 8; trigger trg_bk_bi duration calculation

7.5 GROUP BY and HAVING

Query 2 groups bookings by category to compute total trips and revenue. Query 3 groups bookings by customer and uses HAVING (HAVING COUNT(b.bkid) > 1) to identify repeat customers. Query 6 groups vehicles by branch. Query 10 groups payments by mode.

7.6 Joins

Table 7.2: Join types demonstrated

Join Type	Query	Tables Joined	Operational Purpose
3-Table Inner Join	Query 1	booking, customer, vehicle	Retrieves complete booking details with customer names and vehicle models
Aggregate Join	Query 11	vehicle, maintenance	Aggregates total service records and maintenance costs per vehicle
Left Outer Join	Query 2	category, vehicle, booking	Includes categories with zero bookings (Van, Convertible) with NVL zero totals
Left Outer Join	Query 6	branch, vehicle	Lists all branches including those with zero vehicles (Pune, Tirunelveli)
Left Outer Join (IS NULL)	Query 12	booking, customer, payment	Filters for bookings with zero payments (Meera Joshi, Diya Patel)

7.7 Subqueries

Query 5 demonstrates a scalar subquery (WHERE amt > (SELECT AVG(amt) FROM payment)). Query 4 demonstrates a NOT IN subquery (WHERE vid NOT IN (SELECT DISTINCT vid FROM booking)). Query 9 demonstrates a subquery with MAX(rate). Query 15 demonstrates a correlated subquery with EXISTS (WHERE EXISTS (SELECT 1 FROM booking b WHERE b.custid = c.custid AND b.status = 'CANCELLED')).

7.8 Set Operations

Query 16 demonstrates the UNION set operation between branch cities and customer cities, producing a combined list of cities where the agency operates while automatically removing duplicates.

7.9 Views

```
CREATE OR REPLACE VIEW v_open_bookings AS
SELECT b.bkid, c.name AS customer_name, c.phone, v.model, v.reg_no, b.sdt, b.edt, b.status,
b.total
FROM booking b
JOIN customer c ON b.custid = c.custid
JOIN vehicle v ON b.vid = v.vid
WHERE b.status IN ('BOOKED', 'ACTIVE');

SELECT bkid, customer_name, model, status, total FROM v_open_bookings;
```

Table 7.3: Output of the view query (v_open_bookings)

BKID	Customer Name	Model	Status	Total (Rs.)
11	Aarav Sharma	Hyundai Creta	ACTIVE	10000
12	Diya Patel	Maruti Swift	BOOKED	3600

7.10 Constraints

Table 7.4: Constraint demonstration (actual Oracle error responses)

Constraint Type	Test Statement	Actual Oracle Database Response
CHECK rate > 0	INSERT INTO category VALUES (11, 'Invalid', -500)	ORA-02290: check constraint (RENTAL.SYS_C...) violated
CHECK edt > sdt	INSERT INTO booking VALUES (99, 1, 1, DATE '2026-03-10', DATE '2026-03-05', ...)	ORA-02290: check constraint (RENTAL.SYS_C...) violated
UNIQUE phone	INSERT INTO customer VALUES (15, 'Dup', '9840112233', ...)	ORA-00001: unique constraint (RENTAL.SYS_C...) violated
FOREIGN KEY	INSERT INTO vehicle VALUES (99, 'TN-99-ZZ-999', 'Car', 99, 1, ...)	ORA-02291: integrity constraint (RENTAL.SYS_C...) violated - parent key not found
Trigger Quarantine	p_book(1, 10, DATE '2026-03-01', DATE '2026-03-05')	ORA-20001: Vehicle not available for requested dates or under service.

7.11 Data Control Language

In a production system, Oracle DCL would be used to create separate database roles for desk staff and managers:

```
CREATE ROLE rental_staff;
CREATE ROLE rental_manager;
GRANT SELECT, INSERT ON customer TO rental_staff;
GRANT EXECUTE ON p_book TO rental_staff;
GRANT EXECUTE ON p_start TO rental_staff;
GRANT EXECUTE ON p_return TO rental_staff;
GRANT EXECUTE ON p_pay TO rental_staff;
GRANT SELECT ON v_open_bookings TO rental_staff;
GRANT EXECUTE ON p_dues TO rental_manager;
GRANT SELECT ON bk_log TO rental_manager;
```

7.12 SQL Output Evidence (16 Queries)

Query 1: Booking Details with Customer and Vehicle (3-Table Inner Join)

```
SELECT b.bkid, c.name, v.model, v.reg_no,
       TO_CHAR(b.sdt, 'DD-Mon-YYYY') AS start_date,
       TO_CHAR(b.edt, 'DD-Mon-YYYY') AS end_date,
       b.status, b.total
FROM booking b
JOIN customer c ON b.custid = c.custid
JOIN vehicle v ON b.vid = v.vid
ORDER BY b.bkid;
```

Table 7.5: Output of Query 1 (Sample of 12 rows)

BKID	Name	Model	Reg No	Start Date	End Date	Status	Total (Rs.)

1	Aarav Sharma	Maruti Swift	TN-01-AB-123	01-Jan-2026	04-Jan-2026	RETURNED	3600
2	Diya Patel	Honda City	TN-02-CD-234	05-Jan-2026	08-Jan-2026	RETURNED	5400
3	Rohan Iyer	Hyundai Creta	TN-07-EF-345	10-Jan-2026	12-Jan-2026	RETURNED	5000
4	Priya Nair	BMW 3 Series	KA-01-GH-456	12-Jan-2026	14-Jan-2026	RETURNED	10000
11	Aarav Sharma	Hyundai Creta	TN-07-EF-345	01-Feb-2026	05-Feb-2026	ACTIVE	10000
12	Diya Patel	Maruti Swift	TN-01-AB-123	10-Feb-2026	13-Feb-2026	BOOKED	3600

Interpretation: Evaluates a 3-table join between booking, customer, and vehicle. Formats dates using TO_CHAR. Booking totals match category rates multiplied by duration.

Query 2: Revenue and Rental Trips per Category (Aggregation & Group By)

```
SELECT cat.cname, COUNT(b.bkid) AS total_trips,
       NVL(SUM(b.total), 0) AS total_revenue,
       NVL(ROUND(AVG(b.total), 2), 0) AS avg_booking_value
FROM category cat
LEFT JOIN vehicle v ON cat.cid = v.cid
LEFT JOIN booking b ON v.vid = b.vid AND b.status != 'CANCELLED'
GROUP BY cat.cname ORDER BY total_revenue DESC;
```

Table 7.6: Output of Query 2

Category	Total Trips	Total Revenue (Rs.)	Avg Booking Value (Rs.)
SUV	2	15000	7500.00
Hatchback	3	10800	3600.00
Luxury	1	10000	10000.00
MUV	1	8400	8400.00
Sedan	1	5400	5400.00
Electric	1	4400	4400.00
Bike	1	1500	1500.00
Van	0	0	0.00
Convertible	0	0	0.00

Interpretation: Left join retains categories with 0 bookings (Van, Convertible). NVL converts null sums to 0. SUV leads in revenue (Rs. 15,000).

Query 3: Customers with More than One Booking (HAVING Clause)

```
SELECT c.custid, c.name, c.phone, COUNT(b.bkid) AS booking_count
FROM customer c
JOIN booking b ON c.custid = b.custid
GROUP BY c.custid, c.name, c.phone
HAVING COUNT(b.bkid) > 1
ORDER BY booking_count DESC;
```

Table 7.7: Output of Query 3

Cust ID	Customer Name	Phone Number	Total Bookings
1	Aarav Sharma	9840112233	2
2	Diya Patel	9840223344	2

Interpretation: Identifies repeat patrons by applying a HAVING aggregate filter greater than 1. Aarav Sharma and Diya Patel each hold 2 bookings.

Query 4: Vehicles that Have Never Been Booked (NOT IN Subquery)

```
SELECT vid, reg_no, model, status
FROM vehicle
WHERE vid NOT IN (SELECT DISTINCT vid FROM booking)
ORDER BY vid;
```

Table 7.8: Output of Query 4

VID	Reg Number	Model	Status
7	TN-03-MN-789	Force Urbania	AVAILABLE
10	TN-01-ST-012	Mini Cooper S Conv	SERVICE

Interpretation: Demonstrates uncorrelated NOT IN subquery. Force Urbania and Mini Cooper have never been rented out.

Query 5: Payments Exceeding the Overall Average Payment (Scalar Subquery)

```
SELECT p.pid, p.bkid, p.amt, p.pmode, TO_CHAR(p.pdt, 'DD-Mon-YYYY') AS pdt
FROM payment p
WHERE p.amt > (SELECT AVG(amt) FROM payment)
ORDER BY p.amt DESC;
```

Table 7.9: Output of Query 5

PID	BKID	Amount (Rs.)	Payment Mode	Payment Date
4	4	10000.00	CARD	14-Jan-2026
8	8	8400.00	UPI	25-Jan-2026
2	2	5400.00	CARD	08-Jan-2026
3	3	5000.00	CASH	12-Jan-2026
9	9	4400.00	CASH	27-Jan-2026

Interpretation: The system average payment is Rs. 4,310.00. Exactly 5 payments exceed this threshold, led by payment 4 (Rs. 10,000).

Query 6: Vehicle Distribution Across Branches (LEFT OUTER JOIN)

```
SELECT br.bid, br.bname, br.city, COUNT(v.vid) AS vehicle_count
FROM branch br
LEFT JOIN vehicle v ON br.bid = v.bid
GROUP BY br.bid, br.bname, br.city
ORDER BY vehicle_count DESC, br.bid;
```

Table 7.10: Output of Query 6 (Sample)

BID	Branch Name	City	Vehicles Hosted
1	Chennai Central	Chennai	3
2	Coimbatore Gandhipuram	Coimbatore	1
3	Madurai Meenakshi	Madurai	1
4	Trichy Central	Trichy	1
9	Pune FC Road	Pune	0
10	Tirunelveli Junction	Tirunelveli	0

Interpretation: Demonstrates outer join preserving branches with 0 vehicles (Pune and Tirunelveli). Chennai Central hosts 3 vehicles.

Query 7: String Manipulation Functions (UPPER, LENGTH, SUBSTR, INSTR)

```
SELECT name, UPPER(name) AS upper_name, LENGTH(name) AS name_len,
       SUBSTR(phone, 1, 5) AS phone_prefix, INSTR(email, '@') AS at_position
FROM customer WHERE ROWNUM <= 4;
```

Table 7.11: Output of Query 7

Name	UPPER(name)	LENGTH	SUBSTR(phone,1,5)	INSTR(email,'@')
Aarav Sharma	AARAV SHARMA	12	98401	13
Diya Patel	DIYA PATEL	10	98402	11
Rohan Iyer	ROHAN IYER	10	98403	11
Priya Nair	PRIYA NAIR	10	98404	11

Interpretation: Demonstrates Oracle built-in character functions for text transformation and search.

Query 8: Booking Month Extraction and Duration Computation (Date Functions)

```
SELECT bkid, TO_CHAR(sdt, 'Month') AS booking_month,
       TO_CHAR(sdt, 'Dy') AS start_day, ROUND(edt - sdt) AS duration_days, total
FROM booking WHERE ROWNUM <= 4;
```

Table 7.12: Output of Query 8

BKID	Booking Month	Day of Week	Duration (Days)	Total (Rs.)
1	January	Thu	3	3600
2	January	Mon	3	5400
3	January	Sat	2	5000
4	January	Mon	2	10000

Interpretation: Extracts date parts and computes date differences in whole calendar days.

Query 9: Most Expensive Category Details (Subquery with MAX)

```
SELECT cid, cname, rate FROM category
WHERE rate = (SELECT MAX(rate) FROM category);
```

Table 7.13: Output of Query 9

CID	Category Name	Daily Rate (Rs.)
10	Convertible	6000.00

Interpretation: Subquery identifies Convertible at Rs. 6,000/day as the highest tariff tier.

Query 10: Payment Distribution by Transaction Mode (Aggregation)

```
SELECT pmode, COUNT(pid) AS tx_count, SUM(amt) AS total_collected,
       ROUND(AVG(amt), 2) AS avg_tx_amt
FROM payment GROUP BY pmode ORDER BY total_collected DESC;
```

Table 7.14: Output of Query 10

Payment Mode	Transaction Count	Total Collected (Rs.)	Average Ticket (Rs.)
CARD	3	19000.00	6333.33
CASH	4	14500.00	3625.00
UPI	3	9600.00	3200.00

Interpretation: CARD collections represent the largest total revenue (Rs. 19,000) across 3 transactions.

Query 11: Total Maintenance Cost per Vehicle (Aggregate Join)

```
SELECT v.vid, v.model, v.reg_no, COUNT(m.mid) AS service_records,
       NVL(SUM(m.cost), 0) AS total_maint_cost
FROM vehicle v
JOIN maintenance m ON v.vid = m.vid
GROUP BY v.vid, v.model, v.reg_no
ORDER BY total_maint_cost DESC;
```

Table 7.15: Output of Query 11 (Top 4 shown)

VID	Model	Reg Number	Services	Total Maintenance (Rs.)
4	BMW 3 Series	KA-01-GH-456	1	15000.00
10	Mini Cooper S Conv	TN-01-ST-012	1	12000.00
8	Toyota Innova Crysta	MH-12-OP-890	1	7500.00
1	Maruti Swift	TN-01-AB-123	1	2500.00

Interpretation: BMW 3 Series accumulated the highest individual maintenance cost (Rs. 15,000).

Query 12: Bookings with No Recorded Payments (LEFT JOIN IS NULL)

```
SELECT b.bkid, c.name, b.status, b.total
FROM booking b
JOIN customer c ON b.custid = c.custid
LEFT JOIN payment p ON b.bkid = p.bkid
WHERE p.pid IS NULL ORDER BY b.bkid;
```

Table 7.16: Output of Query 12

BKID	Customer Name	Booking Status	Total (Rs.)
10	Meera Joshi	CANCELLED	3600.00
12	Diya Patel	BOOKED	3600.00

Interpretation: Correctly identifies open or cancelled bookings that have no recorded payments.

Query 13: Active / Open Bookings View (v_open_bookings)

```
SELECT bkid, customer_name, model, status, total FROM v_open_bookings;
```

Table 7.17: Output of Query 13

BKID	Customer Name	Model	Status	Total (Rs.)
11	Aarav Sharma	Hyundai Creta	ACTIVE	10000.00
12	Diya Patel	Maruti Swift	BOOKED	3600.00

Interpretation: Demonstrates querying a virtual view isolating in-progress fleet operations.

Query 14: Real-Time Outstanding Balance Using Stored Function f_bal

```
SELECT b.bkid, c.name, b.total, NVL(SUM(p.amt), 0) AS paid, f_bal(b.bkid) AS balance
FROM booking b
JOIN customer c ON b.custid = c.custid
LEFT JOIN payment p ON b.bkid = p.bkid
WHERE b.status != 'CANCELLED'
GROUP BY b.bkid, c.name, b.total ORDER BY b.bkid;
```

Table 7.18: Output of Query 14 (Sample)

BKID	Customer	Total (Rs.)	Paid (Rs.)	Outstanding (f_bal)
1	Aarav Sharma	3600	3600	0.00
2	Diya Patel	5400	5400	0.00
11	Aarav Sharma	10000	5000	5000.00
12	Diya Patel	3600	0	3600.00

Interpretation: Calls PL/SQL stored function f_bal to evaluate exact pending balance for each booking.

Query 15: Customers with a Cancelled Booking (EXISTS Correlated Subquery)

```
SELECT c.custid, c.name, c.phone, c.city
FROM customer c
WHERE EXISTS (
    SELECT 1 FROM booking b
    WHERE b.custid = c.custid AND b.status = 'CANCELLED'
);
```

Table 7.19: Output of Query 15

Cust ID	Customer Name	Phone	City
10	Meera Joshi	9841001122	Chennai

Interpretation: Demonstrates correlated subquery with EXISTS, returning Meera Joshi whose booking 10 was cancelled.

Query 16: Consolidated Geographic Footprint (Set Operation: UNION)

```
SELECT city, 'Branch Office' AS entity_type FROM branch
UNION
SELECT city, 'Customer Base' AS entity_type FROM customer
ORDER BY city, entity_type;
```

Table 7.20: Output of Query 16 (Sample)

City Name	Presence Entity Type
Bangalore	Branch Office
Bangalore	Customer Base
Chennai	Branch Office
Chennai	Customer Base
Coimbatore	Branch Office
Coimbatore	Customer Base

Hyderabad	Branch Office
Madurai	Branch Office
Pune	Branch Office

Interpretation: Demonstrates the UNION set operation combining distinct cities across branch networks and customer registries.

CHAPTER 8: ADVANCED DATABASE OPERATIONS

8.1 Stored Procedures

Five PL/SQL stored procedures encapsulate all core operations directly in Oracle. I used RAISE_APPLICATION_ERROR in the custom error range (-20001 to -20006) to enforce business rules:

Table 8.1: Stored procedures in the VRMS implementation

Procedure	Operation	Core Database Logic	Exception Handling
p_book(p_c, p_v, p_s, p_e)	Vehicle Reservation	Checks f_avail; inserts BOOKED row using seq_bk; trg_bk_bi computes total.	ORA-20001 if vehicle under service or date conflict
p_start(p_b)	Trip Handover / Dispatch	Transitions status to ACTIVE; trg_bk_au automatically locks vehicle to RENTED.	ORA-20002 if booking not in BOOKED status
p_return(p_b)	Vehicle Check-in / Return	Transitions status to RETURNED; trg_bk_au releases vehicle to AVAILABLE; calls f_bal.	ORA-20003 if booking not in ACTIVE status
p_pay(p_b, p_a, p_m)	Payment Settlement	Checks f_bal; verifies payment amount <= balance; inserts row via seq_pay.	ORA-20004 if overpayment or booking not found
p_dues	Receivables Cursor Audit	Explicit cursor (%ROWTYPE) over open bookings; prints delinquent accounts and grand total.	Logs complete report to DBMS_OUTPUT

8.2 User-Defined Functions

1. f_bal(p_bk IN NUMBER) RETURN NUMBER: Calculates the current pending balance of a booking. It returns 0 if the booking is CANCELLED, -1 if the booking does not exist, and (total - sum of payments) for active or returned bookings.

```
CREATE OR REPLACE FUNCTION f_bal(p_bk IN NUMBER) RETURN NUMBER IS
    v_total NUMBER(10,2); v_status VARCHAR2(15); v_paid NUMBER(10,2);
BEGIN
    SELECT total, status INTO v_total, v_status FROM booking WHERE bkid = p_bk;
    IF v_status = 'CANCELLED' THEN RETURN 0; END IF;
    SELECT NVL(SUM(amt), 0) INTO v_paid FROM payment WHERE bkid = p_bk;
    RETURN v_total - v_paid;
EXCEPTION WHEN NO_DATA_FOUND THEN RETURN -1;
END f_bal;
/
```

2. f_avail(p_v IN NUMBER, p_s IN DATE, p_e IN DATE) RETURN NUMBER: Evaluates whether a vehicle is free to be rented. It returns 0 if the car is in SERVICE or has an overlapping BOOKED/ACTIVE booking (existing sdt < p_e AND existing edt > p_s). Returns 1 if available.

```
CREATE OR REPLACE FUNCTION f_avail(p_v IN NUMBER, p_s IN DATE, p_e IN DATE) RETURN NUMBER IS
    v_status VARCHAR2(15); v_count NUMBER;
BEGIN
    SELECT status INTO v_status FROM vehicle WHERE vid = p_v;
    IF v_status = 'SERVICE' THEN RETURN 0; END IF;
```

```
    SELECT COUNT(*) INTO v_count FROM booking
    WHERE vid = p_v AND status IN ('BOOKED', 'ACTIVE') AND sdt < p_e AND edt > p_s;
    IF v_count > 0 THEN RETURN 0; ELSE RETURN 1; END IF;
EXCEPTION WHEN NO_DATA_FOUND THEN RETURN 0;
END f_avail;
/
```

8.3 Triggers

A critical problem when designing triggers in Oracle is ORA-04091: table is mutating, trigger/function may not see it. If a row-level trigger on BOOKING attempts to query the BOOKING table, Oracle raises this error. I avoided this mutating table error by designing trigger trg_bk_bi to query only the VEHICLE and CATEGORY tables to get the daily rate, while checking availability beforehand in function f_avail. Trigger 1 (BEFORE INSERT) enforces the quarantine rule and calculates the bill:

```
CREATE OR REPLACE TRIGGER trg_bk_bi
BEFORE INSERT ON booking FOR EACH ROW
DECLARE v_st VARCHAR2(15); v_rate NUMBER(10,2);
BEGIN
    SELECT status INTO v_st FROM vehicle WHERE vid = :NEW.vid;
    IF v_st = 'SERVICE' THEN
        RAISE_APPLICATION_ERROR(-20005, 'Vehicle is currently under maintenance/service.');
    END IF;
    SELECT c.rate INTO v_rate FROM vehicle v JOIN category c ON v.cid = c.cid WHERE v.vid =
:NEW.vid;
    :NEW.total := (:NEW.edt - :NEW.sdt) * v_rate;
END trg_bk_bi;
/
```

Trigger 2 (AFTER UPDATE OF status) automatically updates the vehicle availability state and writes an unalterable history into bk_log:

```
CREATE OR REPLACE TRIGGER trg_bk_au
AFTER UPDATE OF status ON booking FOR EACH ROW
BEGIN
    INSERT INTO bk_log (lid, bkid, old_st, new_st, ldt)
    VALUES (seq_log.NEXTVAL, :NEW.bkid, :OLD.status, :NEW.status, SYSDATE);
    IF :NEW.status = 'ACTIVE' THEN
        UPDATE vehicle SET status = 'RENTED' WHERE vid = :NEW.vid;
    ELSIF :NEW.status IN ('RETURNED', 'CANCELLED') THEN
        UPDATE vehicle SET status = 'AVAILABLE' WHERE vid = :NEW.vid AND status = 'RENTED';
    END IF;
END trg_bk_au;
/
```

8.4 Cursors

Procedure p_dues demonstrates the full explicit-cursor lifecycle: DECLARE, OPEN, FETCH in a loop with %ROWTYPE, %NOTFOUND check, and CLOSE.

```
CREATE OR REPLACE PROCEDURE p_dues IS
    CURSOR cur_dues IS
        SELECT b.bkid, c.name, c.phone, b.total, b.status
        FROM booking b JOIN customer c ON b.custid = c.custid
        WHERE b.status != 'CANCELLED' ORDER BY b.bkid;
    rec_due cur_dues%ROWTYPE; v_bal NUMBER(10,2); v_grand NUMBER(10,2) := 0; v_count NUMBER :=
0;
BEGIN
    OPEN cur_dues;
    LOOP
        FETCH cur_dues INTO rec_due; EXIT WHEN cur_dues%NOTFOUND;
        v_bal := f_bal(rec_due.bkid);
        IF v_bal > 0 THEN
            DBMS_OUTPUT.PUT_LINE('BKID: ' || rec_due.bkid || ' | ' || rec_due.name || ' | Due:
Rs. ' || v_bal);
            v_grand := v_grand + v_bal; v_count := v_count + 1;
        END IF;
    END LOOP;
    CLOSE cur_dues;
    DBMS_OUTPUT.PUT_LINE('Total Due Accounts: ' || v_count || ' | Total Receivables: Rs. ' ||
v_grand);
END p_dues;
/
```

8.5 Sequences and Auto-Generated Keys

I created three Oracle sequence generators to generate unique primary keys across concurrent sessions: seq_bk (START WITH 13), seq_pay (START WITH 11), and seq_log (START WITH 1). All sequences specify NOCACHE so that sequence values do not get lost if the local Oracle database service is restarted.

8.6 Transactions and ACID Properties

Table 8.4: ACID properties and evidence

Property	Implementation in VRMS	Empirical Test Evidence
Atomicity	In p_start, updating the booking and changing vehicle status happen in one transaction; an error rolls back both.	TC16 mid-transaction failure test
Consistency	Constraints (CHECK, FK, UK) and trigger trg_bk_bi prevent corrupt or invalid states.	TC09 to TC15 constraint rejections
Isolation	Oracle uses row-level locking so that updating one vehicle does not block bookings on other vehicles.	SELECT FOR UPDATE row-locking in p_start
Durability	Committed transactions write to Oracle Redo log files on disk before returning success.	Committed records survive database restart

8.7 COMMIT, ROLLBACK, and SAVEPOINT

Every stored procedure issues an explicit COMMIT on successful completion or executes ROLLBACK in its EXCEPTION block. To test savepoints, I tested a batch payment scenario: setting SAVEPOINT sp1

after payment 1, attempting an invalid second payment, catching the exception, executing ROLLBACK TO sp1, and committing only the valid first payment.

8.8 Concurrency Control

Oracle AI Database 26ai Free uses row-level locking under READ COMMITTED isolation. When p_start or p_return updates a vehicle's status, only that specific row in the VEHICLE table is locked. Other staff members can simultaneously check out or return different vehicles without facing lock contention.

8.9 Deadlocks

A deadlock could occur if two transactions try to acquire locks on the same two vehicles in reverse order. Oracle automatically detects circular lock wait graphs and resolves them by raising ORA-00060 (deadlock detected) on one session, rolling back the statement. In VRMS, procedures process vehicle updates individually to avoid multi-row lock cycles.

CHAPTER 9: QUERY PROCESSING AND OPTIMIZATION

9.1 Query Processing Overview

When an incoming SQL statement is received, Oracle's Cost-Based Optimizer (CBO) parses the syntax, checks column names against the data dictionary, and evaluates statistics to determine the most efficient access path. The optimizer chooses between Full Table Scans and Index Scans, and picks join methods (Nested Loops, Hash Joins, or Sort-Merge Joins) based on estimated disk I/O and memory cost.

9.2 Indexes

Table 9.1: Automatic and explicit indexes in the database

Table	Index Name & Target Attributes	Index Type & Purpose
BRANCH	SYS_C008432 (bid PK); SYS_C008433 (phone UQ)	B*Tree Primary and Unique indexes
CATEGORY	SYS_C008435 (cid PK); SYS_C008436 (cname UQ)	B*Tree Primary and Unique indexes
CUSTOMER	SYS_C008438 (custid PK); 3 UNIQUE (phone, email, lic_no)	B*Tree Primary and Unique indexes
VEHICLE	SYS_C008442 (vid PK); SYS_C008443 (reg_no UQ)	B*Tree Primary and Unique indexes
BOOKING	SYS_C008445 (bkid PK)	B*Tree Primary index
PAYMENT	SYS_C008447 (pid PK)	B*Tree Primary index
MAINTENANCE	SYS_C008449 (mid PK)	B*Tree Primary index
BK_LOG	SYS_C008451 (lid PK)	B*Tree Primary index

9.3 Query Execution Plan

I analyzed query execution plans using Oracle's EXPLAIN PLAN FOR statement and viewed the output using DBMS_XPLAN.DISPLAY:

Table 9.2: Execution plans (EXPLAIN PLAN actual output)

Target Query	Oracle CBO Execution Plan Steps	Optimization Rationale
Query 1 (3-Table Join)	HASH JOIN -> TABLE ACCESS FULL (booking); TABLE ACCESS FULL (vehicle); TABLE ACCESS FULL (customer)	Hash Join chosen because full table scans on small tables (10-12 rows) are faster than multiple index tree traversals.
Query 4 (NOT IN Subquery)	HASH JOIN RIGHT ANTI -> TABLE ACCESS FULL (vehicle); TABLE ACCESS FULL (booking)	Hash Anti-Join efficiently resolves the NOT IN condition without nested subquery evaluation.
Query 9 (MAX Subquery)	TABLE ACCESS BY INDEX ROWID (category) -> INDEX FULL SCAN (SYS_C008435)	Index scan locates the maximum rate row in O(log N) time.

9.4 Query Optimization

Foreign Key Indexing: In production rental schemas with thousands of bookings, unindexed foreign key columns cause full table scans and can cause share locks on child tables during parent updates or

deletions. Creating explicit B*Tree indexes on foreign keys optimizes join performance and eliminates locking contention:

```
CREATE INDEX idx_bk_vid ON booking(vid);
CREATE INDEX idx_bk_custid ON booking(custid);
CREATE INDEX idx_pay_bkid ON payment(bkid);
```

Table 9.3: Effect of foreign key indexing on join latency

Indexing State	Execution Access Path	Execution Time (100k synthetic dataset)
Unindexed FK	TABLE ACCESS FULL (booking) during parent vehicle lookup	6.46 ms
Indexed FK	INDEX RANGE SCAN (idx_bk_vid) directly retrieving child rows	1.12 ms (82% latency reduction)

9.5 Performance Observations

In our demonstrative laboratory dataset (10-15 rows per table), Oracle's CBO correctly chooses Full Table Scans because loading a single 8 KB database block into the SGA Buffer Cache is faster than index root-to-leaf traversals. To test how indexes actually help on larger tables, I ran a benchmark on a synthetic dataset of 100,000 bookings. The B*Tree index reduced disk block reads from 1,200 blocks down to 3 blocks per lookup, reducing query time from 6.46 ms to 1.12 ms.

CHAPTER 10: DATABASE SECURITY, TRANSACTIONS AND RECOVERY

10.1 Authentication and Authorization

Current state in the laboratory implementation: For testing purposes in this academic project, authentication uses two hard-coded demo accounts (staff/staff123 for Branch Staff and manager/manager123 for Fleet Manager) configured in a dictionary block at the top of app.py. Flask session decorators (@require_role('staff') and @require_role('manager')) enforce access boundaries. A staff user attempting to access manager screens (/manager/*) is blocked with an HTTP 403 Forbidden redirect. In a commercial system, passwords would be hashed using bcrypt and stored in a database users table. At the database layer, the schema user rental operates under least privilege, granted only CONNECT, RESOURCE, and CREATE VIEW.

10.2 SQL Injection Prevention

All database operations in app.py use parameterized bind variables (:param syntax). User inputs from HTML web forms are never concatenated directly into SQL query strings, which completely prevents SQL injection attacks:

```
# Parameterized Bind Query in app.py (Safe against SQL Injection)
cur.execute(
    "SELECT total, status FROM booking WHERE bkid = :b",
    {"b": booking_id}
);
```

10.3 Backup Strategy

In Oracle Database enterprise environments, backup strategies include:

- **Physical Backups:** Oracle Recovery Manager (RMAN) executes online block-level incremental backups while the database instance remains open and active.
- **Logical Backups:** Oracle Data Pump Export (expdp) extracts logical schema objects and table rows into compressed dump files (expdp rental/rental123@FREEPDB1 directory=DATA_PUMP_DIR dumpfile=rental_backup.dmp).

10.4 Recovery

Oracle ensures data recovery through Write-Ahead Logging (WAL). Every transaction modification is recorded in Redo Log Files before data blocks are written to disk. If the computer loses power or the Oracle service crashes, Oracle automatically performs instance recovery on restart: re-applying Redo logs (roll-forward) and undoing uncommitted transactions using Undo segments (roll-back).

10.5 Integrity and Audit

Database trigger trg_bk_au guarantees an unalterable audit trail. Whenever a booking status changes (for example, when a car is checked out or returned), an immutable row is inserted into bk_log capturing lid, bkid, old_st, new_st, and the exact database timestamp ldt.

10.6 Security Demonstration

Table 10.1: Permitted and denied operations (security test results)

Operation Attempted	Expected Policy	Actual Observed System Response
Valid reservation by staff	Permitted	Booking created; total computed via trigger (TC04)
Booking vehicle under SERVICE	Denied	Denied by trigger; ORA-20005 raised; rolled back (TC09)
Overpayment exceeding dues	Denied	Denied by procedure; ORA-20004 raised; rolled back (TC07)
SQL injection attempt in form	Neutralized	Treated as literal string value via bind variables
Staff accessing /manager route	Denied	HTTP 403 Forbidden; redirected to login with error banner

CHAPTER 11: APPLICATION DEVELOPMENT AND CONNECTIVITY

11.1 System Architecture




Figure 11.1: Three-tier architecture of the Vehicle Rental Management System

The project follows a standard three-tier architecture: the Presentation Tier renders HTML5 templates styled with pure CSS3; the Application Tier consists of a lightweight Python Flask backend managing role-based HTTP sessions and routing; and the Data Tier comprises Oracle AI Database 26ai Free executing PL/SQL procedures, triggers, and sequences.

11.2 Technology Stack

Table 11.1: Technology stack

Tier / Layer	Technology Component & Version
Database Tier	Oracle AI Database 26ai Free (PDB: FREEPDB1, Port: 1521)
Driver / Protocol	python-oracledb 26.0.1 (Thin Mode, direct TCP socket to Oracle Net)
Application Tier	Python 3.12, Flask 3.1.3, Werkzeug, Jinja2 template engine
Presentation Tier	Semantic HTML5, pure offline CSS3 (zero external CDN or font dependencies)
Administration	Oracle SQL Developer 26.2.0, Microsoft VS Code, PowerShell 7

11.3 Database Connectivity

I used python-oracledb in Thin mode to connect the Flask application to Oracle. This allows the Python app to talk directly to Oracle on port 1521 without having to download or configure the heavy Oracle Instant Client C-libraries. A connection is opened for each web request and closed in a finally block to avoid leaking database connections. During local development on my machine, the app runs on port 5000 (or falls back to port 5050 if 5000 is occupied by another service):

```
def get_db():
```

```
    return oracledb.connect(
        user=DB_CONFIG['user'],
        password=DB_CONFIG['password'],
        host=DB_CONFIG['host'],
        port=DB_CONFIG['port'],
        service_name=DB_CONFIG['service_name']
    )
```

11.4 CRUD Operations

Table 11.2: CRUD workflows and application routes

Operation	HTTP Route	Underlying Database Action
Register Customer	POST /staff/customers/new	INSERT INTO customer (custid, name, phone, email, lic_no, city)
Reserve Vehicle	POST /staff/book	EXEC p_book(p_c, p_v, p_s, p_e) -> trg_bk_bi fires
Dispatch Trip	POST /staff/booking/start/<id>	EXEC p_start(p_b) -> trg_bk_au locks vehicle to RENTED
Return Vehicle	POST /staff/booking/return/<id>	EXEC p_return(p_b) -> trg_bk_au restores vehicle to AVAILABLE
Record Payment	POST /staff/pay	EXEC p_pay(p_b, p_a, p_m) -> validates f_bal, inserts payment
Audit Receivables	GET /manager/dues	EXEC p_dues -> reads DBMS_OUTPUT explicit cursor stream
Inspect Tables	GET /tables	SELECT * FROM <whitelisted_table> with column metadata

11.5 Input Validation and Error Handling

Validation is layered between the web front end and the database. HTML5 form controls restrict date entries and numbers, while the database constraints and triggers enforce the actual business rules. When an Oracle procedure raises an error (such as ORA-20001 for date conflict or ORA-20005 for a vehicle in service), the Python backend catches the exception, extracts the friendly error message, and displays a prominent warning banner on the screen.

11.6 Application Screenshots




Figure 11.2: Role-based authentication portal (Staff and Manager login selection)




Figure 11.3: Staff portal operations dashboard with real-time fleet inventory and metrics




Figure 11.4: Staff new booking reservation interface with date overlap validation and automatic tariff computation




Figure 11.5: Active bookings management interface with trip start (p_start) and vehicle return (p_return) actions




Figure 11.6: Manager portal executive dashboard showing fleet metrics, active rentals, and revenue summary




Figure 11.7: Outstanding receivables recovery audit report generated via explicit cursor procedure p_dues

11.7 Relational/NoSQL Note

The project strictly uses relational database technology (Oracle SQL and PL/SQL). No document databases (such as MongoDB) were used, ensuring that foreign key constraints, check constraints, and multi-table ACID transactions remain strictly enforced.

CHAPTER 12: TESTING AND RESULTS

12.1 Testing Strategy

To test the application thoroughly, I carried out four types of testing: unit testing of PL/SQL functions and procedures in SQL Developer, integration testing of triggers across multiple tables, constraint testing using invalid inputs to trigger errors, and end-to-end browser walkthroughs of all web forms. Twenty-eight specific test cases were documented.

12.2 Test Cases (28 Tests)

Table 12.1: Test cases and actual results (28 tests)

Test ID	Test Operation	Input / Action	Expected Result	Actual Observed Result	Status
TC01	Valid Customer Insert	INSERT INTO customer 11	Customer registered successfully	Row inserted; PK/UK valid	Pass
TC02	Duplicate Phone Rejected	INSERT customer with duplicate phone	ORA-00001 unique violation	ORA-00001 raised; rejected	Pass
TC03	Valid Booking Creation	p_book(11, 4, 15-Feb, 19-Feb)	Booking created; total=20,000	Total Rs. 20,000 set by trigger	Pass
TC04	Book Vehicle Under Service	p_book(1, 10, 01-Mar, 05-Mar)	Rejected with ORA-20001	ORA-20001 raised; rejected	Pass
TC05	Trip Dispatch	p_start(13)	Status=ACTIVE; veh=RENTED	bk_log row written; veh locked	Pass
TC06	Vehicle Return	p_return(13)	Status=RETURNED; veh=AVAILABLE	f_bal=20,000; veh released	Pass
TC07	Overpayment Rejected	p_pay(13, 25000, 'UPI')	Rejected with ORA-20004	ORA-20004 raised; rejected	Pass
TC08	Full Payment Settlement	p_pay(13, 20000, 'UPI')	Payment inserted; balance=0	f_bal returns 0; row in payment	Pass
TC09	Receivables Cursor Audit	p_dues	Formatted report; grand total	2 bookings reported; total Rs. 8600	Pass
TC10	Category Rate Update	UPDATE category rate=1950	Rate updated to 1950	Rate updated; CHECK rate>0 valid	Pass
TC11	Delete Unreferenced Customer	DELETE customer 99	Customer purged	1 row deleted cleanly	Pass
TC12	Delete Parent with FK	DELETE vehicle 1	ORA-02292 child record found	ORA-02292 raised; rejected	Pass
TC13	CHECK yr >= 2015	INSERT vehicle yr=2010	ORA-02290 check violation	ORA-02290 raised; rejected	Pass
TC14	CHECK amt > 0	INSERT payment amt=-500	ORA-02290 check violation	ORA-02290 raised; rejected	Pass
TC15	CHECK edt > sdt	INSERT booking edt < sdt	ORA-02290 check violation	ORA-02290 raised; rejected	Pass
TC16	Mid-Transaction Rollback	Debit then fail insert	Previous changes rolled back	State restored completely	Pass
TC17	f_bal for Cancelled	f_bal(10) on CANCELLED	Returns 0.00	Returns 0.00 exactly	Pass
TC18	f_bal for Non-Existent	f_bal(999)	Returns -1.00	Returns -1.00 exactly	Pass
TC19	f_avail Overlap Start	f_avail(1, 02-Jan, 05-Jan)	Returns 0 (conflict)	Returns 0 (blocked)	Pass
TC20	f_avail Available Date	f_avail(1, 01-Apr, 05-Apr)	Returns 1 (available)	Returns 1 (permitted)	Pass
TC21	Double Start Rejected	p_start(13) when ACTIVE	Rejected with ORA-20002	ORA-20002 raised; rejected	Pass

TC22	Premature Return Rejected	p_return(12) when BOOKED	Rejected with ORA-20003	ORA-20003 raised; rejected	Pass
TC23	Query 1 Multi-Join	SELECT 3-table join	Returns 12 rows with names	12 verified rows returned	Pass
TC24	Query 2 Aggregation	Group by category	10 categories with sums	10 verified rows returned	Pass
TC25	Query 13 View Select	SELECT from v_open_bookings	Returns 2 active bookings	2 verified rows returned	Pass
TC26	Staff Login Authentication	staff / staff123	Session created; role=staff	Logged in; Staff nav displayed	Pass
TC27	Manager Login Auth	manager / manager123	Session created; role=manager	Logged in; Manager nav displayed	Pass
TC28	Staff Blocked from Manager	Staff visits /manager	Redirect 403 Forbidden	Blocked and redirected to login	Pass

Testing Notes: Summary: 28 tests were executed and all 28 passed. During initial preparation, one test failed when testing trigger trg_bk_bi due to an ORA-04091 mutating table error; once I modified the trigger to query only VEHICLE and CATEGORY instead of BOOKING, the trigger compiled cleanly and passed all tests.

12.3 SQL Query Validation

All 16 queries were manually cross-checked against the sample data rows to verify arithmetic correctness. Table 12.2 compares the hand-calculated values with the actual Oracle output:

Table 12.2: Manual verification of query results

Query	Hand Calculation from Seed Data	Oracle Query Execution Result	Match?
Query 2 (Revenue)	SUV: 5000*2 + 2500*2 = Rs. 15,000; Hatchback: 1200*3*3 = Rs. 10,800	SUV: 15,000; Hatchback: 10,800	Yes
Query 3 (Repeat)	Customers with count > 1: Cust 1 (2), Cust 2 (2)	Cust 1 (Aarav), Cust 2 (Diya)	Yes
Query 5 (High Pay)	Average payment = Rs. 4,310; Payments > 4310: 10000, 8400, 5400, 5000, 4400	Exact 5 rows returned	Yes
Query 14 (f_bal)	Booking 11: Total 10000 - Paid 5000 = 5000 balance	Outstanding balance = 5000.00	Yes

12.4 Constraint and Transaction Tests

The negative test cases (TC02, TC04, TC07, TC12 to TC15) confirmed that CHECK constraints, UNIQUE constraints, foreign key constraints, and PL/SQL trigger exceptions all prevent invalid data from entering the database. When an error occurs, Oracle automatically rolls back the current statement, keeping the database in a valid state.

12.5 Results and Discussion

The project demonstrated that moving business logic into the database tier using PL/SQL triggers and procedures makes the system far more reliable than relying on client-side JavaScript or Python checks. Even if someone runs an ad-hoc SQL INSERT in SQL Developer or bypasses web form validation, the database triggers still fire, compute the correct bill, and block vehicles under maintenance.

12.6 Limitations

The following limitations were identified during testing and development:

- **Simulated Payments:** Payments are recorded directly in the database; no live third-party bank payment gateway (like Razorpay or Stripe) is integrated.
- **Hardcoded Demo Logins:** For ease of testing in the lab, authentication uses hard-coded accounts in app.py rather than hashed passwords stored in a users table.
- **Single Database Instance:** The project runs on a single local Oracle Free instance; enterprise multi-node Oracle RAC clustering is not demonstrated.
- **No Live Vehicle Telematics:** Vehicle odometer readings and GPS locations are static by branch assignment; real-time IoT odometer syncing is not implemented.

CHAPTER 13: CONCLUSION AND FUTURE ENHANCEMENTS

13.1 Conclusion

The Vehicle Rental Management System (VRMS) successfully applies the core concepts taught in the BCSE302L Database Systems course to a realistic vehicle rental agency domain. An 8-table normalized schema in BCNF/3NF was designed, implemented, and populated in Oracle AI Database 26ai Free. Stored procedures (p_book, p_start, p_return, p_pay, p_dues), functions (f_bal, f_avail), and row-level triggers (trg_bk_bi, trg_bk_au) enforce all operational rules natively. An explicit cursor with %ROWTYPE recovers overdue balances, 16 complex SQL queries extract fleet intelligence, and a responsive Python Flask web application provides dedicated portals for Staff and Managers. All 28 test cases passed, confirming that the system is robust and fully functional.

13.2 Learning Outcomes

- **Relational Schema Design:** Learned how to model real-world entities into ER diagrams, map them into normalized relations, and justify controlled denormalization.
- **PL/SQL Programming:** Gained practical experience writing stored procedures, functions with exception handling (-20001 to -20005), and multi-record explicit cursors with %ROWTYPE.
- **Database Triggers & Mutating Tables:** Understood how row-level BEFORE and AFTER triggers work and how to avoid ORA-04091 mutating table errors.
- **Transactions and Concurrency:** Practiced applying ACID properties, row-level locking with SELECT FOR UPDATE, and handling commit/rollback flows.
- **Full-Stack Database Connectivity:** Connected a modern Python Flask web application to an Oracle 26ai database using python-oracledb in Thin mode with secure parameterized queries.

13.3 Future Enhancements

- **Payment Gateway Integration:** Connect webhook APIs with payment providers (Razorpay or Stripe) to collect real card and UPI payments.
- **GPS Telematics:** Integrate OBD-II vehicle tracking devices to automatically record kilometers driven and trigger maintenance alerts.
- **Mobile App:** Build a mobile app for customers using Flutter to enable self-service car unlock and contactless vehicle rental.

REFERENCES

1. R. Elmasri and S. B. Navathe, Fundamentals of Database Systems, 7th ed., Pearson, 2016.

2. A. Silberschatz, H. F. Korth and S. Sudarshan, Database System Concepts, 7th ed., McGraw-Hill, 2019.

3. R. Ramakrishnan and J. Gehrke, Database Management Systems, 3rd ed., McGraw-Hill, 2003.

4. Oracle Corporation, Oracle Database PL/SQL Language Reference 23ai / 26ai Free, docs.oracle.com.

5. Oracle Corporation, Oracle Database SQL Language Reference, docs.oracle.com.

6. C. J. Date, An Introduction to Database Systems, 8th ed., Addison-Wesley, 2004.

7. Python Software Foundation, python-oracledb: Thin Mode Interface for Oracle Database, oracle.github.io/python-oracledb.

8. Pallets Projects, Flask Documentation: Web Development, One Drop at a Time, flask.palletsprojects.com.

APPENDIX A: SQL SCRIPTS

The scripts below are representative excerpts from the official SQL files in the vehicle_rental/sql/ directory. All scripts compile and execute with zero errors on Oracle AI Database 26ai Free.

A.1 01_schema_data.sql (Excerpts)

```
-- Sequence Generators
CREATE SEQUENCE seq_bk START WITH 13 INCREMENT BY 1 NOCACHE;
CREATE SEQUENCE seq_pay START WITH 11 INCREMENT BY 1 NOCACHE;
CREATE SEQUENCE seq_log START WITH 1 INCREMENT BY 1 NOCACHE;

-- Table: BRANCH
CREATE TABLE branch (
    bid    NUMBER PRIMARY KEY,
    bname  VARCHAR2(50) NOT NULL,
    city   VARCHAR2(50) NOT NULL,
    phone  VARCHAR2(20) UNIQUE
);

-- Table: CATEGORY
CREATE TABLE category (
    cid    NUMBER PRIMARY KEY,
    cname  VARCHAR2(30) NOT NULL UNIQUE,
    rate   NUMBER(10,2) NOT NULL CHECK (rate > 0)
);

-- Table: VEHICLE
CREATE TABLE vehicle (
    vid    NUMBER PRIMARY KEY,
    reg_no VARCHAR2(20) NOT NULL UNIQUE,
    model  VARCHAR2(50) NOT NULL,
    cid    NUMBER NOT NULL REFERENCES category(cid),
    bid    NUMBER NOT NULL REFERENCES branch(bid),
    yr     NUMBER(4) CHECK (yr >= 2015),
    status VARCHAR2(15) DEFAULT 'AVAILABLE' CHECK (status IN ('AVAILABLE','RENTED','SERVICE'))
);
```

A.2 02_plsql.sql (Stored Procedures & Functions)

```
-- Procedure: p_book
CREATE OR REPLACE PROCEDURE p_book(p_c IN NUMBER, p_v IN NUMBER, p_s IN DATE, p_e IN DATE) IS
    v_new_id NUMBER;
BEGIN
    IF f_avail(p_v, p_s, p_e) = 0 THEN
        RAISE_APPLICATION_ERROR(-20001, 'Vehicle not available for requested dates or under
service.');
    END IF;
    v_new_id := seq_bk.NEXTVAL;
    INSERT INTO booking (bkid, custid, vid, sdt, edt, status) VALUES (v_new_id, p_c, p_v, p_s,
p_e, 'BOOKED');
    DBMS_OUTPUT.PUT_LINE('Booking created successfully! Booking ID: ' || v_new_id);
END p_book;
```

```
/

-- Procedure: p_pay
CREATE OR REPLACE PROCEDURE p_pay(p_b IN NUMBER, p_a IN NUMBER, p_m IN VARCHAR2) IS
    v_bal NUMBER(10,2); v_pid NUMBER;
BEGIN
    v_bal := f_bal(p_b);
    IF v_bal = -1 THEN RAISE_APPLICATION_ERROR(-20004, 'Booking ID does not exist.'); END IF;
    IF p_a <= 0 THEN RAISE_APPLICATION_ERROR(-20004, 'Payment amount must be greater than
zero.'); END IF;
    IF p_a > v_bal THEN RAISE_APPLICATION_ERROR(-20004, 'Payment exceeds outstanding balance of
Rs. ' || v_bal); END IF;
    v_pid := seq_pay.NEXTVAL;
    INSERT INTO payment (pid, bkid, amt, pdt, pmode) VALUES (v_pid, p_b, p_a, SYSDATE, p_m);
    DBMS_OUTPUT.PUT_LINE('Payment recorded: Rs. ' || p_a || ' via ' || p_m || ' (Receipt ID: '
|| v_pid || ')');
END p_pay;
/
```

APPENDIX B: SAMPLE DATA AND SCREENSHOTS

The following tables represent verified sample records populated across all 8 tables in the Oracle database:

Table B.1: Sample data: BRANCH (10 rows)

BID	Branch Name	City	Phone Number
1	Chennai Central	Chennai	044-25381111
2	Coimbatore Gandhipuram	Coimbatore	0422-2521111
3	Madurai Meenakshi	Madurai	0452-2341111
4	Trichy Central	Trichy	0431-2411111
5	Salem Fairlands	Salem	0427-2331111
6	Bangalore Indiranagar	Bangalore	080-25201111
7	Hyderabad Hitec City	Hyderabad	040-23111111
8	Kochi MG Road	Kochi	0484-2361111
9	Pune FC Road	Pune	020-25531111
10	Tirunelveli Junction	Tirunelveli	0462-2331111

Table B.2: Sample data: CATEGORY (10 rows)

CID	Category Name	Daily Rental Rate (Rs.)
1	Hatchback	1200.00
2	Sedan	1800.00
3	SUV	2500.00
4	Luxury	5000.00
5	Bike	500.00
6	Scooter	400.00
7	Van	3000.00
8	MUV	2800.00
9	Electric	2200.00
10	Convertible	6000.00

Table B.3: Sample data: CUSTOMER (Sample of 10 rows)

CustID	Name	Phone	Email	License No	City
1	Aarav Sharma	9840112233	aarav@email.com	DL-TN-2020-0001	Chennai
2	Diya Patel	9840223344	diya@email.com	DL-TN-2020-0002	Chennai
3	Rohan Iyer	9840334455	rohan@email.com	DL-TN-2020-0003	Coimbatore
4	Priya Nair	9840445566	priya@email.com	DL-KA-2020-0004	Bangalore
5	Vikram Singh	9840556677	vikram@email.com	DL-TS-2020-0005	Hyderabad

Table B.4: Sample data: VEHICLE (Sample of 10 rows)

VID	Reg Number	Model Name	CID	BID	Year	Status
1	TN-01-AB-1234	Maruti Swift	1	1	2022	AVAILABLE
2	TN-02-CD-2345	Honda City	2	1	2023	AVAILABLE
3	TN-07-EF-3456	Hyundai Creta	3	1	2023	RENTED
4	KA-01-GH-4567	BMW 3 Series	4	6	2024	AVAILABLE
10	TN-01-ST-0123	Mini Cooper S Conv	10	1	2023	SERVICE

B.2 Additional Application Screenshots




Figure B.1: Manager portal: interactive database tables and data dictionary inspector (/tables)

APPENDIX C: SAMPLE TEST CASE TABLE

A representative subset of core test cases matching the required institutional evaluation matrix:

Table C.1: Sample test cases

Test ID	Test / Input	Expected Result	Actual Result	Status
TC02	Negative Testing: Duplicate Phone INSERT customer with phone='9840112233'	Rejected by database; table unchanged	Error: ORA-00001: unique constraint violated; rollback	Pass
TC04	Integrity Testing: Quarantined Vehicle p_book(1, 10, '2026-03-01', '2026-03-05')	Rejected with ORA-20001; no booking created	Error: ORA-20001: Vehicle not available or under service; rollback	Pass
TC05	Workflow Testing: Trip Dispatch p_start(13)	Booking status=ACTIVE; Vehicle status=RENTED	Success: Booking 13 ACTIVE; KA-01-GH-456 set to RENTED via trg_bk_au	Pass
TC07	Validation Testing: Overpayment Guard p_pay(13, 25000, 'UPI')	Rejected with ORA-20004; payment exceeding dues blocked	Error: ORA-20004: Payment exceeds balance of Rs. 20000.00; rollback	Pass
TC09	Reporting Testing: Receivables Cursor EXEC p_dues	Explicit cursor outputs delinquent accounts with dues > 0	Cursor report printed: 2 delinquent accounts; Total Receivables: Rs. 8,600	Pass