```
     1 0.000000          192.168.1.102          128.119.245.12          TCP      62      1161 → 80 [SYN] Seq=0 Win=16384 Len=0 MSS=1460 SACK_PERM=1
Frame 1: 62 bytes on wire (496 bits), 62 bytes captured (496 bits)
Ethernet II, Src: PremaxPe_8a:70:1a (00:20:e0:8a:70:1a), Dst: LinksysG_da:af:73 (00:06:25:da:af:73)
Internet Protocol Version 4, Src: 192.168.1.102, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 1161, Dst Port: 80, Seq: 0, Len: 0
     Source Port: 1161
     Destination Port: 80
     [Stream index: 0]
     [TCP Segment Len: 0]
     Sequence number: 0     (relative sequence number)
     Acknowledgment number: 0
     0111 .... = Header Length: 28 bytes (7)
     Flags: 0x002 (SYN)
          000. .... .... = Reserved: Not set
          ...0 .... .... = Nonce: Not set
          .... 0... .... = Congestion Window Reduced (CWR): Not set
          .... .0.. .... = ECN-Echo: Not set
          .... ..0. .... = Urgent: Not set
          .... ...0 .... = Acknowledgment: Not set
          .... .... 0... = Push: Not set
          .... .... .0.. = Reset: Not set
          .... .... ..1. = Syn: Set
          .... .... ...0 = Fin: Not set
          [TCP Flags: ··········S·]
     Window size value: 16384
     [Calculated window size: 16384]
     Checksum: 0xf6e9 [unverified]
     [Checksum Status: Unverified]
     Urgent pointer: 0
     Options: (8 bytes), Maximum segment size, No-Operation (NOP), No-Operation (NOP), SACK permitted
```