

```
190 4.458800      192.168.1.21      128.119.245.12      TCP      66      65013 → 80 [SYN] Seq=0 Win=17520 Len=0 MSS=1460 WS=256
SACK_PERM=1
Frame 190: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface 0
Ethernet II, Src: IntelCor_79:31:87 (a0:c5:89:79:31:87), Dst: Netgear_64:ab:88 (00:8e:f2:64:ab:88)
Internet Protocol Version 4, Src: 192.168.1.21, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 65013, Dst Port: 80, Seq: 0, Len: 0
  Source Port: 65013
  Destination Port: 80
  [Stream index: 4]
  [TCP Segment Len: 0]
  Sequence number: 0 (relative sequence number)
  Acknowledgment number: 0
  1000 .... = Header Length: 32 bytes (8)
  Flags: 0x002 (SYN)
    000. .... = Reserved: Not set
    ...0 .... = Nonce: Not set
    .... 0... = Congestion Window Reduced (CWR): Not set
    .... .0.. = ECN-Echo: Not set
    .... ..0. = Urgent: Not set
    .... ...0 = Acknowledgment: Not set
    .... .... 0... = Push: Not set
    .... .... .0.. = Reset: Not set
    .... .... ..1. = Syn: Set
    .... .... ...0 = Fin: Not set
    [TCP Flags: .....S.]
  Window size value: 17520
  [Calculated window size: 17520]
  Checksum: 0xcf26 [unverified]
  [Checksum Status: Unverified]
  Urgent pointer: 0
  Options: (12 bytes), Maximum segment size, No-Operation (NOP), Window scale, No-Operation (NOP), No-Operation (NOP), SACK permitted
```