```
ICMP
                                                                                        Echo (ping) request id=0x0001, seq=723/54018, ttl=255 (no
  1861 119.513009
                        192.168.1.3
                                               74.125.141.147
                                                                                 554
response found!)
Frame 1861: 554 bytes on wire (4432 bits), 554 bytes captured (4432 bits) on interface 0
Ethernet II, Src: IntelCor_e0:b1:72 (a0:af:bd:e0:b1:72), Dst: Netgear_64:ab:88 (00:8e:f2:64:ab:88)
Internet Protocol Version 4, Src: 192.168.1.3, Dst: 74.125.141.147
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
   Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 540
    Identification: 0x5580 (21888)
    Flags: 0x00
        0... = Reserved bit: Not set
.0.. = Don't fragment: Not set
        ..0. .... = More fragments: Not set
   Fragment offset: 2960
    Time to live: 255
    Protocol: ICMP (1)
    Header checksum: 0xc932 [validation disabled]
    [Header checksum status: Unverified]
    Source: 192.168.1.3
    Destination: 74.125.141.147
    [Source GeoIP: Unknown]
    [Destination GeoIP: Unknown]
    [3 IPv4 Fragments (3480 bytes): #1859(1480), #1860(1480), #1861(520)]
        [Frame: 1859, payload: 0-1479 (1480 bytes)]
[Frame: 1860, payload: 1480-2959 (1480 bytes)]
        [Frame: 1861, payload: 2960-3479 (520 bytes)]
        [Fragment count: 3]
        [Reassembled IPv4 length: 3480]
```

[Reassembled IPv4 data: 08001b52000102d320202020202020202020202020202020...]

Internet Control Message Protocol