

LOGIN PAGE DEVELOPMENT USING HTML

```
#include <ESP8266WiFi.h>

#include <ESP8266WebServer.h>

const char* ssid = "sarvika";
const char* password = "sarvi@24";

ESP8266WebServer server(80);

// HTML page for login
const char htmlPage[] PROGMEM = R"rawliteral(
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta name="viewport" content="width=device-width, initial-scale=1.0">
<title>Login Page</title>
<style>
body {
    background-color: #2c3e50; /* Dark background, you can change */
    font-family: Arial, sans-serif;
    display: flex;
    justify-content: center;
    align-items: center;
    height: 100vh;
    margin: 0;
    color: white;
}
.container {
```

```

padding: 40px 60px;
border-radius: 10px;
text-align: center;
}
input[type="text"], input[type="password"] {
width: 100%;
padding: 12px;
margin: 10px 0;
border-radius: 5px;
border: none;
}
button {
width: 100%;
padding: 12px;
border-radius: 5px;
border: none;
background-color: #3498db;
color: white;
font-size: 16px;
cursor: pointer;
}
button:hover {
background-color: #2980b9;
}
</style>
</head>
<body>
<div class="container">
<h2>Login</h2>
<form action="/login" method="POST">
<input type="text" name="username" placeholder="Username" required><br>

```

```

        <input type="password" name="password" placeholder="Password" required><br>
        <button type="submit">Login</button>
    </form>
</div>
</body>
</html>
)rawliteral";

// Handle root page
void handleRoot() {
    server.send(200, "text/html", htmlPage);
}

// Handle login form submission
void handleLogin() {
    String username = server.arg("username");
    String password = server.arg("password");

    // Simple check (change as needed)
    if(username == "sarvika" && password == "1234") {
        server.send(200, "text/html", "<h1>Login Successful!</h1>");
    } else {
        server.send(200, "text/html", "<h1>Login Failed!</h1><p><a href='/'>Try Again</a></p>");
    }
}

void setup() {
    Serial.begin(115200);

    // Start Wi-Fi AP
    WiFi.softAP(ssid, password);

```

```
Serial.println("Access Point Started");

Serial.print("IP address: ");

Serial.println(WiFi.softAPIP());


// Setup server routes
server.on("/", handleRoot);

server.on("/login", HTTP_POST, handleLogin);


server.begin();

Serial.println("HTTP server started");
}


void loop() {
  server.handleClient();
}
```