



A Record

Last updated 4 October, 2024 • 3 min read

✧ Summarize page



Use the `nios_a_record` module to create, update, or remove an A record object from a NIOS Grid.

The following table describes the parameters you can define in the `nios_a_record` module:

Parameter ↑↓	Required/Optional ↑↓	Description ↑↓
<code>name</code>	Required	Specifies the fully qualified host name to add or remove from NIOS. To update the name of an A record object, define a dictionary object that contains the following parameters: <code>old_name</code> : Specifies the existing name that must be changed. <code>new_name</code> : Specifies the new name.
<code>dns_view/view</code>	Optional	Sets the DNS view to associate the A record with. If a value is not specified, default is used as the DNS view name. If you are using a custom DNS view, then you must specify this parameter.
<code>ipv4addr / ipv4</code>	Required	Specifies the IPv4 address for an A record.

		- To allocate a dynamic IP address the A record, define a dictionary object that contains the <code>nios_next_ip</code> parameter. - To update an A record with a static IP address, define a dictionary object that contains the following parameters: <code>old_ipv4addr</code> : Specifies the IP address that must be changed. <code>new_ipv4addr</code> : Specifies the new IP address. - To update an A record with a dynamic IP address, define a dictionary object that contains the <code>old_ipv4addr</code> and <code>nios_next_ip</code> parameters. Example: <pre>ipv4: {'old_ipv4addr': '10.0.0.5', nios_next_ip: 80.0.0.0/24}</pre>
<code>ttl</code>	Optional	Specifies the Time To Live (TTL) value for the record. The duration that the record is valid for, in seconds (cached).
<code>extattrs</code>	Optional	Specifies the extensible attributes for the A record object.
<code>state</code>	Optional	Specifies the state of the A record instance on the NIOS server. Set one of the following values: <code>present</code> (default): Configures the record. <code>absent</code> : Removes the record.
<code>comment</code>	Optional	Describes the A record object.
<code>provider</code>	Required	Defines the details of the connection: <code>host</code> : The DNS host name or IP address to connect to the remote instance of NIOS. <code>username</code> : The user name to use for authenticating the connection to the remote instance. <code>password</code> : The password to use for authenticating the connection to the remote instance. For information on additional fields you can define, see the list of subparameters in the NIOS Modules for Ansible Collections topic.

connection	Required	The <code>nios_a_record</code> module must be run locally.
------------	----------	--

Examples

```
name: configure an A record
infoblox.nios_modules.nios_a_record:
  name: a.ansibletestzone.com
  ipv4: 192.168.10.1
  comment: this is a test comment
  state: present
  provider:
    host: <nios_hostname_or_hostip>
    username: <nios_username>
    password: <nios_password>
connection: local
```

```
name: Create Nios A record in custom DNS view
infoblox.nios_modules.nios_a_record:
  name: v56.parent.com
  view: custom_view
  ipv4: {nios_next_ip: "192.170.10.0/24"}
  comment: Created with Ansible
  state: present
  provider:
    host: <nios_hostname_or_hostip>
    username: <nios_username>
    password: <nios_password>
connection: local
```

```
name: Update an A record in custom view with a dynamic IP using nios_next_ip
infoblox.nios_modules.nios_a_record:
  name: test.parent.com
  view: default.custom
  ipv4: {'old_ipv4addr': '10.0.0.5', nios_next_ip: 80.0.0.0/24}
  comment: this is a test comment
  state: present
  provider:
    host: <nios_hostname_or_hostip>
    username: <nios_username>
    password: <nios_password>
connection: local
```

```
name: Update an A record with a static IP
infoblox.nios_modules.nios_a_record:
  name: test.parent.com
```

```
ipv4: {'old_ipv4addr': 30.0.0.10, 'new_ipv4addr': 37.0.0.10}
```

```
state: present
```

```
provider:
```

```
  host: <nios_hostname_or_hostip>
```

```
  username: <nios_username>
```

```
  password: <nios_password>
```

```
connection: local
```

```
name: Update host name of an A record
```

```
infoblox.nios_modules.nios_a_record:
```

```
  name: {new_name: a_new.ansible.com, old_name: a.ansible.com}
```

```
  ipv4: 192.168.10.1
```

```
  state: present
```

```
  provider:
```

```
    host: <nios_hostname_or_hostip>
```

```
    username: <nios_username>
```

```
    password: <nios_password>
```

```
connection: local
```