

This is the **latest** (stable) Ansible community documentation. For Red Hat Ansible Automation Platform subscriptions, see [Life Cycle](#) (<https://access.redhat.com/support/policy/updates/ansible-automation-platform>) for version details.

infoblox.nios_modules.nios_host_record module

– Configure Infoblox NIOS host records

📌 Note

This module is part of the [infoblox.nios_modules collection](#) (https://galaxy.ansible.com/ui/repo/published/infoblox/nios_modules/) (version 1.9.0).

You might already have this collection installed if you are using the `ansible` package. It is not included in `ansible-core`. To check whether it is installed, run `ansible-galaxy collection list`.

To install it, use: `ansible-galaxy collection install infoblox.nios_modules`. You need further requirements to be able to use this module, see [Requirements](#) for details.

To use it in a playbook, specify: `infoblox.nios_modules.nios_host_record`.

New in infoblox.nios_modules 1.0.0

- [Synopsis](#)
- [Requirements](#)
- [Parameters](#)
- [Notes](#)
- [Examples](#)

Synopsis

- Adds and/or removes instances of host record objects from Infoblox NIO module manages NIOS `record:host` objects using the Infoblox WAPI int REST.
- Updates instances of host record object from Infoblox NIOS servers.

Requirements

The below requirements are needed on the host that executes this module.

- infoblox-client

Parameters

aliases

list / elements=string

Configures an optional list of additional aliases to add to the host record. These are equivalent to CNAMEs but held within a host record. Must be in list format.

comment

string

Configures a text string comment to be associated with the instance of this object. The provided text string will be configured on the object instance.

configure_for_dns

aliases: dns

boolean

Sets the DNS to particular parent. If user needs to bypass DNS user can make the value to false.

Choices:

- ☐ false
- ☒ true ← (default)

extattrs

dictionary

Allows for the configuration of Extensible Attributes on the instance of the object. This argument accepts a set of key / value pairs for configuration.

ipv4addrs

aliases: ipv4

list / elements=dictionary

Configures the IPv4 addresses for this host record. This argument accepts a list of values (see suboptions).

add

aliases: add

boolean

added in *infoblox.nios_modules 1.0.0*

If user wants to add the ipv4 address to an existing host record. Note that with *add* user will have to keep the *state* as *present*, as new IP address is allocated to existing host record. See examples.

Choices:

- ☐ false
- ☐ true

configure_for_dhcp

aliases: dhcp

boolean

Configure the host_record over DHCP instead of DNS, if user changes it to true, user need to mention MAC address to configure.

Choices:

- ☐ false
- ☐ true

ipv4addr

aliases: address

string / required

Configures the IPv4 address for the host record. Users can dynamically allocate ipv4 address to host record by passing dictionary containing, *nios_next_ip* and *CIDR network range*. If user wants to add or remove the ipv4 address from existing record, *add/remove* params need to be used. See examples.

mac

aliases: mac

string

Configures the hardware MAC address for the host record. If user makes DHCP to true, user need to mention MAC address.

nextserver

aliases: pxe

string

added in *infoblox.nios_modules 1.0.0*

Takes as input the name in FQDN format and/or IPv4 Address of the next server that the host needs to boot from.

remove

aliases: remove

boolean

added in infoblox.nios_modules 1.0.0

If user wants to remove the ipv4 address from an existing host record. Note that with *remove* user will have to change the *state* to *absent*, as IP address is de-allocated from an existing host record. See examples.

Choices:

- ☐ false
- ☐ true

use_for_ea_inheritance

boolean

added in infoblox.nios_modules 1.7.0

When use_for_ea_inheritance is True, the EA is inherited from Host address. The default value is False.

Choices:

- ☒ false ← (default)
- ☐ true

use_nextserver

aliases: use_pxe

boolean

added in infoblox.nios_modules 1.0.0

Enable the use of the nextserver option

Choices:

- ☐ false
- ☐ true

ipv6addrs

aliases: ipv6

list / elements=dictionary

Configures the IPv6 addresses for the host record. This argument accepts a list of values (see options).

configure_for_dhcp

aliases: dhcp

boolean

Configure the host_record over DHCP instead of DNS, if user changes it to true, user need to mention DUID address to configure.

Choices:

- ☐ false
- ☐ true

duid

aliases: duid
string

Configures the hardware DUID address for the host record. If user makes DHCP to true, user need to mention DUID address.

ipv6addr

aliases: address
string / required

Configures the IPv6 address for the host record.

name

string / required

Specifies the fully qualified hostname to add or remove from the system. User can also update the hostname as it is possible to pass a dict containing *new_name*, *old_name*. See examples.

provider

dictionary

A dict object containing connection details.

cert

string

Specifies the client certificate file with digest of x509 config for extra layer secure connection the remote instance of NIOS.

Value can also be specified using `INFOBLOX_CERT` environment variable.

host

string

Specifies the DNS host name or address for connecting to the remote instance of NIOS WAPI over REST

Value can also be specified using `INFOBLOX_HOST` environment variable.

http_pool_connections

integer

Insert description here

Default: `10`

http_pool_maxsize

integer

Insert description here

Default: `10`

http_request_timeout

integer

The amount of time before to wait before receiving a response

Value can also be specified using `INFOBLOX_HTTP_REQUEST_TIMEOUT` environmer

Default: `10`

key
string

Specifies private key file for encryption with the certificate in order to connect with remote instance of NIOS.

Value can also be specified using `INFOBLOX_KEY` environment variable.

max_results
integer

Specifies the maximum number of objects to be returned, if set to a negative number the appliance will return an error when the number of returned objects would exceed the setting.

Value can also be specified using `INFOBLOX_MAX_RESULTS` environment variable.

Default: `1000`

max_retries
integer

Configures the number of attempted retries before the connection is declared usable

Value can also be specified using `INFOBLOX_MAX_RETRIES` environment variable.

Default: `3`

password
string

Specifies the password to use to authenticate the connection to the remote instance of NIOS.

Value can also be specified using `INFOBLOX_PASSWORD` environment variable.

silent_ssl_warnings
boolean

Insert description here

Choices:

- `false`
- `true` ← (default)

username
string

Configures the username to use to authenticate the connection to the remote instance of NIOS.

Value can also be specified using `INFOBLOX_USERNAME` environment variable.

validate_certs

aliases: ssl_verify

boolean

Boolean value to enable or disable verifying SSL certificates

Value can also be specified using `INFOBLOX_SSL_VERIFY` environment variable.

Choices:

- `false` ← (default)
- `true`

wapi_version

string

Specifies the version of WAPI to use

Value can also be specified using `INFOBLOX_WAPI_VERSION` environment variable.

Until ansible 2.8 the default WAPI was 1.4

Default: `"2.12.3"`

state

string

Configures the intended state of the instance of the object on the NIOS server. When this value is set to `present`, the object is configured on the device and when this value is set to `absent` the value is removed (if necessary) from the device.

Choices:

- `"present"` ← (default)
- `"absent"`

ttl

integer

Configures the TTL to be associated with this host record.

use_dns_ea_inheritance

boolean

added in infoblox.nios_modules 1.7.0

When `use_dns_ea_inheritance` is True, the EA is inherited from associated zone. The default value is False.

Choices:

- `false` ← (default)
- `true`

view

aliases: dns_view

string

Sets the DNS view to associate this host record with. The DNS view must already be configured on the system.

Default: `"default"`

Notes

Note

- This module supports `check_mode`.
- This module must be run locally, which can be achieved by specifying `connection: local`.
- Please read the :ref:`nios\_guide` for more detailed information on how to use Infoblox with Ansible.

Examples

- **name:** Configure an ipv4 host record
infoblox.nios_modules.nios_host_record:
 name: host.ansible.com
 ipv4:
 - **address:** 192.168.10.1
 aliases:
 - **cname:** ansible.com
 state: present
 provider:
 host: "{{ inventory_hostname_short }}"
 username: admin
 password: admin
connection: local
- **name:** Add a comment to an existing host record
infoblox.nios_modules.nios_host_record:
 name: host.ansible.com
 ipv4:
 - **address:** 192.168.10.1
 comment: this is a test comment
 state: present
 provider:
 host: "{{ inventory_hostname_short }}"
 username: admin
 password: admin
connection: local
- **name:** Remove a host record from the system
infoblox.nios_modules.nios_host_record:
 name: host.ansible.com
 state: absent
 provider:
 host: "{{ inventory_hostname_short }}"
 username: admin
 password: admin
connection: local
- **name:** Update an ipv4 host record
infoblox.nios_modules.nios_host_record:
 name: {new_name: host-new.ansible.com, old_name: host.ansible.com}
 ipv4:
 - **address:** 192.168.10.1
 state: present
 provider:
 host: "{{ inventory_hostname_short }}"
 username: admin
 password: admin
connection: local
- **name:** Create an ipv4 host record bypassing DNS
infoblox.nios_modules.nios_host_record:
 name: new_host
 ipv4:
 - **address:** 192.168.10.1
 dns: false
 state: present
 provider:
 host: "{{ inventory_hostname_short }}"
 username: admin
 password: admin

```

connection: local

- name: Create an ipv4 host record over DHCP
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    ipv4:
      - address: 192.168.10.1
        dhcp: true
        mac: 00-80-C8-E3-4C-BD
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Create an ipv4 host record with DNS EA inheritance enabled
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    configure_for_dns: true
    use_dns_ea_inheritance: true
    ipv4:
      - address: 192.168.10.1
        dhcp: true
        mac: 00-80-C8-E3-4C-BD
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Create an ipv4 host record with host address EA inheritance enabled
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    configure_for_dns: true
    ipv4:
      - address: 192.168.10.1
        dhcp: true
        mac: 00-80-C8-E3-4C-BD
        use_for_ea_inheritance: true
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Create an ipv4 host record over DHCP with PXE server
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    ipv4:
      - address: 192.168.10.1
        dhcp: true
        mac: 00-80-C8-E3-4C-BD
        use_nextserver: true
        nextserver: pxe-server.com
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

```

```

- name: Dynamically add host record to next available ip
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    ipv4:
      - address: {nios_next_ip: 192.168.10.0/24}
    comment: this is a test comment
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Add ip to host record
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    ipv4:
      - address: 192.168.10.2
        add: true
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Remove ip from host record
  infoblox.nios_modules.nios_host_record:
    name: host.ansible.com
    ipv4:
      - address: 192.168.10.1
        remove: true
    state: absent
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

- name: Create host record with IPv4 and IPv6 addresses
  infoblox.nios_modules.nios_host_record:
    name: hostrec.ansible.com
    ipv4:
      - address: 192.168.10.7
        mac: 12:80:C8:E3:4C:AB
    ipv6:
      - address: fe80::10
        duid: 12:80:C8:E3:4C:B4
    state: present
    provider:
      host: "{{ inventory_hostname_short }}"
      username: admin
      password: admin
    connection: local

```

Authors

- Peter Sprygada (@privateip)

Collection links

Issue Tracker (<https://github.com/infobloxopen/infoblox-ansible/issues>).

Homepage (<https://github.com/infobloxopen/infoblox-ansible>).

Repository (Sources) (<https://github.com/infobloxopen/infoblox-ansible/tree/master>).