

```

Eshell V13.2.2.5 (abort with ^G)
1> ==> Booted jsx
==> Booted iotserv
rr("include/iotserv.hrl").
[iot]
2> whereis(iotserv).
<0.157.0>
3> Device = #iot{id=1, name="sensor", adress="room1", tempature=22.5, indicators=[{water, 100}, {temp, 43}]].
#iot{id = 1,name = "sensor",adress = "room1",
    tempature = 22.5,
    indicators = [{water,100},{temp,43}]}
4> iotserv:add(Device).
ok
5> iotserv:lookup(1).
{ok,#iot{id = 1,name = "sensor",adress = "room1",
    tempature = 22.5,
    indicators = [{water,100},{temp,43}]}}
6> iotserv:change(1, [{name, "new_sensor"}, {tempature, 25.0}, {indicators, [{hum, 55}]}]).
ok
7> iotserv:lookup(1).
{ok,#iot{id = 1,name = "new_sensor",adress = "room1",
    tempature = 25.0,
    indicators = [{hum,55}]}}
8> iotserv:delete(1).
ok
9> iotserv:lookup(1).
{error,instance}

```

```

10> Device2 = #iot{id=2, name="persist", adress="test", tempature=30, indicators=[]}.
#iot{id = 2,name = "persist",adress = "test",tempature = 30,
    indicators = []}
11> iotserv:add(Device2).
ok
12> application:stop(iotserv).
=INFO REPORT==== 9-May-2026::13:12:16.624983 ===
    application: iotserv
    exited: stopped
    type: temporary

ok
13> application:start(iotserv).
ok
14> iotserv:lookup(2).
{ok,#iot{id = 2,name = "persist",adress = "test",
    tempature = 30,indicators = []}}

```

```

15> exit(whereis(iotserv), kill).
=SUPERVISOR REPORT==== 9-May-2026::13:13:19.162391 ===
    supervisor: {local,iotserv_sup}
    errorContext: child_terminated
    reason: killed
    offender: [{pid,<0.183.0>},
                {id,iotserv},
                {mfargs,{iotserv,start_link,[]}},
                {restart_type,permanent},
                {significant,false},
                {shutdown,5000},
                {child_type,worker}]

true
16> iotserv:lookup(2).
{ok,#iot{id = 2,name = "persist",adress = "test",
    tempature = 30,indicators = []}}
17>

```