Multi-Reference Identity-Preserving Inpainting Under Severe Occlusion

Technical Architecture, Prototype Implementation Progress & Comprehensive Execution Roadmap

Status: Core Architecture Implemented & Prototype Validated (Research Validation In Progress)

Trained Checkpoint: step_150.pt (Resumed from step_100 + 50 steps)

Framework: PyTorch 2.14, Diffusers, MediaPipe, ArcFace

Date: September 2026 | **Hardware:** CPU Execution Baseline

1. Executive Summary & Core Research Concept

Facial inpainting under severe occlusion (≥ 20% to 100% facial surface coverage) presents a fundamental challenge for generative vision models. Standard text-to-image inpainting pipelines (e.g., vanilla Stable Diffusion) rely exclusively on unoccluded boundary pixels and text prompts; consequently, when critical biometrics such as the nose, mouth, or eyes are missing, the model synthesizes a plausible facial structure that does not correspond to the subject's true biometric identity.

Proposed Architectural Solution: We implement a three-stage multi-reference framework consisting of **(1) Mask-Aware Reference Retrieval & Scoring (O1)**, **(2) Decoupled Identity Cross-Attention with Regional Transformer Fusion (O2)**, and **(3) Verifier-Aware Sampling with Quality-Constrained Reranking (O3)**. The architecture is designed to decouple *WHERE* facial organs should go (geometry from target mask and landmarks) from *WHO* the subject is (dense ArcFace spatial tokens sourced 100% from verified external reference photos). This structural separation prevents target identity leakage into the cross-attention values while enforcing bit-exact preservation on unmasked target pixels.

Pillar	Component	Mechanism & Technical Specification
O1: Retrieve	MaskAwareReferenceScorer	Multi-attribute scoring evaluating pose alignment (30%), visual quality (25%), landmark visibility (30%), and mask spatial overlap (15%). Assigns normalized weights across input references.
O2: Fuse	Regional Transformer + Decoupled Cross-Attention	Extracts 256 dense spatial ArcFace tokens per reference. Injects identity features via parallel dedicated cross-attention projections (calibrated scale λ=0.10) without modifying text attention weights.
O3: Verify	Verifier-Aware Sampling Reranker	Inference-time reranking sampling K candidate outputs and selecting via joint objective Score = 0.60×Sim_ID + 0.40×Quality_norm. Non-differentiable; operates without training gradients.

2. Mathematical Formulations & Data Flow

Decoupled Identity Cross-Attention: To prevent text conditioning interference, U-Net cross-attention layers execute parallel dual-path processing:

$$Z_{out} = \text{Softmax}(Q K_{text}^T / \sqrt{d}) V_{text} + \lambda \cdot \text{Softmax}(Q K_{id}^T / \sqrt{d}) V_{id}$$

where $K_{id} = W_k T_{fused}$ and $V_{id} = W_v T_{fused}$ are trained projection layers initialized at zero. Under Classifier-Free Guidance (CFG), identity tokens are duplicated across both unconditional and conditional batches so identity steering operates strictly at calibrated scale $\lambda = 0.10$ rather than being multiplied by guidance scale.

Invariance & Anti-Copy Guarantee: The diffusion backbone operates strictly on masked inputs where occluded pixels are zeroed out: $I_{masked} = I_{target} \odot (1 - M)$. The final reconstruction composites the decoded latent output with the original target canvas: $I_{final} = (1 - M) \odot I_{target} + M \odot I_{restored}$. This mathematically ensures exact pixel preservation ($\Delta = 0.0$) on all unmasked pixels while barring direct copy-paste from within the mask.

3. Technical Progress Report (Completed Work)

Phase	Milestone Description	Validated Implementation & Artifacts	Status
Phase 1	Dataset & Infrastructure Setup	CelebA-HQ: 30,000 images; 6,217 unique identities represented in the 30,000-image CelebA-HQ subset. Official CelebA identity annotation: 202,599 images and 10,177 identity classes; 100% of the 30,000 CelebA-HQ images were successfully mapped to verified CelebA identity labels. Deterministic 4-tier synthetic mask engine implemented.	**IMPLEMENTED**
Phase 2	Face Analysis & Pose Pipeline	MediaPipe 478-mesh + 68 canonical landmarks, head pose Euler angles, illumination and sharpness variance analysis.	**IMPLEMENTED**
Phase 3	Mask-Aware Reference Scorer (O1)	Multi-attribute retrieval scoring; generates dynamic weights prioritizing facial organ angle alignment and clarity.	**IMPLEMENTED**
Phase 4	Regional Transformer Fusion (O2)	2-layer transformer with Sinusoidal2D pos encoding, landmark proximity, and mask gating. Strict target anti-leakage.	**IMPLEMENTED**
Phase 5	Latent Diffusion Adapter	AspectRatioPreserver for letterbox/unletterbox, 512x512 working resolution, strict unmasked preservation engine.	**IMPLEMENTED**
Phase 6	Decoupled Cross-Attention & Native Loss	Differentiable ArcFace Native PyTorch backbone (1.0000000 cosine match to ONNX). Decoupled U-Net cross-attention.	**IMPLEMENTED**
Phase 7	Composite Loss Optimization	Resumed from the previously trained step_100 checkpoint. A further 50 optimization steps (steps 101–150) were performed with composite loss (L_diff + 0.15*L_id). The final trained checkpoint is step_150.pt (+163.4% identity steering).	**BENCHMARKED**
Phase 8	Forensic Invariance & Anti-Copy Audit	100% bit-exact unmasked invariance confirmed (Delta=0.0). Inside-mask SHA256 hashes distinct; 0% ground-truth copy.	**AUDITED**
Phase 9	Formal Ablation Matrix (A1–A7)	Evaluated A1-A7 on 25% mask severity. A7 produced the strongest measured result among the evaluated configurations (0.5644 same-ID cosine, +0.6246 biometric gap, 21.77 dB PSNR).	**BENCHMARKED**
Phase 10	External-Image Inference Demonstration	Demonstrated inference pipeline on external unconstrained subject (user_tests/test1) with 3 multi-pose references. Measured 0.5574 ref mean similarity and 0.9151 target similarity; demonstrates operational pipeline execution on external images (not a substitute for controlled multi-subject benchmark).	**DEMONSTRATED**

4. Quantitative Preliminary Benchmark: A1–A7 Ablations (25% Severity)

Using the saved **step_150.pt** checkpoint with zero additional training, we evaluated the formal ablation matrix on CelebA-HQ 7367 under Tier 1 (25% mask severity, 84,250 occluded pixels). On the evaluated 25% mask-severity experiment, A7 produced the strongest measured result among the evaluated configurations:

Code	Ablation Configuration	Sim_Ref	Sim_GT	Sim_Diff	Biometric Gap	PSNR	SSIM
Vanilla	SD Inpainting (No References)	0.5112	0.7799	-0.0296	+0.5408	19.97 dB	0.8126
A1	Single Random Ref (Direct Token)	0.5112	0.7799	-0.0295	+0.5407	19.98 dB	0.8127
A2	Random Multi-Ref (Mean Token Avg)	0.5116	0.7800	-0.0295	+0.5411	19.97 dB	0.8126
A3	Globally Best Ref (Quality Only)	0.5115	0.7800	-0.0296	+0.5411	19.97 dB	0.8126
A4	Multi-Ref (Equal Weights w=[1/3,1/3,1/3])	0.5048	0.7788	-0.0390	+0.5438	20.50 dB	0.8177
A5	Global Attention (No Mask Bias)	0.5047	0.7787	-0.0393	+0.5440	20.49 dB	0.8177
A6	Mask-Aware Regional Fusion (O1+O2, K=1)	0.5050	0.7791	-0.0392	**+0.5442**	20.49 dB	0.8176
A7	**Full System (O1+O2+O3 Reranker)**	**0.5644**	**0.8235**	**-0.0602**	**+0.6246**	**21.77 dB**	**0.8415**

Empirical Observations on Evaluated Configurations:
• **Regional Transformer Contribution (A4 vs A1-A3):** On the evaluated 25% mask-severity experiment, regional cross-attention increased measured PSNR by +0.53 dB and reduced MAE from 18.55 to 17.65, with cross-identity impostor similarity decreasing from -0.0296 to -0.0390.
• **Verifier Reranking Evaluation (A7 vs A6):** On the evaluated 25% mask-severity experiment, A7 produced the strongest measured result among the evaluated configurations. Selecting the top candidate under Score = 0.60×Sim_ID + 0.40×Quality increased the Biometric Identity Gap by +15.5% (from +0.5408 to +0.6246), increased same-ID cosine similarity by +11.8% (to 0.5644), and measured 21.77 dB PSNR.

5. Visual Demonstrations & Diagnostic Panels

Figure 1: Preliminary Benchmark Comparison on 25% Mask Severity across Ground Truth, Masked Input, Vanilla SD, and Ablations A1 through A7.




Figure 2: External-Image Inference Demonstration on user_tests/test1 (Target, Mask, Step-150 Reconstruction, References with dynamic weights). Demonstrates that the implemented pipeline processes images outside the research dataset; not a substitute for controlled multi-subject benchmarking.



6. Phase-Wise Execution Roadmap (Remaining Work To Be Done)

To transition the validated prototype into a fully validated research benchmark and complete software release, the remaining work is structured into 5 concrete phases (Phases 11–15):

Phase	Objective & Task Focus	Key Technical Steps & Implementation Plan	Expected Deliverable
Phase 11	Progressive Mask Severity Evaluation	Execute the evaluation harness across higher occlusion severity levels: • **50% mask severity evaluation:** Multi-organ occlusion (Eyes + Nose). • **75% mask severity evaluation:** Major facial occlusion (Eyes + Nose + Mouth). • **Full-face/severe occlusion evaluation:** ≥95% to 100% full-face occlusion, testing identity retrieval when target context provides minimal or zero facial cues.	Comprehensive multi-severity benchmark report and identity preservation curves.
Phase 12	Multi-Subject & Statistical Validation	Expand evaluation beyond prototype subjects to a rigorous test cohort: • **Multi-subject evaluation:** Stratified test set across diverse demographics, lighting, and head poses. • **Repeated trials/statistical validation:** Multiple random seeds, error variance, and paired t-tests vs baselines. • **Final metrics required by proposal:** Cosine similarity, TAR@FAR=0.1%, ROC AUC, PSNR, SSIM, LPIPS, Laplacian clarity, and bit-exact unmasked invariance.	Statistically validated benchmark across multi-subject cohort with complete proposal metrics.
Phase 13	Runtime Optimization & GPU Acceleration	Transition model from CPU development mode to GPU production runtime: • FP16 mixed-precision and FlashAttention-2 integration. • CUDA graph capture for U-Net denoising steps (reducing step latency from ~27s CPU to <0.8s on GPU). • ONNX / TensorRT export of RegionalIdentityTransformer.	High-speed GPU inference pipeline achieving sub-2-second end-to-end multi-reference generation.
Phase 14	Final Frontend / Demo Integration	Develop an accessible graphical interface for demonstration and testing: • **Final frontend/demo integration:** Interactive HTML5/Gradio canvas allowing users to brush custom masks directly on target portraits. • Multi-reference drag-and-drop gallery with real-time pose and quality diagnostic feedback. • Side-by-side interactive curtain comparison slider showing original vs inpainting.	Standalone interactive web application (Gradio / FastAPI) for real-time demonstration.
Phase 15	Final Paper & Report Preparation	Consolidate research findings into final academic documentation: • **Final paper/report preparation:** Comprehensive academic manuscript with formal mathematical formulations, complete benchmark tables, and literature baseline comparisons. • Clean open-source code release with reproducible conda/venv setup and checkpoint weights.	Final academic paper manuscript, complete code repository, and public benchmark documentation.

7. Current Project Status & Readiness Assessment

The core research architecture has been implemented and validated through controlled prototype experiments. Final research validation remains in progress and requires multi-subject evaluation across higher mask-severity levels (50%, 75%, and full-face), statistical analysis, and final comparison of all proposed components.