Exp.No: 20
Date:

Customer Switch with network modules using cisco packet tracer.

Aim:
To customize a cisco switch by adding or removing network modules using cisco packet tracer and verify changes in switch interface.

Procedure:

1. Open cisco packet tracer
2. Add modular switch to workshop.
3. Open physical tab and turn off switch.
4. Remove existing module, if required and insert a compatible network module.
5. Turn on switch and verify new interface
6. Connect 2 PC's to switch using copper straight through cables.
7. Configure the IP addresses of PC's as 192.168.10.2 and 192.168.10.3 with subnet mask.
8. Open PC0's command prompt and type ping 192.168.10.3 to test connectivity.
9. Save packet tracer file.

Result:
Thus, the switch was customized successfully by adding a network module and connectivity btw the 2 PC's was verified using ping command.

Router0

Physical | Config | CLI | Attributes

```
Cisco CISCO2911/K9 (revision 1.0) with 491520K/32768K bytes of memory.
Processor board ID FTX152400K8
3 Gigabit Ethernet interfaces
DRAM configuration is 64 bits wide with parity disabled.
255K bytes of non-volatile configuration memory.
249856K bytes of ATA System CompactFlash 0 (Read/Write)

         --- System Configuration Dialog ---

Would you like to enter the initial configuration dialog? [yes/no]:

Press RETURN to get started!


Router>configure terminal
% Invalid input detected at '^' marker.

Router>interface GigabitEthernet0/0
% Invalid input detected at '^' marker.

Router>ip address 192.168.10.1 255.255.255.0
% Invalid input detected at '^' marker.

Router>no shutdown
Translating "no"...domain server (255.255.255.255)
% Unknown command or computer name, or unable to find computer address

Router>enable
Router#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Router(config)#interface GigabitEthernet0/0
Router(config-if)#ip address 192.168.10.1 255.255.255.0
Router(config-if)#no shutdown

Router(config-if)#exit
%LINK-5-CHANGED: Interface GigabitEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0, changed state to up

Router(config)#interface GigabitEthernet0/1
Router(config-if)#ip address 192.168.20.1 255.255.255.0
Router(config-if)#no shutdown

Router(config-if)#exit
%LINK-5-CHANGED: Interface GigabitEthernet0/1, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/1, changed state to up
Router(config)#
```

Copy | Paste

